

SILPURAN[®] FILM 2030



Silicone Films

SILPURAN[®] Film 2030 250/xxx is an exceptionally skin-compatible protective film made from cross-linked silicone rubber, specially developed for the healthcare industry. The ultrathin film is showing constant electrical resistance and good comparative tracking resistance across a broad range of temperatures. The width is 250 mm and thickness is given in μm (xxx). xxx stands for

- 20 μm
- 50 μm
- 100 μm
- 200 μm
- 400 μm

SILPURAN[®] Film 2030 250/xxx is also available with a thickness of

- 10 μm and
- 15 μm .

The thickness variation over the entire width is $\pm 1 \mu\text{m}$. The production width is also 250 mm here.

Properties

SILPURAN[®] Film possesses all familiar properties of SILPURAN[®] product range. It fulfills the highest medical standards.

- biocompatible
- chemically stable
- resistant to heat
- flexible at low temperatures
- transparent
- permanently elastic
- food contact application possible on request

Specific features

- Addition Curing
- Biocompatible
- Colorless
- Electrically insulating
- Excellent durability
- FDA compliant
- Flexible at low (-40 °C) and high temperatures (+180 °C)
- Food-contact
- Gas permeable
- Highly transparent
- Patented
- Precise
- Solvent-free
- UV & weathering-resistant
- Water-vapor permeable

Technical data

Properties Cured

Property	Condition	Value	Method
Permittivity	-	2.8	-
Hardness Shore A	-	27	DIN ISO 48-4
Tensile strength	-	6.0 N/mm ²	ISO 37 type 1
Elongation at break	-	450 %	ISO 37 type 1
Compression Set ⁽¹⁾	22 h 100 °C	5 %	DIN ISO 815-1 type B method A
Gas permeability (selectively)	-	CO ₂ /N ₂ 10:1	DIN 53536
Water vapor permeability	24 h 20 µm	3000 g/m ²	JIS 1099 A1
Water vapor permeability	24 h 50 µm	1200 g/m ²	JIS 1099 A1
Water vapor permeability	24 h 100 µm	800 g/m ²	JIS 1099 A1
Biocompatibility (USP class VI)	-	yes	ISO 10993
Tear strength	-	10 N/mm	ASTM D 624 B

¹Cure conditions: 15 min / 165 °C in press, postcuring for 6 h / 200 °C in ventilated air.

These figures are only intended as a guide and should not be used in preparing specifications.

All the information provided is in accordance with the present state of our knowledge. Nonetheless, we disclaim any warranty or liability whatsoever and reserve the right, at any time, to effect technical alterations. The information provided, as well as the product's fitness for an intended application, should be checked by the buyer in preliminary trials. Contractual terms and conditions always take precedence. This disclaimer of warranty and liability also applies particularly in foreign countries with respect to third parties' rights.

Store in a dry and cool place.

Applications

- Medical
- Medical Parts
- Medical Solutions

Processing

General

SILPURAN® Film is manufactured and packed under cleanroom conditions, class 8. Cutting and packing of film sheets is done in a clean environment, outside the cleanroom.

Distributed by: Hisco | 877-447-2650 | info@hiscoinc.com | www.hisco.com

SILPURAN® FILM 2030 | Most recent change: 01.07.2021

Adhesion

Silicon Film can be glued to a numerous substrates with standard silicone adhesives. Depending on your requirements, ELASTOSIL® E43 can be the glue of choice.

Adhesion can generally be achieved and / or improved by using plasma bonding.

Cutting

Silicone Film can be processed by conventional technologies like die cutting, laser cutting or water jet cutting.

Packaging and storage

Packaging

SILPURAN® Film is available in a variety of thicknesses. Our standard portfolio offers film layers from 20 µm to 400 µm with standard thickness of

- 20 µm
- 50 µm
- 100 µm
- 200 µm
- 400 µm

Upon request thicknesses down to 10 µm can be provided

The delivery is always on a PET carrier, either on a rolls or as sheets.

Dimensions and order sizes of the roll:

10 m² ≙ 40 linear meter x 250 mm width

20 m² ≙ 80 linear meter x 250 mm width

The roll stock is supplied with an inner diameter of 3" (≙ 7,62 cm)

Sheets have the dimension of 210 mm x 250 mm, delivered in boxes with 20 sheets each.

Storage

Minimum temperature allowed during storage and transportation: 0 °C

Maximum temperature allowed during storage and transportation: 80 °C

QR Code SILPURAN® FILM 2030



For technical, quality or product safety questions, please contact:

Wacker Chemie AG, Hanns-Seidel-Platz 4, 81737 Munich, Germany
info@wacker.com, www.wacker.com

The data presented in this medium are in accordance with the present state of our knowledge but do not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this medium should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies' raw materials are also being used. The information provided by us does not absolve the user from the obligation of investigating the possibility of infringement of third parties' rights and, if necessary, clarifying the position. Recommendations for use do not constitute a warranty, either express or implied, of the fitness or suitability of the product for a particular purpose.

Distributed by: Hisco | 877-447-2650 | info@hiscoinc.com | www.hisco.com

SILPURAN® FILM 2030 | Most recent change: 01.07.2021