

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

**SECTION 1. IDENTIFICATION**

Product name : ELAN-Tron® MC 62-US Yellow Resin

**Manufacturer or supplier's details**

Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147  
Telephone : (314) 621-5700  
Visit our web site : [www.elantas.com](http://www.elantas.com)  
E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)  
Emergency telephone number : INFOTRAC - 1-800-535-5053

**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.  
Refer to Section 15 for any restrictions that may apply

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Skin irritation : Category 2  
Serious eye damage : Category 1  
Skin sensitisation : Category 1

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.

Precautionary statements : **Prevention:**  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Modified epoxy resin

**Hazardous components**

Component	CAS-No.	Concentration (%)
Epoxy Resin	28064-14-4	>= 14 - < 15
Epoxy Resin	25068-38-6	>= 12 - < 13
1,4-Butanediol diglycidyl ether	2425-79-8	>= 8 - < 9

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

- Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Absorbent paper or other organic material used for cleaning up resin is a fire hazard, as heat and spontaneous combustion can occur, particularly if the resin was catalyzed. Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling** : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
To avoid spills during handling keep bottle on a metal tray.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
The chemical reaction that cures mixed epoxy is exothermic (heat generating). If left to cure in a contained mass, such as in a mixing vessel, it can generate enough heat to melt plastic, burn skin or ignite surrounding combustible materials. The larger or thicker the epoxy mass, the more heat generated.
- Conditions for safe storage** : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
Keep container tightly closed in a dry and well-ventilated place.  
Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Contains no substances with occupational exposure limit values.  
Hazardous components without workplace control parameters

- Engineering measures** : Use with adequate ventilation.  
All application areas should be ventilated in accordance with applicable OSHA regulations. (29 CFR 1910.94)  
This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.  
Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.  
Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.  
Repeated inhalation of such dust may cause lung injury.

**Personal protective equipment**

- Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

Hand protection	
Remarks	: The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Eye protection	: Eye wash bottle with pure water Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Vapour pressure	: No data available
Flash point	: > 201 °F (> 94 °C) Method: No information available. Information taken from reference works and the literature.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

Density : 1.7135 g/cm<sup>3</sup> (77 °F (25 °C))

## Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Ignition temperature : No data available

Thermal decomposition : No data available

## Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 21 mm<sup>2</sup>/s (104 °F (40 °C))**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Hazardous decomposition products : Carbon monoxide in a fire.  
Nitrogen oxides in a fire.**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Product:**Acute oral toxicity : Acute toxicity estimate : 4,356 mg/kg  
Method: Calculation methodAcute inhalation toxicity : Acute toxicity estimate : 123.82 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method

**Components:****25068-38-6 Epoxy Resin:**

Acute oral toxicity : LD50 (Rat): 11,400 mg/kg  
  
LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
GLP: yes

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 23,400 mg/kg  
  
LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

**2425-79-8 1,4-Butanediol diglycidyl ether:**

Acute oral toxicity : LD50 (Mouse): 1.1 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 250 ppm  
Exposure time: 6.00 h

Acute dermal toxicity : LD50 (Rabbit): 1,130 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: Extremely corrosive and destructive to tissue.

**Components:****25068-38-6 Epoxy Resin:**

Species: Rabbit  
Result: Moderate skin irritation

Species: Rabbit  
Exposure time: 4 h  
Method: OECD Test Guideline 404  
Result: Skin irritation  
GLP: yes

**2425-79-8 1,4-Butanediol diglycidyl ether:**

Species: Rabbit  
Exposure time: 24.00 h  
Method: Draize Test  
Result: Moderate skin irritation

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Components:****25068-38-6 Epoxy Resin:**

Species: Rabbit

Result: Eye irritation

**2425-79-8 1,4-Butanediol diglycidyl ether:**

Species: Rabbit

Result: Moderate eye irritation

Method: Draize Test

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Components:****25068-38-6 Epoxy Resin:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

**Carcinogenicity****IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Aspiration toxicity****Components:****25068-38-6 Epoxy Resin:**

No aspiration toxicity classification



**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

**Further information****Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s)

: none

Waste from residues

: Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.  
Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.  
Dispose of the solid mass only if cure is complete and the mass has cooled. Follow federal, state or local disposal regulations.

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 3082  
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.  
(Epoxy resin)  
Class : 9  
Packing group : III  
Labels : Miscellaneous substances and articles  
Packing instruction (cargo aircraft) : 964  
Packing instruction (passenger aircraft) : 964

**IMDG-Code**

UN number : UN 3082  
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,  
N.O.S.  
(EPOXY RESIN)  
Marine Pollutant : (EPOXY RESIN)  
Class : 9  
Packing group : III  
Labels : 9  
EmS Code : F-A, S-F  
Marine pollutant : yes

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 - Emergency Release Notification**

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III  
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**Non-volatile (Wt)** : Refer to the product technical data sheet for VOC information.

**Massachusetts Right To Know**

No components are subject to the Massachusetts Right to Know Act.

**Pennsylvania Right To Know**

Aluminium hydroxide	21645-51-2
Epoxy Resin	28064-14-4
Epoxy Resin	25068-38-6
1,4-Butanediol diglycidyl ether	2425-79-8
1,2,4-Trimethylbenzene	95-63-6

**New Jersey Right To Know**

Aluminium hydroxide	21645-51-2
Epoxy Resin	28064-14-4
Epoxy Resin	25068-38-6

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019


Print Date 03/13/2019

1,4-Butanediol diglycidyl ether

2425-79-8

**New Jersey Trade Secret** : Not Applicable  
**Registry Number for the product (NJ TSRN)**

**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including Cumene, Phenyl glycidyl ether, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**


**TSCA** : We certify that all of the components of this product are either listed on the TSCA Inventory or are not subject to the notification requirements per 40 CFR 720 30(h).

**Section 4 / 12(b)** : Not applicable

**Section 5** : Not applicable

**DSL** : We certify that all of the components of this product are listed on the DSL.

Complex of 2,4,6-Tris-(dimethylamino)-methylphenol and ethylhexanoic acid

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

<b>HEALTH</b>	<b>2</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 03/13/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

**ELAN-Tron® MC 62-US Yellow Resin**

Version 3

Revision Date 03/13/2019

Print Date 03/13/2019

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.