

Page 1/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

#### 1 Identification

· Product identifier

· Trade name: EL319 Fast Hardener

· Article number: I319089

· Application of the substance / the mixture Hardening agent/ Curing agent

· Details of the supplier of the safety data sheet

Sika Advanced Resins, US

EHS Department

· Manufacturer/Supplier:

Supplier's Name: Sika Advanced Resins, US

*Headquarters:* 

30800 Stephenson Hwy Madison Heights, MI 48071

USA

ehs-us@axson.com

· Information department: Product safety department

· Emergency telephone number:

During normal opening times: +1 (248) 588-2270 CHEMTREC 24-hour Emergency: +1 (800) 424-9300

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)



Page 2/12

### Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/19/2019 Printing date 10/19/2019

Trade name: EL319 Fast Hardener

· Hazard pictograms

(Contd. of page 1)





GHS05 GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

3,6-diazaoctanethylenediamin

Polyoxypropylenediamine

· Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Avoid breathing dust/fume/gas/mist/vapors/spray

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = \*3Fire = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)



Page 3/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

· vPvB: Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
1	3,6-diazaoctanethylenediamin	50-100%	
EINECS: 203-950-6			
CAS: 9046-10-0	Polyoxypropylenediamine	5-10%	

### 4 First-aid measures

- Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

· Additional information

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

JS -





Page 4/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

(Contd. of page 3)

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· <i>PAC-1</i> :	· PAC-1:				
112-24-3	3,6-diazaoctanethylenediamin	3 ppm			
9046-10-0	Polyoxypropylenediamine	$4.8 \text{ mg/m}^{3}$			
· PAC-2:	· PAC-2:				
112-24-3	3,6-diazaoctanethylenediamin	14 ppm			
9046-10-0	Polyoxypropylenediamine	$53 \text{ mg/m}^3$			
· PAC-3:	· PAC-3:				
	3,6-diazaoctanethylenediamin	83 ppm			
9046-10-0	Polyoxypropylenediamine	320 mg/m <sup>3</sup>			

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)



Page 5/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

(Contd. of page 4)

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 112-24-3 3,6-diazaoctanethylenediamin

WEEL Long-term value: 6 mg/m³, 1 ppm Skin

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

*Immediately remove all soiled and contaminated clothing.* 

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



Page 6/12


(Contd. of page 5)

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

· Eye protection:



9 Physical and chemical properties

· Information on basic physical and chemical properties

General Information

· Appearance:

Form: Liquid

Color: Amber colored
Odor: Amine-like
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:232 °C (449.6 °F)

• Flash point: 122 °C (251.6 °F)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 335 °C (635 °F)

Decomposition temperature: Not determined.
 Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

Explosion limits:

 Lower:
 0.7 Vol %

 Upper:
 5 Vol %

· Vapor pressure: Not determined.

• Density at 20 °C (68 °F): 0.98 g/cm³ (8.18 lbs/gal)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 7)



Page 7/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

	(Contd. of pag
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: Carbon monoxide and carbon dioxide

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

Acute toxicity.		
· LD/LC50 values that are relevant for classification:		
112-24-3 3,6-diazaoctanethylenediamin		
9ral	LD50	2,000 mg/kg (rat)
		2,000 mg/kg (rabbit)
9046-10-0 Polyoxypropylenediamine		
90 Oral	LD50	2,855 mg/kg (rabbit)
Dermal	LD50	2,980 mg/kg (rabbit)
	L <b>D/LC5</b> 1 <b>12-24-</b> Oral Dermal <b>0046-10</b> Oral Dermal	LD/LC50 value   12-24-3 3,6-de   Dral   LD50     Dermal   LD50     D046-10-0 Poly     Dral   LD50

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive

(Contd. on page 8)



Page 8/12

## Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

(Contd. of page 7)

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

· Toxicity

· Aquatic toxicity:			
9046-10-0 Polyoxypropylenediamine			
48 hr EC50	80 mg/l (daphnia)		
96 hr LC50	772 mg/l (Fish)		
72 or 96 hr ErC50	15 mg/l (Algea)		

- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even extremely small quantities leak into the ground.

Harmful to aquatic organisms

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

US





Page 9/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

(Contd. of page 8)

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

NA2735 UN2735  Polyamines, liquid, corrosive, n.o.s. (Triethylenetetramine) POLYAMINES, LIQUID, CORROSIVE, N. C (TRIETHYLENETETRAMINE)
Polyamines, liquid, corrosive, n.o.s. (Triethylenetetramine) POLYAMINES, LIQUID, CORROSIVE, N.O.
POLYAMINES, LIQUID, CORROSIVE, N.C.
POLYAMINES, LIQUID, CORROSIVE, N.C.
8 Corrosive substances 8
<sup>x</sup>
8 Corrosive substances
8
II
No
Warning: Corrosive substances

(Contd. on page 10)





Page 10/12

### Safety Data Sheet acc. to OSHA HCS

Reviewed on 10/19/2019 Printing date 10/19/2019

Trade name: EL319 Fast Hardener

	(Contd. of page 9)	
· Segregation groups	Alkalis	
· Transport in bulk according to Annex II of  MARPOL73/78 and the IBC Code  Not applicable.		
· UN "Model Regulation":	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (TRIETHYLENETETRAMINE), 8, II	

### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

- · TSCA (Toxic Substances Control Act):
- All components have the value ACTIVE.
- · Chemicals regulated by TSCA Section 12(b)

None of the ingredients is listed.

· Chemical regulated by TSCA 5(a)(2)rule:

None of the ingredients is listed.

· Hazardous Air Pollutants

None of the ingredients is listed.

- Proposition 65
- · Chemicals known to cause cancer:

75-56-9 propylene oxide

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 11)



Page 11/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

(Contd. of page 10)

#### · Listed in CWC Regulations

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05 GHS07

- · Signal word Danger
- Hazard-determining components of labeling:

3,6-diazaoctanethylenediamin

Polyoxypropylenediamine

· Hazard statements

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

Harmful to aquatic life with long lasting effects.

· Precautionary statements

Do not breathe dusts or mists.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Date of preparation / last revision 10/19/2019 / 4
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

(Contd. on page 12)

Page 12/12

# Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2019 Reviewed on 10/19/2019

Trade name: EL319 Fast Hardener

(Contd. of page 11)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Skin Corr. 1A: Skin corrosion/irritation – Category 1A Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

US