

Revision Number: 004.3

PRODUCT AND COMPANY IDENTIFICATION

Product name:

Adhe Product type/use: Cyanoacrylate Restriction of Use: None identified Company address: Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067

LOCTITE 496 INSTANT ADHESIVE known as 496 Super Bonder® Instant

1.

IDH number:

234156

Item number: 49650 **Region: United States** Contact information: Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

HAZARDS IDENTIFICATION 2.

EMERGENCY OVERVIEW WARNING: BONDS SKIN IN SECONDS. COMBUSTIBLE LIQUID. CAUSES EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)

Precautionary Statements

oors, -
o. Iry
ce.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

COMPOSITION / INFORMATION ON INGREDIENTS 3.

Product name: LOCTITE 496 INSTANT ADHESIVE known as 496 Super Bonder® Instant Adhe Page 1 of 5

Hazardous Component(s)	CAS Number	Percentage*
Methyl-2-cyanoacrylate	137-05-3	80 - 100

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. F	IRST AID MEASURES
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.
Ingestion:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.
Symptoms:	See Section 11.
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.
5. FIR	E FIGHTING MEASURES
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or other positive pressure mode.
Unusual fire or explosion hazards:	None
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of breathing apparatus is recommended.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Ventilate area. Do not allow product to enter sewer or waterways.

Clean-up methods:

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Storage:

Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Methyl-2-cyanoacrylate	0.2 ppm TWA 1 ppm STEL (Respiratory sensitization) (Dermal sensitization)	None	None	None
Engineering controls:	Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.			
Respiratory protection:	Use NIC limit(s).	OSH approved respirato	if there is potential to e	xceed exposure
Eye/face protection:		oggles or safety glasse if the potential for splas		
Skin protection:		ile gloves and aprons as ylon or cotton.	necessary to prevent o	ontact. Do not use
9. PH	SICAL AND C	HEMICAL PRO	PERTIES	
Physical state:	Liquid			
Color:	Colorles			
Odor:	characte			
Odor threshold:	1 - 2 pp			
pH: Vapor pressure:		licable, Product reacts v		
Boiling point/range:		m hg (75 °F (23.9 °C)) < °C (> 300.2 °F)None	49 mbar (20 °C (66°F))	
Melting point/ range:		licable, Product is a liqu	id	
Specific gravity:		75 °F (23.89 °C)	iu	
Vapor density:	1.00 ut	10 1 (20.00 0)		
Flash point:		(187.7 °F)		
Flammable/Explosive limits - lower:				
Flammable/Explosive limits - upper				
Autoignition temperature:	Not dete	ermined		
Flammability:	The pro	duct is not flammable.		
Evaporation rate:	Not ava			
Solubility in water:	Reacts	with water.		
Partition coefficient (n-octanol/wate	r): Not ava	ilable.		
VOC content:	< 2 %; <	< 20 g/l (California SCAC	QMD Method 316B) (Est	imated)
	Mart all a	9 - 1.1 -		

Viscosity: Decomposition temperature: Not available. Not available.

10. STABILITY AND REACTIVITYStability:Stable under recommended storage conditions.Hazardous reactions:Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.Hazardous decomposition products:NoneIncompatible materials:Water, amines, alkalis and alcohols.Reactivity:Not available.Conditions to avoid:Spontaneous polymerization.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.
Skin contact:	May cause skin irritation. Bonds skin in seconds. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.
Eye contact: Ingestion:	Irritating to eyes. Causes excessive tearing. Eyelids may bond. Not a likely route of entry.

Acute oral product toxicity: LD50 > 5,000 mg/kg

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Methyl-2-cyanoacrylate	Oral LD50 (Rat) = 1.6 g/kg	Irritant, Allergen, Respiratory
	(, 50	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Methyl-2-cyanoacrylate	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

Proper shipping name:	Combustible liquid, n.o.s. (Cyanoacrylate ester)
Hazard class or division:	Combustible Liquid
Identification number:	NA 1993
Packing group:	III
International Air Transportation	
•	
Proper shipping name:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)
Proper shipping name: Hazard class or division:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) 9
Proper shipping name:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester)
Proper shipping name: Hazard class or division:	Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) 9

Page 4 of 5

Exceptions:

Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted.

Water Transportation (IMO/IMDG)

Proper shipping name: Hazard class or division: Identification number: Packing group: Not regulated None None None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimis	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health, Reactive, Fire None above reporting de minimis.	
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	All components are listed on or are exempt from listing on the Canadian Domestic Substances List.	

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Material Safety Data Sheet contains changes from the previous version in Section(s): 8,9,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 01/24/2023

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.