

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**SECTION 1. IDENTIFICATION**

Product name : CONAP® CE-1171 Acrylic Coating

**Manufacturer or supplier's details**Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)Emergency telephone : INFOTRAC - 1-800-535-5053  
number**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for  
consumer use or retail sale.  
Refer to Section 15 for any restrictions that may apply**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable liquids : Category 2

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 2

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 3 (Respiratory system, Central nervous system)  
- single exposureSpecific target organ toxicity : Category 2 (Kidney, Liver)  
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Danger

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

- Hazard statements** : H225 Highly flammable liquid and vapour.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H351 Suspected of causing cancer.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure.
- Precautionary statements** : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Acrylic Resin Solution

**Hazardous components**

Component	CAS-No.	Concentration (%)
1-Methoxy-2-propanol acetate	108-65-6	>= 53 - < 54
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 10 - < 11
m-xylene	108-38-3	>= 2 - < 3
p-xylene	106-42-3	>= 1 - < 2
Ethyl benzene	100-41-4	>= 1 - < 2
o-xylene	95-47-6	>= 0.1 - < 1
Toluene	108-88-3	>= 0.1 - < 1
n-Butyl methacrylate	97-88-1	>= 0.1 - < 1

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : Consult a physician after significant exposure.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
1-Methoxy-2-propanol acetate	108-65-6	TWA	50 ppm	US WEEL
m-xylene	108-38-3	TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
m-xylene		ST	150 ppm 655 mg/m <sup>3</sup>	NIOSH REL
m-xylene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
m-xylene		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
m-xylene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
m-xylene		TWA	100 ppm	ACGIH
m-xylene		STEL	150 ppm	ACGIH
p-xylene	106-42-3	TWA	100 ppm 435 mg/m <sup>3</sup>	NIOSH REL
p-xylene		ST	150 ppm 655 mg/m <sup>3</sup>	NIOSH REL
p-xylene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA Z-1
p-xylene		STEL	150 ppm 655 mg/m <sup>3</sup>	OSHA P0
p-xylene		TWA	100 ppm 435 mg/m <sup>3</sup>	OSHA P0
p-xylene		TWA	100 ppm	ACGIH
p-xylene		STEL	150 ppm	ACGIH

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

Ethyl benzene	100-41-4	TWA	20 ppm	ACGIH
Ethyl benzene		TWA	100 ppm 435 mg/m3	OSHA Z-1
Ethyl benzene		TWA	100 ppm 435 mg/m3	OSHA P0
Ethyl benzene		STEL	125 ppm 545 mg/m3	OSHA P0
o-xylene	95-47-6	TWA	100 ppm 435 mg/m3	NIOSH REL
o-xylene		ST	150 ppm 655 mg/m3	NIOSH REL
o-xylene		TWA	100 ppm 435 mg/m3	OSHA Z-1
o-xylene		STEL	150 ppm 655 mg/m3	OSHA P0
o-xylene		TWA	100 ppm 435 mg/m3	OSHA P0
o-xylene		TWA	100 ppm	ACGIH
o-xylene		STEL	150 ppm	ACGIH
Toluene	108-88-3	TWA	20 ppm	ACGIH
Toluene		TWA	200 ppm	OSHA Z-2
Toluene		CEIL	300 ppm	OSHA Z-2
Toluene		Peak	500 ppm	OSHA Z-2
Toluene		TWA	100 ppm 375 mg/m3	OSHA P0
Toluene		STEL	150 ppm 560 mg/m3	OSHA P0

Hazardous components without workplace control parameters

**Engineering measures** : Use with adequate ventilation.  
All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)

**Personal protective equipment**

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.

**Hand protection**

**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available : > 95 °F (> 35 °C) Information taken from reference works and the literature.
Vapour pressure	: No data available
Flash point	: 74 °F (23 °C) Method: ASTM D 93
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 0.9802 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 22 mm <sup>2</sup> /s (104 °F (40 °C))

**SECTION 10. STABILITY AND REACTIVITY**

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
	Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Hazardous decomposition products	: Carbon monoxide in a fire. Nitrogen oxides in a fire.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : > 200 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Acute oral toxicity	: LD50 (Rat, female): > 5,000 mg/kg Method: OECD Test Guideline 401 GLP: yes
Acute inhalation toxicity	: LC50 (Rat): > 100 ppm Exposure time: 4 h
Acute dermal toxicity	: LD50 (Rabbit): > 5,000 mg/kg

**64742-49-0 Naphtha (petroleum), hydrotreated light:**

Acute oral toxicity	: LD50 (Rat): > 5,000 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 23.3 mg/l Method: OECD Test Guideline 403 GLP: yes
Acute dermal toxicity	: LD50 (Rabbit): > 2,000 mg/kg

**108-38-3 m-xylene:**

Acute oral toxicity	: LD50 (Rat): 4,988 mg/kg
---------------------	---------------------------



**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

Acute inhalation toxicity : LC50 (Mouse): 5267 ppm  
Exposure time: 6.00 h

Acute dermal toxicity : LD50 (Rabbit): 14.1 mg/kg

**106-42-3 p-xylene:**

Acute oral toxicity : LD50 (Rat): 3,910 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4550 ppm  
Exposure time: 4.00 h

Acute dermal toxicity : Remarks: No data available

**100-41-4 Ethyl benzene:**

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute dermal toxicity : LD50 (Rabbit): 5,510 mg/kg

**95-47-6 o-xylene:**

Acute oral toxicity : LD50 (Rat): 3,567 mg/kg

Acute inhalation toxicity : LC50 (Mouse): 4595 ppm  
Exposure time: 6.00 h

Acute dermal toxicity : Remarks: No data available

**108-88-3 Toluene:**

Acute oral toxicity : LD50 (Rat): 2,600 mg/kg

**97-88-1 n-Butyl methacrylate:**

Acute oral toxicity : LD50 (Rat): 18,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 4910 ppm

Acute dermal toxicity : LD50 (Rabbit): 10,300 mg/kg

**Skin corrosion/irritation****Product:**

Remarks: May cause skin irritation and/or dermatitis.

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

**64742-49-0 Naphtha (petroleum), hydrotreated light:**

Species: Rabbit

Method: OECD Test Guideline 404

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

Result: Repeated exposure may cause skin dryness or cracking.  
GLP: yes

**108-38-3 m-xylene:**

Species: Rabbit  
Exposure time: 24.00 h  
Result: Severe skin irritation

**106-42-3 p-xylene:**

Remarks: No data available

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate skin irritation

**95-47-6 o-xylene:**

Remarks: No data available

**97-88-1 n-Butyl methacrylate:**

Species: Rabbit  
Result: Severe skin irritation

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Rabbit  
Result: No eye irritation  
Method: OECD Test Guideline 405  
GLP: yes

**64742-49-0 Naphtha (petroleum), hydrotreated light:**

Species: Rabbit  
Result: No eye irritation  
GLP: no

**108-38-3 m-xylene:**

Species: Rabbit  
Result: Severe eye irritation  
Exposure time: 24.00 h  
Method: Draize Test

**106-42-3 p-xylene:**

Remarks: No data available

**100-41-4 Ethyl benzene:**

Species: Rabbit  
Result: Moderate eye irritation

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**95-47-6 o-xylene:**

Remarks: No data available

**97-88-1 n-Butyl methacrylate:**

Species: Rabbit

Result: Eye irritation

**Respiratory or skin sensitisation****Product:**

Remarks: Causes sensitisation.

**Components:****108-65-6 1-Methoxy-2-propanol acetate:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: yes

**64742-49-0 Naphtha (petroleum), hydrotreated light:**

Test Type: Maximisation Test

Exposure routes: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Not a skin sensitizer.

GLP: no

**97-88-1 n-Butyl methacrylate:**

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Causes sensitisation.

GLP: yes

**Carcinogenicity****IARC**

Group 2B: Possibly carcinogenic to humans

Ethyl benzene

100-41-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Further information****Product:**

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

: WC: A

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

UN/ID No. : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : III  
Labels : Flammable Liquids  
Packing instruction (cargo aircraft) : 366  
Packing instruction (passenger aircraft) : 355

**IMDG-Code**

UN number : UN 1866  
Proper shipping name : RESIN SOLUTION  
Class : 3  
Packing group : III  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

UN/ID/NA number : UN 1866  
Proper shipping name : Resin solution  
Class : 3  
Packing group : III  
Labels : FLAMMABLE LIQUID  
ERG Code : 127  
Marine pollutant : no

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
p-xylene	106-42-3	100	8961

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

m-xylene	108-38-3	2.5 %
p-xylene	106-42-3	1.1 %
Ethyl benzene	100-41-4	1.0 %

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

m-xylene	108-38-3	2.5 %
p-xylene	106-42-3	1.1 %
Ethyl benzene	100-41-4	1.0 %

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

p-xylene	106-42-3	1.1 %
Ethyl benzene	100-41-4	1.0 %

**Non-volatile (Wt)** : Refer to the product technical data sheet for VOC information.

**Massachusetts Right To Know**

m-xylene	108-38-3
p-xylene	106-42-3
Ethyl benzene	100-41-4
Benzene	71-43-2
Ethyl acrylate	140-88-5

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**Pennsylvania Right To Know**


1-Methoxy-2-propanol acetate	108-65-6
Acrylic Polymers	-
Naphtha (petroleum), hydrotreated light	64742-49-0
m-xylene	108-38-3
p-xylene	106-42-3
Ethyl benzene	100-41-4
o-xylene	95-47-6
Toluene	108-88-3

**New Jersey Right To Know**

1-Methoxy-2-propanol acetate	108-65-6
Acrylic Polymers	-
Naphtha (petroleum), hydrotreated light	64742-49-0
m-xylene	108-38-3
p-xylene	106-42-3
Ethyl benzene	100-41-4
Toluene	108-88-3

**New Jersey Trade Secret** : Not Applicable  
**Registry Number for the product (NJ TSRN)**

**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including Ethyl benzene, Benzene, Naphthalene, Ethyl acrylate, which is/are known to the State of California to cause cancer, and Toluene, Benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**


TSCA	: All components of this product are listed active and/or are exempt
Section 4 / 12(b)	: Not applicable
Section 5	Not applicable
Section 6	Not applicable

**CONAP® CE-1171 Acrylic Coating**

Version 6

Revision Date 01/05/2021

Print Date 01/05/2021

**SECTION 16. OTHER INFORMATION****Further information****NFPA:****HMIS III:**

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>3</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 01/05/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.