

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

### SECTION 1. IDENTIFICATION

Product name : DOW CORNING(R) 3140 MIL-A-46146 RTV COATING  
Product code : 000000000001665341

#### Manufacturer or supplier's details

Company name of supplier : Dow Corning Corporation  
Address : South Saginaw Road  
Midland Michigan 48686  
Telephone : (989) 496-6000  
Emergency telephone : 24 Hour Emergency Telephone : (989) 496-5900  
CHEMTREC : (800) 424-9300

#### Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents  
Electrical industry and electronics

### SECTION 2. HAZARDS IDENTIFICATION

#### GHS classification in accordance with 29 CFR 1910.1200

Reproductive toxicity : Category 2

#### GHS label elements

Hazard pictograms :



Signal Word : Warning

Hazard Statements : H361f Suspected of damaging fertility.

Precautionary Statements :

**Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.

**Storage:**  
P405 Store locked up.

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version: 7.0      Revision Date: 09/14/2017      SDS Number: 1265102-00011      Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture  
Chemical nature : Silicone elastomer

### Hazardous ingredients

Chemical name	CAS-No.	Concentration (% w/w)
Hexamethyldisilazane reaction with Silica	68909-20-6	$\geq 12 - \leq 16$
Methyltrimethoxysilane	1185-55-3	$\geq 2.1 - \leq 3.5$
Octamethylcyclotetrasiloxane	556-67-2	$\geq 0.21 - \leq 0.22$
Methanol	67-56-1	$\geq 0.1 - \leq 0.13$

## SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.

If inhaled : If inhaled, remove to fresh air.  
Get medical attention.

In case of skin contact : In case of contact, immediately flush skin with soap and plenty of water.  
Remove contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.

If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention.  
Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and delayed : Suspected of damaging fertility.

Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment

## SAFETY DATA SHEET

**DOW CORNING**

### DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

||| when the potential for exposure exists.  
Notes to physician : Treat symptomatically and supportively.

#### SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical

Unsuitable extinguishing media : None known.

Specific hazards during fire fighting : Exposure to combustion products may be a hazard to health.

Hazardous combustion products : Carbon oxides  
Silicon oxides  
Formaldehyde  
Nitrogen oxides (NO<sub>x</sub>)

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.  
Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for fire-fighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g., by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material.  
For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable

**SAFETY DATA SHEET****DOW CORNING****DOW CORNING(R) 3140 MIL-A-46146 RTV  
COATING**Version  
7.0Revision Date:  
09/14/2017SDS Number:  
1265102-00011Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

**SECTION 7. HANDLING AND STORAGE**

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : Use only with adequate ventilation.
- Advice on safe handling : Avoid inhalation of vapor or mist.  
Do not swallow.  
Avoid contact with eyes.  
Avoid prolonged or repeated contact with skin.  
Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment.  
Keep away from water.  
Protect from moisture.  
Take care to prevent spills, waste and minimize release to the environment.
- Conditions for safe storage : Keep in properly labeled containers.  
Store in accordance with the particular national regulations.
- Materials to avoid : Do not store with the following product types:  
Strong oxidizing agents

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION****Ingredients with workplace control parameters**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Hexamethyldisilazane reaction with Silica	68909-20-6	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m <sup>3</sup> / %SiO <sub>2</sub> (Silica)	OSHA Z-3
Methyltrimethoxysilane	1185-55-3	TWA	7.5 ppm	DCC OEL
Octamethylcyclotetrasiloxane	556-67-2	TWA	10 ppm	US WEEL
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm	NIOSH REL

**SAFETY DATA SHEET****DOW CORNING****DOW CORNING(R) 3140 MIL-A-46146 RTV  
COATING**

Version 7.0      Revision Date: 09/14/2017      SDS Number: 1265102-00011      Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

			260 mg/m <sup>3</sup>	
		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1

These substance(s) are inextricably bound in the product and therefore do not contribute to a dust inhalation hazard.

**II**

Hexamethyldisilazane reaction with Silica

**Occupational exposure limits of decomposition products**

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methanol	67-56-1	TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		TWA	200 ppm 260 mg/m <sup>3</sup>	NIOSH REL
		ST	250 ppm 325 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA Z-1

**Biological occupational exposure limits**

Ingredients	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Methanol	67-56-1	Methanol	Urine	End of shift (As soon as possible after exposure ceases)	15 mg/l	ACGIH BEI

**Engineering measures** : Processing may form hazardous compounds (see section 10).  
Ensure adequate ventilation, especially in confined areas.  
Minimize workplace exposure concentrations.

**Personal protective equipment**

**Respiratory protection** : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

## SAFETY DATA SHEET

**DOW CORNING**

### DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

circumstance where air purifying respirators may not provide adequate protection.

#### Hand protection

Material : Chemical-resistant gloves

Remarks : For prolonged or repeated contact use protective gloves. Choose gloves to protect hands against chemicals depending on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are located close to the working place.  
When using do not eat, drink or smoke.  
Wash contaminated clothing before re-use.  
These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may require added precautions.  
For further information regarding the use of silicones / organic oils in consumer aerosol applications, please refer to the guidance document regarding the use of these type of materials in consumer aerosol applications that has been developed by the silicone industry ([www.SEHSC.com](http://www.SEHSC.com)) or contact the Dow Corning customer service group.

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Color	: white, translucent
Odor	: slight
Odor Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available

## SAFETY DATA SHEET

**DOW CORNING**

### DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

Initial boiling point and boiling range : > 65 °C

Flash point : > 101.1 °C  
Method: closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Flammability (liquids) : Ignitable (see flash point)

Self-ignition : The substance or mixture is not classified as pyrophoric. The substance or mixture is not classified as self heating.

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Relative density : 1.05

Solubility(ies)  
Water solubility : No data available

Partition coefficient: n-octanol/water : No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : 300 Poise

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

Particle size : Not applicable

#### SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

## SAFETY DATA SHEET

**DOW CORNING**

### DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Can react with strong oxidizing agents.  
Adequate ventilation is required.  
See OSHA formaldehyde standard, 29 CFR 1910.1048  
When heated to temperatures above 180 °C (356 °F) in the presence of air, trace quantities of formaldehyde may be released.  
Hazardous decomposition products will be formed upon contact with water or humid air.  
Hazardous decomposition products will be formed at elevated temperatures.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents  
Water

**Hazardous decomposition products:**  
Contact with water or humid air : Methanol  
air

Thermal decomposition : Formaldehyde

## SECTION 11. TOXICOLOGICAL INFORMATION

### Information on likely routes of exposure

Inhalation  
Skin contact  
Ingestion  
Eye contact

### Acute toxicity

Not classified based on available information.

### Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 200 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg  
Method: Calculation method

### Ingredients:

#### Hexamethyldisilazane reaction with Silica:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg



# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version: 7.0      Revision Date: 09/14/2017      SDS Number: 1265102-00011      Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

Assessment: The substance or mixture has no acute oral toxicity

Remarks: Based on data from similar materials

### Methyltrimethoxysilane:

Acute oral toxicity : LD50 (Rat): 12.3 ml/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: Information taken from reference works and the literature.

Acute inhalation toxicity : LC50 (Rat): > 42.1 mg/l  
Exposure time: 6 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 9,500 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

### Octamethylcyclotetrasiloxane:

Acute oral toxicity : LD50 (Rat): > 4,800 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity  
Remarks: On basis of test data.

Acute inhalation toxicity : LC50 (Rat): 2975 ppm  
Exposure time: 4 h  
Test atmosphere: vapor  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: On basis of test data.

Acute dermal toxicity : LD50 (Rabbit): > 2.5 ml/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: On basis of test data.

### Methanol:

Acute oral toxicity : Acute toxicity estimate (Humans): 300 mg/kg  
Method: Expert judgment

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapor  
Method: Expert judgment  
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

Acute dermal toxicity : Acute toxicity estimate (Humans): 300 mg/kg  
Method: Expert judgment

### **Skin corrosion/irritation**

Not classified based on available information.

### **Ingredients:**

#### **Hexamethyldisilazane reaction with Silica:**

Assessment: Repeated exposure may cause skin dryness or cracking.

#### **Methyltrimethoxysilane:**

Species: Rabbit  
Result: No skin irritation  
Remarks: On basis of test data.

#### **Octamethylcyclotetrasiloxane:**

Species: Rabbit  
Result: No skin irritation  
Remarks: On basis of test data.

#### **Methanol:**

Species: Rabbit  
Result: No skin irritation

### **Serious eye damage/eye irritation**

Not classified based on available information.

### **Ingredients:**

#### **Hexamethyldisilazane reaction with Silica:**

Species: Rabbit  
Result: No eye irritation  
Remarks: Based on data from similar materials

#### **Methyltrimethoxysilane:**

Species: Rabbit  
Result: No eye irritation  
Remarks: On basis of test data.

#### **Octamethylcyclotetrasiloxane:**

Species: Rabbit  
Result: No eye irritation  
Remarks: On basis of test data.

#### **Methanol:**

Species: Rabbit

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

Result: No eye irritation

### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### Product:

Assessment: Does not cause skin sensitization.

Test Type: Buehler Test

Species: Guinea pig

Result: negative

Remarks: Based on data from similar materials

#### Ingredients:

##### Methyltrimethoxysilane:

Assessment: Probability or evidence of low to moderate skin sensitization rate in humans

Test Type: Buehler Test

Species: Guinea pig

Result: positive

Remarks: On basis of test data.

##### Octamethylcyclotetrasiloxane:

Assessment: Does not cause skin sensitization.

Test Type: Maximization Test

Species: Guinea pig

Result: negative

Remarks: On basis of test data.

##### Methanol:

Test Type: Maximization Test

Routes of exposure: Skin contact

Species: Guinea pig

Result: negative

### Germ cell mutagenicity

Not classified based on available information.

#### Ingredients:

##### Hexamethyldisilazane reaction with Silica:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

### II

#### Methyltrimethoxysilane:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.
- Test Type: Mutagenicity (in vitro mammalian cytogenetic test)  
Result: positive  
Remarks: On basis of test data.
- Test Type: Chromosome aberration test in vitro  
Result: positive  
Remarks: On basis of test data.
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative  
Remarks: On basis of test data.
- Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

#### Octamethylcyclotetrasiloxane:

- Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: On basis of test data.
- Test Type: Mutagenicity (in vitro mammalian cytogenetic test)  
Result: negative  
Remarks: On basis of test data.
- Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: On basis of test data.
- Test Type: In vitro sister chromatid exchange assay in mammalian cells  
Result: negative  
Remarks: On basis of test data.
- Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)  
Result: negative  
Remarks: On basis of test data.
- Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: Inhalation (vapor)  
Result: negative

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

Remarks: On basis of test data.

Test Type: Rodent dominant lethal test (germ cell) (in vivo)  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: On basis of test data.

Germ cell mutagenicity - Assessment : Animal testing did not show any mutagenic effects.

### Methanol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Test Type: In vitro mammalian cell gene mutation test  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Result: negative

### Carcinogenicity

Not classified based on available information.

### Ingredients:

#### Methanol:

Species: Mouse  
Application Route: inhalation (vapor)  
Exposure time: 18 Months  
Result: negative

#### IARC

No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

#### OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

#### NTP

No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Suspected of damaging fertility.

### Ingredients:

#### Methyltrimethoxysilane:

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

- Effects on fertility** : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat, male and female  
Application Route: Ingestion  
Symptoms: No effects on fertility.  
Remarks: On basis of test data.
- Effects on fetal development** : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat, male and female  
Application Route: Ingestion  
Symptoms: No effects on fetal development.  
Remarks: On basis of test data.
- Reproductive toxicity - Assessment** : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.

### **Octamethylcyclotetrasiloxane:**

- Effects on fertility** : Test Type: Two-generation reproduction toxicity study  
Species: Rat, male and female  
Application Route: inhalation (vapor)  
Symptoms: Effects on fertility.  
Remarks: On basis of test data.
- Effects on fetal development** : Test Type: Prenatal development toxicity study (teratogenicity)  
Species: Rabbit  
Application Route: inhalation (vapor)  
Symptoms: No effects on fetal development.  
Remarks: On basis of test data.
- Reproductive toxicity - Assessment** : Some evidence of adverse effects on sexual function and fertility, based on animal experiments.

### **Methanol:**

- Effects on fertility** : Test Type: Fertility/early embryonic development  
Species: Mouse  
Application Route: Ingestion  
Result: negative
- Effects on fetal development** : Test Type: Embryo-fetal development  
Species: Mouse  
Application Route: Ingestion  
Result: positive  
Remarks: The effects were seen only at maternally toxic doses.

### **STOT-single exposure**

Not classified based on available information.

## SAFETY DATA SHEET

**DOW CORNING**

### DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

#### Ingredients:

##### **Methanol:**

Target Organs: Eyes, Central nervous system  
Assessment: Causes damage to organs.

##### **STOT-repeated exposure**

Not classified based on available information.

#### Ingredients:

##### **Methyltrimethoxysilane:**

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

##### **Octamethylcyclotetrasiloxane:**

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/kg bw or less.

Routes of exposure: inhalation (vapor)

Assessment: No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Routes of exposure: Skin contact

Assessment: No significant health effects observed in animals at concentrations of 200 mg/kg bw or less.

##### **Repeated dose toxicity**

#### Ingredients:

##### **Methyltrimethoxysilane:**

Species: Rat

Application Route: inhalation (vapor)

Remarks: On basis of test data.

Species: Rat

Application Route: Ingestion

Remarks: On basis of test data.

##### **Octamethylcyclotetrasiloxane:**

Species: Rat

Application Route: Ingestion

Remarks: On basis of test data.

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0      Revision Date: 09/14/2017      SDS Number: 1265102-00011      Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

Species: Rat  
Application Route: Inhalation (vapor)  
Remarks: On basis of test data.

Species: Rabbit  
Application Route: Skin contact  
Remarks: On basis of test data.

### **Methanol:**

Species: Rat  
NOAEL: 1.06 mg/l  
Application Route: inhalation (vapor)  
Exposure time: 90 Days

### **Aspiration toxicity**

Not classified based on available information.

### **Product:**

No aspiration toxicity classification

### **Further information**

### **Ingredients:**

#### **Octamethylcyclotetrasiloxane:**

Remarks: Results from a 2 year repeated vapor inhalation exposure study to rats of octamethylcyclotetrasiloxane (D4) indicate effects (benign uterine adenomas) in the uterus of female animals. This finding occurred at the highest exposure dose (700 ppm) only. Studies to date have not demonstrated if these effects occur through pathways that are relevant to humans. Repeated exposure in rats to D4 resulted in protoporphyrin accumulation in the liver. Without knowledge of the specific mechanism leading to the protoporphyrin accumulation the relevance of this finding to humans is unknown.

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

### **Ingredients:**

#### **Methyltrimethoxysilane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 110 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia sp. (Water flea)): > 122 mg/l  
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 120 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201



# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version: 7.0      Revision Date: 09/14/2017      SDS Number: 1265102-00011      Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

Toxicity to microorganisms : EC50: > 100 mg/l  
Method: OECD Test Guideline 209

### Octamethylcyclotetrasiloxane:

Toxicity to fish : LC50 (Cyprinodon variegatus (sheepshead minnow)): > 0.0063 mg/l  
Exposure time: 336 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Mysidopsis bahia (opossum shrimp)): > 0.0091 mg/l  
Exposure time: 96 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 0.022 mg/l  
Exposure time: 72 h  
Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): >= 0.0044 mg/l  
Remarks: On basis of test data.  
No toxicity at the limit of solubility.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): >= 0.0079 mg/l  
Exposure time: 21 d  
Remarks: On basis of test data.  
No toxicity at the limit of solubility.

### Ecotoxicology Assessment

Chronic aquatic toxicity : May cause long lasting harmful effects to aquatic life.

### Methanol:

Toxicity to fish : LC50 (Lepomis macrochirus (Bluegill sunfish)): 15,400 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 22,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC (Oryzias latipes (Orange-red killifish)): 15,800 mg/l  
Exposure time: 200 h

Toxicity to microorganisms : IC50: > 1,000 mg/l  
Exposure time: 3 h

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

### Persistence and degradability

#### Ingredients:

##### **Octamethylcyclotetrasiloxane:**

Biodegradability	: Result: Not readily biodegradable. Biodegradation: 3.7 % Exposure time: 28 d Method: OECD Test Guideline 310
Stability in water	: Degradation half life: 69.3 - 144 h (24.6 °C) pH: 7 Method: OECD Test Guideline 111

##### **Methanol:**

Biodegradability	: Result: Readily biodegradable. Biodegradation: 95 % Exposure time: 20 d
------------------	---

### Bioaccumulative potential

#### Ingredients:

##### **Methyltrimethoxysilane:**

Partition coefficient: n-octanol/water	: log Pow: -2.36
--	------------------

##### **Octamethylcyclotetrasiloxane:**

Bioaccumulation	: Species: Pimephales promelas (fathead minnow) Bioconcentration factor (BCF): 12,400
Partition coefficient: n-octanol/water	: log Pow: 6.48 (25.1 °C)

##### **Methanol:**

Bioaccumulation	: Species: Leuciscus idus (Golden orfe) Bioconcentration factor (BCF): < 10
Partition coefficient: n-octanol/water	: log Pow: -0.77

### Mobility in soil

No data available

### Other adverse effects

#### Ingredients:

##### **Octamethylcyclotetrasiloxane:**

Results of PBT and vPvB assessment	: Remarks: Octamethylcyclotetrasiloxane (D4) meets the current REACH Annex XIII criteria for PBT and vPvB. In Canada, D4 has been assessed and deemed to meet the PIT criteria.
------------------------------------	---

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version:  
7.0

Revision Date:  
09/14/2017

SDS Number:  
1265102-00011

Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

However, D4 does not behave similarly to known PBT/vPvB substances. The weight of scientific evidence from field studies shows that D4 is not biomagnifying in aquatic and terrestrial food webs. D4 in air will degrade by reaction with naturally occurring hydroxyl radicals in the atmosphere. Any D4 in air that does not degrade by reaction with hydroxyl radicals is not expected to deposit from the air to water, to land, or to living organisms.

### SECTION 13. DISPOSAL CONSIDERATIONS

#### Disposal methods

Resource Conservation and Recovery Act (RCRA) : This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
If not otherwise specified: Dispose of as unused product.

### SECTION 14. TRANSPORT INFORMATION

#### International Regulations

##### UNRTDG

Not regulated as a dangerous good

##### IATA-DGR

Not regulated as a dangerous good

##### IMDG-Code

Not regulated as a dangerous good

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### Domestic regulation

##### 49 CFR

Not regulated as a dangerous good

### SECTION 15. REGULATORY INFORMATION

#### EPCRA - Emergency Planning and Community Right-to-Know

##### CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
Methanol	67-56-1	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
----------------	------------------------------	------------------------------	---

### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

**SARA 311/312 Hazards** : Reproductive toxicity

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### US State Regulations

#### Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated	70131-67-8
Hexamethyldisilazane reaction with Silica	68909-20-6
Methanol	67-56-1

#### California Prop. 65

WARNING: This product can expose you to chemicals including Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The ingredients of this product are reported in the following inventories:

NZIoC	: All ingredients listed or exempt.
TSCA	: All chemical substances in this product are either listed on the TSCA Inventory or are in compliance with a TSCA Inventory exemption.
AICS	: All ingredients listed or exempt.
IECSC	: All ingredients listed or exempt.
ENCS/ISHL	: All components are listed on ENCS/ISHL or exempted from inventory listing.
KECI	: All ingredients listed, exempt or notified.
PICCS	: All ingredients listed or exempt.
DSL	: All chemical substances in this product comply with the CEPA 1999 and NSNR and are on or exempt from listing on the Canadian Domestic Substances List (DSL).
REACH	: For purchases from Dow Corning EU legal entities, all ingredients are currently pre/registered or exempt under REACH. Please refer to section 1 for recommended uses. For purchases from non-EU Dow Corning legal entities with the intention to export into EEA please contact your DC representative/local office.
TCSI	: All ingredients listed or exempt.

## SAFETY DATA SHEET

**DOW CORNING**

### DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version  
7.0

Revision Date:  
09/14/2017


SDS Number:  
1265102-00011

Date of last issue: 03/07/2017  
Date of first issue: 02/10/2015

#### SECTION 16. OTHER INFORMATION

##### Further Information

###### NFPA:



###### HMIS® IV:

HEALTH	*	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

##### Full text of other abbreviations

ACGIH	: USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	: ACGIH - Biological Exposure Indices (BEI)
DCC OEL	: Dow Corning Guide
NIOSH REL	: USA. NIOSH Recommended Exposure Limits
OSHA Z-1	: USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
OSHA Z-3	: USA. Occupational Exposure Limits (OSHA) - Table Z-3 Mineral Dusts
US WEEL	: USA. Workplace Environmental Exposure Levels (WEEL)
ACGIH / TWA	: 8-hour, time-weighted average
ACGIH / STEL	: Short-term exposure limit
DCC OEL / TWA	: Time weighted average
NIOSH REL / TWA	: Time-weighted average concentration for up to a 10-hour workday during a 40-hour workweek
NIOSH REL / ST	: STEL - 15-minute TWA exposure that should not be exceeded at any time during a workday
OSHA Z-1 / TWA	: 8-hour time weighted average
OSHA Z-3 / TWA	: 8-hour time weighted average
US WEEL / TWA	: Time weighted average

AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized Sys-

# SAFETY DATA SHEET

**DOW CORNING**

## DOW CORNING(R) 3140 MIL-A-46146 RTV COATING

Version: 7.0	Revision Date: 09/14/2017	SDS Number: 1265102-00011	Date of last issue: 03/07/2017 Date of first issue: 02/10/2015
-----------------	------------------------------	------------------------------	---

tem; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECS - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Revision Date : 09/14/2017

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8