

Revision Number 010.0

Issue date: 10/31/2017

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:

TECHNOMELT PUR 834A known as

PURMELT QR 834A

Product type:

Restriction of Use:

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Adhesive

This product is for industrial use only.

EXPOSURE.

Item number:

IDH number:

Region:

1621666 **United States**

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1621666

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

i i	
<u>"</u>	EMERGENCY OVERVIEW
DANGER!	MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.
	STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR
	FLAMMABLE VAPORS MAY CAUSE IGNITION.
	VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND
	RESPIRATORY TRACT IRRITATION
	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING
	DIFFICULTIES IF INHALED.
į	CAUSES DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
RESPIRATORY SENSITIZATION	1
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1

SKIN SENSITIZATION SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	1
PICTOGRAM(S)	

Precautionary Statements

Prevention:

Do not breathe dust or fumes. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection. In case of inadequate ventilation wear respiratory protection.

IDH number; 1621666

Product name: TECHNOMELT PUR 834A known as PURMELT QR 834A Page 1 of 7

Response:

IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do: Continue rinsing. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. If experiencing respiratory symptoms. Call a poison center or physician. Take

off contaminated clothing.

Storage: Disposal: Not prescribed

Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazarcous Component(s)	CAS Number	Percentage*
Isocyan te terminated urethane prepolymer	Unknown	70 80.
Methyl hebis (phenylisocyanate)	101-68-8	1 - 5

^{*} Exact properties may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

la halation:

Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. Get medical attention. If not breathing, give artificial respiration.

Skin contact:

Cool melted product on skin with plenty of water. Do not remove solidified product. Cover affected areas with clean sheeting or gauze and seek immediate medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily

torn. Molten adhesive may cause severe burns.

Eje contact:

If eye contact occurs with molten material immediately cool with water. Do not

remove adhesive. Seek medical attention.

legestion:

If material is ingested, immediately contact a physician or poison control

center.

Simptoms:

See Section 11.

Notes to physician:

Persons with asthmatic-type conditions, chronic bronchitis, other chronic respiratory diseases or recurrent skin eczema or sensitization should be

excluded from working with isocyanates.

5. FIRE FIGHTING MEASURES

E tinguishing media:

Use extinguishing measures appropriate to local circumstances and the surrounding environment. Dry chemical, Carbon dioxide.

Special firefighting procedures:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. Keep unnecessary personnel away.

Unusual fire or explosion hazards:

Sealed containers at elevated temperatures or contaminated with water may rupture explosively. In case of fire, keep containers cool with water spray.

IDH number: 1621666

Product name: TECHNOMELT PUR 834A known as PURMELT QR 834A Page 2 of 7

Hazardous combustion products:

Irritating and toxic gases or fumes may be released during a fire. Isocyanate vapors. Oxides of carbon. Hydrogen cyanide.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Do not allow material to contaminate ground water system. Prevent further leakage or spillage if safe to do so.

Clean-up methods:

If product is spilled in the solid state, pick up and place in an appropriate waste disposal container. If product is spilled in the molten state, allow product to solidify before scraping up and disposing of in an appropriate waste disposal container. Persons not wearing appropriate protective equipment should be excluded from area of spill until clean-up has been completed.

7. HANDLING AND STORAGE

Handling:

Wear suitable protective clothing, safety glasses and gloves. Always be careful around molten material. Avoid skin contact with molten resins. Precaution - this product should only be heated to recommended temperatures. Hazards of pyrolysis products emitted are unknown and may be hazardous to health. If recommended temperature is exceeded, there is an increased possibility that MDI may be released. Equipment should be closely monitored. Follow suggested application temperature. Use caution if using container unloading equipment that inverts product, in order to avoid dislodging product prematurely. Do not place wet or damp solid into melt tank.

Storage:

Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or promptly disposed of. Keep containers closed when not in use. Do not let moisture contaminate this material. Product reacts with water to release carbon dioxide, which could build up pressure in closed containers and lead to bursting. Do not reseat if moisture contamination is suspected.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Isocyanate terminated trethane prepolymer	None	:None	None	None
Methylenebis(phenylisccyanate)	0.005 ppm TWA	0.02 ppm (0.2 mg/m3) Ceiling	None	None

Engineering controls:

Work should be done in an adequately ventilated area (i.e., ventilation sufficient to maintain concentrations below one half of the PEL and other relevant standards). Local exhaust ventilation is recommended when general ventilation is not sufficient to control airborne contamination. Local exhaust should be used to maintain levels below the TLV whenever MDI is processed, heated or spray applied. Monitoring of airborne isocyanates in the breathing zone of individuals should become part of the overall employee exposure characterization program. Once a person is diagnosed as sensitized to an isocyanate, no further exposure can be permitted.

IDH number: 1621666

Product name: TECHNOMELT PUR 834A known as PURMELT QR 834A Page 3 of 7

Figspiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s). A positive pressure, supplied-air respirator or a self-contained breathing apparatus is recommended when: airborne concentrations of isocyanate are known to exceed 0.005 ppm; operations are performed in a confined space or area with limited ventilation; material is heated or sprayed. Do not inhale vapors and fumes. Concentrations greater than the TLV can occur when MDI is sprayed, heated or used in a poorly ventilated area.

E lefface protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Do not wear

contact lenses.

Sit protection: Insulated gloves and long sleeved clothing are strongly recommended when

working with molten adhesive. Wear face shield:

9. PHYSICAL AND CHEMICAL PROPERTIES

Plysical state: Solid

Color: Lavender Olor: Slight

Of or threshold: Not available. Not applicable

Whor pressure:

Billing point/range:

Witting point/ range:

Not available.

Not available.

Specific gravity: 1.10

Ve por density: Not available.

Fish point: > 165.00 °C (> 329°F) Cleveland open cup

F mmable/Explosive limits - lower:
Not available.
Not available.
Not available.
Not available.
Not available.
Not available.
Not applicable
Exploration rate:
Not available.
Not applicable.
Insoluble.

Epaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VIC content:

Not available.

Not available.

0.00 %

Vicosity: Not available. Not available. Not available.

10. STABILITY AND REACTIVITY

Stable Stable

Historican Exothermic. Polymerization may occur at elevated temperature or in the presence of

incompatible materials.

Hazardous decomposition

products:

Upon decomposition, this product may yield gaseous nitrogen oxides, carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons, Hydrogen cyanide, Isocyanates,

Indompatible materials: Humid air and/or water will produce carbon dioxide which will pressurize the container.

Reaction with water, formation of CO2 Alcohols, Amines, Ammonia.

Reactivity: MDI reacts slowly with water to form carbon dioxide gas.

Container can be pressurised by carbon dioxide due to reaction with humid air

and/or water.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Eyes, Lungs

IDH number: 1621666

Product name: TECHNOMELT PUR 834A known as PURMELT QR 834A Page 4 of 7

Potential Health Effects/Symptoms

Inhalation:

Dusts from solid adhesive may cause irritation. Heating this product may release haimful vapors. May cause allergic skin and respiratory tract reaction. Methylene bisphenyl isocyanate (MDI) vapors or mist at concentrations above the TLV can irritate the mucous membranes in the respiratory tract (nose, throat, lungs) causing runny nose, sore throat, coughing, chest discomfort, shortness of breath and reduced lung function (breathing obstruction). As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to

isocyanate at levels well below the TLV. Chronic overexposure to isocyanates has been

reported to cause lung damage.

Skin contact:

Molten adhesive may cause severe burns. Repeated or prolonged skin contact may result in

allergic sensitization.

Eye contact:

Molten adhesive in eyes will cause severe and permanant damage. Vapors may also produce

eye irritation. Can cause mechanical irritation if dusts are generated.

Ingestion:

Ingestion can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Molten adhesive

may cause severe burns.

Hazardous Component	(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Isocyanate terminated un prepolymen	rethane	None	No Data
Methylenebis(phenylisoc	yanate)	Inhalation LC50 (Rat, 4 h) = 0.38 mg/l	Irritant, Respiratory, Allergen

Hazardous Component(s)	()	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Isocyanate terminated treth	thane	No	No	No
Methylenebis(phenylisocyar	anate)	.No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Do not empty into drains / surface water / ground water.

Product name: TECHNOMELT PUR 834A known as PURMELT QR 834A Page 5 of 7

IDH number: 1621666

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal:

Legal disposition of wastes is the responsibility of the owner/generator of the waste. Applicable federal, state and/or local regulations must be followed during treatment, storage, or disposal of waste containing this product. Follow all local, state, federal and provincial regulations for disposal.

zardous waste number:

To the best of our knowledge, this product is not listed nor does it meet the criteria of a hazardous waste if discarded in its purchased form. However, under RCRA, it is the responsibility of the user to determine at the time of disposal whether a product meets any of the RCRA hazardous waste criteria. This is because product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability. corrosivity, reactivity and toxicity characteristics under the new Toxicity Characteristics Leaching Procedure (TCLP) 40 Code of Federal Regulations 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any kage/configuration.

Department of Transportation Ground (49 CFR)

Proper shipping name:

Not regulated

Hazard class or division:

None None

Identification number: Packing group:

None

Ingrnational Air Transportation (ICAO/IATA)

Proper shipping name:

Not regulated

Hazard class or division:

None

Identification number:

None

Packing group:

None

Water Transportation (IMO/IMDG)

Proper shipping name:

Not regulated

Hazard class or division: Identification number:

None

Packing group:

None None

15. REGULATORY INFORMATION

United States Regulatory Information

TECA 8 (b) Inventory Status:

All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TECA 12 (b) Export Notification:

None above reporting de minimis

CARCLA/SARA Section 302 EHS:

None above reporting de minimis.

CRCLA/SARA Section 311/312:

Immediate Health, Delayed Health, Reactive

CRCLA/SARA Section 313:

This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Methylenebis(phenylisocyanate) (CAS# 101-68-8).

California Proposition 65:

This product contains a chemical known in the State of California to cause cancer.

Canada legulatory Information

CEPA DSL/NDSL Status:

All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

IDH nui ber: 1621666

Product name: TECHNOMELT PUR 834A known as PURMELT QR 834A Page 6 of 7

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2, 3, 8, 11.

Prepared by:

Product Safety and Regulatory Affairs

Issue date:

10/31/2017

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

IDH number: 1621666

	100000	· 'b	
	Constitution of the consti		
	Livering Control		
	o constante		
	de constante		
	rock to the second		
•	AND THE PROPERTY OF THE PROPER		
	TOTAL CONTRACTOR		
	ALANDAM A		
	N. Donatous		
:	Approximately and a second of the second of		
	CONTRACTOR		
:	Action Control		
	entropies .		
	015-1790-150-150-150-150-150-150-150-150-150-15		
	CHECKING THE		
	Andrew Commence of the Commenc		
	- Carachana		
	Annahamana da co		
	Acceptant		
	Personal Services		
	STATE		
	-		
:			
	derockouds Pransition		
	-		
	SCHOOL STATE		
	Control of the Contro		
	PAGE CONTRACTOR		
:	- Annual Control		
	-		
	7000000		
	A A BOOK A		
	ACCOUNTS OF THE PERSONS OF THE PERSO		
	HOMEST WAS		
	enderske skriver		
	Statistical Company		
	denote de la composito de la c		
:	Descentation of the contract o		
•	PAGE STATE OF THE		
	: 1		