



Revision date: 2020/08/07 Page: 1/10 (30690990/SDS GEN US/EN) Version: 3.0

1. Identification

Product identifier used on the label

Ardrox AV100D

Recommended use of the chemical and restriction on use

Recommended use*: corrosion inhibitor

Unsuitable for use: Uses other than recommended

Details of the supplier of the safety data sheet

Company: Chemetall U.S., Inc. 675 Central Avenue New Providence, NJ 07974 - USA +1 800 526-4473 sds.na-chemetall@basf.com

Emergency telephone number

Telephone: 800-424-9300, 1-703-527-3887

Other means of identification

organic solvents Chemical family:

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
Aguatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Flam. Liq.	3	Flammable liquids

Label elements

^{*} The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Revision date : 2020/08/07 Page: 2/10

Version: 3.0 (30690990/SDS_GEN_US/EN)

Pictogram:



Signal Word: Warning

Hazard Statement:

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H401 Toxic to aquatic life.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statements (Prevention):

P210 Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing and eye protection or face

protection.

P240 Ground and bond container and receiving equipment.

P233 Keep container tightly closed.

P264 Wash contaminated body parts thoroughly after handling.

P242 Use only non-sparking tools.

P241 Use explosion-proof electrical, ventilating and lighting equipment.

P243 Take action to prevent static discharges.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES; Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 If eye irritation persists: Get medical attention.

P303 + P361 + P353 IF ON SKIN (or hair): Remove or Take off immediately all contaminated

clothing. Rinse skin with water or shower.

P332 + P313 If skin irritation occurs: Get medical attention.

P362 + P364 Take off contaminated clothing and wash it before reuse.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P370 + P378 In case of fire: Use water spray for extinction.

Precautionary Statements (Storage):

P403 + P235 Store in a well-ventilated place. Keep cool.

Precautionary Statements (Disposal):

P501 Dispose of contents and container to hazardous or special waste

collection point.

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Limestone

Revision date: 2020/08/07 Page: 3/10

Version: 3.0 (30690990/SDS_GEN_US/EN)

CAS Number: 1317-65-3

Content (W/W): >= 10.0 - < 15.0% Synonym: No data available.

Ethanol, 2,2'-(9-octadecenylimino)bis-

CAS Number: 25307-17-9 Content (W/W): >= 1.0 - < 3.0% Synonym: No data available.

Naphtha (petroleum), hydrotreated heavy

CAS Number: 64742-48-9
Content (W/W): >= 15.0 - < 30.0%
Synonym: No data available.

Distillates (petroleum), solvent-dewaxed heavy paraffinic

CAS Number: 64742-65-0 Content (W/W): >= 7.0 - < 10.0%

Synonym: H304

barium bis(di C8-C10, branched, C9 rich, alkylnaphthalenesul

CAS Number: 25619-56-1 Content (W/W): >= 1.0 - < 3.0% Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Remove affected person from danger area. Immediately remove contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

If inhaled:

Remove the affected individual into fresh air and keep the person calm. If symptoms persist, seek medical advice. If breathing is irregular or stopped, administer artificial respiration.

If on skin:

If symptoms persist, seek medical advice. Remove contaminated clothing. Wash skin with soap and water, rinse abundantly. Do NOT use solvents or thinners.

If in eyes:

Remove contact lenses, if present. Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist. Immediate medical attention required.

If swallowed:

Do not induce vomiting. Rinse mouth thoroughly with water, seek medical attention. If adverse health effects develop seek medical attention.

Most important symptoms and effects, both acute and delayed

Revision date: 2020/08/07

Page: 4/10

Version: 3.0 (30690990/SDS_GEN_US/EN)

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Naphtha (petroleum), hydrotreated heavy

Symptoms: Overexposure may cause:, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps, Ingestion may provoke the following symptoms:, asphyxia, dyspnea, choking, respiratory arrest, circulatory collapse, death

Information on: Limestone

Symptoms: Overexposure may cause:, rhinitis, irritation of the mucous membranes, irritates the eyes and respiratory tract, skin irritation, coughing, nausea, vomiting, dizziness, diarrhea, abdominal

cramps

Hazards: Eye irritation skin irritation

Indication of any immediate medical attention and special treatment needed

Note to physician

Antidote:

No known specific antidote.

Treatment:

Symptomatic treatment (decontamination, vital functions).

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:

carbon dioxide, alcohol-resistant foam, dry powder, water spray

Unsuitable extinguishing media for safety reasons:

water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:

carbon oxides

Fire will produce dense black smoke. Inhalation of dangerous decomposition products may cause serious damage to health.

Advice for fire-fighters

Protective equipment for fire-fighting:

Appropriate breathing apparatus may be required.

Further information:

Cool closed containers in the vicinity of the source of fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Avoid breathing vapours. Keep away from sources of ignition. Ensure adequate ventilation. Advice on product handling can be found in sections 7 and 8 of this safety data sheet.

Revision date: 2020/08/07 Page: 5/10

(30690990/SDS_GEN_US/EN) Version: 3.0

Environmental precautions

Do not allow to enter drains or waterways. Do not discharge into the subsoil/soil. If the product enters drains or sewers, the local water company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the Environment Agency.

Methods and material for containment and cleaning up

Contain and collect spillage with non-combustible absorbent materials, e.g. sand, earth, vermiculite, diatomaceous earth and place in a suitable container for diposal according with the waste regulations (see section 13). Clean preferably with a detergent; avoid the use of solvents. Ensure adequate ventilation.

7. Handling and Storage

Precautions for safe handling

Provide good ventilation of working area (local exhaust ventilation if necessary). Do not return residues to the storage containers. Smoking, eating and drinking are forbidden in application area. For personal protection see section 8. Comply with the health and safety at work laws. Avoid inhalation of vapour and spray mist. The workplace should be equipped with an emergency shower and eve-rinsing facility. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice.

Protection against fire and explosion:

Avoid all sources of ignition: heat, sparks, open flame. Product may charge electrostatically: always use earthing leads when transferring from one container to another and earth containers. It is recommended that operators should wear antistatic clothing and footwear. Solvent vapours are heavier than air and spread along floors. Vapour forms explosive mixtures with air. The relevant fire protection measures should be noted. Use explosion-proof equipment.

Conditions for safe storage, including any incompatibilities

Suitable materials for containers: High density polyethylene (HDPE), Low density polyethylene (LDPE), Polyethylenetherephtalate (PET), Polypropylene (PP), Carbon steel (Iron), tinned carbon steel (Tinplate)

Further information on storage conditions: The entrance to storage rooms is to be granted only to appropriately trained personnel. Keep only in the original container. Keep container dry. Keep container tightly closed in a cool, well-ventilated place. Avoid direct sunlight. Keep away from heat. Protect from frost.

Storage stability:

Storage temperature: 5 - 35 °C Storage duration: 36 Months

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

PEL 5 mg/m3 Respirable fraction; PEL 15 OSHA PEL Limestone

mg/m3 Total dust; TWA value 5 mg/m3 Respirable fraction; TWA value 15 mg/m3

Total dust;

Distillates (petroleum),

OSHA PEL

PEL 500 ppm 2,000 mg/m3; PEL 5 mg/m3

solvent-dewaxed heavy

Mist: TWA value 5 mg/m3 Mist;

TWA value 5 mg/m3 Inhalable fraction;

paraffinic

ACGIH TLV

Revision date: 2020/08/07

Page: 6/10 Version: 3.0 (30690990/SDS_GEN_US/EN)

Advice on system design:

Use only in well-ventilated areas.

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Hand protection:

chloroprene rubber (Neoprene), Use suitable protective gloves made of nitrile rubber or butyl rubber. Please observe the glove manufacturer's instructions on permeability and ruptur times as well as the specific workplace conditions., Chemical resistant protective gloves (EN 374), Further information on penetration time is available from the manufacturer of the glove., The protection glove should be tested for its specific suitability (e.g. mechanical strength, product compatibility, anti-static properties).

Eye protection:

Tightly fitting safety goggles (splash goggles) (e.g. EN 166)

Body protection:

Chemical resistant protective clothing according to DIN EN 13034 (Type 6)

General safety and hygiene measures:

Do not breathe vapour/spray. Eye wash fountains and safety showers must be easily accessible. Avoid contact with the skin, eyes and clothing. Handle in accordance with good industrial hygiene and safety practice. Remove contaminated clothing immediately and dispose of safely. Hands and/or face should be washed before breaks and at the end of the shift. Keep separated from food stuffs and feed stocks.

9. Physical and Chemical Properties

Form:

No data available. Odour:

No applicable information available. Odour threshold:

beige Colour:

not applicable pH value: not determined solidification

temperature:

not determined Melting point: 150 - 200 °C onset of boiling: 150 - 200 °C Boiling range:

No applicable information available. Sublimation point:

47 °C Flash point:

Flammable liquid and vapour. Flammability:

Lower explosion limit: not determined

No applicable information available. Upper explosion limit:

not determined Autoignition:

(20°C) Vapour pressure:

not determined

(DIN 51757) 0.99 g/cm3 Density:

(20°C)

No applicable information available. Relative density: No applicable information available. Vapour density: No applicable information available. Partitioning coefficient n-

octanol/water (log Pow):

Revision date: 2020/08/07 Page: 7/10 (30690990/SDS GEN US/EN) Version: 3.0

Thermal decomposition: Viscosity, dynamic:

No applicable information available. No applicable information available.

Viscosity, kinematic:

122 mm2/s (40°C)

Solubility in water: Miscibility with water: insoluble immiscible

Solubility (quantitative): Solubility (qualitative):

No applicable information available. No applicable information available. No applicable information available.

Molar mass: Evaporation rate:

No applicable information available.

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

Vapours may form explosive mixture with air.

Conditions to avoid

Avoid all sources of ignition: heat, sparks, open flame. Avoid direct sunlight. Avoid heat. Avoid freezing.

Incompatible materials

strong oxidizing agents, strong bases, strong acids

Hazardous decomposition products

Decomposition products:

When exposed to high temperatures hazardous decomposition products such as carbon monoxide, carbon dioxide, smoke, oxides of nitrogen may be produced., No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No applicable information available.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

No applicable information available.

Inhalation

Revision date: 2020/08/07 Page: 8/10

Version: 3.0 (30690990/SDS_GEN_US/EN)

No applicable information available.

<u>Dermal</u>

No applicable information available.

Irritation / corrosion

Assessment of irritating effects: Contact may result in skin irritation. Causes serious eye irritation.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Based on available Data, the classification criteria are not met.

12. Ecological Information

Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Toxic to aquatic life. Harmful to aquatic life with long lasting effects. Do not allow to enter drains or waterways. There are no test results available for this product.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

No data available concerning biodegradation and elimination.

Bioaccumulative potential

Bioaccumulation potential

No data available.

Mobility in soil

Assessment transport between environmental compartments

No data available.

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements.

Container disposal:

Contaminated packaging should be emptied as far as possible and disposed of in the same manner as the substance/product.

14. Transport Information

Land transport

USDOT

Hazard class:

ì

Packing group:

III

ID number:

UN 1139

Revision date: 2020/08/07

Version: 3.0

Page: 9/10 (30690990/SDS GEN US/EN)

Hazard label:

3

Proper shipping name:

COATING SOLUTION

Sea transport

IMDG

Hazard class:

3

Packing group:

111

ID number:

UN 1139

Hazard label:

3

Marine pollutant:

NO

Proper shipping name:

COATING SOLUTION

Air transport

IATA/ICAO

3

Hazard class: Packing group:

Ш

ID number:

UN 1139

Hazard label:

Proper shipping name:

COATING SOLUTION

15. Regulatory Information

Federal Regulations

Registration status:

Chemical

TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

CAS Number

Chemical name

25619-56-1

barium bis(di C8-C10, branched, C9 rich,

alkylnaphthalenesul

CERCLA RQ

CAS Number

Chemical name

1000 LBS

25619-56-1

barium bis(di C8-C10, branched, C9 rich,

alkylnaphthalenesul

State regulations

State RTK	CAS Number	Chemical name
NJ	64742-48-9	Naphtha (petroleum), hydrotreated heavy (benzene <
	1317-65-3	0,1 %)
	25619-56-1	Limestone
		barium bis(di C8-C10, branched, C9 rich,
		alkylnaphthalenesul
PA	1317-65-3	Limestone
	8006-54-0	lanolin
	64742-48-9	Naphtha (petroleum), hydrotreated heavy (benzene <
	64742-65-0	0,1 %)
	25619-56-1	Distillates (petroleum), solvent-dewaxed heavy paraffinic
		barium bis(di C8-C10, branched, C9 rich,

Revision date: 2020/08/07 Page: 10/10

Version: 3.0 (30690990/SDS_GEN_US/EN)

alkylnaphthalenesul

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 2 Fire: 2 Reactivity: 1 Special:

HMIS III rating

Health: 2 Flammability: 2 Physical hazard: 1

16. Other Information

SDS Prepared by:

Chemetall (now part of BASF Group) NA Product Regulations

SDS Prepared on: 2020/08/07

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. **END OF DATA SHEET**