

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

**SECTION 1. IDENTIFICATION**

Product name : EpoxyLite® C 6203 Hi Temp Hardener

**Manufacturer or supplier's details**Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)

Emergency telephone number : INFOTRAC - 1-800-535-5053

**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.  
Refer to Section 15 for any restrictions that may apply**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Serious eye damage : Category 1

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

H350 May cause cancer.  
 H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**Precautionary statements**
**: Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P285 In case of inadequate ventilation wear respiratory protection.

**Response:**

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P363 Wash contaminated clothing before reuse.

**Storage:**

P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Chemical nature : Modified Aromatic Anhydride

**Hazardous components**

Component	CAS-No.	Concentration (%)
Pyromellitic dianhydride	89-32-7	>= 68 - < 69
Crystalline silica	14808-60-7	>= 15 - < 16

## EpoxyLite® C 6203 Hi Temp Hardener

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	>= 14 - < 15
1,2,4,5-Benzenetetracarboxylic acid	89-05-4	>= 1 - < 2

### SECTION 4. FIRST AID MEASURES

- General advice** : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled** : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact** : If on skin, rinse well with water.
- In case of eye contact** : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.  
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
Continue rinsing eyes during transport to hospital.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed** : Keep respiratory tract clear.  
Do NOT induce vomiting.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

### SECTION 5. FIREFIGHTING MEASURES

- Unsuitable extinguishing media** : High volume water jet
- Specific hazards during firefighting** : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information** : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters** : Wear self-contained breathing apparatus for firefighting if necessary.

## EpoxyLite® C 6203 Hi Temp Hardener

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Avoid dust formation.  
Avoid breathing dust.  
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Keep in suitable, closed containers for disposal.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of respirable particles.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

Crystalline silica	14808-60-7	TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica		TWA (respirable)	250 mppcf / %SiO <sub>2</sub> +5	OSHA Z-3
Crystalline silica		TWA (respirable)	10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
Crystalline silica		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
Magnesium Silicate Talc (contains no asbestos fibers)		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH

Hazardous components without workplace control parameters

**Engineering measures** : Use with adequate ventilation.  
 All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)  
 This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.  
 Repeated inhalation of such dust may cause lung injury.

**Personal protective equipment**

**Respiratory protection** : In the case of dust or aerosol formation use respirator with an approved filter.  
 Dust safety masks are recommended when the dust concentration is more than 10 mg/m<sup>3</sup>.

**Hand protection**  
**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Eye wash bottle with pure water  
 Tightly fitting safety goggles  
 Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
 When using do not smoke.  
 Wash hands before breaks and at the end of workday.

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: solid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Vapour pressure	: No data available
Flash point	: > 201 °F (> 94 °C) Method: No information available. Information taken from reference works and the literature.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.9048 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

Viscosity, kinematic : Not applicable

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Hazardous decomposition products : Carbon monoxide in a fire.  
Nitrogen oxides in a fire.**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Components:****89-32-7 Pyromellitic dianhydride:**

Acute dermal toxicity : LD50 : Remarks: No data available

**Skin corrosion/irritation****Product:**

Remarks: Extremely corrosive and destructive to tissue.

**Components:****89-32-7 Pyromellitic dianhydride:**

Remarks: No data available

**Serious eye damage/eye irritation****Product:**

Remarks: May cause irreversible eye damage.

**Components:****89-32-7 Pyromellitic dianhydride:**

Species: Rabbit

Result: Severe eye irritation

Method: Draize Test

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

**Respiratory or skin sensitisation**
**Product:**

Remarks: Causes sensitisation.

**Components:**
**89-32-7 Pyromellitic dianhydride:**

Result: No data available

**Carcinogenicity**

<b>IARC</b>	Group 1: Carcinogenic to humans	
	Crystalline silica	14808-60-7
<b>OSHA</b>	OSHA specifically regulated carcinogen	
	Crystalline silica	14808-60-7
<b>NTP</b>	Known to be human carcinogen	
	Crystalline silica	14808-60-7
	Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**Further information**
**Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**
**Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

	very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.
Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**
**Disposal methods**

EPA Hazardous Waste Code(s) : none

Waste from residues : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION**
**International Regulations**
**IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations**
**49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION**

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**EpoxyLite® C 6203 Hi Temp Hardener**

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

**Non-volatile (Wt)** : Refer to the product technical data sheet for VOC information.

**Massachusetts Right To Know**

Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**Pennsylvania Right To Know**

Pyromellitic dianhydride	89-32-7
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**New Jersey Right To Know**

Pyromellitic dianhydride	89-32-7
--------------------------	---------

## EpoxyLite® C 6203 Hi Temp Hardener

Version 6

Revision Date 07/29/2021

Print Date 07/29/2021

Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
1,2,4,5-Benzenetetracarboxylic acid	89-05-4

**New Jersey Trade Secret** : NOT APPLICABLE  
**Registry Number for the product (NJ TSRN)**

### California Prop. 65

**⚠ WARNING:** This product can expose you to chemicals including Crystalline silica, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

**TSCA** : All components of this product are listed active and/or are exempt

**Section 4 / 12(b)** : Not applicable


**Section 5** : Not applicable

**Section 6** : Not applicable

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
 2 = Moderate, 3 = High  
 4 = Extreme, \* = Chronic

Revision Date : 07/29/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

**SECTION 1. IDENTIFICATION**

Product name : EpoxyLite® E 6203 Hi Temp Resin

**Manufacturer or supplier's details**Company : ELANTAS PDG, INC.  
5200 North 2nd Street  
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : [www.elantas.com](http://www.elantas.com)E-mail address : [Todd.Thomas@altana.com](mailto:Todd.Thomas@altana.com)

Emergency telephone number : INFOTRAC - 1-800-535-5053

**Recommended use of the chemical and restrictions on use**

Recommended use : Electrical Insulation

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.  
Refer to Section 15 for any restrictions that may apply**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.  
H350 May cause cancer.

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

**Precautionary statements**
**: Prevention:**

P201 Obtain special instructions before use.  
 P202 Do not handle until all safety precautions have been read and understood.  
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
 P264 Wash skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P272 Contaminated work clothing should not be allowed out of the workplace.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**  
 P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
 P337 + P313 If eye irritation persists: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.

**Storage:**  
 P405 Store locked up.

**Disposal:**  
 P501 Dispose of contents/ container to an approved waste disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**
**Chemical nature** : Modified epoxy resin

**Hazardous components**

Component	CAS-No.	Concentration (%)
Epoxy Resin	28064-14-4	>= 73 - < 74
Crystalline silica	14808-60-7	>= 11 - < 12
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	>= 10 - < 11
Epoxy Resin	25068-38-6	>= 3 - < 4

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Show this safety data sheet to the doctor in attendance.  
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.  
If on skin, rinse well with water.  
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.  
Remove contact lenses.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.  
Keep respiratory tract clear.  
Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.

**SECTION 5. FIREFIGHTING MEASURES**

- Unsuitable extinguishing media : High volume water jet
- Further information : Standard procedure for chemical fires.  
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## EpoxyLite® E 6203 Hi Temp Resin

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
Keep in suitable, closed containers for disposal.  
Absorbent paper or other organic material used for cleaning up resin is a fire hazard, as heat and spontaneous combustion can occur, particularly if the resin was catalyzed. Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.

### SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Dispose of rinse water in accordance with local and national regulations.  
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.  
The chemical reaction that cures mixed epoxy is exothermic (heat generating). If left to cure in a contained mass, such as in a mixing vessel, it can generate enough heat to melt plastic, burn skin or ignite surrounding combustible materials. The larger or thicker the epoxy mass, the more heat generated.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.  
Keep container tightly closed in a dry and well-ventilated place.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Crystalline silica	14808-60-7	TWA (total dust)	30 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica		TWA	250 mppcf /	OSHA Z-3

## EpoxyLite® E 6203 Hi Temp Resin

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

Crystalline silica		(respirable) TWA (respirable)	%SiO <sub>2</sub> +5 10 mg/m <sup>3</sup> / %SiO <sub>2</sub> +2	OSHA Z-3
Crystalline silica		TWA (respirable dust fraction)	0.1 mg/m <sup>3</sup>	OSHA P0
Crystalline silica		TWA (Respirable fraction)	0.025 mg/m <sup>3</sup> (Silica)	ACGIH
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
Magnesium Silicate Talc (contains no asbestos fibers)		TWA (Respirable fraction)	2 mg/m <sup>3</sup>	ACGIH

Hazardous components without workplace control parameters

**Engineering measures** : Use with adequate ventilation.  
All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)  
This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.  
Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.  
Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.  
Repeated inhalation of such dust may cause lung injury.

### Personal protective equipment

**Respiratory protection** : In the case of vapour formation use a respirator with an approved filter.

**Hand protection**  
**Remarks** : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

**Eye protection** : Eye wash bottle with pure water  
Tightly fitting safety goggles  
Wear face-shield and protective suit for abnormal processing problems.

**Skin and body protection** : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

**Hygiene measures** : When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and at the end of workday.

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	: liquid
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: No data available
Vapour pressure	: No data available
Flash point	: > 201 °F (> 94 °C) Method: No information available. Information taken from reference works and the literature.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.8300 g/cm <sup>3</sup> (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

Viscosity, kinematic : > 21 mm<sup>2</sup>/s (104 °F (40 °C))**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous reactions : No decomposition if stored and applied as directed.

Conditions to avoid : No data available

Hazardous decomposition products : The by-products expected in incomplete pyrolysis or combustion of epoxy resins are mainly phenolics, CO and water.

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure****Acute toxicity****Product:**Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation methodAcute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg  
Method: Calculation method**Components:****25068-38-6 Epoxy Resin:**

Acute oral toxicity : LD50 (Rat): 11,400 mg/kg

LD50 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420  
GLP: yes

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 23,400 mg/kg

LD50 (Rat, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

## EpoxyLite® E 6203 Hi Temp Resin

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

### Skin corrosion/irritation

#### Product:

Remarks: May cause skin irritation and/or dermatitis.

#### Components:

##### 25068-38-6 Epoxy Resin:

Species: Rabbit

Result: Moderate skin irritation

Species: Rabbit

Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

### Serious eye damage/eye irritation

#### Product:

Remarks: May cause irreversible eye damage.

#### Components:

##### 25068-38-6 Epoxy Resin:

Species: Rabbit

Result: Eye irritation

### Respiratory or skin sensitisation

#### Product:

Remarks: Causes sensitisation.

#### Components:

##### 25068-38-6 Epoxy Resin:

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

### Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	Crystalline silica	14808-60-7
OSHA	OSHA specifically regulated carcinogen	
	Crystalline silica	14808-60-7

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

<b>NTP</b>	Known to be human carcinogen	
	Crystalline silica	14808-60-7
	Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

**Aspiration toxicity**
**Components:**
**25068-38-6 Epoxy Resin:**

No aspiration toxicity classification

**Further information**
**Product:**

Remarks: No data available

**SECTION 12. ECOLOGICAL INFORMATION**
**Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**
**Product:**

Results of PBT and vPvB assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**Regulation**

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

**Remarks**

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

**Additional ecological information**

: No data available

**EpoxyLite® E 6203 Hi Temp Resin**

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

EPA Hazardous Waste Code(s) : none

Waste from residues : Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company. Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of. Dispose of the solid mass only if cure is complete and the mass has cooled. Follow federal, state or local disposal regulations.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers.

**SECTION 14. TRANSPORT INFORMATION****International Regulations****IATA-DGR**

Not regulated as a dangerous good

**IMDG-Code**

Not regulated as a dangerous good

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****49 CFR**

Not regulated as a dangerous good

**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

**SARA 304 - Emergency Release Notification**

This material does not contain any components with a section 304 EHS RQ.

## EpoxyLite® E 6203 Hi Temp Resin

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

### US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

**SARA 311/312 Hazards** : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

### Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM1 Intermediate or Final VOC's (40 CFR 60.489).

**Non-volatile (Wt)** : Refer to the product technical data sheet for VOC information.

### Massachusetts Right To Know

Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

### Pennsylvania Right To Know

Epoxy Resin	28064-14-4
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Epoxy Resin	25068-38-6

### New Jersey Right To Know

Epoxy Resin	28064-14-4
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Epoxy Resin	25068-38-6

## EpoxyLite® E 6203 Hi Temp Resin

Version 9

Revision Date 07/29/2021

Print Date 07/29/2021

**New Jersey Trade Secret Registry Number for the product (NJ TSRN)** : NOT APPLICABLE

### California Prop. 65

⚠ **WARNING:** This product can expose you to chemicals including Crystalline silica, Phenyl glycidyl ether, which is/are known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### The components of this product are reported in the following inventories:

**TSCA** : All components of this product are listed active and/or are exempt

**Section 4 / 12(b)** : Not applicable


**Section 5** : Not applicable

**Section 6** : Not applicable

## SECTION 16. OTHER INFORMATION

### Further information

#### NFPA:



#### HMIS III:

<b>HEALTH</b>	<b>2*</b>
<b>FLAMMABILITY</b>	<b>1</b>
<b>PHYSICAL HAZARD</b>	<b>0</b>

0 = not significant, 1 = Slight,  
2 = Moderate, 3 = High  
4 = Extreme, \* = Chronic

Revision Date : 07/29/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.