

Revision Number: 007.0

Issue date: 10/13/2023

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name:266 TIProduct type/use:AnaenRestriction of Use:NoneCompany address:Henkel CorporationOne Henkel WayRocky Hill, Connecticut 06067

266 Threadlocker High Strength Anaerobic Sealant None identified

### 2. HAZARDS IDENTIFICATION

	EMERGENCY OVERVIEW
DANGER:	CAUSES SKIN IRRITATION.
	MAY CAUSE AN ALLERGIC SKIN REACTION.
	CAUSES SERIOUS EYE IRRITATION.
	TOXIC IF INHALED.
	SUSPECTED OF CAUSING CANCER.
	MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR
	REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
ACUTE TOXICITY INHALATION	3
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
CARCINOGENICITY	2
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



#### **Precautionary Statements**

Prevention:	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face protection.
Response:	F ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage: Disposal:	Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*	
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	193486-90-7	30 - 60	
Maleimide resin	3006-93-7	10 - 30	
Hydroxyalkyl methacrylate	27813-02-1	5 - 10	
Ethene, tetrafluoro-, homopolymer	9002-84-0	1 - 5	
Ethene, homopolymer	9002-88-4	1 - 5	
Cumene hydroperoxide	80-15-9	1 - 5	
Saccharin	81-07-2	1 - 5	
1-Acetyl-2-phenylhydrazine	114-83-0	0.1 - 1	
Polypropylene glycol monomethacrylate	39420-45-6	0.1 - 1	

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.	
Skin contact:	Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Wash clothing before reuse. Get medical attention.	
Eye contact:	Rinse immediately with plenty of water, also under the eyelids, for at least 1 minutes. Get medical attention.	
Ingestion:	DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention.	
Symptoms:	See Section 11.	
5. F	IRE FIGHTING MEASURES	
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.	
Special firefighting procedures:	Wear self-contained breathing apparatus and full protective clothing, such a turn-out gear. In case of fire, keep containers cool with water spray.	
Unusual fire or explosion hazards:	Uncontrolled polymerization may occur at high temperatures resulting in explosions or rupture of storage containers.	
Hazardous combustion products:	Oxides of carbon. Oxides of nitrogen. Formaldehyde. Irritating organic vapours.	
6. ACCII	DENTAL RELEASE MEASURES	

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Clean-up methods:

Do not allow product to enter sewer or waterways.

Remove all sources of ignition. Evacuate and ventilate spill area; dike spill to prevent entry into water system; wear full protective equipment during cleanup. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up as much material as possible. Store in a partly filled, closed container until disposal. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

# 7. HANDLING AND STORAGE

Handling:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Use only with adequate ventilation. Keep container closed. Refer to Section 8.

Storage:

For safe storage, store at or below 38 °C (100.4 °F) Keep in a cool, well ventilated area away from heat, sparks and open flame. Keep container tightly closed until ready for use.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	None	None	None	None
Maleimide resin	None	None	None	None
Hydroxyalkyl methacrylate	None	None	None	1 ppm TWA 3 ppm STEL
Ethene, tetrafluoro-, homopolymer	None	None	None	10 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.
Ethene, homopolymer	10 mg/m3 TWA Inhalable particles. 3 mg/m3 TWA Respirable particles.	15 MPPCF TWA Respirable fraction. 15 mg/m3 TWA Total dust. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 5 mg/m3 PEL Respirable fraction. 15 mg/m3 PEL Total dust.	None	None
Cumene hydroperoxide	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Saccharin	None	None	None	None
1-Acetyl-2-phenylhydrazine	None	None	None	None
Polypropylene glycol monomethacrylate	None	None	None	None

Engineering controls:

**Respiratory protection:** 

Eye/face protection:

limit(s). Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety

Use NIOSH approved respirator if there is potential to exceed exposure

showers and eye wash stations should be available.

Provide adequate local exhaust ventilation to maintain worker exposure below

Skin protection:

Use chemical resistant, impermeable clothing including gloves and either an apron or body suit to prevent skin contact. Neoprene gloves.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

exposure limits.

Physical state: Color: Odor: Odor threshold: pH: Vapor pressure:

Boiling point/range: Melting point/ range: Specific gravity: Vapor density: IDH number: 232327 Liquid Red, Orange Mild Not available. Not applicable, Product is non-polar/aprotic. <  $6.67 \text{ mbar } (27 \text{ }^{\circ}\text{C} (80.6 \text{ }^{\circ}\text{F})) < 300 \text{ mbar } (50 \text{ }^{\circ}\text{C} (122^{\circ}\text{F})) \text{ no method / method}$ unknown <  $0.13 \text{ mbar } (20 \text{ }^{\circ}\text{C} (68^{\circ}\text{F}))$ >  $150 \text{ }^{\circ}\text{C} (> 302^{\circ}\text{F})$ Not applicable, Product is a liquid 1.1937 >  $120 \text{ }^{\circ}\text{C}$ 

Page 3 of 6

Product name: 266 Threadlocker High Strength

Flash point: Flammable/Explosive limits - lower: Flammable/Explosive limits - upper: Autoignition temperature: Flammability: Evaporation rate: Solubility in water: Solubility in water: Partition coefficient (n-octanol/water): VOC content: Viscosity: Decomposition temperature: > 100.00 °C (> 212°F); No flash point up to 100 °C Not available. Not available. Not available. The product is not flammable. Not available. Slight Miscible Not available. 1.16 %; 11.08 g/l Not available. Not available. Not available. Not available.

## **10. STABILITY AND REACTIVITY**

Stability:	Stable under normal conditions of storage and use.	
Hazardous reactions:	None under normal processing. Polymerization may occur at elevated temperature or in the presence of incompatible materials.	
Hazardous decomposition products:	Oxides of carbon. Formaldehyde. Irritating organic vapours. Oxides of nitrogen.	
Incompatible materials:	Strong acids and oxidizing agents. Amines. Sulfur. Strong alkalis. Reducing agents. Peroxides. Azo-compounds.	
Reactivity:	Not available.	
Conditions to avoid:	Elevated temperatures. Heat, flames, sparks and other sources of ignition. Store away from incompatible materials.	
11. TOXICOLOGICAL INFORMATION		

Relevant routes of exposure:

Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

#### Inhalation:

Toxic by inhalation. Inhalation of vapors or mists of the product may be irritating to the respiratory system. Skin contact: Causes skin irritation. May cause allergic skin reaction. Eye contact: Causes serious eye irritation. Ingestion: May cause gastrointestinal tract irritation if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	None	Allergen, Irritant
Maleimide resin	None	No Target Organs
Hydroxyalkyl methacrylate	None	Irritant, Allergen
Ethene, tetrafluoro-, homopolymer	None	No Target Organs
Ethene, homopolymer	None	No Target Organs
Cumene hydroperoxide	None	Allergen, Central nervous system, Corrosive, Irritant, Mutagen
Saccharin	Oral LD50 (Mouse) = 17 g/kg	No Target Organs
1-Acetyl-2-phenylhydrazine	Oral LD50 (Mouse) = 270 mg/kg	Allergen, Blood, Kidney, Mutagen, Some evidence of carcinogenicity
Polypropylene glycol monomethacrylate	None	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silsesquioxanes, 3-[(2-methyl-1-oxo-2- propenyl)oxy]propyl Ph, polymers with silicic acid (H4SiO4) tetra-Et ester	No	No	No
Maleimide resin	No	No	No
Hydroxyalkyl methacrylate	No	No	No
Ethene, tetrafluoro-, homopolymer	No	No	No
Ethene, homopolymer	No	No	No
Cumene hydroperoxide	No	No	No
Saccharin	No	No	No
1-Acetyl-2-phenylhydrazine	No	No	No
Polypropylene glycol monomethacrylate	No	No	No

## **12. ECOLOGICAL INFORMATION**

**Ecological information:** 

Not available.

## **13. DISPOSAL CONSIDERATIONS**

Information provided is for unused product only.

Recommended method of disposal:

Follow all local, state, federal and provincial regulations for disposal.

## **14. TRANSPORT INFORMATION**

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (	49 CFR)
Proper shipping name:	RQ, Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III
DOT Hazardous Substance(s):	alpha,alpha-Dimethylbenzylhydroperoxide
International Air Transportation (ICAO/IATA)	
Proper shipping name:	RQ, Environmentally hazardous substance, liquid, n.o.s.
Hazard class or division:	9
Identification number:	UN 3082
Packing group:	III

Water Transportation (IMO/IMDG) Proper shipping name: Hazard class or division: Identification number: Packing group:

RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. 9 UN 3082 III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: TSCA 12 (b) Export Notification:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory. None above reporting de minimisNone above reporting de minimis	
CERCLA/SARA Section 302 EHS: CERCLA/SARA Section 311/312: CERCLA/SARA Section 313:	None above reporting de minimis. Immediate Health, Delayed Health This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Cumene hydroperoxide (CAS# 80-15-9). Saccharin (CAS# 81-07-2).	
CERCLA Reportable quantity: Cumene hydroperoxide (CAS# 80-15-9) 10 lbs. (4.54 kg)		
California Proposition 65:	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	
Canada Regulatory Information		
CEPA DSL/NDSL Status:	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.	

**16. OTHER INFORMATION** 

This safety data sheet contains changes from the previous version in sections: 3,8,9,11,13,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 10/13/2023

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.