

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date: 10/25/2019

SECTION 1: Identification

Identification 1.1.

: Mixture Product form

: SUR-PREP 5606 STRUT WIPE Product name

Recommended use and restrictions on use

: Hydraulic fluids: Washing and Cleaning products (Including solvent based products) Use of the substance/mixture

: Hydraulic fluids Recommended use

Supplier 1.3.

Manufacturer

Zip-Chem Products 400 Jarvis Drive Morgan Hill, CA 95037 - United States T 408-782-2335 - F 408-782-6304

4info@zipchem.com

Emergency telephone number

: 1-800-424-9300 Emergency number

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid H350 May cause cancer Carcinogenicity Category 1B

On basis of test data Calculation method

Full text of H statements : see section 16

GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US)



Signal word (GHS US) : Danger

H227 - Combustible liquid Hazard statements (GHS US) H350 - May cause cancer

P201 - Obtain special instructions before use. Precautionary statements (GHS US)

P202 - Do not handle until all safety precautions have been read and understood.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

P280 - Wear eye protection, protective gloves.

P308+P313 - If exposed or concerned: Get medical advice/attention.

P370+P378 - In case of fire: Use ABC-powder, alcohol resistant foam, an extinguishing

blanket, extinguishing powder, dry extinguishing powder, foam to extinguish. P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

P501 - Dispose of contents/container to a hazardous or special waste collection point.

Other hazards which do not result in classification

No additional information available

Unknown acute toxicity (GHS US) 2.4.

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. **Mixtures**

Page 1 EN (English US) 03/05/2020

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

| Name | Product identifier | % | GHS US classification |
|--|----------------------|---------|-----------------------|
| BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC | (CAS-No.) 64742-53-6 | 5-10 | Carc. 1B, H350 |
| KEROSINE - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT | (CAS-No.) 64742-47-8 | 5-10 | Asp. Tox. 1, H304 |
| Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] | (CAS-No.) 64742-55-8 | 10 – 25 | Carc. 1B, H350 |

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If medical advice is needed, have product container or label at hand. IF exposed or concerned:

Get medical advice/attention.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.

First-aid measures after skin contact : Wash skin with plenty of water.

First-aid measures after eye contact : Rinse eyes with water as a precaution.

First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May cause irritation to the digestive tract.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

Fire hazard : Combustible liquid.

Hazardous decomposition products in case of : Toxic fumes may be released.

fire

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing

apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable

protective equipment may intervene.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information

refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public

waters.

03/05/2020 EN (English US) 2/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling

: Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly.

Hygiene measures

Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke

when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions

: Store in a well-ventilated place. Keep cool. Store locked up.

Incompatible products

: Oxidizing agent. Strong acids.

Storage area

: Store away from heat. Store in a well-ventilated place.

Special rules on packaging

: Keep only in original container. Store in a closed container.

Packaging materials

: Keep only in the original container in a cool, well-ventilated place away from combustible

materials.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SUR-PREP 5606 STRUT WIPE

No additional information available

KEROSINE - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (64742-47-8)

No additional information available

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (64742-53-6)

No additional information available

Distillates (petroleum), hydrotreated light paraffinic, Baseoil - unspecified, [A complex combination of hydrocarbons obtained by treating a petroleum fraction with hydrogen in the presence of a catalyst. It consists of hydrocarbons having carbon numbers predominantly in the range of C15 through C30 and produces a finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt at 40 °C). It contains a relatively large proportion of saturated hydrocarbons.] (64742-55-8)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Environmental exposure controls

: Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

03/05/2020 EN (English US) 3/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Personal protective equipment symbol(s):









SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Color : red

Odor : Barely perceptible odour

Odor threshold : No data available pH : No data available Melting point : No data available. Freezing point : No data available Boiling point : No data available no data available boiling point : No data available

Flash point : 82 °C

Relative evaporation rate (butyl acetate=1) : No data available Flammability (solid, gas) : Not applicable. Vapor pressure : No data available Relative vapor density at 20 °C : No data available.

Relative density : 0.87 Specific gravity / density : 0.87 g/ml

Solubility : No data available Partition coefficient n-octanol/water (Log Pow) : No data available : No data available. Auto-ignition temperature Decomposition temperature : No data available Viscosity, kinematic : 4900000 mm²/s Viscosity, dynamic : No data available **Explosion limits** No data available Explosive properties : No data available Oxidizing properties : No data available

9.2. Other information

VOC content : 320 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

03/05/2020 EN (English US) 4/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : May cause cancer.

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified
Viscosity, kinematic : 4900000 mm²/s

Symptoms/effects after inhalation : Inhalation may cause irritation (cough, short breathing, difficulty in breathing).

Symptoms/effects after skin contact : Causes skin irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after eye contact : Causes serious eye irritation.

Symptoms/effects after ingestion : May cause irritation to the digestive tract.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : NA1993 Combustible liquid, n.o.s., 3, III

UN-No.(DOT) : NA1993

Proper Shipping Name (DOT) : Combustible liquid, n.o.s.

Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

03/05/2020 EN (English US) 5/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Packing group (DOT)

: III - Minor Danger

DOT Packaging Non Bulk (49 CFR 173.xxx) DOT Packaging Bulk (49 CFR 173.xxx)

: 203 : 241

DOT Symbols

: D - Proper shipping name for domestic use only, or to and from Canada, G - Identifies PSN

requiring a technical name

DOT Special Provisions (49 CFR 172.102)

: 148 - Except for transportation by aircraft, when transported as a limited quantity or a consumer commodity, the maximum net capacity specified in §173.150(b)(2) of this subchapter for inner

packaging may be increased to 5 L (1.3 gallons).

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table

2 for UN2672)

T1 - 1.5 178.274(d)(2) Normal...... 178.275(d)(2)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = 97 / 1 + a (tr - tf) Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

DOT Packaging Exceptions (49 CFR 173.xxx) DOT Quantity Limitations Passenger aircraft/rail : 60 L (49 CFR 173.27)

DOT Quantity Limitations Cargo aircraft only (49 : 220 L

CFR 175.75)

DOT Vessel Stowage Location

: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a

passenger vessel.

Other information

: No supplementary information available.

Transportation of Dangerous Goods

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

SECTION 15: Regulatory information

15.1. US Federal regulations

SUR-PREP 5606 STRUT WIPE

Listed on the United States TSCA (Toxic Substances Control Act) inventory

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory except for:

| Distillates (petroleum), hydrotreated light paraffinic, Baseoil - |
|---|
| unspecified, [A complex combination of hydrocarbons obtained |
| by treating a petroleum fraction with hydrogen in the presence of |
| a catalyst. It consists of hydrocarbons having carbon numbers |
| predominantly in the range of C15 through C30 and produces a |
| finished oil with a viscosity of less than 100 SUS at 100 °F (19cSt |
| at 40 °C). It contains a relatively large proportion of saturated |
| hydrocarbons.] |

| CAS-No. 64742-55-8 | 10 – 25% | | |
|--------------------|----------|--|--|
| | | | |
| | | | |

15.2. International regulations

CANADA

KEROSINE - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT (64742-47-8)

Listed on the Canadian DSL (Domestic Substances List)

BASEOIL - UNSPECIFIED - DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHTHENIC (64742-53-6)

Listed on the Canadian DSL (Domestic Substances List)

03/05/2020 EN (English US) 6/7

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

National regulations

SUR-PREP 5606 STRUT WIPE

Listed on the AICS (Australian Inventory of Chemical Substances) Listed on KECI (Korean Existing Chemicals Inventory)

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 10/25/2019

Full text of H-phrases:

| ii toxii or i i prii docci. | | |
|-----------------------------|--|--|
| H227 | Combustible liquid | |
| H304 | May be fatal if swallowed and enters airways | |
| H350 | May cause cancer | |

Hazard Rating

: 1 Slight Hazard - Irritation or minor reversible injury possible Health

Flammability 2 Moderate Hazard - Materials which must be moderately heated or exposed to high ambient

temperatures before ignition will occur. Includes liquids having a flash point at or above 100 F

but below 200 F. (Classes II & IIIA)

1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high Physical

temperatures and pressures. Materials may react non-violently with water or undergo

hazardous polymerization in the absence of inhibitors.

: C Personal protection

C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

7/7 03/05/2020 EN (English US)