SAFETY DATA SHEET



Section 1. Identification

Product name

Aero 40 Red

SDS#

459670

Code

459670-US03

Relevant identified uses of the substance or mixture and uses advised against

Product use

Hydraulic fluid

For specific application advice see appropriate Technical Data Sheet or consult our

company representative.

Supplier

BP Lubricants USA Inc.

1500 Valley Road Wayne, NJ 07470

Telephone: +1-888-CASTROL

EMERGENCY HEALTH

INFORMATION:

+1-800-447-8735

EMERGENCY SPILL

+1-800-424-9300 (CHEMTREC USA)

INFORMATION:

+1-703-527-3887 (CHEMTREC outside the US)

Section 2. Hazards identification

OSHA/HCS status

This material is not considered hazardous by the OSHA Hazard Communication

Standard (29 CFR 1910.1200).

Classification of the

substance or mixture

Not classified.

GHS label elements

Signal word

No signal word.

Hazard statements

No known significant effects or critical hazards.

Precautionary statements

Prevention

Not applicable.

Response

Not applicable.

Storage

Not applicable.

Disposal

Not applicable.

Hazards not otherwise

Defatting to the skin.

classified

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure

constitute a major medical emergency.

See 'Notes to physician' under First-Aid Measures, Section 4 of this Safety Data Sheet.

Section 3. Composition/information on ingredients

Ingredient name	CAS number	%
Distillates (petroleum), hydrotreated light naphthenic Distillates (petroleum), hydrotreated light paraffinic Distillates (petroleum), hydrotreated light Zinc dialkyl dithiophosphate	64742-53-6 64742-55-8 64742-47-8 68457-79-4	≥50 - ≤75 ≥10 - ≤25 ≥10 - ≤25 <3

Format US

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Product name Aero 40 Red

Version 4.02 Date of issue 04/19/2022.

Product code

459670-US03 Page: 1/9

Section 3. Composition/information on ingredients

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.

Eyelids should be held away from the eyeball to ensure thorough rinsing. Check for and

remove any contact lenses. Get medical attention.

Skin contact Wash skin thoroughly with soap and water or use recognized skin cleanser. Remove

contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly

before reuse. Get medical attention if symptoms occur.

Inhalation If inhaled, remove to fresh air. Get medical attention if symptoms occur.

Ingestion To not induce vomiting unless directed to do so by medical personnel. Get medical

attention if symptoms occur.

No action shall be taken involving any personal risk or without suitable training. Protection of first-aiders

Most important symptoms/effects, acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician

Preatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discolored and extremely painful with extensive subcutaneous necrosis.

Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to minimize tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along tissue planes.

Specific treatments

No specific treatment.

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

In case of fire, use foam, dry chemical or carbon dioxide extinguisher or spray.

Unsuitable extinguishing

media

Do not use water jet.

Specific hazards arising

from the chemical

Hazardous combustion products

In a fire or if heated, a pressure increase will occur and the container may burst.

Combustion products may include the following:

carbon oxides (CO, CO₂) (carbon monoxide, carbon dioxide)

Special protective actions

for fire-fighters

Special protective equipment for fire-fighters

No action shall be taken involving any personal risk or without suitable training. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA)

and full turnout gear.

Product name Aero 40 Red Version 4.02 Date of issue 04/19/2022.

Product code

459670-US03 Page: 2/9

Format US

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment. Floors may be slippery; use care to avoid falling.

For emergency responders

F specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Absorb with an inert material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Advice on general occupational hygiene

Fut on appropriate personal protective equipment (see Section 8).

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Wash thoroughly after handling. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Store and use only in equipment/containers designed for use with this product. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Sulfur compounds in this material may decompose when heated to release hydrogen sulfide gas which may accumulate to potentially lethal concentrations in enclosed air spaces. Vapor concentrations of hydrogen sulfide above 50 ppm, or prolonged exposure at lower concentrations, may saturate human odor perceptions so that the smell of gas may not be apparent. Exposure to concentrations of hydrogen sulfide vapor above 500 ppm may cause rapid death. Do not rely on the sense of smell to detect hydrogen sulfide.

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure limits Ingredient name Distillates (petroleum), hydrotreated light naphthenic ACGIH TLV (United States). TWA: 5 mg/m³ 8 hours. Issued/Revised: 11/2009 Form: Inhalable fraction OSHA PEL (United States). TWA: 5 mg/m³ 8 hours. Issued/Revised: 6/1993 Distillates (petroleum), hydrotreated light paraffinic ACGIH TLV (United States).

Product name Aero 40 Red

Version 4.02 Date of issue 04/19/2022.

Product code

459670-US03 Page: 3/9

Format US Language ENGLISH

Section 8. Exposure controls/personal protection

TWA: 5 mg/m³ 8 hours. Issued/Revised:
11/2009 Form: Inhalable fraction
OSHA PEL (United States).
TWA: 5 mg/m³ 8 hours. Issued/Revised:
6/1993

Distillates (petroleum), hydrotreated light

ACGIH TLV (United States). Absorbed through skin.
TWA: 200 mg/m³, (as total hydrocarbon vapor) 8 hours. Issued/Revised: 1/2003

Zinc dialkyl dithiophosphate

None.

While specific OELs for certain components may be shown in this section, other components may be present in any mist, vapor or dust produced. Therefore, the specific OELs may not be applicable to the product as a whole and are provided for guidance only.

Appropriate engineering controls

All activities involving chemicals should be assessed for their risks to health, to ensure exposures are adequately controlled. Personal protective equipment should only be considered after other forms of control measures (e.g. engineering controls) have been suitably evaluated. Personal protective equipment should conform to appropriate standards, be suitable for use, be kept in good condition and properly maintained. Your supplier of personal protective equipment should be consulted for advice on selection and appropriate standards. For further information contact your national organisation for standards.

Provide exhaust ventilation or other engineering controls to keep the relevant airborne concentrations below their respective occupational exposure limits.

The final choice of protective equipment will depend upon a risk assessment. It is important to ensure that all items of personal protective equipment are compatible.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection Skin protection

Safety glasses with side shields.

Hand protection

Wear protective gloves if prolonged or repeated contact is likely. Wear chemical resistant gloves. Recommended: Nitrile gloves. The correct choice of protective gloves depends upon the chemicals being handled, the conditions of work and use, and the condition of the gloves (even the best chemically resistant glove will break down after repeated chemical exposures). Most gloves provide only a short time of protection before they must be discarded and replaced. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. Gloves should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Body protection

Use of protective clothing is good industrial practice.

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Cotton or polyester/cotton overalls will only provide protection against light superficial contamination that will not soak through to the skin. Overalls should be laundered on a regular basis. When the risk of skin exposure is high (e.g. when cleaning up spillages or if there is a risk of splashing) then chemical resistant aprons and/or impervious chemical suits and boots will be required.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Product name Aero 40 Red Product code 459670-US03 Page: 4/9

Version 4.02 Date of issue 04/19/2022. Format US Language ENGLISH

Section 8. Exposure controls/personal protection

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

The correct choice of respiratory protection depends upon the chemicals being handled, the conditions of work and use, and the condition of the respiratory equipment. Safety procedures should be developed for each intended application. Respiratory protection equipment should therefore be chosen in consultation with the supplier/manufacturer and with a full assessment of the working conditions.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state

Liquid.

Color

Red. [Dark]

Odor

Not available.

Odor threshold

Not available.

pН

Not applicable.

Melting point/freezing point

Bolling point, initial boiling

Not available.

point, and boiling range

Not available.

Flash point

Open cup: 110°C (230°F) [Cleveland]

Evaporation rate

Not available.

Flammability

Not applicable. Based on - Physical state

Lower and upper explosion limit/flammability limit

Not available.

Vapor pressure

	Vapor Pressure at 20°C			Vapor pressure at 50°C		sure at 50°C
Ingredient name	mm Hg	kPa	Method	mm Hg	kPa	Method
Distillates (petrolaum), hydrotreated light paraffinic	<0.08	<0.011	ASTM D 5191			
Distillates (petroleum), hydrotreated light	0.23 to 0.45	0.031 to 0.08				
Zinc dialkyl dithiophosphate	0	0	EU A.4	0	0	EU A.4
Fatty acids, C16-18 and C18-unsatd., Me esters	3.15	0.42	EU A.4			

Relative vapor density

Not available.

Density

<1000 kg/m³ (<1 g/cm³) at 15.6°C

Solubility

insoluble in water.

Partition coefficient: n-

octanol/water

Not applicable.

Auto-ignition temperature

Ingredient name	°C	°F	Method
Distillates (petroleum), hydrotreated light	>220	>428	

Decomposition temperature

Not available.

Viscosity

Kinematic: 13/2 mm²/s (13.2 cSt) at 37.7°C

VOC

570.3 g/l

Particle characteristics

Median particle size

Not applicable.

Product name Aero 40 Red Version 4.02 Date of issue 04/19/2022.

Product code

459670-US03

Page: 5/9

Format US

Section 10. Stability and reactivity

No specific test data available for this product. Refer to Conditions to avoid and Reactivity

Incompatible materials for additional information.

Chemical stability The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to avoid No specific data.

Incompatible materials Reactive or incompatible with the following materials: oxidizing materials.

Hazardous decomposition

products

Hydrogen Sulfide (H2S)

Section 11. Toxicological information

Information on toxicological effects

Aspiration hazard

Name Result Distillates (petroleum), hydrotreated light naphthenic ASPIRATION HAZARD - Category 1 Distillates (petroleum), hydrotreated light paraffinic ASPIRATION HAZARD - Category 1 Distillates (petroleum), hydrotreated light ASPIRATION HAZARD - Category 1

information on the likely

routes of exposure

Routes of entry anticipated: Dermal, Inhalation.

Potential acute health effects

Eye contact

No known significant effects or critical hazards.

Skin contact

No known significant effects or critical hazards.

Inhalation

Vapor inhalation under ambient conditions is not normally a problem due to low vapor

pressure.

Ingestion

No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact

No specific data.

Skin contact

Adverse symptoms may include the following:

irritation dryness

cracking

Inhalation

No specific data.

Ingestion

No specific data.

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

Not available.

effects

Potential delayed effects

Not available.

Long term exposure

Potential immediate

Not available.

effects

Potential delayed effects

Not available.

Potential chronic health effects

General

Product name

No known significant effects or critical hazards.

Carcinogenicity

No known significant effects or critical hazards.

Aero 40 Red Version 4.02 Date of issue 04/19/2022. **Product code**

459670-US03

Page: 6/9

Format US

Section 11. Toxicological information

Mutagenicity No known significant effects or critical hazards.

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	203398.12 mg/kg

Section 12. Ecological information

Toxicity

No testing has been performed by the manufacturer.

Persistence and degradability

Not expected to be rapidly degradable.

Bioaccumulative potential

Not available.

Mobility in soil

Soil/water partition coefficient (Koc)

Not available.

Mobility

Liquid. insoluble in water.

Other adverse effects

No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

The generation of waste should be avoided or minimized wherever possible. Significant quantities of waste product residues should not be disposed of via the foul sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	IMDG	IATA
JN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-
Fransport nazard class(es)	-	-	-	-

Product name Aero 40 Red

Product code

459670-US03

Page: 7/9

Version 4.02 Date of Issue 04/19/2022.

Format US

Section 14. Transport information

Packing group	-	•	-	-
Environmental hazards	No.	No.	No.	No.
Additional information	•	-	-	-

Special precautions for user

Not available.

Transport in bulk according

to IMO instruments

Not available.

Section 15. Regulatory information

U.S. Federal regulations

United States inventory

All components are active or exempted.

(TSCA 8b) **SARA 302/304**

Composition/information on ingredients

No products were found.

SARA 311/312

Classification

Not applicable.

SARA 313

	Product name	CAS number	Concentration
Form R - Reporting requirements	Zinc dialkyl dithiophosphate	68457-79-4	1.326
Supplier notification	Zinc dialkyl dithiophosphate	68457-79-4	1.326

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

The following components are listed: MINERAL OIL, PETROLEUM DISTILLATES,

HYDROTREATED LIGHT NAPHTHENIC; MINERAL OIL, PETROLEUM DISTILLATES,

HYDROTREATED LIGHT PARAFFINIC

New Jersey

The following components are listed: ZINC compounds

Pennsylvania

The following components are listed: ZINC COMPOUNDS

California Prop. 65

⚠ WARNING: This product can expose you to chemicals including Ethylbenzene and cumene, which are known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Other regulations

Australia inventory (AliC)

All components are listed or exempted.

Canada inventory

All components are listed or exempted.

China inventory (IECSC)

All components are listed or exempted.

Japan inventory (CSCL)

All components are listed or exempted.

Korea inventory (KECI)

All components are listed or exempted.

Philippines inventory

All components are listed or exempted.

(PICCS)

Taiwan Chemical

Substances Inventory

(TCSI)

Not determined.

REACH Status

The company, as identified in Section 1, sells this product in the EU in compliance with

the current requirements of REACH.

Product name Aero 40 Red

Product code

Page: 8/9

Version 4.02 Date of issue 04/19/2022.

Format US

Language ENGLISH

459670-US03

Section 16. Other information

National Fire Protection Association (U.S.A.)



History

Date of issue/Date of

revision

04/19/2022.

Date of previous issue

03/23/2022.

Prepared by

Product Stewardship

Key to abbreviations

ACGIH = American Conference of Industrial Hygienists

ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

CAS Number = Chemical Abstracts Service Registry Number

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978. ("Marpol" = marine pollution)

OEL = Occupational Exposure Limit

SDS = Safety Data Sheet STEL = Short term exposure limit TWA = Time weighted average

UN = United Nations

UN Number = United Nations Number, a four digit number assigned by the United

Nations Committee of Experts on the Transport of Dangerous Goods.

Varies = may contain one or more of the following 64741-88-4, 64741-89-5, 64741-95-3, 64741-96-4, 64742-01-4, 64742-44-5, 64742-45-6, 64742-52-5, 64742-53-6, 64742-54-7, 64742-55-8, 64742-56-9, 64742-57-0, 64742-58-1, 64742-62-7, 64742-63-8, 64742-65-0,

64742-70-7, 72623-85-9, 72623-86-0, 72623-87-1

 $oldsymbol{\mathbb{Z}}$ Indicates information that has changed from previously issued version.

Notice to reader

All reasonably practicable steps have been taken to ensure this data sheet and the health, safety and environmental information contained in it is accurate as of the date specified below. No warranty or representation, express or implied is made as to the accuracy or completeness of the data and information in this data sheet.

The data and advice given apply when the product is sold for the stated application or applications. You should not use the product other than for the stated application or applications without seeking advice from BP Group.

It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The BP Group shall not be responsible for any damage or injury resulting from use, other than the stated product use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material. Purchasers of the product for supply to a third party for use at work, have a duty to take all necessary steps to ensure that any person handling or using the product is provided with the information in this sheet. Employers have a duty to tell employees and others who may be affected of any hazards described in this sheet and of any precautions that should be taken. You can contact the BP Group to ensure that this document is the most current available. Alteration of this document is strictly prohibited.

Product name Aero 40 Red Version 4.02 Date of issue 04/19/2022.

Product code

459670-US03 ·

Page: 9/9

Format US