

# Safety Data Sheet

Material: 60004449

**ELASTOSIL® RT 625 A**

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

## 1. Product and company identification

### 1.1 Identification of the substance or preparation:

**Commercial product name:****ELASTOSIL® RT 625 A**

Product group:

Elastosil®

Use of substance / preparation

Industrial.

Raw material for: elastomer products .

### 1.2 Company/undertaking identification:

Manufacturer/distributor:

Wacker Chemical Corporation  
4950 S State Road  
Ann Arbor, MI 48108  
USA

Customer information:

InfoLine:  
Tel (517) 264-8240  
Hours of operation:  
Monday - Friday, 8 am to 5 pm (eastern standard time)  
Corporate website: [www.wacker.com](http://www.wacker.com)**Emergency telephone no. (24h):****(517) 264-8500****Transportation emergency:**(800) 424-9300 (CHEMTREC, USA)  
(703) 527-3887 (CHEMTREC, international)

This SDS was prepared by the Regulatory Affairs and Product Safety Department (RAPS) of Wacker Chemical Corporation.

## 2. Hazards identification

### 2.1 Classification of the substance or mixture

**Classification (GHS):**

Not a hazardous substance or mixture.

### 2.2 Label elements

**Labelling (GHS):**

No labeling according to GHS required.

### 2.3 Other hazards

Product can release hydrogen. Risk of hydrogen gas formation with water, alcohols, acids, metallic salts, amines and alkalis. In combination with oxygen, the released hydrogen can form oxyhydrogen.

## 3. Composition/information on ingredients

### 3.1 Chemical characterization (preparation)

Chemical characteristics

Polydimethylsiloxane with functional groups and auxiliaries for addition cross-linking

### 3.2 Information on ingredients:

This material does not contain any ingredients above the permitted limit(s).

Substances listed in the Subsections "HAPS" and "California Proposition 65 Carcinogens / Reproductive Toxins" that are not listed in this section are only present at quantities below 0.1% for California Proposition 65 listed toxins or below 1% for non-carcinogenic HAPS or they are inextricably bound in the product. Specific chemical identities and/or exact percentage (concentration) of the composition may have been withheld as a trade secret.

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57) in amounts above  $\geq 0.1\%$ .

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

## 4. First-aid measures

### 4.1 General information:

Get medical attention if irritation or other symptoms occur. Before seeking medical attention remove contaminated clothing and shoes. Take a copy of the Safety Data Sheet when going for medical treatment.

### 4.2 After inhalation

No special treatment required.

### 4.3 After contact with the skin

Wipe off excess material with cloth or paper. Use a waterless hand cleaner to remove as much of the remaining material as possible. Wash with soap and water.

### 4.4 After contact with the eyes

If contact with eyes, immediately hold eyelids apart and flush with plenty of water for at least 15 min.

### 4.5 After swallowing

No special treatment required.

## 5. Fire-fighting measures

### 5.1 Flammable properties:

Property:	Value:	Method:
Flash point.....	> 200 °C (> 392 °F)	(DIN 51376)
Boiling point / boiling range .....	not applicable	
Lower explosion limit (LEL) .....	not applicable	
Ignition temperature .....	> 450 °C (> 842 °F)	(DIN 51794)
NFPA Hazard Class (comb./flam.liquid) .....	IIIB	

### 5.2 Fire and explosion hazards:

Caution! Under certain conditions this material may generate flammable hydrogen gas. Consider possible formation of explosive mixtures with air, for example in uncleansed containers by moisture. Never use welding or cutting torch on or near any container of this material, even if empty, because an explosion could occur. Spontaneous ignition is possible due to electrostatic discharge. The generation of hydrogen gas is increased under circumstances mentioned in Sect. 10 "Stability and reactivity". Explosion limits for hydrolysis product: 4-75.6% v/v (hydrogen).

### 5.3 Recommended extinguishing media:

carbon dioxide , dry sand , alcohol-resistant foam .

### 5.4 Unsuitable extinguishing media:

water , dry chemical , halones .

### 5.5 Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases

Hazardous decomposition products: carbon dioxide , carbon monoxide , formaldehyde , silicon dioxide and incompletely burnt hydrocarbons .

### 5.6 Fire fighting procedures:

Fire fighters should wear full protective clothing including a self-contained breathing apparatus. Cool endangered containers with water. Hydrogen gas can become trapped under foam blankets, so sources of ignition must be eliminated during the clean-up and recovery process.

## 6. Accidental release measures

### 6.1 Precautions:

Secure the area. Wear personal protection equipment (see section 8). Keep unprotected persons away. If material is released indicate risk of slipping. Do not walk through spilled material.

**HAZWOPER PPE Level: D**

# Safety Data Sheet

**Material: 60004449****ELASTOSIL® RT 625 A**

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

**6.2 Containment:**

Prevent material from entering surface waters, drains or sewers and soil. Close leak if possible without risk. Contain any fluid that runs out using suitable material (e.g. earth). Retain contaminated water/extinguishing water. Dispose of in prescribed marked containers. Inform authorities if substance leaks into surface waters, sewerage or ground.

Spills of material which could reach surface waters must be reported to the United States Coast Guard National Response Center's toll free phone number (800) 424-8802.

**6.3 Methods for cleaning up**

Take up mechanically and dispose of according to local/state/federal regulations. Do not flush away with water. For small amounts: Absorb with a neutral (non-acidic / non-basic) liquid binding material such as diatomaceous earth and dispose of according to government regulations. For large amounts: Liquids may be recovered using suction devices or pumps. Use only air driven or properly rated electrical equipment. Use vented recovery containers. Clean any slippery coating that remains using a detergent / soap solution or another biodegradable cleaner. Silicone fluids are slippery; spills are a safety hazard. Apply sand or other inert granular material to improve traction.

**6.4 Further information:**

Exhaust vapours. Eliminate all sources of ignition. Consider explosion protection. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Do not blend contaminated material with uncontaminated material. Do not seal collecting vessel gas-tight. Observe notes under section 7.

## 7. Handling and storage

**7.1 General information:**

Stir thoroughly before use or catalysing.

**7.2 Handling****Precautions for safe handling:**

Ensure adequate ventilation. Open and handle container with care. Keep container closed when not in use. Keep away from incompatible substances in accordance with section 10. Where possible, inert process equipment and blanket vessels, tanks and containers with nitrogen to reduce the available oxygen level. Contact WACKER for additional publications on the safe Handling of SiH Products. Avoid formation of aerosols. In case of aerosol formation special protective measures are required (exhausting by suction, respiratory protection). Spilled substance increases risk of slipping. Observe information in section 8.

**Precautions against fire and explosion:**

Product can release hydrogen. Flammable vapors may accumulate and form explosive mixtures with air in containers, process vessels, including partial, empty and uncleaned containers and vessels, or other enclosed spaces. Keep away from sources of ignition and do not smoke. Take precautionary measures against electrostatic charging. Cool endangered containers with water.

**7.3 Storage****Conditions for storage rooms and vessels:**

Do not store in virgin glass containers with basic surface. Observe local/state/federal regulations.

**Advice for storage of incompatible materials:**

Do not store with: basic substances (e.g. alkalis, ammonia, amines) , oxidizing agents , strong acids . Observe local/state/federal regulations.

**Further information for storage:**

Store in a dry and cool place. Protect against moisture. Store container in a well ventilated place.

## 8. Exposure controls and personal protection

**8.1 Engineering controls****Ventilation:**

Use only with adequate ventilation.

**Local exhaust:**

Local exhaust ventilation which meets the requirements of ANSI Z9.2 is recommended to control airborne contaminants at the point of use.

**8.2 Associate substances with specific control parameters such as limit values**

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

none known

## 8.3 Personal protection equipment (PPE)

**Respiratory protection:**

Respiratory protection is not normally required.

**Hand protection:**

Recommendation: butyl rubber protective gloves , neoprene gloves , PVC gloves .

**Eye protection:**

Safety glasses with side shields or chemical safety goggles.

**Other protective clothing or equipment:**

Additional protective clothing or equipment is not normally required. Provide eye bath and safety shower.

## 8.4 General hygiene and protection measures:

When handling do not eat, drink, smoke or apply cosmetics. Wash thoroughly after handling.

## 9. Physical and chemical properties

### 9.1 Appearance

Physical state .....	liquid
Colour.....	colourless dark
Odour .....	odourless

### 9.2 Safety parameters

Property:	Value:	Method:
Melting point / melting range .....	not applicable	
Boiling point / boiling range .....	not applicable	
Flash point.....	> 200 °C (> 392 °F)	(DIN 51376)
Ignition temperature .....	> 450 °C (> 842 °F)	(DIN 51794)
Lower explosion limit (LEL) .....	not applicable	
Vapour pressure.....	not applicable	
Density .....	ca. 1.12 g/cm <sup>3</sup> at 20 °C (68 °F)	(DIN 51757)
Water solubility / miscibility.....	virtually insoluble at 20 °C (68 °F)	
pH-Value .....	not applicable	
Viscosity (dynamic) .....	ca. 50000 mPa.s at 20 °C (68 °F)	(-)

### 9.3 Further information

According to previous experience spontaneous combustion temperature for polymer siloxane with SiH compounds is above 240 °C (464 °F). On a catalytically active surface ignition may occur at much lower temperature. This applies to porous or fibrous substances including those with alkaline surfaces, such as thermal insulation and cementaceous insulating materials. Explosion limits for released hydrogen: 4 - 75.6%(V). pH Value: Product displays neutral reaction.

Odour limit..... : no data available

Thermal decomposition..... : &gt; 200 °C (&gt; 392 °F)

(-)

## 10. Stability and reactivity

### 10.1 General information:

If stored and handled in accordance with standard industrial practices no hazardous reactions are known.

### 10.2 Conditions to avoid

moisture , Heat, open flames, and other sources of ignition. Contact with contaminated piping or vessels or with corroded and rusty containers can increase the rate of hydrogen formation. Observe information in section 7.

### 10.3 Materials to avoid

proton-active substances . Reacts violently with: acids , basic substances (e.g. alkalis, ammonia, amines) . Reacts with: alcohols , water , moisture , oxidizing agents , catalyst . Reaction causes the formation of: hydrogen .

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

## 10.4 Hazardous decomposition products

In contact with incompatible substances this material may quickly generate a large volume of flammable hydrogen gas. Measurements have shown the formation of small amounts of formaldehyde at temperatures above about 150 °C (302 °F) through oxidation.

## 10.5 Further information:

Hazardous polymerization cannot occur.

## 11. Toxicological information

### 11.1 Information on toxicological effects

#### 11.1.1 Acute toxicity

**Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
Oral	LD50: > 2000 mg/kg	Rat	Conclusion by analogy
dermal	LD50: > 2000 mg/kg	Rat	Conclusion by analogy

#### 11.1.2 Skin corrosion/irritation

**Product details:**

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by analogy

#### 11.1.3 Serious eye damage / eye irritation

**Product details:**

Result/Effect	Species/Test system	Source
not irritating	Rabbit	Conclusion by analogy

#### 11.1.4 Respiratory or skin sensitization

**Product details:**

Route of exposure	Result/Effect	Species/Test system	Source
dermal	not sensitizing	Guinea pig; Buehler Test	Conclusion by analogy OECD 406

#### 11.1.5 Germ cell mutagenicity

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.6 Carcinogenicity

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.7 Reproductive toxicity

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

#### 11.1.8 Specific target organ toxicity (single exposure)

**Assessment:**

For this endpoint no toxicological test data is available for the whole product.

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

## 11.1.9 Specific target organ toxicity (repeated exposure)

### Assessment:

For this endpoint no toxicological test data is available for the whole product.

## 11.1.10 Aspiration hazard

### Assessment:

Based on the physical-chemical properties of the product no aspiration hazard must be expected.

## 11.1.11 Further toxicological information

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

## 12. Ecological information

### 12.1 Toxicity

#### Assessment:

Assessment based on ecotoxicological tests with similar products under consideration of the physical-chemical properties: For this product no effects on aquatic organisms, relevant for classification, are expected. According to current knowledge adverse effects on water purification plants are not expected.

### 12.2 Persistence and degradability

#### Assessment:

Silicone content: biologically not degradable. Separation by sedimentation.

### 12.3 Bioaccumulative potential

#### Assessment:

Polymer component: No adverse effects expected.

### 12.4 Mobility in soil

#### Assessment:

Silicone content: Insoluble in water.

### 12.5 Results of PBT and vPvB assessment

No data available.

### 12.6 Other adverse effects

none known

### 12.7 Additional information

Easily separable from water by filtration.

## 13. Disposal considerations

### 13.1 Product disposal

#### Recommendation:

Risk of oxyhydrogen formation upon contact with the substances mentioned in 10. Material designated for disposal must be segregated from incompatible substances or materials specified in Sect. 10. Wastes of this material should not be mixed with other wastes. Provide measures such as vented bungs to ensure pressure relief in the waste containers. Material that cannot be used, reprocessed or recycled should be disposed of in accordance with Federal, State, and local regulations at an approved facility. Depending on the regulations, waste treatment methods may include, e.g., landfill or incineration.

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

## 13.2 Packaging disposal

### Recommendation:

Containers may contain hazardous quantities of hydrogen gas. Uncleaned containers should not be reused to hold another material due to the potential for reaction between residual product and incompatible materials. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local/state/federal regulations. Uncleaned packaging should be treated with the same precautions as the material.

## 14. Transport information

### 14.1 US DOT & CANADA TDG SURFACE

Valuation .....: Not regulated for transport

### 14.2 Transport by sea IMDG-Code

Valuation .....: Not regulated for transport

### 14.3 Air transport ICAO-TI/IATA-DGR

Valuation .....: Not regulated for transport

## 15. Regulatory information

### 15.1 U.S. Federal regulations

#### TSCA inventory status and TSCA information:

This material or its components are listed on or are in compliance with the requirements of the TSCA Chemical Substance Inventory.

#### TSCA 12(b) Export Notification:

This material does not contain reportable amounts of any TSCA 12(b) listed chemicals.

#### CERCLA Regulated Chemicals:

This material does not contain any CERCLA regulated chemicals.

#### SARA 302 EHS Chemicals:

This material does not contain any SARA extremely hazardous substances.

#### SARA 311/312 Hazard Class:

This product does not present any SARA 311/312 hazards.

#### SARA 313 Chemicals:

This material does not contain any SARA 313 chemicals above de minimus levels.

#### HAPS (Hazardous Air Pollutants):

This material does not contain any hazardous air pollutants.

### 15.2 U.S. State regulations

#### California Proposition 65 (Safe Drinking Water and Toxic Enforcement Act of 1986):

This material does not contain any chemicals known to the State of California to cause cancer.

This material does not contain any chemicals known to the State of California to cause reproductive effects.

#### Massachusetts Substance List:

This material contains no listed components.

#### New Jersey Right-to-Know Hazardous Substance List:

This material contains no listed components.

#### Pennsylvania Right-to-Know Hazardous Substance List:

This material contains no listed components.

### 15.3 Details of international registration status

Relevant information about individual substance inventories, where available, is given below.

Japan ..... : **ENCS** (Handbook of Existing and New Chemical Substances):  
This product is listed in, or complies with, the substance inventory.

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

Australia .....	: <b>AICS</b> (Australian Inventory of Chemical Substances): This product is listed in, or complies with, the substance inventory.
China.....	: <b>IECSC</b> (Inventory of Existing Chemical Substances in China): This product is listed in, or complies with, the substance inventory.
Canada .....	: <b>DSL</b> (Domestic Substance List): This product is listed in, or complies with, the substance inventory.
Philippines.....	: <b>PICCS</b> (Philippine Inventory of Chemicals and Chemical Substances): This product is listed in, or complies with, the substance inventory.
United States of America (USA).....	: <b>TSCA</b> (Toxic Substance Control Act Chemical Substance Inventory): All components of this product are listed as active or are in compliance with the substance inventory.
Taiwan .....	: <b>TCSI</b> (Taiwan Chemical Substance Inventory): This product is listed in, or complies with, the substance inventory. General note: The Taiwanese chemicals regulation requires a phase 1 registration for TCSI-listed or TCSI-compliant substances if imports to Taiwan or manufacturing in Taiwan exceed the trigger quantity of 100 kg/a (for mixtures to be calculated per each ingredient). It is the duty of the importing/manufacturing legal entity to take care of this obligation.
European Economic Area (EEA).....	: <b>REACH</b> (Regulation (EC) No 1907/2006): General note: the registration obligations for substances imported into the EEA or manufactured within the EEA by the supplier mentioned in section 1 are fulfilled by the said supplier. The registration obligations for substances imported into the EEA by customers or other downstream users must be fulfilled by the latter.
South Korea (Republic of Korea) .....	: <b>AREC</b> (Act on Registration and Evaluation of Chemicals; "K-REACH"): General note: in case of registration obligations for substances or polymers imported into Korea or manufactured within Korea these are fulfilled by the supplier mentioned in section 1. The registration obligations for substances or polymers imported into Korea by customers or other downstream users must be fulfilled by the latter.

## 16. Other information

### 16.1 Additional information:

This Safety Data Sheet (SDS) meets the requirements of the Federal OSHA Hazard Communication Standard (29 CFR 1910.1200). This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief accurate and reliable as of the date compiled. However, no representation, warranty or guarantee expressed or implied, is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. We do not accept liability for any loss or damage that may occur from the use of this information. Nothing herein shall be construed as a recommendation for uses which infringe valid patents or as extending a license under valid patents. This SDS provides selected regulatory information on this product, including its components. This is not intended to include all regulations. It is the responsibility of the user to know and comply with all applicable rules, regulations and laws relating to the product being used.

Vertical lines in the left-hand margin indicate changes compared with the previous version.

WACKER restricts the use of its products inside the human body or in contact with bodily fluids and mucosa. For further details please review our Health Care Policy on [www.wacker.com](http://www.wacker.com). WACKER may cancel any delivery obligation(s) if the Health Care Policy is not observed.

### 16.2 Glossary of Terms:

ACGIH - American Conference of Governmental Industrial Hygienists  
DOT - Department of Transportation  
hPa - Hectopascals  
mPa\*s - Milli Pascal-Seconds  
OSHA - Occupational Safety and Health Administration  
PEL - Permissible Exposure Limit

Flash point determination methods .....

ASTM D56..... Tagliabue (Tag) closed cup  
ASTM D92, DIN 51376, ISO 2592 ..... Cleveland open cup

ppm - Parts per Million  
SARA - Superfund Amendments and Reauthorization Act  
STEL - Short Term Exposure Limit  
TSCA - Toxic Substances Control Act  
TWA - Time Weighted Average  
WHMIS - Canadian Workplace Hazardous Materials Identification System

Common name

# Safety Data Sheet

Material: 60004449

ELASTOSIL® RT 625 A

Version: 2.7 (US)

Date of print: 10/22/2022

Date of last alteration: 11/16/2019

---

ASTM D93, DIN 51758, ISO 2719 ..... Pensky-Martens closed cup  
ASTM D3278, DIN 55680, ISO 3679 ..... Setaflash or Rapid closed cup  
DIN 51755 ..... Abel-Pensky closed cup

## 16.3 Conversion table:

Pressure: .....: 1 hPa \* 0.75 = 1 mm Hg = 1 torr; 1 bar = 1000 hPa

Viscosity: .....: 1 mPa\*s = 1 centipoise (cP)