## **Safety Data Sheet**



Revision Number: 005.0 Issue date: 12/20/2022

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: LOCTITE SI 5290 known as

Shadowcure(R) 5290(TM) Conform

Product type/use: Silicone Coating Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 229779

Item number: 18618
Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711

TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

### 2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW		
WARNING:	COMBUSTIBLE LIQUID.	•
	MAY CAUSE AN ALLERGIC SKIN REACTION.	

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
SKIN SENSITIZATION	1

# PICTOGRAM(S)



#### **Precautionary Statements**

IDH number: 229779

**Prevention:** Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors,

mist, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, eye protection, and face protection.

**Response:** IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention.

Wash contaminated clothing before reuse. In case of fire: Use foam, dry chemical or carbon

dioxide to extinguish.

Storage: Store in a well-ventilated place. Keep cool.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Substituted Polysiloxane	Proprietary	80 - 100
Photoinitiator	Proprietary	1 - 5
Silane derivative	Proprietary	0.1 - 1

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

Product name: LOCTITE SI 5290 known as Shadowcure(R) 5290(TM) Conform Page 1 of 5

Exposure to moisture during cure will release 0.1 - 0.9% methanol.

### 4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:** Wash with soap and water.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. If eye irritation persists, consult a specialist.

**Ingestion:** Do not induce vomiting. If symptoms develop and persist, get medical

attention.

Symptoms: See Section 11.

### 5. FIRE FIGHTING MEASURES

**Extinguishing media:** Foam, dry chemical or carbon dioxide.

Special firefighting procedures: None
Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon. Oxides of silicon. Formaldehyde.

### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:**Do not allow material to contaminate ground water system.

Clean-up methods: Wipe up with adsorbent material (e.g. cloth, fleece). Place scrap material in a

well ventilated area and allow to cure to rubber. Contaminated surfaces will be

extremely slippery.

### 7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Do not handle contact lenses until

all sealant has been removed from hands. Residual sealant may transfer to

lenses and cause eye irritation.

Storage: Store in tightly closed containers to prevent moisture contamination. Store in a

dry area below 90° F.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Substituted Polysiloxane	None	None	None	None
Photoinitiator	None	None	None	None
Silane derivative	None	None	None	None

Engineering controls: Use only with adequate ventilation. Ensure adequate ventilation, especially in

confined areas.

**Respiratory protection:**Not required; except in case of aerosol formation. **Eye/face protection:**Safety goggles or safety glasses with side shields.

**Skin protection:** Use impermeable gloves and protective clothing as necessary to prevent skin

contact.

IDH number: 229779 Product name: LOCTITE SI 5290 known as Shadowcure(R) 5290(TM) Conform

Page 2 of 5

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Color: Pale yellow

Odor: Slightly, Alcoholic, Mild

Odor threshold: Not available.

**pH:** Not applicable, Product is non-soluble (in water).

Vapor pressure: < 10 mm hg (20 °C (68°F))

**Boiling point/range:** > 141 °C (> 285.8 °F)Polymerizes before boiling point is reached.

Melting point/ range: Not applicable, Product is a liquid

Specific gravity: 0.99

Vapor density:> 1 20 °C Heavier than air.Flash point:79.4 °C (174.92 °F) Closed cup

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Flammability:
Evaporation rate:

Not available.
Not available.
Combustible Liquid
Less than butyl acetate.

Solubility in water:

Solubility in water:

Soluble

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Decomposition temperature:

Insoluble

Soluble

Not available.

Not available.

Not available.

### 10. STABILITY AND REACTIVITY

Stability: Stable

Hazardous reactions: Will not occur.

Hazardous decomposition Oxides of carbon. Ox

products:

Oxides of carbon. Oxides of silicon. Formaldehyde. Methanol is liberated slowly upon

exposure to moisture.

Incompatible materials: Acids. Bases. Oxidizing agents. Water.

Reactivity: Not available.

**Conditions to avoid:** High temperatures. Exposure to moisture. Exposure to light.

### 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

#### **Potential Health Effects/Symptoms**

Inhalation: When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may

form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible

limit.

**Skin contact:** Causes skin irritation. May cause allergic skin reaction.

**Eye contact:** Causes serious eye irritation.

**Ingestion:** Not expected under normal conditions of use.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Substituted Polysiloxane	None	No Records
Photoinitiator	None	Irritant
Silane derivative	Inhalation LC50 (Rat, 4 h) = > 26000 ppm	Irritant, Allergen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Substituted Polysiloxane	No	No	No
Photoinitiator	No	No	No
Silane derivative	No	No	No

IDH number: 229779 Product name: LOCTITE SI 5290 known as Shadowcure(R) 5290(TM) Conform

Page 3 of 5

### 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

### 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Cured

rubber can be incinerated or landfilled following EPA and local regulations.

### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Combustible liquid, n.o.s. (Trimethoxymethyl silane)

Hazard class or division: Combustible Liquid

Identification number: NA 1993 Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

### 15. REGULATORY INFORMATION

**United States Regulatory Information** 

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

TSCA 12 (b) Export Notification: Control Act (TSCA) inventory.

None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
None above reporting de minimis.

California Proposition 65: This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other

components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities.

Please contact Regulatory Affairs for additional details.

### 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 2,3,9

Prepared by: Product Safety and Regulatory Affairs

Issue date: 12/20/2022

IDH number: 229779 Product name: LOCTITE SI 5290 known as Shadowcure(R) 5290(TM) Conform

Page 4 of 5

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 229779