Safety Data Sheet



Revision Number: 004.2 Issue date: 06/15/2021

PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: BONDERITE S-ST HOT 50 PAINT

STRIPPER known as P3 HOT

STRIPPER 50

Product type/use: Paint stripping agents Restriction of Use:

Company address: Henkel Corporation

One Henkel Way Rocky Hill, Connecticut 06067

None identified

Item number: 1669690 Region: **United States** Contact information:

MEDICAL EMERGENCY Phone: Poison Control Center

1669690

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

Telephone: +1 (860) 571-5100

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MAY BE CORROSIVE TO METALS.

HARMFUL IF SWALLOWED.

CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

HAZARD CLASS	HAZARD CATEGORY
CORROSIVE TO METALS	1
ACUTE TOXICITY ORAL	4
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1

PICTOGRAM(S)



Precautionary Statements

Keep only in original packaging. Wash affected area thoroughly after handling. Do not eat, drink Prevention:

or smoke when using this product. Wear protective gloves, clothing, eye and face protection. Response: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Rinse mouth. Do

NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

Storage: Store locked up. Store in corrosive resistant container with a resistant inner liner. Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Potassium hydroxide	1310-58-3	40 - 50

IDH number: 1669690 Product name: BONDERITE S-ST HOT 50 PAINT STRIPPER known as P3 HOT STRIPPER 50

Page 1 of 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

Skin contact: Remove contaminated clothing and footwear. For skin contact, flush with large

amounts of water. Seek immediate medical attention.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. DO NOT induce vomiting unless directed to

do so by medical personnel. Give one to two glasses of water or milk. Never give anything by mouth to a victim who is unconscious or is having

give anything by mouth to a victim who is unconscious or is having

convulsions.

Symptoms: See Section 11.

Notes to physician: If the product is ingested, probable mucosal damage may contraindicate the

use of gastric lavage. Treat the affected person appropriately. Treat

symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: This product is an aqueous mixture which will not burn.

Hazardous combustion products: Irritating and toxic gases or fumes may be released during a fire.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate personal

protective equipment. Do not allow product to enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. NEVER ADD WATER TO PRODUCT. For dilutions, add product slowly to water while stirring. Use caution; heat may be

generated. For industrial use only.

Storage: For safe storage, store at or above 40 °F (4.4 °C)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Potassium hydroxide	2 mg/m3 Ceiling	None	None	None

IDH number: 1669690 Product name: BONDERITE S-ST HOT 50 PAINT STRIPPER known as P3 HOT STRIPPER 50

Page 2 of 5

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eyelface protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious apron and boots

are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:TanOdor:StrongOdor threshold:Not available.pH:> 12.5

Vapor pressure:

Not determined

> 100 °C (> 212°F)

Melting point/ range: -23.3 °C (-9.9 °F) calculated

1.43 - 1.46 Specific gravity: Vapor density: Not determined Flash point: Not applicable Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not determined Flammability: Not applicable Evaporation rate: Not available. Solubility in water: Complete Partition coefficient (n-octanol/water): Not determined **VOC** content: Not applicable Not available. Viscosity: **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition Upon de

products:

IDH number: 1669690

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons.

Incompatible materials: This product reacts with acids. Adding water to this product may cause localized overheating

and splattering.

Reactivity: Not available.

Conditions to avoid: Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Product name: BONDERITE S-ST HOT 50 PAINT STRIPPER known as P3 HOT STRIPPER 50

Page 3 of 5

Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns.

Skin contact: Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation

and burns.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness.

Ingestion: This product may produce corrosive damage to the gastrointestinal tract if it is swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Potassium hydroxide	Oral LD50 (Rat) = 273 mg/kg Oral LD50 (Rat) = 1.23 g/kg	Corrosive, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Potassium hydroxide	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:Because of the high pH of this product, it would be expected to produce

significant ecotoxicity upon exposure to aquatic organisms and aquatic

systems.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Potassium hydroxide, solution

Hazard class or division: 8
Identification number: UN 1814

Packing group:

DOT Hazardous Substance(s): Potassium hydroxide

International Air Transportation (ICAO/IATA)

Proper shipping name: Potassium hydroxide solution Hazard class or division: 8

Identification number: UN 1814

Packing group:

Water Transportation (IMO/IMDG)

Proper shipping name: POTASSIUM HYDROXIDE SOLUTION

Hazard class or division: 8
Identification number: UN 1814
Packing group: II

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.
Immediate Health, Reactive
None above reporting de minimis.

CERCLA Reportable quantity: Potassium hydroxide (CAS# 1310-58-3) 1,000 lbs. (454 kg)

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

IDH number: 1669690 Product name: BONDERITE S-ST HOT 50 PAINT STRIPPER known as P3 HOT STRIPPER 50

Page 4 of 5

Canada Regulatory Information

IDH number: 1669690

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: Reviewed SDS. Reissued with new date.

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/15/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

Product name: BONDERITE S-ST HOT 50 PAINT STRIPPER known as P3 HOT STRIPPER 50

Page 5 of 5