



Item # \_\_\_\_\_

We put space to work.

Job \_\_\_\_\_

## MetroMax Q® Polymer / Wire Shelving

Quick-to-adjust, corrosion resistant shelving constructed of removable polymer open grid shelf mats, wire shelf frames, and corner releases. Shelf frames and steel posts have an epoxy coating over an electroplated substrate. Shelves offer a 20 year warranty against rust and corrosion. Polymer posts are rust proof. Microban® antimicrobial product protection is built into the shelf mats and posts. Shelf has a rigid four-sided frame with center truss(es). Robust corner provides complete 360° capture of the wedge and post for added stability. Stationary units have maximum capacity of 2,000 lbs. (907kg) evenly distributed. Mobile units (with stem casters) offer a maximum total unit load of 900 lbs. (408kg). Units assemble easily — shelves mount on four one-piece wedges along grooved, numbered posts and adjust on 1" (25mm) increments.

- **Forever Strong:** Proven corner connection and four-sided shelf frame with center truss(es) assures stability and strength in stationary, mobile, and high-density track shelving configurations.  
800 lbs. (363kg) per shelf for lengths of 24" to 48" (610 to 1219mm)  
600 lbs. (272kg) per shelf for lengths of 54" (1372mm) or longer  
Stationary unit: 2000lbs (907kg) evenly distributed.  
Mobile unit (with stem casters): Up to 900lbs. (408kg).  
Multiply the caster load rating by 3 to determine actual rating.
- **Long life Rust Resistance:** Shelves offer a 20 year limited corrosion warranty and are combined with rust proof polymer posts.
- **Easy to Clean and Maintain:** Polymer mats can be easily removed and cleaned in a sink or commercial washer / dish machine.
- **Microban® Antimicrobial Product Protection** is built into the shelf mats and posts to inhibit the growth of bacteria, mold, mildew, and fungus that cause odors and product degradation. Microban product protection keeps the product "cleaner between cleanings".
- **Quick-to-Adjust:** Patented corner release allows shelves to be adjusted without tools. Simply flip each corner release, relocate the wedge connectors on the posts, and reposition the shelf. Quickly adjust shelves to reclaim wasted vertical space.
- **Efficient Use of Space:** Shelves adjust on 1" (25mm) increments along the post to maximize the use of available vertical space.
- **Fast, Easy Assembly:** Shelves are ready to use right out of the box. One-piece wedges securely attach to the posts. Raised beads on the back of each wedge snap into grooves on the post. Window on wedge aligns with numbers on the post to locate the desired shelf position. Shelf mounts on four wedges. A unit can be assembled without tools in minutes.
- **Interchangeable:** Part of the MetroMax platform, MetroMax Q shelves are compatible on the same shelving units with MetroMax i and MetroMax 4 shelves.
- **Open Grid and Solid Mat Options:** MetroMax Q is available with open grid mats. Open grid shelves promote air circulation and light penetration. If a solid shelf is required, MetroMax i or MetroMax 4 solid shelves may be added to the MetroMax Q unit.
- **NSF Listed** for all environments.
- **Optional Accessories** are on spec sheet 9.25.



### Material Specifications:

- **Shelf Mats:** Injection-molded polypropylene with exclusive built-in Microban® antimicrobial product protection.
- **Shelf frames:** Steel with electroplated substrate and highly durable, abrasion-resistant epoxy finish.
- **Epoxy-coated posts:** Steel with electroplated substrate and highly durable, abrasion-resistant epoxy finish. Epoxy finish has built-in Microban antimicrobial product protection. The adjustable foot is reinforced nylon.
- **Temperature range:** -20°F (-29°C) to 125°F (52°C) continuous use, with intermittent exposure to 200°F (93°C) for cleaning.

\*MICROBAN® and the MICROBAN® symbol are registered trademarks of the Microban® Products Company, Huntersville, NC. Microban® product protection does not by itself protect a user from food borne illness. Product must be routinely cleaned.



All Metro Catalog Sheets are available on our website: [www.metro.com](http://www.metro.com)



**InterMetro Industries Corporation**  
North Washington Street, Wilkes-Barre, PA 18705  
Product Information. U.S. and Canada: 1.800.992.1776  
Outside U.S. and Canada: [www.metro.com/contactus](http://www.metro.com/contactus)

L02-178  
Printed in U.S.A. 6/22

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2022 InterMetro Industries Corp.



**MetroMax Q®** Polymer / Wire Shelving

**9.21**



# MetroMax Q<sup>®</sup> POLYMER / WIRE SHELVING

We put space to work.™

## Standard Interchangeable Shelves

Part number includes shelf with removable mats and one bag of wedges

Nominal Width/Length (in.) (mm)		Cat. No. Shelf w/ grid Mats	Nominal Width/Length (in.) (mm)		Cat. No. Shelf w/ grid Mats
14x24	355x610	<b>MQ1424G</b>	21x24	530x610	<b>MQ2124G</b>
14x30	355x760	<b>MQ1430G</b>	21x30	530x760	<b>MQ2130G</b>
14x36	355x914	<b>MQ1436G</b>	21x36	530x914	<b>MQ2136G</b>
14x42	355x1060	<b>MQ1442G</b>	21x42	530x1060	<b>MQ2142G</b>
14x48	355x1219	<b>MQ1448G</b>	21x48	530x1219	<b>MQ2148G</b>
-	-	-	21x54	530x1372	<b>MQ2154G</b>
14x60	355x1524	<b>MQ1460G</b>	21x60	530x1524	<b>MQ2160G</b>
14x72	355x1829	<b>MQ1472G</b>	21x60	530x1829	<b>MQ2172G</b>
18x24	457x610	<b>MQ1824G</b>	24x24	610x610	<b>MQ2424G</b>
18x30	457x760	<b>MQ1830G</b>	24x30	610x760	<b>MQ2430G</b>
18x36	457x914	<b>MQ1836G</b>	24x36	610x914	<b>MQ2436G</b>
18x42	457x1060	<b>MQ1842G</b>	24x42	610x1060	<b>MQ2442G</b>
18x48	457x1219	<b>MQ1848G</b>	24x48	610x1219	<b>MQ2448G</b>
18x54	457x1372	<b>MQ1854G</b>	24x54	610x1372	<b>MQ2454G</b>
18x60	457x1524	<b>MQ1860G</b>	24x60	610x1524	<b>MQ2460G</b>
18x72	457x1829	<b>MQ1872G</b>	24x60	610x1829	<b>MQ2472G</b>

## Heavy-Duty Dunnage Shelves

- Weight capacity per shelf evenly distributed: 1,200 lbs. (544kg) on shelves up to and including 48" (1219mm) long; 900 lbs. (408kg) for shelves 54" (1370mm) and longer.
- Dunnage shelves must be used on shelving units with four posts.

Grid Mat Model No.	Nominal Width (mm)		Nominal Length (mm)		Approx. Pkd. Wt. (lbs./kg)	
	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
<b>MHP2436G</b>	24	610	36	914	21	9.5
<b>MHP2448G</b>	24	610	48	1220	27	12.2
<b>MHP2454G</b>	24	610	54	1370	29	13.2
<b>MHP2460G</b>	24	610	60	1524	33	15.0

## Shelving Height Guidelines – MetroMax

Shelf Depth	14" (356mm)	18" (457mm)	21" (533mm)	24" (610mm)
<b>Maximum Post Height Allowable</b>	▼	▼	▼	▼
Stationary	63" (1600mm)	86" (2184mm)	86" (2184mm)	86" (2184mm)
Mobile	54" (1372mm)	74" (1880mm)	74" (1880mm)	86" (2184mm)

Note: 14" deep stationary shelving taller than 63" must be properly fastened to floor or the wall. Reference spec sheet 9.25, page 2 for options.


## Rust Proof Polymer Posts - Lifetime warranty against rust.

### Stationary - with leveling foot

Epoxy-Coated Steel Model No.	Approx. Pkd. Wt. (lbs.) (kg)	Nominal Height (in.) (mm)	Actual Height (in.) (mm)
<b>MX13P</b>	0.5 0.2	13 370	14 <sup>3</sup> / <sub>16</sub> 360
<b>MX27P</b>	0.9 0.4	27 685	28 <sup>3</sup> / <sub>16</sub> 716
<b>MX33P</b>	1.0 0.5	33 875	34 <sup>3</sup> / <sub>16</sub> 868
<b>MX54P</b>	1.6 0.7	54 1370	54 <sup>3</sup> / <sub>16</sub> 1376
<b>MX63P</b>	1.8 0.8	63 1585	62 <sup>3</sup> / <sub>16</sub> 1580
<b>MX74P</b>	2.3 1.0	74 1690	74 <sup>3</sup> / <sub>16</sub> 1884
<b>MX86P</b>	2.5 1.4	86 2195	86 <sup>3</sup> / <sub>16</sub> 2189

### Mobile - for stem casters

Polymer Model No.	Approx. Pkd. Wt. (lbs.) (kg)	Nominal Height (in.) (mm)	Actual Height (in.) (mm)
<b>MX13UP</b>	0.5 0.2	13 370	14 <sup>3</sup> / <sub>16</sub> 360
<b>MX27PE</b>	2.0 0.9	27 685	28 <sup>3</sup> / <sub>16</sub> 716
<b>MX33UP</b>	1.0 0.5	33 875	34 <sup>3</sup> / <sub>16</sub> 868
<b>MX54UP</b>	1.6 0.7	54 1370	54 <sup>3</sup> / <sub>16</sub> 1376
<b>MX63UP</b>	1.8 0.8	63 1585	62 <sup>3</sup> / <sub>16</sub> 1580
<b>MX70UP</b>	2.0 0.9	70 1778	69 <sup>3</sup> / <sub>16</sub> 1757
<b>MX74UP</b>	2.3 1.0	74 1690	74 <sup>3</sup> / <sub>16</sub> 1884
<b>MX86UP</b>	3.0 1.4	86 2195	86 <sup>3</sup> / <sub>16</sub> 2189



**Shelf Wedge Connector:**  
Reinforced nylon. Replacement MetroMax Q Wedges Cat. No. MQ9985 (Bag of 4)

## Epoxy Coated Steel Posts - For heavy-duty mobile applications. 15 year limited rust warranty.

### Stationary - with leveling foot

Polymer Model No.	Approx. Pkd. Wt. (lbs.) (kg)	Nominal Height (in.) (mm)	Actual Height (in.) (mm)
<b>MQ13PE</b>	1.0 0.5	13 370	14 <sup>3</sup> / <sub>16</sub> 360
<b>MQ27PE</b>	2.0 0.9	27 685	28 <sup>3</sup> / <sub>16</sub> 716
<b>MQ33PE</b>	2.5 1.1	33 875	34 <sup>3</sup> / <sub>16</sub> 868
<b>MQ54PE</b>	4.0 1.8	54 1370	54 <sup>3</sup> / <sub>16</sub> 1376
<b>MQ63PE</b>	4.5 2.0	63 1585	62 <sup>3</sup> / <sub>16</sub> 1580
<b>MQ74PE</b>	5.5 2.5	74 1690	74 <sup>3</sup> / <sub>16</sub> 1884
<b>MQ86PE</b>	6.5 2.9	86 2195	86 <sup>3</sup> / <sub>16</sub> 2189

### Mobile - for stem casters

Epoxy-Coated Steel Model No.	Approx. Pkd. Wt. (lbs.) (kg)	Nominal Height (in.) (mm)	Actual Height (in.) (mm)
<b>MQ13UPE</b>	1.0 0.5	13 370	14 <sup>3</sup> / <sub>16</sub> 360
<b>MQ27UPE</b>	2.0 0.9	27 685	28 <sup>3</sup> / <sub>16</sub> 716
<b>MQ33UPE</b>	2.5 1.1	33 875	34 <sup>3</sup> / <sub>16</sub> 868
<b>MQ54UPE</b>	4.0 1.8	54 1370	54 <sup>3</sup> / <sub>16</sub> 1376
<b>MQ63UPE</b>	4.5 2.0	63 1585	62 <sup>3</sup> / <sub>16</sub> 1580
<b>MQ70UPE</b>	2.0 0.9	70 1778	69 <sup>3</sup> / <sub>16</sub> 1757
<b>MQ74UPE</b>	5.5 2.5	74 1690	74 <sup>3</sup> / <sub>16</sub> 1884
<b>MQ86UPE</b>	6.5 2.9	86 2195	86 <sup>3</sup> / <sub>16</sub> 2189

