



Item # _____

Job _____

SUPER ERECTA SHELF® STEM CASTER CARTS — WIRE SHELVES

- **Stem Caster Carts combine Super Erecta Shelf® wire shelving features with the mobility of stem casters** to provide a high-quality, strong and versatile material handling cart.
- **Carts are preconfigured with two swivel and two swivel brake casters.** All Metro casters are non-marking and come complete with a 3½" (89mm) donut bumper.


Total cart capacity (evenly distributed)

Cart with Polyurethane casters: 900 lb. (408kg)

Cart with Resilient Rubber casters: 600 lb. (272kg)

- **Unique Design: Open wire surfaces minimize dust accumulation** and allow a free circulation of air and greater visibility.
- **Fast, Secure Assembly: Post has rolled, circular grooves** along its entire height at 1" (25mm) intervals. A tapered split sleeve snaps together around each post. Tapered openings in the shelf corners slide over the tapered split sleeves providing a positive lock. Cart is assembled in minutes without the use of any special tools.
- **Unique Post Design: SiteSelect post design** provides a visual guide for positioning and adjusting shelves, saving considerable time during assembly and adjustment. An easy-to-identify double groove, every 8" (203mm), offers a quick way to align all shelves. Posts are numbered at 2" (51mm) intervals.
- **Adjustability: Shelves can be adjusted at 1" (25mm) intervals** along the entire height of the post.
- **Versatile Construction: Super Erecta wire Shelves** can change as quickly as your needs change. By using various accessories, hundreds of shelving combinations become possible.

Note: For additional caster options see spec sheet 11.20



SiteSelect Post



SUPER ERECTA SHELF®
Wire Shelf Carts (Stem Caster Style)



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



11.01



SUPER ERECTA SHELF® STEM CASTER CARTS — WIRE SHELVES

STANDARD UNITS

Consist of four shelves, posts, plastic split sleeves*, donut bumpers and designated casters.**

With Super Erecta Brite™ Shelves & Plated Posts

63" (1600mm) Posts – Overall Height 69" (1753mm)

Model Number with Casters		Shelf Width/Length		Approx. Pkd. Wt.	
Two Swivel Two Brake Resilient Rubber Casters	Two Swivel Two Brake Polyurethane Casters	(in.)	(mm)	(lbs.)	(kg)
N336BBR	N336EBR	18x36	457x914	60	27
N356BBR	N356EBR	18x48	457x1219	72	32
N366BBR	N366EBR	18x60	457x1524	88	40
N436BBR	N436EBR	21x36	530x914	69	31
N456BBR	N456EBR	21x48	530x1219	81	36
N466BBR	N466EBR	21x60	530x1524	98	44
N536BBR	N536EBR	24x36	610x914	76	34
N556BBR	N556EBR	24x48	610x1219	92	41
N566BBR	N566EBR	24x60	610x1524	112	51

With Chrome Shelves & Plated Posts

63" (1600mm) Posts – Overall Height 69" (1753mm)

N336BC	N336EC	18x36	457x914	60	27
N356BC	N356EC	18x48	457x1219	72	32
N366BC	N366EC	18x60	457x1524	88	40
N436BC	N436EC	21x36	530x914	69	31
N456BC	N456EC	21x48	530x1219	81	36
N466BC	N466EC	21x60	530x1524	98	44
N536BC	N536EC	24x36	610x914	76	34
N556BC	N556EC	24x48	610x1219	92	41
N566BC	N566EC	24x60	610x1524	112	51

Note: Posts used on carts are Model Number 63UP.

TO ORDER BY COMPONENTS

- Order shelves from sheet 10.01 or price list. (Will be packed with plastic split sleeves*.)
- Order stem casters from sheet 11.20 or price list. Donut bumper comes with caster.

* Aluminum split sleeves are recommended when unit will be towed, transported over the road or otherwise subjected to vibration or jolting. To order, see sheet #11.06 or price list.

** Carts with polyurethane casters are designed to hold up to 900 lbs. (408 kg).

Carts with rubber casters can hold up to 600 lbs. (272 kg).

Important: When ordering by components remember that stability decreases as the ratio of height to width increases. Units should be kept as wide and low as possible.

Accessories

Aluminum Split Sleeves

Recommended when the unit will be towed, transported over-the-road, or otherwise subjected to vibration or jolting. One bag needed per shelf.

Model No. 9986Z

Bag of four aluminum sleeves with C-rings.



**Aluminum
Split Sleeves**

Handles

Can be added to stem caster carts to improve maneuverability and ergonomics. (Split sleeves are included)

Note: Handles fit unit widths only. Push handles add roughly 1" (25mm) to the length of the unit. Extended handles add 6" (153mm) to the length of the unit.



Push Handle



Extended Handle

All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741

Product Information. U.S. and Canada: 1.800.992.1776

Outside U.S. and Canada: www.metro.com/contactus

L02-035
Printed in U.S.A. Rev. 03/14

Information and specifications are subject to change without notice. Please confirm at time of order

Copyright © 2014 InterMetro Industries Corp.

