Safety Data Sheet



1. Product and Company Identification

Product Name: Ultralane® Thinner #1 (formerly known as Ultralane Thinner)

Material Uses: Thinner for Urethane, Epoxy, and other Polymeric Coatings & Adhesives

(M)SDS#: Thinner1-20181109 Validation Date: November-09-2018

Supplier/Manufacturer: Specialty Polymers & Services, Inc. (SP&S, Inc.)

27822 Fremont Court

Valencia, California (CA) 91355, U.S.A.

Non-emergency phone number: (661) 294-1790 (7AM - 5PM PST)

E-mail: msds@spolymers.com

Chemtrec (800) 424-9300 or (703) 527-3887 In case of emergency:

2. Hazards Identification

GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE:

Flammability: Category 2, H225 Skin corrosion: Category 2, H315

Skin sensitization: Category 1, H317 Reproductive Toxicity: Category 2, H361 Toxicity:

Category1, H304 Category 2A, H319 Eye damage:

Category 2, H373

Respiratory Sensitization: Category 3, H336

GHS LABEL ELEMENTS:

HAZARD SYMBOLS:







Specific target Organ:

SIGNAL WORDS:

DANGER!

HAZARD STATEMENTS:

H225 Highly Flammable liquid and vapor

H315 Causes skin irritation

H317 May Cause an allergic skin reaction

H361 Suspected of damaging fertility or the unborn child

H304 May be fatal if swallowed and enters airways

H319 Causes serious eye irritation

H336 May cause drowsiness or dizziness

H373 Causes damage to organs through prolonged or

repeated exposure.

PRECAUTIONARY STATEMENTS:

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P243 Take precautionary measures against static discharge

P260 Do not breathe mists.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P273 Avoid release to the environment.

P280 Wear protective gloves, clothing, and eye/face protection.

Printed: 11/15/2018 Ultralane® Thinner #1 (formerly Ultralane® Thinner) Page 1 of 7 RESPONSE: P301+P330+P331+P312 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. Call

POISON CENTER and/or doctor if you feel unwell.

P303+P361+P634+P353+P352 IF ON SKIN (or hair): Take off immediately all contaminated clothing and wash before reuse. Rinse skin with water/shower. Wash with plenty of soap and

P333+P313 If skin irritation or rash occurs: Get medical attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical attention.

P391 Collect spillage.

STORAGE: P403+P233 Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL: P501 Dispose of contents and containers in accordance with local, regional and international

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS) - Annex III

See toxicological information (section 11)

General Information: Read entire MSDS for a more thorough evaluation of the hazards

3. Composition / Information on Ingredients CAS Number Name 30 - 60 Toluene 108-88-3 78-93-3 30 - 502-Butanone

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, nonhazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

Eye Contact: Check for and remove any contact lenses. Immediately flush eyes for at least 15 minutes with running water. Hold eyelids apart to ensure rinsing of the entire eye surface and lids with water. Get immediate medical attention.

In case of contact, wash affected areas with plenty of water, and soap, if available, for several minutes. Remove Skin Contact:

and clean contaminated clothing and shoes before re-use. Get medical attention if irritation occurs. Inhalation:

Move exposed person to fresh air. If not breathing, give artificial respiration or oxygen. If breathing is difficult,

transport to medical care and, if available, give supplemental oxygen. Loosen tight clothing such as a collar, tie,

belt, or waistband. Get immediate medical attention.

Ingestion: Wash out mouth with water. If swallowed dilute by giving two (2) glasses water to drink. Do not induce vomiting until

direct to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate

Note to physician: No specific treatment. Treat symptomatically. Call poison control center if large quantities were ingested

5. Fire-Fighting Measures

Flash point:

>-5°C (>23°F) closed cup

Hazardous Thermal Decomposition Products: Decomposition products may include the following materials: carbon dioxide, carbon

monoxide, halogenated compounds, metal oxides and other oxides.

Extinguishing Media: Carbon dioxide, foam, dry chemical, water spray as suitable for the surrounding fire.

> Promptly isolate the scene by removing all persons from the vicinity of the fire. No actions shall be taken involving any personal risk or without suitable training.

Special Protective equipment

for fire-fighters:

Special Exposure Hazards:

No Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

6. Accidental Release Measures

Personal Precautions:

No actions shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering area. Do not touch or walk through spilled material. Avoid breathing vapor or mist and provide adequate

Printed: 11/15/2018	Ultralane® Thinner #1 (formerly Ultralane® Thinner)	Page 2 of 7
---------------------	-----------------------------------------------------	-------------

ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see Section 8).

Environmental Precautions: Methods of Clean Up:

Avoid dispersal of spitled material and runoff that leads to contact with soil, waterways, drains, and sewers. Inform the relevant authorities if the product has caused environmental pollution. Stop leak if without risk. Move containers from spill area. Approach spill from up wind if possible. Prevent spill from entering sewers, rivers and other water courses, basements, or confined areas. Wash into effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material (e.g. sand, earth, vermiculite, or diatomaceous earth) and place in container for disposal according to local regulations. Dispose of only using a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact

7.	Н	andling	and	Sto	rage

Handling:

Wear appropriate personal protective equipment (see Section 8) when handling. Eating, drinking, and smoking should be prohibited in areas where chemical are handled, stored, or processed. Workers should wash hands and face before eating, drinking, and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Persons with a history of skin sensitization problems should be employed in processes where this material is used. Keep in the original container or a suitable alternate made from a compatible material. Keep all containers tightly closed when not in use. Empty containers retain product residue and should be disposed of properly. Do not reuse empty containers for other purposes or to hold other materials.

Storage:

Store in accordance with local regulations. Store in original containers, at 15°C - 38°C (59°F - 100°F) Protect from heat, flames, sparks, and other sources of ignition. Keep away from and food and drink. Keep all containers tightly closed when not in use and tightly re-seal after use. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure	8. Exposure Controls / Personal Protection							
Ingredient	Exposure limits							
Toluene	NIOSH – TWA: 100 ppm / 375 mg/m ³							
	NIOSH - ST: 150 ppm / 560 mg/m ³							
	OSHA – TWA: 200 ppm							
Butanone	NIOSH - TWA: 200 ppm / 590 mg/m ³							
	NIOSH - ST: 300 ppm / 885 mg/m ³							
	OSHA – TWA: 200 ppm / 590 mg/m ³							
Recommende	d If this product contains ingredients with exposure limits, personal, workplace, atmospheric, or biological							
Monitoring	monitoring may be required to determine the effectiveness of the ventilation system or other control							

Procedures:

measures and/or to determine whether it is necessary to use respiratory protective equipment. It will also be necessary to reviewed national guidance documents for determining how to handle and relevant

Hazardous Substances

Engineering measures:

No special ventilation requirements are necessary for this product. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation, or other engineering controls to keep worker exposure below the recommended or statutory limits

Hygiene measures: Wash hands, forearms, and face thoroughly after handling any chemical products, before eating, smoking, and using the layatory and at the end of the work period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Personal Protection

Respiratory:

In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the

Hands:

Chemical Resistant, impervious gloves that comply with an approved safety standard should be worn at all times when handling chemical products if a risk assessment indicates that this is necessary. Consider the parameters specified by the glove manufacture and check gloves during use to ensure they are retaining their protective properties.

Printed: 11/15/2018	Ultralane® Thinner #1 (former	ly Ultralane® Thinner)	Page 3 of 7
---------------------	-------------------------------	------------------------	-------------

Eyes:

Safety eyewear complying with an approved standard should be used when a risk assessment indicates

this is necessary to avoid exposure to liquid splashes, mists, or dusts. If contact is possible, use

chemical splash googles unless a higher degree of protection is required. Skin:

Personal Protective equipment for the body should be selected based on the task being performed and the risks involved. Typical protective equipment includes non-absorbent lab coats, disposable protective sleeves, coats, or whole body suits. See a safety specialist to determine the appropriate level of protection for your task, but in general for incidental and limited splash exposure consider 7mil or

thicker latex gloves and natural rubber gloves. Supported PVA gloves may also be suitable.

Environmental Exposure Controls

Flash Point:

Emissions from ventilation or work processes should be checked to ensure they comply with the requirements of environmental regulations. In some cases, tume scrubbers, filters, or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. Physical and Chemical Properties Appearance: Clear to very light yellow liquid Boiling Point:

79°C (174°F) (initial) >-5°C (>23°F) closed cup

Freezing Point: nH· Flammable Limits:

Odor

Aromatic solvent Not determined Not determined Not determined

Auto-ignition Temperature: Not determined Vapor Pressure: Specific Gravity:

~22mm Hg at 20°C (68°F) (estimated) Water Solubility: Vapor Density:

Appreciable >1 (Air = 1)

Evaporation Rate: Viscosity:

5 (butyl acetate =1) ~10 cps

~430 g/ L (estimated) VOC:

10. Stability and Reactivity

Chemical Stability:

This product is stable, under normal conditions of storage and use, hazardous reactions will not occur.

Hazardous Polymerization: Under normal conditions of storage and use, hazardous polymerization will not occur.

Conditions to Avoid: Avoid sources of ignition (sparks or flames). Do not pressurize, cut, weld, braze, solder, drill, grind, or expose containers to heat. Avoid high temperatures and exposure to strong exidizing agents, acids, and

Hazardous Decomposition Under normal conditions of storage and use, hazardous decomposition products should not be produced.

11. Toxicological Information

cute	Toxicity	

Product/Ingredient Name	Test	Endpoint	Species	Result
2-Butanone		LC50 Inhalation	Mammal	38000 mg/m³
	1	Dusts & mists		1
		LD50 Dermal	Rabbit	>6480 mg/kg
		LD50 Oral	Rat	2737 mg/kg
Toluene		LC50 Inhalation	Rat, 4hours	12500 - 28800 mg/m ³
		Vapor		
	T	LD50 Dermal	Rabbit	12196 mg/kg
		LD50 Oral	Rat - male	>5580 ml/kg

imitation / Corresion -			
Product/Ingredient Name	Test	Species	Result
2-Butanone	OECD 404 Acute Dermal Initation/Corrosion	Rabbit	Skin - non-irritant
		Rabbit	Eyes - irritating
Toluene	OECD 404 Acute Dermal Imitation/Corrosion	Rabbit	Skin irritating
		Rabbit	Eyes - non-initant

Mutagenicity

Product/Ingredient Name	Test	Result
2-Butanone		No date available
Toluene	Rat	Liver & DNA damage

Conclusion/ Summary: the weight of scientific evidence indicates that the components of this product are not cenotoxic

Toluene is classified by IARC as Group 3 (Not classifiable as to its carcinogenicity to humans). No other component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human

Printed: 11/15/2018	Ultralane® Thinner #1 (formerly Ultralane® Thinner)	Page 4 of 7

carcinogen by IARC. No components of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by ACGIH, NTP or OSHA.

Perceductive Toxicity

Product/Ingredient Name Test		Species	Maternal Toxicity	Fortility	Developmental Effects
Toluene	Inhalation effects	Rat	Yes	Yes	Stunted fetus

I BESTOCK IICHA			
Product/Ingredient Name	Test	Species	Results
2-Butanone			No data available
Tobiene			No data available

Potential Acute Health Effects

Irritating to the respiratory system, may cause drowsiness or dizziness Inhalation:

Ingestion: Toxic by ingestion.

Skin Contact:

May cause skin dryness and sensitization by skin contact.

Eye Contact:

May cause serious eye imitation

Potential Chronic Health Effects

Product/Ingredient Name	Test	Endpoint	Species	Results
Totuene	Long term Inhalation studies		Animal	Lung & stomach irritation, chest pain, pulmonary edema, an ulcerous lesion on the penis, prepuce, and scrotum.
Toluene	Long term exposure studies		Humans	Central nervous system & stomach irregularities possible based on human evidence

General:

Once sensitized, an allergic reaction may occur when subsequently exposed to very low levels

Target Organs: Carcinogenicity: Primarily Lungs, stomach, & central nervous system No known significant effects or critical hazards No known significant effects or critical hazards

Mutagenicity: Teratogenicity: Developmental Effects:

No known significant effects or critical hazards Evidence of effects on fetal development in animals

Fertility Effects: Evidence of effects on fertility in animals

12. Ecological Information

Environmental Effects: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Amustia Esstavisit

Product/Ingredient Name	Test	Endpoint	Exposure	Species	Result
Toluene	OECD 202 Daphnia Sp. Acute Immobilization Test	Acute EC50	24 hours Static	Daphnia	>8 mg/L
	OECD 203 Fish, Acute toxicity test	Acute LC50	96 hours Static	Fish	7.63 mg/L
	OECD 203 Fish, Acute toxicity test	Acute LC50	96 hours Static	Fish	245 mg/L
2-Butanaone	OECD 202 Daphnia Sp. Acute Immobilization Test	Acute EC50	24 hours Static	Daphnia	>7060 mg/L
	OECD 203 Fish, Acute toxicity test	Acute LC50	96 hours Static	Fish	400 mg/L
	OECD 203 Fish. Acute toxicity test	Acute LC50	96 hours Static	Fish	mg/L

Persistance and Doomdobilla

	Persistence and Degradad	HILL			
1	Product/ingredient Name	Test		Period	Result
1	2-Butanone	-OECD der	ved from OECD 301F (Biodegradation test)		Readily biodegradable
	Toluene	-OECD der	ved from OECD 301F (Biodegradation test)		Readily biodegradable
•					
- 1	Product/Ingredient Name		Aquatic half-life	Photolysis	Biodegradability
1	Toluene			•	readily

Bioaccumulative potential			
Product/Ingredient Name	Log Pow	BCF	Potential
Toluene	•	•	-
2-Butanone	•	. •	-

Other adverse effects:

Other information:

No known significant effects or critical hazards

BOD5: Not Determined

COD: Not Determined

TOC: Not Determined

Printed: 11/15/2018	Ultralane® Thinner #1 (formerly Ultralane® Thinner)	Page 5 of 7

13. Disposal Consideration

Waste Disposal Method: Disposal of this products, solutions, and by-products should at all times comply with the requirements of environmental and waste disposal legislation and any regional or local authority requirements. Dispose of surplus, non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed on untreated to the sewer system unless this is complaint with all applicable laws and regulations. Incineration by an approved and licensed contractor is the most common disposal method. Packaging materials that and absorbents containing the product can typically be landfilled or incinerated. Contact local authorities to determine the proper means of disposal in your area.

14. Transport Information

DOT. 49CFR: Non-Bulk

Label:

Flammable liquid

Proper Shipping Name: Hazard Class:

Flammable Liquid, n.o.s. (Ethyl Methyl Ketone, Toluene) ID Number:

UN1993 Packing Group: PGII

Reportable Quantity (RQ): >2000 lbs. (Toluene)

Flammable liquid

IATA: Non-Rulk

Proper Shipping Name: Hazard Class:

Flammable Liquid, n.o.s. (Ethyl Methyl Ketone, Toluene)

ID Number: UN1993 Packing Group: PGII

15. REGULATORY INFORMATION

US Federal Regulations:

Occupational Safety and Health Act (OSHA): This product is a hazardous chemical under the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Resource Conservation and Recovery Act (RCRA): This product is a hazardous waste under RCRA (40 CFR 261).

SARA Title III: Section 304 - CERCLA: This product contains one or more chemicals regulated under Section 304 as extremely hazardous substance(s) for emergency release notification ("CERCLA" List):

Ingredient	CAS#	Component RQ (lbs.)	Calculated Product RQ (Lbs.
Toluene	108-88-3	1000	>2000
Butanone	78-93-3	5000	>10000

SARA Title III: Section 311/312 - Hazard Communication Standard (HCS): Immediate (acute) health hazard

Delayed (chronic) health hazard

SARA Title III: Section 313 Toxic Chemical List (TCL): This product does not contain a toxic chemical for routine annual Toxic Chemical Release Reporting under section 313 (40 CFR 372).

TSCA Section 8(b) - Inventory Status: All chemical(s) comprising this product are listed on the TSCA inventory.

TSCA Section 12(b) - Export Notification: This product does not contain chemicals which are subject to Section 12(b) export notification

State Regulations:

California Proposition 65: A WARNING: This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

International Regulations:

REACH Status (EC 1907/2008): This material has been registered, pre-registered, or is otherwise exempt from registration under REACH.

REACH Annex XIV (SVHC): No listed components as of validation date

Reach Annex XVIII (Restrictions on the manufacture, placing on the market & use of certain dangerous substances, mixtures, and articles); No list components as of validation date

WHMIS:

Class B-2: Flammable Liquids: Flashpoint of <37.8°C (100°F)

Class D-2B: Material causing other toxic effects

International Lists:

Australia Inventory (AICS) Canadian Inventory (CEPA-DSL):

all components are listed or exempt all components are listed or exempt Malaysia Inventory (EHS register): New Zealand Inv. of Chem. (NZioC):

not determined all components are listed or exempt

China Inventory (IECSC): Japan Inventory (ENCS):

all components are listed or exempt all components are listed or exempt

Philippines Inventory (PICCS): Talwan Inventory (CSNN):

Not determined not determined

Printed: 11/15/2018 Ultralane® Thinner #1 (formerly Ultralane® Thinner) Page 6 of 7

all components are listed or exempt

16. OTHER INFORMATION

Hazardous Material Information Sys	tem (HMIS) - USA	National Fire Protection Association (USA):
Health	2	-VMV
Flammability	ω	
Physical Hazards		
Personal Protection	Ç.	

Reason Issued: Prepared by: update Chris Meyer

NOTICE TO READER. While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE. Approved by: Chris Meyer Title: Vice President

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF PRODUCTS FOR THE USER'S PARTICULAR PURPOSE(S).

THIS PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST. The product(s) has not been tested for, and is therefore not recommended for, uses for which prolonged contact with mucous membranes, abraded skin, or blood is intended; or for uses for which implentation within the human body is intended.

Printed: 11/15/2018 Ultralane® Thinner #1 (formerly Ultralane® Thinner) Page 7 of 7