



Revision Number: 005.0

Issue date: 08/23/2021

1. PRODUCT AND COMPANY IDENTIFICATION


Product name: BONDERITE M-NT 1455 CR FREE CONVERSION COATING known as BONDERITE 1455
IDH number: 595577
Product type/use: Coating
Item number: 595577
Restriction of Use: None identified
Region: United States
Company address: Henkel Corporation
 Telephone: +1 (860) 571-5100
 One Henkel Way
 MEDICAL EMERGENCY Phone: Poison Control Center
 1-877-671-4608 (toll free) or 1-303-592-1711
 Rocky Hill, Connecticut 06067
 TRANSPORT EMERGENCY Phone: CHEMTREC
 1-800-424-9300 (toll free) or 1-703-527-3887
 Internet: www.henkeln.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: CONTAINS FLUORIDES. MAY CAUSE DELAYED BURNS (NOT IMMEDIATELY PAINFUL OR VISIBLE)! LONG TERM EXPOSURE TO FLUORIDES OVER YEARS MAY CAUSE FLUOROSIS!
 COMBUSTIBLE LIQUID.
 HARMFUL IF SWALLOWED OR IF INHALED.
 TOXIC IN CONTACT WITH SKIN.
 CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.
 MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
ACUTE TOXICITY ORAL	4
ACUTE TOXICITY INHALATION	4
ACUTE TOXICITY DERMAL	3
SKIN CORROSION	1C - Corrosive
SERIOUS EYE DAMAGE	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2



Precautionary Statements

Prevention:

Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not breathe vapors, mist, or spray. Wash affected area thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves, clothing, eye and face protection.

Response:

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. Take off contaminated clothing. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.

IDH number: 595577

Product name: BONDERITE M-NT 1455 CR FREE CONVERSION COATING known as BONDERITE 1455

Storage:

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:

Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
1-Propoxy-2-propanol	1569-01-3	5 - 10
Phosphoric acid, manganese salt	10124-54-6	1.0 - 5.0
Hexafluorotitanic acid	17439-11-1	1.0 - 5.0
Phosphoric acid	7664-38-2	0.1 - 1
Hydrogen fluoride	7664-39-3	0.1 - 1

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:

If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist. If breathing is difficult, give oxygen. Trained personnel should administer 2.5% calcium gluconate through a nebulizer for 20 minutes.

Skin contact:

Remove contaminated clothing and footwear while rinsing the affected area with large amounts of running water for at least 15 minutes. GET IMMEDIATE MEDICAL ATTENTION. If iced solution of 0.13% aqueous Benzalkonium Chloride (Zephiran) or 2.5% calcium gluconate gel is available, rinsing may be limited to 5 minutes, with the soak solution or gel applied as soon as the rinsing is stopped. Gloves should be worn when applying the gel to prevent transfer of HF and secondary burns. If using calcium gluconate gel, it should be continuously re-applied and massaged into the affected area until pain has been relieved for at least 30 minutes. If Benzalkonium Chloride (Zephiran) or calcium gluconate gel is not available, rinsing must continue until medical treatment is provided.

Eye contact:

Immediately flush affected eye with large amounts of gently flowing water or 0.9% sterile saline solution for at least 15 minutes. Hold eyelid wide open. Get immediate medical attention. Eye flushing should continue during transportation to a doctor.

Ingestion:

Get immediate medical attention. Do not induce vomiting. Attempt immediate administration of a fluoride binding substance: milk, chewable calcium carbonate tablets or 4-8 ounces (120-240 ml) of milk of magnesia or a liquid antacid. Avoid large amounts of liquid as it may induce vomiting.

Symptoms:

See Section 11.

Notes to physician:

Treatment of hypocalcemia associated with corrosive fluoride compounds exposure may be corrected by intravenous calcium gluconate or calcium chloride. Treatment of hypomagnesemia may be corrected by intravenous magnesium sulfate.

5. FIRE FIGHTING MEASURES

Extinguishing media:

Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures:

Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Hydrogen fluoride.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. For industrial use only. Do not take internally.

Storage: For safe storage, store between 40 °F (4.4 °C) and 100 °F (37.8 °C) Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
1-Propoxy-2-propanol	None	None	None	None
Phosphoric acid, manganese salt	0.02 mg/m ³ TWA (as Mn) Respirable fraction. 0.1 mg/m ³ TWA (as Mn) Inhalable fraction.	5 mg/m ³ Ceiling (as Mn)	None	None
Hexafluorotitanic acid	2.5 mg/m ³ TWA (as F) 2.5 mg/m ³ TWA (as F)	2.5 mg/m ³ PEL (as F) 2.5 mg/m ³ TWA Dust. 2.5 mg/m ³ PEL (as F) 2.5 mg/m ³ TWA Dust.	None	None
Phosphoric acid	3 mg/m ³ STEL 1 mg/m ³ TWA	1 mg/m ³ PEL	None	None
Hydrogen fluoride	2 ppm Ceiling (as F) 0.5 ppm TWA (as F) (SKIN) (as F)	2.5 mg/m ³ PEL (as F) 3 ppm TWA	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Liquid
Color:	Brown
Odor:	Bland
Odor threshold:	Not available.
pH:	< 2 (6% solution)
Vapor pressure:	Not determined
Boiling point/range:	> 155.6 °C (> 312.1 °F)
Melting point/ range:	Not determined
Specific gravity:	1.09 - 1.12 at 15.6 °C (60.08 °F)
Vapor density:	Not determined
Flash point:	63.3 °C (145.94 °F) Tagliabue closed cup
Flammable/Explosive limits - lower:	Not available.
Flammable/Explosive limits - upper:	Not available.
Autoignition temperature:	Not determined
Flammability:	Not applicable
Evaporation rate:	Not determined
Solubility in water:	Complete
Partition coefficient (n-octanol/water):	Not determined
VOC content:	5 % EPA Method 24
Viscosity:	Not available.
Decomposition temperature:	Not available.

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	None under normal processing.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. May liberate hydrogen fluoride.
Incompatible materials:	This product may react with strong alkalis. This material will react with glass, concrete, certain metals, silica containing materials, rubber, leather, and many organics.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure:	Skin, Inhalation, Eyes, Ingestion
-------------------------------------	-----------------------------------

Potential Health Effects/Symptoms

Inhalation:	Mists, vapors or liquid may cause severe irritation or burns. Contains fluorides. Exposure to fluorides over years may cause fluorosis.
Skin contact:	This product is severely irritating to the skin and may cause burns. Liquid or vapor can cause fluoride-type irritation or burns which may not be immediately painful or visible. Hydrofluoric acid will penetrate the skin and attack underlying tissue and bone. Large burns (over 25 square inches) may also cause hypocalcemia and other systemic effects which may be fatal.
Eye contact:	This product is severely irritating to the eyes and may cause irreversible damage including burns and blindness.
Ingestion:	Ingestion of small amounts of this product may result in potentially fatal hypocalcemia and systemic toxicity. Ingestion of large amounts of this product may result in fluoride poisoning including symptoms of calcification of the ligaments and severe bone changes making normal movements painful, mottling of the teeth, pulmonary fibrosis, anemia, anorexia, dental effects, and possibly death. Ingestion causes burns of the upper digestive and respiratory tracts. Contains fluorides. Exposure to fluorides over years may cause fluorosis.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
1-Propoxy-2-propanol	Oral LD50 (Rat) = 2.8 g/kg Dermal LD50 (Rabbit) = 3.55 g/kg	Central nervous system, Eyes, Irritant, Kidney
Phosphoric acid, manganese salt	None	Behavioral, Blood, Developmental, Irritant, Kidney, Liver, Lung, Mutagen, Nervous System, Reproductive, Respiratory, Vascular
Hexafluorotitanic acid	None	No Records
Phosphoric acid	Oral LD50 (Rat) = 1,530 mg/kg Dermal LD50 (Rabbit) = 2,740 mg/kg	Irritant, Corrosive
Hydrogen fluoride	None	Allergen, Blood, Bone Marrow, Cardiac, Central nervous system, Corrosive, Irritant, Kidney, Liver, Lung, Muscle, Nervous System, Respiratory, Teeth

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
1-Propoxy-2-propanol	No	No	No
Phosphoric acid, manganese salt	No	No	No
Hexafluorotitanic acid	No	No	No
Phosphoric acid	No	No	No
Hydrogen fluoride	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Do not empty into drains / surface water / ground water / soil.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (Hexafluoro titanic acid, Phosphoric acid)
Hazard class or division: 8
Identification number: UN 3264
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Corrosive liquid, acidic, inorganic, n.o.s. (Hexafluoro titanic acid, Phosphoric acid)
Hazard class or division: 8
Identification number: UN 3264
Packing group: III

Water Transportation (IMO/IMDG)**Proper shipping name:**

CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Hexafluoro titanate acid, Phosphoric acid)

Hazard class or division:

8

Identification number:

UN 3264

Packing group:

III

15. REGULATORY INFORMATION**United States Regulatory Information**

TSCA 8 (b) Inventory Status:	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification:	None above reporting de minimis
CERCLA/SARA Section 302 EHS:	Hydrogen fluoride (CAS# 7664-39-3).
CERCLA/SARA Section 311/312:	Immediate Health, Delayed Health
CERCLA/SARA Section 313:	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Manganese dioxide (CAS# 1313-13-9). Phosphoric acid, manganese salt (CAS# 10124-54-6).
California Proposition 65:	This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status:	One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.
------------------------------	---

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: This Safety Data Sheet contains changes from the previous version in Section(s): 2, 3, 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 08/23/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.