



3M General Offices
3M Center
St. Paul, MN 55144-1000
1-800-364-3577 or (651) 737-6501 (24 hours)

Safety Data Sheet

2023-05-12 13:09:01.23

| | | |
|-------------------|------------|------------------------|
| Purchase Order #: | 81034 | SDS Coordinator |
| Customer Number: | 0016124695 | HISCO |
| | | CONCORD PARK DR 6650 |
| | | HOUSTON, TX 77040-4098 |
| | | USA |

Dear SDS Coordinator

Enclosed is the Safety Data Sheet (SDS)* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at www.3m.com/MSDSSearch.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at emsdsadmin@mmm.com

*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Safety Data Sheet

Copyright,2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 41-7884-4 | Version Number: | 1.05 |
| Issue Date: | 02/28/23 | Supersedes Date: | 08/08/22 |

Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8710NS, Black, Kit

| ID Number | UPC | ID Number | UPC |
|----------------|-----|----------------|-----|
| 62-2870-1445-0 | | 62-2870-3630-5 | |
| 62-2870-5030-6 | | | |

7100233348, 7100233349, 7100291547

Recommended use

Adhesive

Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet (SDS), Article Information Sheet (AIS), or Article Information Letter (AIL) for each of these components is included. Please do not separate the component documents from this cover page. The document numbers for components of this product are:

41-7837-2, 41-7883-6

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy.

In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright,2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 41-7837-2 | Version Number: | 1.05 |
| Issue Date: | 02/08/23 | Supersedes Date: | 11/29/21 |

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8710NS, Black, Part B

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 2A.

Skin Sensitizer: Category 1.

Specific Target Organ Toxicity (single exposure): Category 3.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause respiratory irritation.

Precautionary Statements**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves and eye/face protection.
 Wash thoroughly after handling.
 Contaminated work clothing must not be allowed out of the workplace.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 If eye irritation persists: Get medical advice/attention.
 IF ON SKIN: Wash with plenty of soap and water.
 If skin irritation or rash occurs: Get medical advice/attention.
 Wash contaminated clothing before reuse.
 Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

Store in a well-ventilated place. Keep container tightly closed.
 Store locked up.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

14% of the mixture consists of ingredients of unknown acute oral toxicity.
 14% of the mixture consists of ingredients of unknown acute dermal toxicity.
 68% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|---------------|-------------------------|
| Hydroxyethyl Methacrylate | 868-77-9 | 25 - 50 Trade Secret * |
| Butadiene-Acrylonitrile Polymer | 9003-18-3 | 1 - 20 Trade Secret * |
| Fillers (NJTS Reg. No. 04499600-6923) | Trade Secret* | 0.1 - 20 Trade Secret * |
| Cyclohexyl methacrylate | 101-43-9 | 1 - 15 Trade Secret * |
| Lauryl methacrylate | 142-90-5 | 1 - 15 Trade Secret * |
| Polymeric Methacrylate (NJTS Reg. No. 04499600-7447) | Trade Secret* | 3 - 15 Trade Secret * |
| Acrylic Copolymer (NJTS Reg. No. 04499600-7448) | Trade Secret* | <= 10 Trade Secret * |
| Amorphous silica | 67762-90-7 | 1 - 5 Trade Secret * |
| Hexadecyl methacrylate | 2495-27-4 | 0.1 - 5 Trade Secret * |
| Hydroxypropyl methacrylate | 27813-02-1 | 0.1 - 5 Trade Secret * |
| Myristyl methacrylate | 2549-53-3 | 1 - 5 Trade Secret * |
| Urethane Acrylate Oligomer (NJTS Reg. No. 04499600-7410) | Trade Secret* | 0.1 - 5 Trade Secret * |
| Phosphate Esters of PPG Methacrylate | 95175-93-2 | < 3 Trade Secret * |
| 4-Methoxyphenol | 150-76-5 | < 1 Trade Secret * |

| | | |
|---------------------|-----------|-----------------------|
| Carbon Black | 1333-86-4 | < 1 Trade Secret * |
| Methyl Methacrylate | 80-62-6 | < 1 Trade Secret * |
| Copper Naphthenates | 1338-02-9 | < 0.25 Trade Secret * |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Irritating to the respiratory tract (coughing, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain). Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide
Carbon dioxide
Hydrogen Chloride
Oxides of Nitrogen

Condition

During Combustion
During Combustion
During Combustion
During Combustion

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

| Ingredient | C.A.S. No. | Agency | Limit type | Additional Comments |
|---------------------------------------|--------------|--------|---|---|
| Carbon Black | 1333-86-4 | ACGIH | TWA(inhalable fraction):3 mg/m ³ | A3: Confirmed animal carcin. |
| Carbon Black | 1333-86-4 | OSHA | TWA:3.5 mg/m ³ | |
| COPPER COMPOUNDS | 1338-02-9 | ACGIH | TWA(as Cu, fume):0.2 mg/m ³ ;TWA(as Cu dust or mist):1 mg/m ³ | |
| 4-Methoxyphenol | 150-76-5 | ACGIH | TWA:5 mg/m ³ | |
| SILICA, AMORPHOUS | 67762-90-7 | OSHA | TWA:20 millions of particles/cu. ft.;TWA concentration:0.8 mg/m ³ | |
| Methyl Methacrylate | 80-62-6 | ACGIH | TWA:50 ppm;STEL:100 ppm | A4: Not class. as human carcin, Dermal Sensitizer |
| Methyl Methacrylate | 80-62-6 | OSHA | TWA:410 mg/m ³ (100 ppm) | |
| Fillers (NJTS Reg. No. 04499600-6923) | Trade Secret | ACGIH | TWA(respirable fraction):2 mg/m ³ | A4: Not class. as human carcin |
| Fillers (NJTS Reg. No. | Trade | OSHA | TWA(as total dust):15 | |

| | | | | |
|---------------------------------------|--------------|------|---|--|
| 04499600-6923) | Secret | | mg/m3;TWA(as total dust):50 millions of particles/cu. ft.(15 mg/m3);TWA(respirable fraction):5 mg/m3;TWA(respirable fraction):15 millions of particles/cu. ft.(5 mg/m3) | |
| Fillers (NJTS Reg. No. 04499600-6923) | Trade Secret | OSHA | TWA(as total dust):15 mg/m3;TWA(respirable fraction):5 mg/m3 | |

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 OSHA : United States Department of Labor - Occupational Safety and Health Administration
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

- Safety Glasses with side shields
- Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:
 Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--|
| Appearance | |
| Physical state | Liquid |
| Color | Black |
| Specific Physical Form: | Paste |
| Odor | Acrylate |
| Odor threshold | <i>No Data Available</i> |
| pH | <i>Not Applicable</i> |
| Melting point | <i>Not Applicable</i> |
| Boiling Point | <i>No Data Available</i> |
| Flash Point | > 200 °F [Test Method: Closed Cup] |
| Evaporation rate | <i>No Data Available</i> |
| Flammability (solid, gas) | Not Applicable |
| Flammable Limits(LEL) | <i>No Data Available</i> |
| Flammable Limits(UEL) | <i>No Data Available</i> |
| Vapor Pressure | <i>No Data Available</i> |
| Vapor Density | <i>No Data Available</i> |
| Density | 1.04 g/ml |
| Specific Gravity | 1.04 [Ref Std: WATER=1] |
| Solubility in Water | Nil |
| Solubility- non-water | <i>No Data Available</i> |
| Partition coefficient: n-octanol/ water | <i>No Data Available</i> |
| Autoignition temperature | <i>No Data Available</i> |
| Decomposition temperature | <i>No Data Available</i> |
| Viscosity | 40,000 centipoise |
| Hazardous Air Pollutants | <=1 % weight [Test Method: Calculated] |
| Molecular weight | <i>Not Applicable</i> |
| VOC Less H2O & Exempt Solvents | <=10 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A] |
| VOC Less H2O & Exempt Solvents | <=575 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: as supplied] |
| VOC Less H2O & Exempt Solvents | <=1 % [Test Method: calculated SCAQMD rule 443.1] [Details: when used as intended with Part A] |

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat

Sparks and/or flames

10.5. Incompatible materials

Amines

Strong acids

Strong bases

Strong oxidizing agents

10.6. Hazardous decomposition products**Substance**

None known.

Condition

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects**Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Mild Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Carcinogenicity:

| Ingredient | CAS No. | Class Description | Regulation |
|-------------------|----------------|-------------------------------|---|
| Carbon black | 1333-86-4 | Grp. 2B: Possible human carc. | International Agency for Research on Cancer |

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|---------------------------|------------------------|-----------------|--|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Inhalation-Vapor(4 hr) | | No data available; calculated ATE >50 mg/l |
| Overall product | Ingestion | | No data available; calculated ATE >5,000 mg/kg |
| Hydroxyethyl Methacrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Hydroxyethyl Methacrylate | Ingestion | Rat | LD50 5,564 mg/kg |
| Cyclohexyl methacrylate | Dermal | Rat | LD50 > 2,000 mg/kg |
| Cyclohexyl methacrylate | Ingestion | Rat | LD50 12,900 mg/kg |
| Cyclohexyl methacrylate | Inhalation-Vapor | similar compoun | LC50 estimated to be 20 - 50 mg/l |

| | | ds | |
|---------------------------------------|--------------------------------|------------------------|------------------------------------|
| Lauryl methacrylate | Dermal | | estimated to be > 5,000 mg/kg |
| Lauryl methacrylate | Inhalation-Dust/Mist | | estimated to be > 12.5 mg/l |
| Lauryl methacrylate | Ingestion | | estimated to be > 5,000 mg/kg |
| Fillers (NJTS Reg. No. 04499600-6923) | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Fillers (NJTS Reg. No. 04499600-6923) | Ingestion | Human | LD50 > 15,000 mg/kg |
| Butadiene-Acrylonitrile Polymer | Dermal | Rabbit | LD50 > 15,000 mg/kg |
| Butadiene-Acrylonitrile Polymer | Ingestion | Rat | LD50 > 30,000 mg/kg |
| Amorphous silica | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Amorphous silica | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.691 mg/l |
| Amorphous silica | Ingestion | Rat | LD50 > 5,110 mg/kg |
| Myristyl methacrylate | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Myristyl methacrylate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Phosphate Esters of PPG Methacrylate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Phosphate Esters of PPG Methacrylate | Dermal | similar health hazards | LD50 estimated to be > 5,000 mg/kg |
| Hydroxypropyl methacrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Hydroxypropyl methacrylate | Ingestion | Rat | LD50 > 11,200 mg/kg |
| Hexadecyl methacrylate | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Hexadecyl methacrylate | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Carbon Black | Dermal | Rabbit | LD50 > 3,000 mg/kg |
| Carbon Black | Ingestion | Rat | LD50 > 8,000 mg/kg |
| Methyl Methacrylate | Dermal | Rabbit | LD50 > 5,000 mg/kg |
| Methyl Methacrylate | Inhalation-Vapor (4 hours) | Rat | LC50 29 mg/l |
| Methyl Methacrylate | Ingestion | Rat | LD50 7,900 mg/kg |
| Copper Naphthenates | Dermal | similar compound | LD50 > 2,000 mg/kg |
| Copper Naphthenates | Ingestion | similar compound | LD50 > 300, < 2,000 mg/kg |
| 4-Methoxyphenol | Dermal | Rat | LD50 > 2,000 mg/kg |
| 4-Methoxyphenol | Ingestion | Rat | LD50 1,630 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------------------------|------------------------|---------------------------|
| Hydroxyethyl Methacrylate | Rabbit | Minimal irritation |
| Cyclohexyl methacrylate | Rabbit | Minimal irritation |
| Butadiene-Acrylonitrile Polymer | Professional judgement | No significant irritation |
| Fillers (NJTS Reg. No. 04499600-6923) | Professional judgement | No significant irritation |
| Amorphous silica | Rabbit | No significant irritation |
| Myristyl methacrylate | Rabbit | Minimal irritation |
| Phosphate Esters of PPG Methacrylate | Not available | Irritant |
| Hydroxypropyl methacrylate | Rabbit | Minimal irritation |
| Hexadecyl methacrylate | Rabbit | Minimal irritation |
| Carbon Black | Rabbit | No significant irritation |
| Methyl Methacrylate | Human and animal | Mild irritant |

| | | |
|---------------------|--------|---------------------------|
| Copper Naphthenates | Rabbit | No significant irritation |
| 4-Methoxyphenol | Rabbit | Mild irritant |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---------------------------------------|------------------------|---------------------------|
| Hydroxyethyl Methacrylate | Rabbit | Moderate irritant |
| Cyclohexyl methacrylate | In vitro data | Mild irritant |
| Butadiene-Acrylonitrile Polymer | Professional judgement | No significant irritation |
| Fillers (NJTS Reg. No. 04499600-6923) | Professional judgement | No significant irritation |
| Amorphous silica | Rabbit | No significant irritation |
| Myristyl methacrylate | Rabbit | No significant irritation |
| Phosphate Esters of PPG Methacrylate | Not available | Corrosive |
| Hydroxypropyl methacrylate | Rabbit | Moderate irritant |
| Hexadecyl methacrylate | Rabbit | No significant irritation |
| Carbon Black | Rabbit | No significant irritation |
| Methyl Methacrylate | Rabbit | Moderate irritant |
| Copper Naphthenates | In vitro data | No significant irritation |
| 4-Methoxyphenol | Rabbit | Severe irritant |

Skin Sensitization

| Name | Species | Value |
|----------------------------|------------------------|--|
| Hydroxyethyl Methacrylate | Human and animal | Sensitizing |
| Cyclohexyl methacrylate | Guinea pig | Sensitizing |
| Lauryl methacrylate | Guinea pig | Not classified |
| Amorphous silica | Human and animal | Not classified |
| Myristyl methacrylate | Professional judgement | Some positive data exist, but the data are not sufficient for classification |
| Hydroxypropyl methacrylate | Human and animal | Sensitizing |
| Hexadecyl methacrylate | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Methyl Methacrylate | Human and animal | Sensitizing |
| Copper Naphthenates | Guinea pig | Not classified |
| 4-Methoxyphenol | Guinea pig | Sensitizing |

Respiratory Sensitization

| Name | Species | Value |
|---------------------|---------|----------------|
| Methyl Methacrylate | Human | Not classified |

Germ Cell Mutagenicity

| Name | Route | Value |
|----------------------------|----------|--|
| Hydroxyethyl Methacrylate | In vivo | Not mutagenic |
| Hydroxyethyl Methacrylate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Amorphous silica | In Vitro | Not mutagenic |
| Myristyl methacrylate | In Vitro | Not mutagenic |
| Hydroxypropyl methacrylate | In vivo | Not mutagenic |
| Hydroxypropyl methacrylate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| Carbon Black | In Vitro | Not mutagenic |
| Carbon Black | In vivo | Some positive data exist, but the data are not sufficient for classification |
| Methyl Methacrylate | In vivo | Not mutagenic |
| Methyl Methacrylate | In Vitro | Some positive data exist, but the data are not sufficient for classification |
| 4-Methoxyphenol | In vivo | Not mutagenic |
| 4-Methoxyphenol | In Vitro | Some positive data exist, but the data are not sufficient for classification |

Carcinogenicity

| Name | Route | Species | Value |
|---------------------------------------|---------------|-------------------------|--|
| Fillers (NJTS Reg. No. 04499600-6923) | Inhalation | Multiple animal species | Not carcinogenic |
| Amorphous silica | Not Specified | Mouse | Some positive data exist, but the data are not sufficient for classification |
| Carbon Black | Dermal | Mouse | Not carcinogenic |
| Carbon Black | Ingestion | Mouse | Not carcinogenic |
| Carbon Black | Inhalation | Rat | Carcinogenic |
| Methyl Methacrylate | Ingestion | Rat | Not carcinogenic |
| Methyl Methacrylate | Inhalation | Human and animal | Not carcinogenic |
| 4-Methoxyphenol | Dermal | Multiple animal species | Not carcinogenic |
| 4-Methoxyphenol | Ingestion | Multiple animal species | Some positive data exist, but the data are not sufficient for classification |

Reproductive Toxicity

Reproductive and/or Developmental Effects

| Name | Route | Value | Species | Test Result | Exposure Duration |
|----------------------------|-----------|--|---------|-----------------------|--------------------------------|
| Hydroxyethyl Methacrylate | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | prematuring & during gestation |
| Hydroxyethyl Methacrylate | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 49 days |
| Hydroxyethyl Methacrylate | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | prematuring & during gestation |
| Amorphous silica | Ingestion | Not classified for female reproduction | Rat | NOAEL 509 mg/kg/day | 1 generation |
| Amorphous silica | Ingestion | Not classified for male reproduction | Rat | NOAEL 497 mg/kg/day | 1 generation |
| Amorphous silica | Ingestion | Not classified for development | Rat | NOAEL 1,350 mg/kg/day | during organogenesis |
| Hydroxypropyl methacrylate | Ingestion | Not classified for female reproduction | Rat | NOAEL 1,000 mg/kg/day | prematuring into lactation |
| Hydroxypropyl methacrylate | Ingestion | Not classified for male reproduction | Rat | NOAEL 1,000 mg/kg/day | 49 days |

| | | | | | |
|----------------------------|------------|--|-------|-----------------------|----------------------------|
| Hydroxypropyl methacrylate | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |
| Methyl Methacrylate | Inhalation | Not classified for male reproduction | Mouse | NOAEL 36.9 mg/l | |
| Methyl Methacrylate | Inhalation | Not classified for development | Rat | NOAEL 8.3 mg/l | during organogenesis |
| 4-Methoxyphenol | Ingestion | Not classified for female reproduction | Rat | NOAEL 300 mg/kg/day | prematuring into lactation |
| 4-Methoxyphenol | Ingestion | Not classified for male reproduction | Rat | NOAEL 300 mg/kg/day | 28 days |
| 4-Methoxyphenol | Ingestion | Not classified for development | Rat | NOAEL 200 mg/kg/day | during gestation |

Target Organ(s)

Specific Target Organ Toxicity - single exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--------------------------------------|------------|------------------------|--|------------------------|---------------------|-----------------------|
| Myristyl methacrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | Professional judgement | NOAEL not available | |
| Phosphate Esters of PPG Methacrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Hydroxypropyl methacrylate | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |
| Methyl Methacrylate | Inhalation | respiratory irritation | May cause respiratory irritation | Human | NOAEL Not available | occupational exposure |
| 4-Methoxyphenol | Inhalation | respiratory irritation | Some positive data exist, but the data are not sufficient for classification | similar health hazards | NOAEL Not available | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------------------------|------------|--|--|-------------------------|-----------------------|-----------------------|
| Fillers (NJTS Reg. No. 04499600-6923) | Inhalation | pneumoconiosis | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL NA | occupational exposure |
| Fillers (NJTS Reg. No. 04499600-6923) | Inhalation | pulmonary fibrosis | Not classified | Rat | NOAEL Not available | |
| Amorphous silica | Inhalation | respiratory system silicosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Hydroxypropyl methacrylate | Inhalation | blood | Not classified | Rat | NOAEL 0.5 mg/l | 21 days |
| Hydroxypropyl methacrylate | Ingestion | hematopoietic system heart endocrine system liver immune system nervous system kidney and/or bladder | Not classified | Rat | NOAEL 1,000 mg/kg/day | 41 days |
| Carbon Black | Inhalation | pneumoconiosis | Not classified | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Dermal | peripheral nervous system | Not classified | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Inhalation | olfactory system | Causes damage to organs through prolonged or repeated exposure | Human | NOAEL Not available | occupational exposure |
| Methyl Methacrylate | Inhalation | kidney and/or bladder | Not classified | Multiple animal species | NOAEL Not available | 14 weeks |
| Methyl Methacrylate | Inhalation | liver | Not classified | Mouse | NOAEL 12.3 mg/l | 14 weeks |
| Methyl Methacrylate | Inhalation | respiratory system | Not classified | Human | NOAEL Not available | occupational exposure |

| | | | | | | |
|-----------------|-----------|---|----------------|-----|---------------------|---------|
| 4-Methoxyphenol | Ingestion | gastrointestinal tract | Not classified | Rat | LOAEL 300 mg/kg/day | 28 days |
| 4-Methoxyphenol | Ingestion | liver immune system | Not classified | Rat | NOAEL 300 mg/kg/day | 28 days |
| 4-Methoxyphenol | Ingestion | kidney and/or bladder | Not classified | Rat | LOAEL 300 mg/kg/day | 28 days |
| 4-Methoxyphenol | Ingestion | heart endocrine system hematopoietic system nervous system respiratory system | Not classified | Rat | NOAEL 300 mg/kg/day | 28 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Respiratory or Skin Sensitization

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. One or more chemical components of this material have been commercialized under the TSCA polymer exemption at 40CFR723.250. Polymers subject to this exemption are not listed on the TSCA Inventory, but are in compliance with TSCA requirements.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification****Health:** 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 41-7837-2 | Version Number: | 1.05 |
| Issue Date: | 02/08/23 | Supersedes Date: | 11/29/21 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 41-7883-6 | Version Number: | 1.02 |
| Issue Date: | 02/28/23 | Supersedes Date: | 04/07/21 |

SECTION 1: Identification

1.1. Product identifier

3M™ Scotch-Weld™ Low Odor Acrylic Adhesive DP8710NS, Black, Part A

1.2. Recommended use and restrictions on use

Recommended use

Adhesive

1.3. Supplier's details

| | |
|----------------------|---|
| MANUFACTURER: | 3M |
| DIVISION: | Industrial Adhesives and Tapes Division |
| ADDRESS: | 3M Center, St. Paul, MN 55144-1000, USA |
| Telephone: | 1-888-3M HELPS (1-888-364-3577) |

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Skin Sensitizer: Category 1B.

2.2. Label elements

Signal word

Warning

Symbols

Exclamation mark |

Pictograms



Hazard Statements

May cause an allergic skin reaction.

Precautionary Statements**Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray.
Wear protective gloves.
Contaminated work clothing must not be allowed out of the workplace.

Response:

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/attention.
Wash contaminated clothing before reuse.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

SECTION 3: Composition/information on ingredients

| Ingredient | C.A.S. No. | % by Wt |
|--|---------------|-------------------------|
| Dibenzoate Propanol | 27138-31-4 | 45 - 65 Trade Secret * |
| Acrylate Polymer | 25101-28-4 | 10 - 30 Trade Secret * |
| Catalyst (NJTS Reg. No. 04499600-6922) | Trade Secret* | 1 - 20 Trade Secret * |
| Organic Peroxide | 13122-18-4 | 0.1 - 10 Trade Secret * |

NJTS or NJTSRN: New Jersey Trade Secret Registry Number.

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye Contact:

If exposed, flush eyes with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms develop, get medical attention.

If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

Allergic skin reaction (redness, swelling, blistering, and itching).

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|------------------|-------------------|
| Carbon monoxide | During Combustion |
| Carbon dioxide | During Combustion |

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

For industrial/occupational use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.)

7.2. Conditions for safe storage including any incompatibilities

Protect from sunlight. Store away from heat. Store away from acids. Store away from strong bases. Store away from oxidizing agents. Store in a dry place. Store away from amines.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

No occupational exposure limit values exist for any of the components listed in Section 3 of this SDS.

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

None required.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Neoprene

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron - Neoprene

Respiratory protection

None required.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state
Color

Liquid
Gray

Specific Physical Form:

Paste

Odor

Hydrocarbon

Odor threshold

No Data Available

pH

Not Applicable

Melting point

Not Applicable

Boiling Point

≥ 150 °F

Flash Point

> 200 °F [*Test Method: Closed Cup*]

Evaporation rate

No Data Available

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)

No Data Available

Flammable Limits(UEL)

No Data Available

Vapor Pressure

No Data Available

Vapor Density

No Data Available

Density

1.08 g/ml

Specific Gravity

1.08 [*Ref Std: WATER=1*]

Solubility in Water

Nil

Solubility- non-water

No Data Available

Partition coefficient: n-octanol/ water

No Data Available

Autoignition temperature

No Data Available

Decomposition temperature

No Data Available

| | |
|--------------------------------|--|
| Viscosity | 20,000 centipoise |
| Hazardous Air Pollutants | 0 % weight |
| Molecular weight | <i>Not Applicable</i> |
| Volatile Organic Compounds | <=61 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :EU VOC content] |
| Percent volatile | < 6 |
| VOC Less H2O & Exempt Solvents | <=10 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :when used as intended with Part B] |
| VOC Less H2O & Exempt Solvents | <=61 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :as supplied] |
| VOC Less H2O & Exempt Solvents | <=1 % [<i>Test Method</i> :calculated SCAQMD rule 443.1] [<i>Details</i> :when used as intended with Part B] |

SECTION 10: Stability and reactivity

10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Heat
Sparks and/or flames

10.5. Incompatible materials

Amines
Strong acids
Strong bases
Strong oxidizing agents

10.6. Hazardous decomposition products

| <u>Substance</u> | <u>Condition</u> |
|------------------|------------------|
| None known. | |

Refer to section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

This product may have a characteristic odor; however, no adverse health effects are anticipated.

Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation. Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

Eye Contact:

Contact with the eyes during product use is not expected to result in significant irritation.

Ingestion:

May be harmful if swallowed.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

| Name | Route | Species | Value |
|--|--------------------------------|------------------------|---|
| Overall product | Dermal | | No data available; calculated ATE >5,000 mg/kg |
| Overall product | Ingestion | | No data available; calculated ATE >2,000 - =5,000 mg/kg |
| Dibenzoate Propanol | Dermal | Rat | LD50 > 2,000 mg/kg |
| Dibenzoate Propanol | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 200 mg/l |
| Dibenzoate Propanol | Ingestion | Rat | LD50 3,295 mg/kg |
| Acrylate Polymer | Dermal | | LD50 estimated to be > 5,000 mg/kg |
| Acrylate Polymer | Ingestion | Rat | LD50 > 5,000 mg/kg |
| Catalyst (NJTS Reg. No. 04499600-6922) | Dermal | Professional judgement | LD50 estimated to be 2,000 - 5,000 mg/kg |
| Catalyst (NJTS Reg. No. 04499600-6922) | Ingestion | Rat | LD50 > 2,000 mg/kg |
| Organic Peroxide | Dermal | Rat | LD50 > 2,000 mg/kg |
| Organic Peroxide | Inhalation-Dust/Mist (4 hours) | Rat | LC50 > 0.8 mg/l |
| Organic Peroxide | Ingestion | Rat | LD50 12,905 mg/kg |

ATE = acute toxicity estimate

Skin Corrosion/Irritation

| Name | Species | Value |
|---------------------|---------|---------------------------|
| Dibenzoate Propanol | Rabbit | No significant irritation |
| Organic Peroxide | Rabbit | No significant irritation |

Serious Eye Damage/Irritation

| Name | Species | Value |
|---------------------|---------|---------------------------|
| Dibenzoate Propanol | Rabbit | No significant irritation |
| Organic Peroxide | Rabbit | No significant irritation |

Skin Sensitization

| Name | Species | Value |
|--|------------|----------------|
| Dibenzoate Propanol | Guinea pig | Not classified |
| Catalyst (NJTS Reg. No. 04499600-6922) | Mouse | Not classified |
| Organic Peroxide | Guinea pig | Sensitizing |

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

| Name | Route | Value |
|--|----------|---------------|
| Dibenzoate Propanol | In Vitro | Not mutagenic |
| Catalyst (NJTS Reg. No. 04499600-6922) | In Vitro | Not mutagenic |

Carcinogenicity

For the component/components, either no data are currently available or the data are not sufficient for classification.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

| Name | Route | Value | Species | Test Result | Exposure Duration |
|---------------------|-----------|--|---------|-----------------------|-------------------|
| Dibenzoate Propanol | Ingestion | Not classified for female reproduction | Rat | NOAEL 500 mg/kg/day | 2 generation |
| Dibenzoate Propanol | Ingestion | Not classified for male reproduction | Rat | NOAEL 400 mg/kg/day | 2 generation |
| Dibenzoate Propanol | Ingestion | Not classified for development | Rat | NOAEL 1,000 mg/kg/day | during gestation |

Target Organ(s)**Specific Target Organ Toxicity - single exposure**

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|--|-----------|-----------------|----------------|---------|-------------------|-------------------|
| Catalyst (NJTS Reg. No. 04499600-6922) | Ingestion | nervous system | Not classified | Rat | NOAEL 2,000 mg/kg | |

Specific Target Organ Toxicity - repeated exposure

| Name | Route | Target Organ(s) | Value | Species | Test Result | Exposure Duration |
|---------------------|-----------|------------------------------|----------------|---------|-----------------------|-------------------|
| Dibenzoate Propanol | Ingestion | hematopoietic system liver | Not classified | Rat | NOAEL 2,500 mg/kg/day | 90 days |

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations

13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): Not regulated

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information**15.1. US Federal Regulations**

Contact 3M for more information.

EPCRA 311/312 Hazard Classifications:**Physical Hazards**

Not applicable

Health Hazards

Respiratory or Skin Sensitization

15.2. State Regulations

Contact 3M for more information.

15.3. Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

15.4. International Regulations

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information**NFPA Hazard Classification**

Health: 2 **Flammability:** 1 **Instability:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

| | | | |
|------------------------|-----------|-------------------------|----------|
| Document Group: | 41-7883-6 | Version Number: | 1.02 |
| Issue Date: | 02/28/23 | Supersedes Date: | 04/07/21 |

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com

