



THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 1 of 11

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **THERM-A-GAP™ GEL75**

Other means of identification : Gel75

Recommended use of the chemical and restrictions on use

: Fully cured dispensable gel for use in gap filling.
No restrictions on use known.

Chemical family : Mixture

SDS number : PHC-463

Name, address, and telephone number of the manufacturer:

Parker Hannifin Corp.

Chomerics Division
77 Dragon Court
Woburn, MA, USA
01888

Manufacturer's Telephone # : (781) 935-4850

24 Hr. Emergency Tel # : INFOTRAC - (800) 535-5053 (Within Continental US); (352) 323-3500 (Outside US)

Name, address, and telephone number of the supplier:

Refer to manufacturer

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

grey -gel. Little or no odour.

Most important hazards:

Occupational exposure to the substance or mixture may cause adverse effects. For further information, please refer to section 11 of the SDS.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. See Section 12 for more environmental information.

This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Label elements

Hazard pictogram(s)

None required under U.S. OSHA Hazcom 2012 and Canadian WHMIS 2015 regulations.

Signal Word

None required under U.S. OSHA HazCom 2012 and Canadian WHMIS 2015 regulations.

Hazard statement(s)

None required under U.S. OSHA HazCom 2012 and Canadian WHMIS 2015 regulations.

Precautionary statement(s)

None required under U.S. OSHA HazCom 2012 and Canadian WHMIS 2015 regulations.

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 2 of 11

SAFETY DATA SHEET

Other hazards

Other hazards which do not result in classification None reported by the manufacturer. : .

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
aluminum oxide	Aluminum trioxide Alumina	1344-28-1	80.0 - 100.0
Siloxanes and Silicones, di-Me	Dimethicone PDMS	63148-62-9	1.0 - 5.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Do not induce vomiting. Rinse mouth. Never give anything by mouth to an unconscious person. Obtain medical attention if symptoms develop and persist.
- Inhalation* : Move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing stops, provide artificial respiration. Obtain medical attention if symptoms develop and persist.
- Skin contact* : For skin contact, wash with soap and water while removing contaminated clothing. If irritation or symptoms develop, seek medical attention. Wash contaminated clothing before reuse.
- Eye contact* : Immediately flush eye(s) with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, seek prompt medical attention.

Most important symptoms and effects, both acute and delayed

- : None expected, when used as intended. .
Prolonged or repeated contact with skin may cause irritation in some cases. Prolonged exposure may cause eye irritation. Exposure may cause temporary irritation, redness or discomfort.
Inhalation of fumes may result in metal fume fever, a flu-like illness. Symptoms of metal fume fever may include fever, fatigue, vomiting, muscle aches and shortness of breath.
Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Indication of any immediate medical attention and special treatment needed

- : Provide general supportive measures and treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Unsuitable extinguishing media

- : None known.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Not considered flammable. However, may burn if exposed to extreme heat and flame. Toxic fumes, gases or vapours may evolve on burning. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Not classified as flammable.

Hazardous combustion products

- : Carbon oxides; Nitrogen oxides (NOx); Other unidentified organic compounds.

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 3 of 11

SAFETY DATA SHEET

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Cool closed containers exposed to fire with water spray. Do not get water inside containers. Do not allow run-off from fire fighting to enter drains or water courses. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Keep people away from and upwind of spill/leak. Restrict access to area until completion of clean-up. Wear appropriate protective equipment. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Prevent product from entering drains, sewers, waterways and soil.

Methods and material for containment and cleaning up

- : Ventilate the area. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Scrape up product and place it into a container for disposal. Use inert, non-combustible absorbents to assist the pick up of material. Keep in properly labelled containers. Contaminated absorbent material may pose the same hazards as the spilled product. Contact the proper local authorities. For waste disposal, see Section 13 of the SDS.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): None reportable.

In Canada: Contact appropriate local and provincial environmental authorities for assistance and/or reporting requirements.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Provide adequate ventilation. Wear suitable protective equipment during handling. Avoid breathing vapors, fumes or dust. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and direct flame. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling.

Conditions for safe storage : Store in cool/well-ventilated place. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Keep away from incompatibles. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

Incompatible materials : Strong oxidizing agents; Strong acids; Strong bases; Halocarbons

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 4 of 11

SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
<u>Chemical Name</u>				
aluminum oxide	1 mg/m ³ (respirable)	N/Av	15 mg/m ³ (total dust); 5 mg/m ³ (respirable)	N/Av
Siloxanes and Silicones, di-Me	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

- : Provide adequate ventilation. Apply technical measures to comply with the occupational exposure limits. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. In case of insufficient ventilation wear suitable respiratory equipment.

Respiratory protection

- : If airborne concentrations are above the permissible exposure limit or are not known, use NIOSH-approved respirators. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02. Advice should be sought from respiratory protection specialists.

Skin protection

- : Gloves impervious to the material are recommended. The suitability for a specific workplace should be discussed with the producers of the protective gloves. Wear sufficient clothing to prevent skin contact.

Eye / face protection

- : Wear as appropriate: Tightly fitting safety goggles; Safety glasses with side shields.

Other protective equipment

- : Ensure that eyewash stations and safety showers are close to the workstation location. Other equipment may be required depending on workplace standards.

General hygiene considerations

- : Avoid breathing vapors, fumes or dust. Avoid contact with skin, eyes and clothing. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use. Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: grey-gel
Odour	: Little or no odour.
Odour threshold	: N/Av
pH	: N/Av
Melting Point/Freezing point	: N/Av
Initial boiling point and boiling range	: N/Av
Flash point	: >95°C
Flashpoint (Method)	: N/Av
Evaporation rate (BuAe = 1)	: N/Av
Flammability (solid, gas)	: Not applicable.
Lower flammable limit (% by vol.)	: N/Av
Upper flammable limit (% by vol.)	: N/Av
Oxidizing properties	: None.

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 5 of 11

SAFETY DATA SHEET

Explosive properties : Not explosive
Vapour pressure : N/Av
Vapour density : N/Av
Relative density / Specific gravity
: >1
Solubility in water : Insoluble.
Other solubility(ies) : N/Av
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution
: N/Av
Auto-ignition temperature : N/Av
Decomposition temperature : N/Av
Viscosity : N/Av
Volatiles (% by weight) : Negligible.
Volatile organic Compounds (VOC's)
: N/Av
Absolute pressure of container
: N/Av
Flame projection length : N/Av
Other physical/chemical comments
: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Direct sources of heat. Do not use in areas without adequate ventilation. Avoid contact with incompatible materials.
Incompatible materials : Strong oxidizing agents; Strong acids; Strong bases; Halocarbons
Hazardous decomposition products
: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : NO
Routes of entry skin & eye : NO
Routes of entry Ingestion : NO
Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: None reasonably foreseeable. Inhalation of fumes may result in metal fume fever, a flu-like illness. Symptoms of metal fume fever may include fever, fatigue, vomiting, muscle aches and shortness of breath.

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 6 of 11

SAFETY DATA SHEET

Sign and symptoms ingestion

: None reasonably foreseeable. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

: None reasonably foreseeable. Prolonged or repeated contact with skin may cause irritation in some cases.

Sign and symptoms eyes

: None reasonably foreseeable. Exposure may cause temporary irritation, redness or discomfort.

Potential Chronic Health Effects

:

Mutagenicity

: No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This product is not expected to cause reproductive or developmental effects.

Sensitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: According to the classification criteria of U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015), this product is not expected to cause target organ toxicity through single or repeated exposures.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

Synergistic materials

: No data available.

Toxicological data

: Not classified for acute toxicity based on available data.

There is no available data for the product itself, only for the ingredients. See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
aluminum oxide	> 2.3 mg/L (dust) (no deaths)	> 2000 mg/kg (No mortality)	N/Av
Siloxanes and Silicones, di-Me	N/Av	> 2000 mg/kg	> 19 400 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Not expected to be harmful to aquatic organisms. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. See the following tables for individual ingredient ecotoxicity data.

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 7 of 11

SAFETY DATA SHEET

Ecotoxicity data:

<u>Ingredients</u>	CAS #	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
aluminum oxide	1344-28-1	> 100 mg/L (Brown trout)	N/Av	None.
Siloxanes and Silicones, di-Me	63148-62-9	350 mg/L Pleuronectes platessa (European plaice)	N/Av	None.

<u>Ingredients</u>	CAS #	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
aluminum oxide	1344-28-1	> 100 mg/L (Daphnia magna)	N/Av	None.
Siloxanes and Silicones, di-Me	63148-62-9	> 200 mg/L (Daphnia magna)	N/Av	None.

<u>Ingredients</u>	CAS #	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
aluminum oxide	1344-28-1	> 100 mg/L/72hr (Green algae)	N/Av	None.
Siloxanes and Silicones, di-Me	63148-62-9	N/Av	N/Av	None.

Persistence and degradability

- : The product itself has not been tested.
Contains the following chemicals which are not readily biodegradable: Aluminium oxide

Bioaccumulation potential

- : The product itself has not been tested. See the following data for ingredient information.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
-------------------	--------------------------------------------------------	--------------------------------------

Mobility in soil

- : The product itself has not been tested.

Other Adverse Environmental effects

- : No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

- : Handle in accordance with good industrial hygiene and safety practice. Refer to protective measures listed in sections 7 and 8. This material and its container must be disposed of in a safe way.

Methods of Disposal

- : Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

- : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

Therm-A-Gap™ GEL75





SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 8 of 11

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	None.	Not regulated.	not regulated	none	
49CFR/DOT Additional information	None.				
TDG	None.	Not regulated.	not regulated	none	
TDG Additional information	None.				
ICAO/IATA	None.	Not regulated.	not regulated	none	
ICAO/IATA Additional information	None.				
IMDG	None.	Not regulated.	not regulated	none	
IMDG Additional information	None.				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep containers dry and tightly closed to avoid moisture absorption and contamination.

Environmental hazards : This product does not meet the criteria for an environmentally hazardous mixture, according to the IMDG Code. See Section 12 for more environmental information.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
aluminum oxide	1344-28-1	Yes	None.	None.	Yes	1%
Siloxanes and Silicones, di-Me	63148-62-9	Yes	None.	None.	No	N/Ap



THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 9 of 11

SAFETY DATA SHEET

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes:
None.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
aluminum oxide	1344-28-1	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Siloxanes and Silicones, di-Me	63148-62-9	No	N/Ap	No	No	No	No	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

Canadian National Pollutant Release Inventory (NPRI): This product contains the following substances listed on the NPRI:

aluminum oxide (Part 1, Group A Substance) (fibrous forms only)

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
aluminum oxide	1344-28-1	215-691-6	Present	Present	(1)-23	KE-01012	Present	May be used as a single component chemical under an appropriate group standard.
Siloxanes and Silicones, di-Me	63148-62-9	Polymer	Present	Present	(7)-476	KE-31068	Present	HSR003036

SECTION 16. OTHER INFORMATION

Legend

- : ACGIH: American Conference of Governmental Industrial Hygienists
- AICS: Australian Inventory of Chemical Substances
- CAS: Chemical Abstract Services
- CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
- CFR: Code of Federal Regulations
- CSA: Canadian Standards Association
- DOT: Department of Transportation
- EC50: Effective Concentration 50%
- ENCS: Existing and New Chemical Substances
- EPA: Environmental Protection Agency

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): **03/12/2021**

Page 10 of 11

SAFETY DATA SHEET

HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
IBC: Intermediate Bulk Container
IECSC: Inventory of Existing Chemical Substances
IMDG: International Maritime Dangerous Goods
IOC: Inventory of Chemicals
KECI: Korean Existing Chemicals Inventory
KECL: Korean Existing Chemicals List
LC: Lethal Concentration
LD: Lethal Dose
N/Ap: Not Applicable
N/Av: Not Available
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organisation for Economic Co-operation and Development
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
PICCS: Philippine Inventory of Chemicals and Chemical Substances
RCRA: Resource Conservation and Recovery Act
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TSCA: Toxic Substance Control Act
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices
2. ECHA - European Chemical Agency
3. Canadian Centre for Occupational Health and Safety, CCHInfoWeb databases, (Chempendium, HSDB and RTECs).
4. Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists
6. California Proposition 65 List
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal

Preparation Date (mm/dd/yyyy)

: 03/21/2020

Reviewed Date SDS (dd/mm/yyyy)

: 12/03/2021

Revision No.

: 2

Revision Information

: (M)SDS sections updated 2. HAZARDS IDENTIFICATION;9. PHYSICAL AND CHEMICAL PROPERTIES

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

THERM-A-GAP™ GEL75

SDS No: PHC-463

SDS Revision Date (mm/dd/yyyy): 03/12/2021

Page 11 of 11

SAFETY DATA SHEET

<p><u>Prepared for:</u> Parker Hannifin Corp. Chomerics Division 77 Dragon Court Woburn, MA, U.S.A. 01888 Telephone: (781) 935-4850</p>	 The logo for Parker Chomerics, featuring the word "Parker" in a stylized white font on a black background, followed by a vertical yellow bar and the word "Chomerics" in a white sans-serif font.
<p><u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	 The logo for ICC Compliance Center, featuring the letters "icc" in white inside a blue circle, followed by the words "Compliance Center" in a blue sans-serif font.

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.

END OF DOCUMENT