



CFC Free NU Contact Cleaner



FEATURES

- Contains NO Chlorinated solvents
- Fast Drying, No Residue
- Penetrating action removes dirt, flux, moisture, dust, oxides, and other contaminants
- Safe on plastics
- Conforms to VOC regulations of CARB, OTC, and LADCO

APPLICATIONS

- Connectors
- Contacts
- Magnetic Tap Heads
- Printed Circuits
- Office Equipment
- Semiconductor Assemblies
- Switches
- Telecommunication Equipment
- Telephone Equipment

SPECIFICATIONS AND APPROVALS

- NSF International, K2
- Boeing D6-17487, Revision T

PROPERTIES

Appearance / Physical State	Gas
Odor	Mild
Melting / Freezing Point	-198.4 °F (-128 °C) estimated
Boiling Point / Range	140.9 °F (60.5 °C)
Vapor Pressure	352.53 mm Hg @ 38°C
Partition Coefficient	Not Established
Percent volatile	100%
Flammability	lower: 0.6%, upper: 7%
Propellant	HFC-152a
VOC Content	74% (600g/L)
Color	Clear
Flash Point	< 1.4 °F (< -17.0 °C) TCC
Density	N/A
Evaporation Rate	<1 BuAc (Ethyl Ether = 1)
Vapor Density	>1 (air = 1)
Auto-Ignition Temperature	582.8 °F (306 °C)
Viscosity	< 3 cSt @ 25°C
Specific Gravity	0.8 - 0.82 @ 20°C
Temperature Range	N/A
KB Value	26
Surface Tension	17.3 dynes/cm @ 77°F (25°C)

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to remove any contaminants. DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Do not re-use empty containers. Do not breathe gas. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling.

STORAGE

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition.

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/ or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada				
05416	C05416	11 wt oz / 312 g / 416 mL	aerosol	12	13 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved