















# SAFETY DATA SHEET

## 1. Identification

**Product identifier HumiSeal UV40** 

Other means of identification

**Product code** EX0000-4191

Recommended use Protective coating for printed circuit board. Industrial use.

Recommended restrictions No other uses are advised. Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name CHASE CORPORATION Zeta Drive Plant

**Address** 201 Zeta Drive

Pittsburgh, Pennsylvania 15238

**United States** 

1-866-932-0800 **Telephone** 

E-mail techsupport@humiseal.com

**Emergency phone number** 1-800-424-9300 Chemtrec, US

> Chemtrec, outside of US (+1)703-527-3887

## 2. Hazard(s) identification

Physical hazards Category 4 Flammable liquids **Health hazards** Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Sensitization, respiratory Category 1 Sensitization, skin Category 1

> Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

> > Category 1

Category 1

**Environmental hazards** Hazardous to the aquatic environment, acute

hazard

Hazardous to the aquatic environment,

long-term hazard Not classified.

Label elements

**OSHA** defined hazards



Signal word Danger

**Hazard statement** 

H227	Combustible liquid.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Material name: HumiSeal UV40 SDS US EX0000-4191 Version #: 03 Revision date: 03-28-2022 Issue date: 08-09-2021

#### **Precautionary statement**

	er	

Keep away from flames and hot surfaces. - No smoking. P210 Avoid breathing mist/vapors. P261

Avoid release to the environment. P273

Wear protective gloves/protective clothing/eve protection/face protection. P280

In case of inadequate ventilation wear respiratory protection. P285

Response

P338

P304 + P340 P305 + P351 + If inhaled: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If experiencing respiratory symptoms: Call a poison center/doctor. P342 + P311

In case of fire: Use appropriate media to extinguish. P370 + P378

Collect spillage. P391

Storage

Store in a well-ventilated place. Keep cool. P403 + P235

Disposal Not available. Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

## 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Exo-1,7,7-trimethylbicyclo[2.2.1]he t-2-yl acrylate	p	5888-33-5	40 - < 50
Isocyanatoacrylate		Unknown	40 - < 50
Hexamethylene diisocyanate, oligomers		28182-81-2	3 - < 5
2-hydroxy-2-methylpropiophenone		7473-98-5	1 - < 3
n-butyl acetate		123-86-4	1 - < 3
Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide		162881-26-7	< 1
Tosyl isocyanate		4083-64-1	< 1
1,7,7-trimethyltricyclo[2.2.1.02,6]heptane		508-32-7	< 0.3
Camphene		79-92-5	< 0.3

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If experiencing respiratory symptoms: Call a poison center or

doctor/physician.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Immediately flush eves with plenty of water for at least 15 minutes. Remove contact lenses, if Eve contact

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Material name: HumiSeal UV40 SDS US 2 / 10

### 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

Water. Do not use water jet as an extinguisher, as this will spread the fire.

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting equipment/instructions In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards

Combustible liquid.

### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions** 

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. When using do not smoke. Avoid breathing mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

## 8. Exposure controls/personal protection

### Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

## US. OSHA Table 7-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	, Value	
n-butyl acetate (CAS 123-86-4)	PEL	710 mg/m3	
		150 ppm	
US. ACGIH Threshold Limit Val	ues		
Components	Туре	Value	
n-butyl acetate (CAS 123-86-4)	STEL	150 ppm	
	TWA	50 ppm	

Material name: HumiSeal UV40 SDS US **US. NIOSH: Pocket Guide to Chemical Hazards** 

 Components
 Type
 Value

 n-butyl acetate (CAS 123-86-4)
 STEL
 950 mg/m3

 200 ppm
 TWA
 710 mg/m3

Biological limit values No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. General ventilation normally

150 ppm

adequate. Provide eyewash station and safety shower.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Chemical respirator with organic vapor cartridge and full facepiece.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.Other Wear appropriate chemical resistant clothing.

**Respiratory protection** Chemical respirator with organic vapor cartridge and full facepiece.

Thermal hazards Not applicable.

General hygiene considerations

When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not

be allowed out of the workplace.

## 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.

Form Not available.
Color Not available.
Odor Not available.
Odor threshold Not available.
PH Not available.
Melting point/freezing point Not available.

Initial boiling point and boiling

range

527 °F (275 °C) estimated

Flash point 167.0 °F (75.0 °C) Closed Cup

Evaporation rate Not available.
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits
Explosive limit - lower (%) Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.003 kPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity Not available.

Other information

**Density** 1.05 - 1.15 g/cm<sup>3</sup>

Material name: HumiSeal UV40

**Explosive properties** Not explosive. Kinematic viscosity 430 - 765 mm<sup>2</sup>/s Kinematic viscosity 73.4 °F (23 °C)

temperature

Oxidizing properties Not oxidizing. VOC 2.67 %

## 10. Stability and reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport. Reactivity

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the Conditions to avoid

flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

## 11. Toxicological information

## Information on likely routes of exposure

May cause irritation to the respiratory system. May cause allergy or asthma symptoms or Inhalation

breathing difficulties if inhaled. Prolonged inhalation may be harmful.

Causes skin irritation. May cause an allergic skin reaction. Skin contact

Eye contact Causes serious eye irritation.

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause respiratory irritation. Difficulty in breathing. Skin irritation. May cause redness

and pain. May cause an allergic skin reaction. Dermatitis. Rash.

#### Information on toxicological effects

#### Acute toxicity

Components	Species	Test Results	
2-hydroxy-2-methylpropiophenone (CAS 7473-98-5)			
<u>Acute</u>			
Dermal			
LD50	Rat	6929 mg/kg	
Oral			
LD50	Rat	1694 mg/kg	
Camphene (CAS 79-92-5)			
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 2000 mg/kg	
Oral			
LD50	Rat	> 2000 mg/kg	
Exo-1,7,7-trimethylbicyclo[	[2.2.1]hept-2-yl acrylate (CAS 5888-33-5)		
<u>Acute</u>			
Dermal			
LD50	Rabbit	> 3000 mg/kg	
Oral			
LD50	Rat	4350 mg/kg	
Hexamethylene diisocyana	ate, oligomers (CAS 28182-81-2)		
<u>Acute</u>			
Dermal			
LD50	Rat	> 2000 mg/kg	

Material name: HumiSeal UV40 SDS US

**Species Test Results** Components Inhalation Mist LC50 Rat 0.39 mg/l, 4 hours Oral Rat LD50 > 2000 mg/kg Isocyanatoacrylate **Acute** Dermal LD50 Rabbit > 2000 mg/kg Inhalation Mist LC50 Rat > 5 mg/l, 4 hours Oral LD50 Rat > 5000 mg/kg n-butyl acetate (CAS 123-86-4) Acute Dermal LD50 Rabbit 14110 mg/kg Inhalation Vapor LC50 Rat 23.4 mg/l, 4 hours Oral LD50 Rat 10760 mg/kg Phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide (CAS 162881-26-7) **Acute Dermal** LD50 Rat > 2000 mg/kg Oral LD50 Rat > 2000 mg/kg Tosyl isocyanate (CAS 4083-64-1) **Acute** Dermal LD50 Rat > 2000 mg/kg Oral Rat LD50 2330 mg/kg Skin corrosion/irritation Causes skin irritation. Serious eye damage/eye Causes serious eye irritation. irritation Respiratory or skin sensitization May cause allergy or asthma symptoms or breathing difficulties if inhaled. Respiratory sensitization Skin sensitization May cause an allergic skin reaction. No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity mutagenic or genotoxic. Not classifiable as to carcinogenicity to humans. Carcinogenicity IARC Monographs. Overall Evaluation of Carcinogenicity Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Material name: HumiSeal UV40 SDS US 6 / 10 EX0000-4191 Version #: 03 Revision date: 03-28-2022 Issue date: 08-09-2021

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

### 12. Ecological information

**Ecotoxicity** Very toxic to aquatic life with long lasting effects.

Product		Species	Test Results
HumiSeal UV40			
Aquatic			
Fish	LC50	Fish	11432.1602, 96 hours estimated
Acute			
Algae	EC50	Algae	69.6429, 72 hours estimated
Crustacea	EC50	Daphnia	45.6963, 48 hours estimated
Fish	LC50	Fish	0.8328, 96 hours estimated
Components		Species	Test Results
2-hydroxy-2-methylprop	piophenone (CAS	7473-98-5)	
Aquatic			
Acute			
Algae	EC50	Algae	1.95, 72 hours
Camphene (CAS 79-92	:-5)		
Aquatic			
Acute			
Crustacea	EC50	Daphnia	0.72, 48 hours
Fish	LC50	Fish	0.72, 96 hours
Exo-1,7,7-trimethylbicyd	clo[2.2.1]hept-2-yl	acrylate (CAS 5888-33-5)	
Aquatic			
Acute			
Fish	LC50	Fish	0.704, 96 hours
Isocyanatoacrylate			
Aquatic			
Acute			
Crustacea	EC50	Daphnia	58, 48 hours
Tosyl isocyanate (CAS	4083-64-1)		
Aquatic			
Acute			
Crustacea	EC50	Daphnia	> 100 mg/l, 48 hours
Fish	LC50	Fish	> 45 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Camphene 4.22 n-butyl acetate 1.78

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Material name: HumiSeal UV40

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

Not regulated as dangerous goods.

IATA

UN3082 **UN** number

Environmentally hazardous substance, liquid, n.o.s. (Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl **UN proper shipping name** 

acrylate)

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group **Environmental hazards** Yes **ERG Code** 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

Allowed with restrictions.

aircraft

Cargo aircraft only Allowed with restrictions.

As per IATA S.P. A197: These substances when transported in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net weight per single or inner packaging of 5 kg or less for solids, are not subject to any other provisions of these Regulations provided the packagings meet the general provisions 5.0.2.4.1, 5.0.2.6.1.1 and 5.0.2.8.

#### **IMDG**

**UN** number UN3082

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. **UN proper shipping name** 

(Exo-1,7,7-trimethylbicyclo[2.2.1]hept-2-yl acrylate), MARINE POLLUTANT

Transport hazard class(es)

Class 9 Subsidiary risk Packing group Ш **Environmental hazards** 

Yes Marine pollutant F-A, S-F **EmS** 


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

As per section 2.10.2.7 of IMDG Code: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 L or less for liquids or having a net mass per single or inner packaging of 5 Kg or less for solids are not subject to any other provisions of the IMDG Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In case of marine pollutants also meeting the criteria for inclusion in another hazard class, all provisions of the IMDG Code relevant to any additional hazards continue to apply.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not established.

IATA; IMDG



Material name: HumiSeal UV40 8 / 10

#### Marine pollutant



**General information** IMDG Regulated Marine Pollutant.

## 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

n-butyl acetate (CAS 123-86-4) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation categories

Yes

Serious eye damage or eye irritation Respiratory or skin sensitization

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

n-butyl acetate (CAS 123-86-4) Low priority

**US** state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Tosyl isocyanate (CAS 4083-64-1)

California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

International Inventories

Country(s) or region Inventory name On inventory (yes/no)\* Australia Australian Inventory of Industrial Chemicals (AICIS) No Canada Domestic Substances List (DSL) No

Material name: HumiSeal UV40 SDS US EX0000-4191 Version #: 03 Revision date: 03-28-2022 Issue date: 08-09-2021 9 / 10

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

## 16. Other information, including date of preparation or last revision

08-09-2021 Issue date 03-28-2022 **Revision date** 

Version # 03

**HMIS®** ratings Health: 2\*

Flammability: 2 Physical hazard: 0

NFPA ratings Health: 2

Flammability: 2 Instability: 0

AICIS: Australian Inventory of Industrial Chemicals. List of abbreviations

Disclaimer The information offered in this data sheet is designed only as guidance for the safe use, storage

and handling of the product. This information is correct to the best of our knowledge and belief at the date of publication, however, no guarantee is made to its accuracy. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any other process. This material is intended for industrial use only.

No warranty, expressed or implied is made.

**Revision information** Composition / Information on Ingredients: Ingredients

Accidental release measures: Methods and materials for containment and cleaning up

Stability and reactivity: Possibility of hazardous reactions

Transport information: General information

Material name: HumiSeal UV40 SDS US 10 / 10