

TRUECAST 55 PART A

PRODUCT AND COMPANY IDENTIFICATION

Supplier Details:	Chemline Incorporated 5151 Natural Bridge Road Saint Louis, MO 63115
Phone:	314-664-2230
Fax:	314-664-1355
Web:	www.chemline.net
Emergency:	CHEMTREC 800-424-9300 (24 HOUR SERVICE)

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Skin corrosion/irritation, 2

Health, Respiratory or skin sensitization, 1 Skin

Health, Serious Eye Damage/Eye Irritation, 1

Health, Serious Eye Damage/Eye Irritation, 2 A

Health, Respiratory or skin sensitization, 1 Respiratory

Health, Specific target organ toxicity - Single exposure, 3

Health, Carcinogenicity, 2

Environmental, Hazards to the aquatic environment - Acute, 3 Environmental, Hazards to the aquatic environment - Chronic, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

- H315 Causes skin irritation
- H317 May cause an allergic skin reaction
- H318 Causes serious eye damage
- H319 Causes serious eye irritation
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled
- H336 May cause drowsiness or dizziness
- H351 Suspected of causing cancer
- H402 Harmful to aquatic life
- H412 Harmful to aquatic life with long lasting effects

GHS Precautionary Statements:

- P201 Obtain special instructions before use.
- P202 Do not handle until all safety precautions have been read and understood.
- P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P264 Wash skin thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.
- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves/ eye protection/ face protection.
- P284 Wear respiratory protection.
- P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.

P302 + P352 - IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/ physician.

P320 - Specific treatment is urgent (see supplemental first aid instructions on this label).

P330 - Rinse mouth.

P333 + P313 - If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 - If eye irritation persists: Get medical advice/ attention.

P362 - Take off contaminated clothing and wash before reuse.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P405 - Store locked up.

P501 - Dispose of contents/ container to an approved waste disposal plant.

COMPOSITION/INFORMATION ON INGREDIENTS

CAS#		Ingredients: Chemical Name:
584-84-9	<3%	Toluene diisocyanates
91-08-7	<3%	2,4-Toluene diisocyanate

4 FIRST AID MEASURES Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Remove contaminated clothing. Gently wash with plenty of soap and water followed by rinsing with water for at least 15 minutes. Call a Poison Center or doctor/physician if you feel unwell. Wash contaminated clothing before reuse.

Eye Contact: Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

Ingestion: Do not induce vomiting. Rinse mouth. Immediately call Poison Center or physician.

FIRE FIGHTING MEASURES

Flash Point: >400F

Use dry chemical, water spray, or other extinguishing media appropriate for surrounding fire.. Do not use heavy water stream. A heavy water stream may spread burning liquid. Not considered flammable, but may burn at high temperatures. Product is not explosive. Do not weld, burn, or cut empty containers.

Exercise caution when fighting any chemical fire. Fire fighters should wear self-contained breathing apparatus to protect against inhalation of cyanates vapors and other decomposition/combustion products. Do not release runoff from fire control methods to sewers or waterways. Because fire may produce toxic thermal decomposition products, wear a self-contained breathing apparatus with a full face piece operated in pressure-demand or positive-pressure mode.

ACCIDENTAL RELEASE MEASURES

Avoid all contact with skin, eyes, or clothing. Avoid breathing (dust, vapor, mist, gas). Use appropriate personal protection equipment. Evacuate unnecessary personnel. Equip cleanup crew with proper protection. Stop leak if safe to do so. Eliminate ignition sources. Ventilate area. Prevent entry into sewers and public waters. Notify authorities if liquid enters sewers or public waters. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal.

HANDLING AND STORAGE

Handling Precautions:

Keep away from sources of ignition - no smoking. Keep away from heat and open flame. Avoid all eye and skin contact and do not breathe vapor or mist. Always wash hands after handling. Do nto eat, drink or smoke when using this product. Ensure there is adequate ventialtion. Wear recommended personal protective equipment. Take precautionary measures against static discharge. Use grounded electrical/mechanical equipment.

Storage Requiremen	Keep/store away from direct sunlight, extremely high or low temperatures, and incompatible materials
8	EXPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Control	safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.
Equipment:	Toluene diisocyanates cas#:(584-84-9) [<3%]
	Personal protective equipment
	Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
	Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: > 480 min Material tested:Butoject (Aldrich Z677647, Size M)
	Splash protection: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: > 30 min Material tested:Camatril (Aldrich Z677442, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an Industrial Hygienist familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.
	Eye protection: Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
	Skin and body protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
	Hygiene measures: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.
	2,4-Toluene diisocyanate cas#:(91-08-7) [<3%]
	Personal protective equipment
	Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
	Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested:Butoject (KCL 897 / Aldrich Z677647, Size M)

Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 240 min Material tested:Camatril (KCL 730 / Aldrich Z677442, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Toluene diisocyanates cas#:(584-84-9) [<3%]

Components with workplace control parameters Potential Occupational Carcinogen See Appendix A

TWA 0.0050 ppm USA. ACGIH Threshold Limit Values (TLV) Eye irritation Asthma Respiratory sensitization Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Not classifiable as a human carcinogen Sensitizer

STEL 0.02 ppm USA. ACGIH Threshold Limit Values (TLV) Eye irritation Asthma Respiratory sensitization Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Not classifiable as a human carcinogen Sensitizer

С	0.02 ppm	USA. Occupational Exposure Limits (OSHA) - Table Z- 1

0.14 mg/m3 Limits for Air Contaminants

The value in mg/m3 is approximate. Ceiling limit is to be determined from breathing-zone air samples.

TWA	0.0050 ppm 0.04 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
STEL	0.02 ppm 0.15 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

2,4-Toluene diisocyanate cas#:(91-08-7) [<3%]

Components with workplace control parameters

TWA 0.0050 ppm USA. ACGIH Threshold Limit Values (TLV) Eye irritation Asthma Respiratory sensitization Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Not classifiable as a human carcinogen Sensitizer

STEL 0.02 ppm USA. ACGIH Threshold Limit Values (TLV)

Eye irritation Asthma Respiratory sensitization Adopted values or notations enclosed are those for which changes are proposed in the NIC See Notice of Intended Changes (NIC) Not classifiable as a human carcinogen Sensitizer

Conomizon				
9	PHYS	ICAL AND CHEMICAL PRO	PERTIES	
Appearance: Physical State: Boiling Point:	Clear Liquid >350F		Odor: Flash Point:	Slight >400F
10	STAB	ILITY AND REACTIVITY		
Chemical Stability: Conditions to Avoid: Materials to Avoid: Hazardous Decomposition:		Hazardous reactions will not occur under normal conditions. Stable under recommended handling and storage conditions. Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials. Isocyanates react slowly with water, alcohols, amines, acids, and bases. High temperatures will release cyanates and hydrocarbons. Oxides of carbon, nitrogen, and small amount of HCN under burning conditions. Will not occur		
11	ΤΟΧΙΟ	COLOGICAL INFORMATION	1	
Toluene diisocyanates	as#:(584	-84-9) [<3%]		
Information on toxicologi	cal effect	S		
Acute toxicity: Oral LD50 LD50 Oral - rat - male - 5,110 mg/kg Inhalation LC50 LC50 Inhalation - rat - male and female - 1 h - 0.48 mg/l Dermal LD50 LD50 Dermal - rabbit - male and female - > 9,400 mg/kg Other information on acute toxicity no data available				
Skin corrosion/irritation:	Skin - rab	bit - Skin irritation - 24 h		
Serious eye damage/eye	e irritation	: Eyes - rabbit - Severe eye irritation	n	
Respiratory or skin sens	itization: ı	no data available		
May cause allergic respi	ratory and	d skin reactions		
Germ cell mutagenicity: Genotoxicity in vitro - mouse - lymphocyte				
Genotoxicity in vitro - Hamster - ovary Sister chromatid exchange Genotoxicity in vitro - Ames test - S. typhimurium - with or without metabolic activation - positive				
Carcinogenicity: This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification. Limited evidence of carcinogenicity in animal studies				
IARC: 2B - Group 2B: Possibly carcinogenic to humans (Toluene-2,4-di-isocyanate) NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.				
Reproductive toxicity: no data available				
Teratogenicity: no data available				
Specific target organ toxicity - single exposure (Globally Harmonized System): May cause respiratory irritation.				

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be fatal if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation. Aggravated Acts as a mild acetyl cholinesterase inhibitor. , Medical Condition

Signs and Symptoms of Exposure: Cough, Shortness of breath, Headache, Nausea, Vomiting

Synergistic effects: no data available

Additional Information:

RTECS: CZ6300000

2,4-Toluene diisocyanate cas#:(91-08-7) [<3%]

Information on toxicological effects

Acute toxicity: LD50 Oral - Bird (wild) - 100 mg/kg Inhalation: Irritating to respiratory system. Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: Germ cell mutagenicity:

Hamster ovary Cytogenetic analysis Sister chromatid exchange

Carcinogenicity: This product is or contains a component that has been reported to be possibly carcinogenic based on its IARC, ACGIH, NTP, or EPA classification. Limited evidence of carcinogenicity in animal studies

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Toluene-2,4-di-isocyanate) NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP. OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause respiratory irritation.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: CZ6310000

Cough, Shortness of breath, Headache, Nausea, Vomiting Stomach - Irregularities - Based on Human Evidence

ECOLOGICAL INFORMATION

Toluene diisocyanates cas#:(584-84-9) [<3%]

Information on ecological effects

Toxicity:

Toxicity to fish static test LC50 - Oncorhynchus mykiss (rainbow trout) - 133 mg/l - 96 h. Method: OECD Test Guideline 203 Toxicity to daphnia static test EC50 - Daphnia magna (Water flea) - mg/l - 48 h. and other aquatic Method: OECD Test Guideline 202 invertebrates Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 4,300 mg/l - 96 h. Method: OECD Test Guideline 201 Toxicity to bacteria EC50 - Sludge Treatment - > 100 mg/l - 3 h.

Persistence and degradability: Biodegradability aerobic Biochemical oxygen demand Result: 0 % - Not biodegradable Remarks: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

2,4-Toluene diisocyanate cas#:(91-08-7) [<3%]

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

DISPOSAL CONSIDERATIONS

Dispose of waste material in accordance with all local, regional, national, and international regulations. Do not dispose of waste in sewer.

TRANSPORT INFORMATION

Non DOT/RCRA regulated

REGULATORY INFORMATION

[%] RQ (CAS#) Substance - Reg Codes

[<3%] RQ(10LBS), Toluene diisocyanates (584-84-9) CERCLA, EHS302, HAP, MASS, NJEHS, NJHS, NRC, OSHAWAC, PA, SARA313, TSCA, TXAIR

[<3%] RQ(10LBS), 2,4-Toluene diisocyanate (91-08-7) CERCLA, EHS302, MASS, NJHS, PA, SARA313, TSCA, TXAIR

This product does not contain chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.


Regulatory Code Legend

RQ = Reportable Quantity CERCLA = Superfund clean up substance EHS302 = Extremely Hazardous Substance HAP = Hazardous Air Pollutants MASS = MA Massachusetts Hazardous Substances List NJEHS = NJ Extraordinarily Hazardous Substances NJHS = NJ Right-to-Know Hazardous Substances NRC = Nationally Recognized Carcinogens OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level

16 OTHER INFORMATION

NFPA:Health = 2, Fire = 1, Reactivity = 1, Specific Hazard = NoneHMIS III:Health = 2, Fire = 1, Physical Hazard = 1HMIS PPE:X - Consult your supervisor for special instructions





Revision Date: 1/21/2021