

Revision Number: 005.3 Issue date: 10/21/2021

PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE M-CR 1001 AERO IDH number: 594417 Product type/use: Conversion coating Item number: 594417 Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

United States Region:

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER: MAY CAUSE AN ALLERGIC SKIN REACTION.

MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING

DIFFICULTIES IF INHALED. MAY CAUSE GENETIC DEFECTS.

MAY CAUSE CANCER.

MAY DAMAGE FERTILITY OR THE UNBORN CHILD.

| HAZARD CLASS | HAZARD CATEGORY |
|---------------------------|-----------------|
| RESPIRATORY SENSITIZATION | 1 |
| SKIN SENSITIZATION | 1 |
| GERM CELL MUTAGENICITY | 1B |
| CARCINOGENICITY | 1A |
| REPRODUCTIVE TOXICITY | 1B |

PICTOGRAM(S)



Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, clothing, eye and face

protection. In case of inadequate ventilation wear respiratory protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: If breathing is difficult, remove victim to Response:

fresh air and keep at rest in a position comfortable for breathing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. Wash contaminated

clothing before reuse.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* |
|------------------------|------------|-------------|

| Chromic acid | 7738-94-5 | 0.1 - 1 |
|---------------------------------|------------|---------|
| Dipotassium hexafluorozirconate | 16923-95-8 | 0.1 - 1 |

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist. Delayed effects possible after inhalation. Administer oxygen or artificial respiration as needed.

Do not use mouth-to-mouth method if victim ingested or inhaled the

substance.

Skin contact: Remove contaminated clothing and footwear. Rinse with large amounts of

running water. GET MEDICAL ATTENTION IMMEDIATELY! If iced 0.13% benzalkonium chloride (Zephiran) solution or 2.5% calcium gluconate gel are available, the rinsing may be limited to 5 minutes, with the soaks or gel applied as soon as the rinsing is stopped. If benzalkonium chloride or calcium gluconate gel is not available, rinsing must continue until medical treatment is provided. Launder contaminated clothing before reuse. Discard any shoes or

clothing items that cannot be decontaminated.

Eye contact: Immediately flush affected eye with large amounts of gently flowing water or

0.9% sterile saline solution for at least 15 minutes. Hold eyelid wide open. Get immediate medical attention. Eye flushing should continue during

transportation to a doctor.

Ingestion: Get medical attention. Do not induce vomiting. If individual is conscious, wash

out mouth with water. Provide a glass of water to dilute the material in the stomach. Never give anything by mouth to a victim who is unconscious or is

having convulsions.

Symptoms: See Section 11.

Notes to physician: Treatment of hypocalcemia associated with corrosive fluoride compounds

exposure may be corrected by intravenous calcium gluconate or calcium chloride. Treatment of hypomagnesemia may be corrected by intravenous

magnesium sulfate.

5. FIRE FIGHTING MEASURES

Extinguishing media: Use media appropriate for surrounding material.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: This product is an aqueous mixture which will not burn. If evaporated to

dryness, solid residue is an oxidizing agent and may cause spontaneous

ignition of combustible materials.

Hazardous combustion products: Upon decomposition, this product may yield gaseous nitrogen oxides, carbon

monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Chromium oxide. Irritating and toxic gases or fumes may be released during a

fire.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Block any potential routes

to water systems.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

egulations

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Avoid breathing vapors or mists of this product. Use only with adequate ventilation. Launder work clothes frequently. Do not store or consume food, drink, or tobacco products in areas where they may become contaminated with this material. Do not take internally. Clothing or other material wet with this product and allowed to dry may become flammable. For industrial use

only.

Storage: Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials. Protect from freezing.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|-----------|-------|
| Chromic acid | 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. 0.0002 mg/m3 TWA (as Cr(VI)) Inhalable fraction. 0.0005 mg/m3 STEL (as Cr(VI)) Inhalable fraction. (SKIN) (as Cr(VI)) Inhalable fraction. (Dermal sensitization) (Respiratory sensitization) | 0.005 mg/m3 TWA 0.0025 mg/m3 OSHA_ACT 0.1 mg/m3 Ceiling | None | None |
| Dipotassium hexafluorozirconate | 5 mg/m3 TWA (as Zr) 10 mg/m3 STEL (as Zr) 2.5 mg/m3 TWA (as F) | 5 mg/m3 PEL (as Zr) 2.5 mg/m3 PEL (as F) 2.5 mg/m3 TWA Dust. | None | None |

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Wear chemical goggles; face shield (if splashing is possible).

Skin protection: Wear impervious gloves for prolonged contact. Gloves should be tested to

determine suitability for prolonged contact. Use of impervious boots is

recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Liquid Orange Color: Odor: None Odor threshold: Not available. pH: 2 - 3 Not applicable 212 °F (100°C) Vapor pressure: Boiling point/range: Not available. Melting point/ range: Specific gravity: 1.00 - 1.01 Vapor density: Not applicable Flash point: Not applicable Flammable/Explosive limits - lower: Not applicable Flammable/Explosive limits - upper: Not applicable Not applicable Autoignition temperature: Flammability: Not applicable

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

VOC content:

Viscosity:

Not available.

Not available.

Not available.

Not available.

Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

Incompatible materials:

products:

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. May liberate hydrogen fluoride. Chromium oxide.

This product may react with strong reducing agents. Avoid contact with organic materials, oils,

greases, and any oxidizable materials. Strong bases. Metals.

Reactivity: Not available.

Conditions to avoid: Store away from incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: May be harmful or fatal if inhaled. Nasal itch and soreness, perforation of the nasal septum,

dental erosion, and chronic asthmatic bronchitis may result from repeated exposure. Mists, vapors or liquid may cause severe irritation or burns. Prolonged or repeated breathing may

cause ulceration of nasal membranes.

Skin contact: A component in this product may be absorbed through the skin in harmful amounts. Mists,

vapors or liquid may cause severe irritation or burns. Product contains chromium, which may cause an allergic skin sensitization reaction. Contact with broken skin may lead to formation of firmly marginated "chrome sores". Liquid or vapor can cause fluoride-type irritation or burns

which may not be immediately painful or visible.

Eye contact: This product is severely irritating to the eyes and may cause irreversible damage including

burns and blindness.

Ingestion: Harmful or fatal if swallowed. May cause burns of the mouth, throat and stomach. May also

 $cause\ gastrointestinal\ disturbances\ such\ as\ nausea,\ vomiting,\ abdominal\ pain,\ and\ diarrhea.$

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects |
|---------------------------------|------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Chromic acid | None | Allergen, Blood, Carcinogen, Central nervous system, Corrosive, Developmental, Eyes, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Reproductive, Respiratory |
| Dipotassium hexafluorozirconate | Oral LD50 (Mouse) = 98 mg/kg | Allergen, Blood, Cardiac, Central nervous system, Corrosive, Gastrointestinal tract, Irritant, Kidney, Lung, Metabolic, Muscle, Teeth, Less weight gain and food intake. |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---------------------------------|----------------------------------|-----------------|------------------------------------------|
| Chromic acid | Known To Be Human Carcinogen. | Group 1 | Yes |
| Dipotassium hexafluorozirconate | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9

Identification number:UN 3082Packing group:IIIDOT Hazardous Substance(s):Chromic acid

International Air Transportation (ICAO/IATA)

Proper shipping name: RQ, Environmentally hazardous substance, liquid, n.o.s.

Hazard class or division: 9

Identification number: UN 3082 Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: RQ, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.

Hazard class or division: 9

Identification number: UN 3082
Packing group: III

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: Chromic acid (CAS# 7738-94-5).

CERCLA/SARA Section 302 EHS: None above reporting de minimis. CERCLA/SARA Section 311/312: Immediate Health, Delayed Health

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Chromic acid (CAS# 7738-94-5).

CERCLA Reportable quantity: Chromic acid (CAS# 7738-94-5) 10 lbs. (4.54 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

Issue date: 10/21/2021

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.