

Revision Number: 002.5 Issue date: 11/13/2019

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product name: BONDERITE L-MR B-204 SEMI

SYNTHETIC COOLANT known as

**MULTAN B-204** 

Product type/use: Lubricant
Restriction of Use: None identified

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

**IDH number:** 1052551

Item number: 1052551
Region: United States

Contact information:

Telephone: +1 (860) 571-5100

MEDICAL EMERGÉNCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

## 2. HAZARDS IDENTIFICATION

**EMERGENCY OVERVIEW** 

WARNING: CAUSES SKIN IRRITATION.

MAY CAUSE AN ALLERGIC SKIN REACTION.

CAUSES SERIOUS EYE IRRITATION.

SUSPECTED OF DAMAGING FERTILITY OR THE UNBORN CHILD.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
REPRODUCTIVE TOXICITY	2

#### PICTOGRAM(S)



#### **Precautionary Statements**

IDH number: 1052551

**Prevention:** Obtain special instructions before use. Do not handle until all safety precautions have been

read and understood. Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear

protective gloves, clothing, eye and face protection.

Response: IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several

minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical attention. If skin irritation or rash occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store locked up.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

3 % of the mixture consists of ingredient(s) of unknown acute toxicity.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

#### See Section 11 for additional toxicological information.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	10 - 30
(Z)-N-[2-(2-hydroxyethoxy)ethyl]-9- octadecenamide	20429-33-8	5 - 10
Boric acid (H3BO3), compd. with 2-(2-aminoethoxy)	124756-59-8	5 - 10
Dicyclohexylamine	101-83-7	1 - 5

<sup>\*</sup> Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections

#### 4. FIRST AID MEASURES

Inhalation: If mist or vapor of this product is inhaled, remove person immediately to fresh

air. Seek medical attention if symptoms develop or persist.

**Skin contact:** For skin contact flush with large amounts of water. Obtain medical attention if

irritation persists.

Eye contact: Immediately flush eyes with water for at least 15 minutes, while holding

eyelids open. Seek medical attention at once.

**Ingestion:** Get immediate medical attention. DO NOT induce vomiting unless directed to

do so by medical personnel. Never give anything by mouth to a victim who is

unconscious or is having convulsions.

Symptoms: See Section 11.

Notes to physician: Treat symptomatically and supportively.

## 5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses.

Hazardous combustion products: Upon decomposition, this product emits oxides of sulfur, carbon monoxide,

carbon dioxide and/or low molecular weight hydrocarbons.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

**Environmental precautions:** Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Collect spilled material with an inert absorbent such as sand or vermiculite.

Place in properly labeled closed container. Flush area with water to remove trace residue. Dispose of according to Federal, State and local governmental

regulations.

## 7. HANDLING AND STORAGE

Handling: Avoid skin and eye contact. Wash thoroughly after handling. Use only with

adequate ventilation. Do not mix this product with fluids which contain

NITRITES/NITRATES. NITROSAMINE may be formed.

Storage: For safe storage, store between 5 °C (41°F) and 50 °C (122°F)

Store in a cool, dry, well-ventilated area. Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
(Z)-N-[2-(2-hydroxyethoxy)ethyl]-9- octadecenamide	None	None	None	None
Boric acid (H3BO3), compd. with 2-(2-aminoethoxy)	None	None	None	None
Dicyclohexylamine	None	None	None	None

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

**Eye/face protection:** Wear safety glasses; chemical goggles (if splashing is possible).

**Skin protection:** Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended. Gloves should be tested to determine suitability for

prolonged contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:AmberOdor:AmineOdor threshold:Not available.pH:9.8 - 10.3Vapor pressure:Not determined

**Boiling point/range:** > 100 °C (> 212°F)calculated

Melting point/ range:Not determinedSpecific gravity:1.00 - 1.01Vapor density:Not determined

Flash point: > 93.33 °C (> 199.99 °F) calculated

Flammable/Explosive limits - lower:

Flammable/Explosive limits - upper:

Autoignition temperature:

Flammability:

Evaporation rate:

Solubility in water:

Partition coefficient (n-octanol/water):

Not available.

Not determined

Not determined

Complete

Not determined

IDH number: 1052551 Product name: BONDERITE L-MR B-204 SEMI SYNTHETIC COOLANT known as MULTAN B-204 Page 3 of 6

VOC content:Not applicableViscosity:60 mPa.sDecomposition temperature:Not available.

## 10. STABILITY AND REACTIVITY

**Stability**: Stable at normal conditions.

Hazardous reactions: Will not occur.

**Hazardous decomposition** 

products:

IDH number: 1052551

Upon decomposition, this product emits oxides of sulfur, carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials: This product may react with strong acids or oxidizing agents. Nitrites may react with organic

amines to form nitrosamines which can cause cancer.

Reactivity: Not available.

**Conditions to avoid:** Avoid excessive heat and ignition sources.

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

#### Potential Health Effects/Symptoms

**Inhalation:** Inhalation of high vapor concentrations may produce respiratory irritation, and may cause

central nervous system (CNS) depression.

Skin contact: This product is irritating to the skin. Prolonged or repeated contact with this product may dry

and/or defat the skin. This product may cause an allergic skin reaction.

**Eye contact:** This product is severely irritating to the eyes and may cause eye burns.

Ingestion: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Small amounts

of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = 2.18 mg/l Inhalation LC50 (Rat, 4 h) = < 5.7 mg/l Inhalation LC50 (Rat, 4 h) = > 5.2 mg/l Inhalation LC50 (Rat, 4 h) = 10.5 mg/l Inhalation LC50 (Rat, 4 h) = > 4.026 mg/l	Irritant
(Z)-N-[2-(2-hydroxyethoxy)ethyl]-9- octadecenamide	None	No Records
Boric acid (H3BO3), compd. with 2-(2-aminoethoxy)	None	Cardiac, Central nervous system, Developmental, Gastrointestinal, Irritant, Kidney, Metabolic, Reproductive
Dicyclohexylamine	Oral LD50 (Rat) = 373 mg/kg	Allergen, Blood, Central nervous system, Corrosive, Irritant, Kidney, Liver, Mutagen

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
(Z)-N-[2-(2-hydroxyethoxy)ethyl]-9- octadecenamide	No	No	No
Boric acid (H3BO3), compd. with 2-(2-aminoethoxy)	No	No	No
Dicyclohexylamine	No	No	No

# 12. ECOLOGICAL INFORMATION

**Ecological information:** Harmful to aquatic organisms.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: Material, if discarded, is not expected to be a characteristic hazardous waste

under RCRA.

#### 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

#### U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated

Hazard class or division:
Identification number:
Packing group:
None

#### International Air Transportation (ICAO/IATA)

Proper shipping name: Environmentally hazardous substance, liquid, n.o.s. (Dicyclohexyl amine)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Water Transportation (IMO/IMDG)

Proper shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Dicyclohexyl

amine)

Hazard class or division: 9
Identification number: UN 3082
Packing group: III

Marine pollutant: Dicyclohexyl amine

**Exceptions:** Classified per IMDG Amendment 34; Effective Jan 1, 2010.

## 15. REGULATORY INFORMATION

#### **United States Regulatory Information**

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

inventory.

TSCA 12 (b) Export Notification: Amine borates (CAS# 124756-59-8).

CERCLA/SARA Section 302 EHS:
CERCLA/SARA Section 311/312:
CERCLA/SARA Section 313:

None above reporting de minimis.

None above reporting de minimis.

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

**Canada Regulatory Information** 

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

IDH number: 1052551 Product name: BONDERITE L-MR B-204 SEMI SYNTHETIC COOLANT known as MULTAN B-204 Page 5 of 6

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Regulatory Affairs

**Issue date:** 11/13/2019

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.