



Revision Number: 006.0

Issue date: 11/05/2020

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product name:** BONDERITE L-GP SN 400C  
CORROSION INHIBITOR known as P3  
PREVOX SN-400C

**IDH number:** 595510

**Product type/use:** Industrial Metal Working Agents

**Restriction of Use:** None identified

**Region:** United States

**Company address:** Henkel Corporation  
One Henkel Way  
Rocky Hill, Connecticut 06067


**Contact information:**  
Telephone: +1 (860) 571-5100  
MEDICAL EMERGENCY Phone: Poison Control Center  
1-877-671-4608 (toll free) or 1-303-592-1711  
TRANSPORT EMERGENCY Phone: CHEMTREC  
1-800-424-9300 (toll free) or 1-703-527-3887  
Internet: www.henkeln.com

**2. HAZARDS IDENTIFICATION**

**EMERGENCY OVERVIEW**

**DANGER:** MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.  
CAUSES SKIN IRRITATION.  
CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
ASPIRATION HAZARD	1



**Precautionary Statements**

**Prevention:** Wash affected area thoroughly after handling. Wear protective gloves, eye protection, and face protection.

**Response:** IF SWALLOWED: Immediately call a physician or poison control center. IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do NOT induce vomiting. If skin irritation occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.

**Storage:** Store locked up.

**Disposal:** Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	30 - 60
Mineral oil-		10 - 30
2-methylpentane-2,4-diol	107-41-5	5 - 10

IDH number: 595510

Product name: BONDERITE L-GP SN 400C CORROSION INHIBITOR known as P3 PREVOX SN-400C

Benzenesulfonic acid, mono-C19-28-alkyl derivs., sodium salts	70024-73-6	5 - 10
Sodium sulfonate~		5 - 10
Barium sulfonate	61790-48-5	1 - 5
Poly(oxy-1,2-ethanediyl), .alpha.-9-octadecenyl-.omega.-hydroxy-, (Z)-	9004-98-2	1 - 5
Fatty acids, C18-unsatd., dimers, polymers with ethylenediamine	68650-50-0	1 - 5

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

## 4. FIRST AID MEASURES

<b>Inhalation:</b>	If mist or vapor of this product is inhaled, remove person immediately to fresh air. Seek medical attention if symptoms develop or persist.
<b>Skin contact:</b>	Immediately flush skin with plenty of water (using soap, if available). If symptoms develop and persist, get medical attention.
<b>Eye contact:</b>	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
<b>Ingestion:</b>	Immediate medical treatment necessary. DO NOT induce vomiting unless directed to do so by medical personnel.
<b>Symptoms:</b>	See Section 11.
<b>Notes to physician:</b>	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

## 5. FIRE FIGHTING MEASURES

<b>Extinguishing media:</b>	Use media appropriate for surrounding material.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	This product is combustible at high temperatures.
<b>Hazardous combustion products:</b>	Irritating and toxic gases or fumes may be released during a fire.

## 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Prevent further leakage or spillage if safe to do so. Wear suitable protective clothing, gloves and eye/face protection.
<b>Clean-up methods:</b>	Absorb spill with inert material. Shovel material into appropriate container for disposal. Dispose of according to Federal, State and local governmental regulations.

## 7. HANDLING AND STORAGE

<b>Handling:</b>	Avoid contact with eyes, skin and clothing. Do not take internally. For industrial use only.
<b>Storage:</b>	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Manufacturer recommends storing above 4.4 °C (40 °F). Thaw and mix thoroughly if frozen.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m3 TWA Inhalable fraction.	500 ppm (2,000 mg/m3) PEL 5 mg/m3 PEL Mist.	None	None
Mineral oil~	None	None	None	None
2-methylpentane-2,4-diol	10 mg/m3 STEL Aerosol, inhalable. 50 ppm STEL Vapor fraction 25 ppm TWA Vapor fraction	None	None	None
Benzenesulfonic acid, mono-C19-28-alkyl derivs., sodium salts	None	None	None	None
Sodium sulfonate~	None	None	None	None
Barium sulfonate	0.5 mg/m3 TWA (as Ba)	0.5 mg/m3 PEL (as Ba)	None	None
Poly(oxy-1,2-ethanediyl), .alpha.-9-octadecenyl-.omega.-hydroxy-, (Z)-	None	None	None	None
Fatty acids, C18-unsatd., dimers, polymers with ethylenediamine	None	None	None	None

**Engineering controls:**

Provide local and general exhaust ventilation to effectively remove and prevent buildup of any vapors or mists generated from the handling of this product.

**Respiratory protection:**

If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

**Eye/face protection:**

Wear safety glasses; chemical goggles (if splashing is possible).

**Skin protection:**

Chemical resistant, impermeable gloves. Gloves should be tested to determine suitability for prolonged contact. Use of impervious apron and boots are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Liquid
<b>Color:</b>	Brown
<b>Odor:</b>	Petroleum
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	7.00
<b>Vapor pressure:</b>	Not determined
<b>Boiling point/range:</b>	215 °F (101.7 °C)None
<b>Melting point/ range:</b>	Not available.
<b>Specific gravity:</b>	0.942 at 20 °C (68°F)
<b>Vapor density:</b>	Not determined
<b>Flash point:</b>	100 °C (212°F)
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not available.
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Complete
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	Not applicable
<b>Viscosity:</b>	Not available.
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable at normal conditions.
<b>Hazardous reactions:</b>	None under normal processing.
<b>Hazardous decomposition products:</b>	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.
<b>Incompatible materials:</b>	Strong oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Heat, flames, sparks and other sources of ignition.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Skin, Inhalation, Eyes

### Potential Health Effects/Symptoms

<b>Inhalation:</b>	Inhalation of vapors or mists of the product may be irritating to the respiratory system. Excessive inhalation of this material causes headache, dizziness, nausea and incoordination.
<b>Skin contact:</b>	Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis. Contact with skin can cause irritation and allergic reaction (sensitization) in some individuals.
<b>Eye contact:</b>	Severe eye irritation.
<b>Ingestion:</b>	Ingestion of this product may cause nausea, vomiting and diarrhea. May cause dizziness, incoordination, headache, nausea, and vomiting. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Distillates (petroleum), hydrotreated heavy naphthenic	Inhalation LC50 (Rat, 4 h) = 2.18 mg/l	Irritant
Mineral oil~	None	No Data
2-methylpentane-2,4-diol	Oral LD50 (Rat) = 4.79 g/kg Oral LD50 (Mouse) = 3.5 g/kg	Irritant, Central nervous system
Benzenesulfonic acid, mono-C19-28-alkyl derivs., sodium salts	None	No Records
Sodium sulfonate~	None	No Data
Barium sulfonate	None	No Records
Poly(oxy-1,2-ethanediyl), .alpha.-9-octadecenyl-.omega.-hydroxy-, (Z)-	None	Allergen, Irritant, Kidney
Fatty acids, C18-unsatd., dimers, polymers with ethylenediamine	None	Allergen, Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Distillates (petroleum), hydrotreated heavy naphthenic	No	No	No
Mineral oil~	No	No	No
2-methylpentane-2,4-diol	No	No	No
Benzenesulfonic acid, mono-C19-28-alkyl derivs., sodium salts	No	No	No
Sodium sulfonate~	No	No	No
Barium sulfonate	No	No	No
Poly(oxy-1,2-ethanediyl), .alpha.-9-octadecenyl-.omega.-hydroxy-, (Z)-	No	No	No
Fatty acids, C18-unsatd., dimers, polymers with ethylenediamine	No	No	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** No data available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Dispose of according to Federal, State and local governmental regulations.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

### International Air Transportation (ICAO/IATA)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

### Water Transportation (IMO/IMDG)

<b>Proper shipping name:</b>	Not regulated
<b>Hazard class or division:</b>	None
<b>Identification number:</b>	None
<b>Packing group:</b>	None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis.
<b>CERCLA/SARA Section 311/312:</b>	Immediate Health
<b>CERCLA/SARA Section 313:</b>	This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Barium sulfonate (CAS# 61790-48-5).
<b>California Proposition 65:</b>	This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada Regulatory Information

<b>CEPA DSL/NDSL Status:</b>	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
------------------------------	---

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Material Safety Data Sheet format.

**Prepared by:** Timothy Pratt, Regulatory Affairs Specialist

**Issue date:** 11/05/2020

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.