

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

SECTION 1. IDENTIFICATION

Product name : Epoxylite® E 8822 Hi Temp Resin

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone number : INFOTRAC - 1-800-535-5053

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.
Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Carcinogenicity : Category 1A

Specific target organ toxicity - single exposure : Category 3 (Respiratory system)

Specific target organ toxicity - repeated exposure (Inhalation) : Category 1 (Lungs)

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H315 Causes skin irritation.

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H350 May cause cancer.
H372 Causes damage to organs (Lungs) through prolonged or repeated exposure if inhaled.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.

Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.

Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified epoxy resin

Hazardous components

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Component	CAS-No.	Concentration (%)
Epoxy Resin	28064-14-4	>= 52 - < 53
Aluminum oxide	1344-28-1	>= 20 - < 21
Crystalline silica	14808-60-7	>= 10 - < 11
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	>= 10 - < 11
Benzyl alcohol	100-51-6	>= 2 - < 3
Epoxy Resin	25068-38-6	>= 1 - < 2

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.
Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Unsuitable extinguishing media : High volume water jet
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment : Wear self-contained breathing apparatus for firefighting if

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

for firefighters

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions,
protective equipment and
emergency procedures

: Use personal protective equipment.

Environmental precautions

: Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform
respective authorities.

Methods and materials for
containment and cleaning up

: Absorb with inert absorbent material and dispose of in
accordance with applicable regulations.

Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.
Absorbent paper or other organic material used for cleaning
up resin is a fire hazard, as heat and spontaneous combustion
can occur, particularly if the resin was catalyzed. Catalyzed
resin can generate hazardous exothermic heat if allowed to
polymerize in a mass. All soiled or waste materials must be
water soaked, and kept in a closed bin until disposed of.

Soak up with inert absorbent material (e.g. sand, silica gel,
acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling

: Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the
application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national
regulations.
Persons susceptible to skin sensitisation problems or asthma,
allergies, chronic or recurrent respiratory disease should not
be employed in any process in which this mixture is being
used.
The chemical reaction that cures mixed epoxy is exothermic
(heat generating). If left to cure in a contained mass, such as
in a mixing vessel, it can generate enough heat to melt plastic,
burn skin or ignite surrounding combustible materials. The

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

larger or thicker the epoxy mass, the more heat generated.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Aluminum oxide	1344-28-1	TWA (Total)	10 mg/m3	OSHA P0
Aluminum oxide		TWA (Respirable fraction)	5 mg/m3	OSHA P0
Aluminum oxide		TWA (Respirable fraction)	1 mg/m3	ACGIH
Crystalline silica	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO ₂ +2	OSHA Z-3
Crystalline silica		TWA (respirable)	250 mppcf / %SiO ₂ +5	OSHA Z-3
Crystalline silica		TWA (respirable)	10 mg/m3 / %SiO ₂ +2	OSHA Z-3
Crystalline silica		TWA (respirable dust fraction)	0.1 mg/m3	OSHA P0
Crystalline silica		TWA (Respirable fraction)	0.025 mg/m3 (Silica)	ACGIH
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
Magnesium Silicate Talc (contains no asbestos fibers)		TWA (Respirable fraction)	2 mg/m3	ACGIH
Benzyl alcohol	100-51-6	TWA	10 ppm	US WEEL

Hazardous components without workplace control parameters

Engineering measures : Use with adequate ventilation.
All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)
This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Section III as a precautionary warning.
Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.
Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.
Repeated inhalation of such dust may cause lung injury.

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Vapour pressure : No data available
- Flash point : > 201 °F (> 94 °C)
Method: ASTM D 93, closed cup
- Upper explosion limit : No data available
- Lower explosion limit : No data available

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.6490 g/cm ³ (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm ² /s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Hazardous decomposition products	: Carbon monoxide in a fire. Nitrogen oxides in a fire.

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 151.84 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**1344-28-1 Aluminum oxide:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.38 mg/l

100-51-6 Benzyl alcohol:

Acute oral toxicity : LD50 (Rat): 1,230 mg/kg

Acute inhalation toxicity : LC50 (Rat, male and female): 4 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): 2,000 mg/kg

25068-38-6 Epoxy Resin:

Acute oral toxicity : LD50 (Rat): 11,400 mg/kg

LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
GLP: yes

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 23,400 mg/kg

LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Components:**1344-28-1 Aluminum oxide:**

Species: Rabbit

Result: Moderate skin irritation

100-51-6 Benzyl alcohol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

25068-38-6 Epoxy Resin:

Species: Rabbit

Result: Moderate skin irritation

Species: Rabbit

Exposure time: 4 h

Method: OECD Test Guideline 404

Result: Skin irritation

GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Components:**1344-28-1 Aluminum oxide:**

Species: Rabbit

Result: Eye irritation

100-51-6 Benzyl alcohol:

Species: Rabbit

Result: Eye irritation

Method: OECD Test Guideline 405

GLP: yes

25068-38-6 Epoxy Resin:

Species: Rabbit

Result: Eye irritation

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**25068-38-6 Epoxy Resin:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

EpoxyLite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Method: OECD Test Guideline 429
Result: May cause sensitisation by skin contact.
GLP: yes

Carcinogenicity

IARC	Group 1: Carcinogenic to humans	
	Crystalline silica	14808-60-7
OSHA	OSHA specifically regulated carcinogen	
	Crystalline silica	14808-60-7
NTP	Known to be human carcinogen	
	Crystalline silica	14808-60-7
	Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6

Aspiration toxicity**Components:****25068-38-6 Epoxy Resin:**

No aspiration toxicity classification

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Regulation	40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks	This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).
Additional ecological information	: No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : none

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F

EpoxyLite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3082

Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)

Class : 9

Packing group : III

Labels : CLASS 9

ERG Code : 171

Marine pollutant : yes (Epoxy resin)

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 - Emergency Release Notification

Calculated RQ exceeds reasonably attainable upper limit.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This product contains the following toxic chemical(s) subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Aluminum oxide	1344-28-1	20.9 %
----------------	-----------	--------

Epoxylite® E 8822 Hi Temp Resin

Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

Benzyl alcohol	100-51-6	2.6 %
----------------	----------	-------

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

Massachusetts Right To Know

Aluminum oxide	1344-28-1
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Benzyl alcohol	100-51-6

Pennsylvania Right To Know


Epoxy Resin	28064-14-4
Aluminum oxide	1344-28-1
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Benzyl alcohol	100-51-6

New Jersey Right To Know

Epoxy Resin	28064-14-4
Aluminum oxide	1344-28-1
Crystalline silica	14808-60-7
Magnesium Silicate Talc (contains no asbestos fibers)	14807-96-6
Benzyl alcohol	100-51-6

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : NOT APPLICABLE

California Prop. 65

 **WARNING:** This product can expose you to chemicals including Crystalline silica, Phenyl glycidyl ether, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : All components of this product are listed active and/or are exempt

Section 4 / 12(b) : Not applicable

EpoxyLite® E 8822 Hi Temp Resin


Version 7

Revision Date 02/11/2022

Print Date 02/10/2023

Section 5 Not applicable

Section 6 Not applicable

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 02/11/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

SECTION 1. IDENTIFICATION

Product name : Epoxylite® C 8822 Hi Temp Hardener

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone : INFOTRAC - 1-800-535-5053
number

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.
Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Acute toxicity (Oral) : Category 4

Acute toxicity (Inhalation) : Category 3

Skin irritation : Category 2

Serious eye damage : Category 1

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

H331 Toxic if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statements**: Prevention:**

P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.

P280 Wear protective gloves/ eye protection/ face protection.

P285 In case of inadequate ventilation wear respiratory protection.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.

P304 + P340 + P311 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P342 + P311 If experiencing respiratory symptoms: Call a POISON CENTER/ doctor.

P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature

: Modified Aromatic Anhydride

Hazardous components

Component	CAS-No.	Concentration (%)
Pyromellitic dianhydride	89-32-7	>= 57 - < 58

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

Methendic anhydride	25134-21-8	>= 39 - < 40
1,2,4,5-Benzenetetracarboxylic acid	89-05-4	>= 1 - < 2

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment : Wear self-contained breathing apparatus for firefighting if

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

for firefighters

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Keep container tightly closed in a dry and well-ventilated place.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

Contains no substances with occupational exposure limit values.
Hazardous components without workplace control parameters

- Engineering measures** : Use with adequate ventilation.

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)
This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.
Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.
Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.
Repeated inhalation of such dust may cause lung injury.

Personal protective equipment

- Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Vapour pressure : No data available
- Flash point : > 201 °F (> 94 °C)
Method: No information available.

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

	Information taken from reference works and the literature.
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Relative vapour density	: No data available
Relative Density/Specific Gravity	: No data available
Density	: 1.4800 g/cm ³ (77 °F (25 °C))
Solubility(ies)	
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: > 21 mm ² /s (104 °F (40 °C))

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No decomposition if stored and applied as directed.
Chemical stability	: No decomposition if stored and applied as directed.
Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Hazardous decomposition products	: Carbon monoxide in a fire. Nitrogen oxides in a fire.

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

Inhalation

Skin contact

Acute toxicity**Product:**

Acute oral toxicity : Acute toxicity estimate : 1,624 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate : 7.6 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**89-32-7 Pyromellitic dianhydride:**

Acute dermal toxicity : LD50 : Remarks: No data available

25134-21-8 Methendic anhydride:

Acute oral toxicity : LD50 (Rat): 641 mg/kg

Acute inhalation toxicity : LC50 (Rat): 750 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rat): 4,920 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Components:**89-32-7 Pyromellitic dianhydride:**

Remarks: No data available

25134-21-8 Methendic anhydride:

Result: Causes burns.

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

Components:**89-32-7 Pyromellitic dianhydride:**

Species: Rabbit

Result: Severe eye irritation

Method: Draize Test

25134-21-8 Methendic anhydride:

Result: Risk of serious damage to eyes.

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**89-32-7 Pyromellitic dianhydride:**

Result: No data available

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

Other adverse effects

No data available

Product:

Regulation 40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information : No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

EPA Hazardous Waste Code(s) : none

Waste from residues : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

EPCRA - Emergency Planning and Community Right-to-Know Act**US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

Pennsylvania Right To Know

Pyromellitic dianhydride	89-32-7
Methendic anhydride	25134-21-8
Nadic Anhydride	826-62-0

New Jersey Right To Know

Pyromellitic dianhydride	89-32-7
--------------------------	---------

Epoxylite® C 8822 Hi Temp Hardener

Version 4

Revision Date 01/11/2022

Print Date 01/12/2022

Methendic anhydride 25134-21-8

Nadic Anhydride 826-62-0

Silicon dioxide, modified 68611-44-9

New Jersey Trade Secret : Not Applicable
Registry Number for the product (NJ TSRN)

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.


The components of this product are reported in the following inventories:

TSCA : All components of this product are listed active and/or are exempt

Section 4 / 12(b) : Not applicable

Section 5 : Not applicable

Section 6 : Not applicable

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

HEALTH	3
FLAMMABILITY	1
PHYSICAL HAZARD	1

0 = not significant, 1 = Slight,
 2 = Moderate, 3 = High
 4 = Extreme, * = Chronic

Revision Date : 01/11/2022

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.