

Safety Data Sheet

FOR REGULATORY AND SDS QUESTIONS (U.S. AND CANADA):

CALL THE PRODUCT STEWARDSHIP LINE 1-908-791-2336 9 AM TO 6 PM ET (Mon-Fri)

Section 1. Identification

Product name : ALPHA® 2110 SAPONIFIER CLEANER

Product code : 116381
Product type : Liquid.

Date of issue/Date of

revision

: January 20 2022.

| Manufacturer - Supplier | Telephone no.: | Emergency phone: |
|--|---|---|
| Alpha Assembly Solutions Inc. Global Headquarters 300 Atrium Drive Somerset, New Jersey 08873 | Toll Free: (800) 367-5460 Main Phone: (908) 791-3000 | DOMESTIC NORTH AMERICA 202-464-2554 |
| ALPHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico | Tel: +52 81 1156-6602 | Tel: 01 800 022 1400 Tel: +52 55 5559-1588 |
| Alpha Assembly Solutions Brasil Soldas Ltda Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil | Tel: 55 92 3614-7400 | Tel: 55 92 3614-7423 |

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

ACUTE TOXICITY (dermal) - Category 4
 ACUTE TOXICITY (inhalation) - Category 4

SKIN CORROSION - Category 1 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1

TOXIC TO REPRODUCTION (Unborn child) - Category 1B

SPECIFIC TARGET ORGAN TOXICITY (Respiratory tract irritation) - Category 3 SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) (kidneys) -

Category 2

AQUATIC HAZARD (ACUTE) - Category 2 AQUATIC HAZARD (LONG-TERM) - Category 2

GHS label elements

Hazard pictograms









Signal word : Danger

Section 2. Hazards identification

Hazard statements

: Harmful in contact with skin or if inhaled.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction. May damage the unborn child.

May cause respiratory irritation.

May cause damage to organs through prolonged or repeated exposure. (kidneys)

Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves. Wear eye or face protection. Wear protective clothing. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Do not breathe vapor. Wash hands thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.

Response

: Collect spillage. Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.

Storage

Disposal

: Store locked up.

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label

elements

: Do not taste or swallow. Wash thoroughly after handling.

Hazards not otherwise

classified

: Causes digestive tract burns.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

| Ingredient name | % | CAS number |
|--------------------|---------|------------|
| Amines | 50-60 | - |
| Proprietary Glycol | 30-40 | - |
| Solvent. | 1-10 | - |
| surfactant | 1-10 | - |
| surfactant | 0.1-1.0 | - |
| surfactant | 0.1-1.0 | - |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Chemical burns must be treated promptly by a physician.

Page: 3/13

Section 4. First aid measures

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Harmful if inhaled. May cause respiratory irritation.

Skin contact: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.

Ingestion: Corrosive to the digestive tract. Causes burns.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion : Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

Section 4. First aid measures

Notes to physician

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media

: None known.

nitrogen oxides

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst. This material is toxic to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials: carbon dioxide carbon monoxide

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For nonemergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities. Collect spillage.

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Page: 5/13

Section 6. Accidental release measures

Large spill

: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Keep away from acids. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Storage temperature: 5 to 40°C (41 to 104°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Separate from acids. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits | |
|-----------------|--|--|
| Amines | ACGIH TLV (United States, 3/2017). | |
| | STEL: 15 mg/m³ 15 minutes. | |
| | STEL: 6 ppm 15 minutes. | |
| | TWA: 7.5 mg/m³ 8 hours. | |
| | TWA: 3 ppm 8 hours. | |
| | NIOSH REL (United States, 10/2016). | |
| | STEL: 15 mg/m³ 15 minutes. | |
| | STEL: 6 ppm 15 minutes. | |
| | TWA: 8 mg/m³ 10 hours. | |
| | TWA: 3 ppm 10 hours. | |
| | OSHA PEL (United States, 6/2016). | |
| | TWA: 6 mg/m³ 8 hours. | |
| | TWA: 3 ppm 8 hours. | |
| | OSHA PEL 1989 (United States, 3/1989). | |
| | STEL: 15 mg/m³ 15 minutes. | |
| | STEL: 6 ppm 15 minutes. | |
| | TWA: 8 mg/m³ 8 hours. | |

Section 8. Exposure controls/personal protection

Proprietary Glycol

surfactant

TWA: 3 ppm 8 hours.

ACGIH TLV (United States, 3/2017).

TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor

ACGIH TLV (United States, 3/2017).

STEL: 10 mg/m³ 15 minutes. Form: Inhalable fraction. Aerosol only.

STEL: 50 ppm 15 minutes. Form: Vapor fraction TWA: 25 ppm 8 hours. Form: Vapor fraction OSHA PEL 1989 (United States, 3/1989).

CEIL: 125 mg/m³ CEIL: 50 ppm

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

: Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

: Liquid. [Clear.] **Physical state** Color : Clear, Blue, : Ammonia. [Slight] Odor

Odor threshold : Not available.

: 13.4 pН

Melting point : Not available. **Boiling point** : >35°C (>95°F)

Flash point : Closed cup: >93°C (>199.4°F) [Pensky-Martens.]

Evaporation rate : Not available. Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

: Not available. Vapor pressure : Not available. Vapor density

Relative density

Solubility : Soluble in the following materials: cold water and hot water.

VOC : 945 g/l

Partition coefficient: n-

octanol/water

: Not available.

: 410°C (770°F) **Auto-ignition temperature Decomposition temperature** : Not available. : Not available. **Viscosity**

Aerosol product

Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Incompatibility with various substances

: Extremely reactive or incompatible with the following materials: oxidizing materials, reducing materials, organic materials, metals and acids.

Slightly reactive or incompatible with the following materials: combustible materials,

alkalis and moisture. Acetic anhydride

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Other Hazardous decomposition products : carbon oxides (CO, CO₂), nitrogen oxides (NO, NO₂ etc.), Ammonia.

Hazardous polymerization : Under normal conditions of storage and use, hazardous polymerization will not occur.

Section 11. Toxicological information

Routes of entry Acute toxicity

: Dermal contact. Eye contact. Inhalation. Ingestion.

Section 11. Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------------|---------|-------------------------|----------|
| Amines | LC50 Inhalation Vapor | Cat | >2420 mg/m ³ | 2 hours |
| | LC50 Inhalation Vapor | Mouse | >2420 mg/m ³ | 2 hours |
| | LD50 Dermal | Rabbit | 1 mL/kg | - |
| | LD50 Oral | Rat | 1720 mg/kg | - |
| | LDLo Oral | Mammal | 1400 mg/kg | - |
| Proprietary Glycol | LD50 Dermal | Rabbit | 2700 mg/kg | - |
| | LD50 Oral | Rat | 4500 mg/kg | - |
| Solvent. | LD50 Oral | Rat | 1350 mg/kg | - |
| surfactant | LD50 Dermal | Rabbit | >3000 mg/kg | - |
| | LD50 Oral | Rat | 2745 mg/kg | - |
| surfactant | LC50 Inhalation Vapor | Rat | >20 mg/l | 1 hours |
| | LD50 Dermal | Rat | >2000 mg/kg | - |
| | LD50 Oral | Rat | 4600 mg/kg | - |
| surfactant | LD50 Oral | Rat | 4700 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|----------------|-------------|
| Amines | Eyes - Severe irritant | Rabbit | - | 250 | - |
| | | | | Micrograms | |
| | Skin - Moderate irritant | Rabbit | - | 505 | - |
| | | | | milligrams | |
| Proprietary Glycol | Eyes - Moderate irritant | Rabbit | - | 24 hours 20 | - |
| | | | | milligrams | |
| | Eyes - Severe irritant | Rabbit | - | 20 milligrams | - |
| Solvent. | Eyes - Moderate irritant | Rabbit | - | 100 | - |
| | | | | milligrams | |
| surfactant | Eyes - Severe irritant | Rabbit | - | 0.1 Mililiters | - |
| | Skin - Mild irritant | Rabbit | - | 0.5 Grams | - |
| surfactant | Eyes - Mild irritant | Rabbit | - | 24 hours 500 | - |
| | | | | milligrams | |
| | Eyes - Mild irritant | Rabbit | - | 1 hours 100 | - |
| | | | | milligrams | |
| | Eyes - Moderate irritant | Rabbit | - | 6 hours 1440 | - |
| | | | | milligrams | |
| | Skin - Mild irritant | Rabbit | - | 555 | - |
| | | | | milligrams | |

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

No applicable toxicity data

Additional information:

Reproductive toxicity

| Product/ingredient name | Maternal toxicity | Fertility | Development toxin | Species | Dose | Exposure |
|-------------------------|-------------------|-----------|-------------------|--------------|-------------------------|----------|
| surfactant | - | - | Equivocal | Rat - Female | Oral: 50 g/ kg | - |
| | - | - | Equivocal | Rat - Female | Oral: 8580 mg/ kg | - |

Teratogenicity

Page: 9/13

Section 11. Toxicological information

| Product/ingredient name | Result | Species | Dose | Exposure |
|-------------------------|-----------------|---------|-------------------------------|----------|
| Amines | Positive - Oral | | 500 mg/kg During Pregnancy | - |

Specific target organ toxicity

| Name | • | Route of exposure | Target organs |
|--------|------------|-------------------|------------------------------|
| Amines | Category 3 | | Respiratory tract irritation |

Specific target organ toxicity (repeated exposure)

| Name | | Route of exposure | Target organs |
|------------|------------|-------------------|---------------|
| surfactant | Category 2 | Oral | kidneys |

Aspiration hazard

Not available.

Information on the likely

routes of exposure

: Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation: Harmful if inhaled. May cause respiratory irritation.

Skin contact: Causes severe burns. Harmful in contact with skin. May cause an allergic skin reaction.

Ingestion : Corrosive to the digestive tract. Causes burns.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

reduced fetal weight increase in fetal deaths skeletal malformations

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur reduced fetal weight increase in fetal deaths skeletal malformations

Ingestion: Adverse symptoms may include the following:

stomach pains reduced fetal weight increase in fetal deaths skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Page: 10/13

Section 11. Toxicological information

Long term exposure

Potential immediate

effects

: Not available.

Potential delayed effects : Not available.

Potential chronic health effects

General : May cause damage to organs through prolonged or repeated exposure. Once

sensitized, a severe allergic reaction may occur when subsequently exposed to very low

levels.

Carcinogenicity : No known significant effects or critical hazards.Mutagenicity : No known significant effects or critical hazards.

Teratogenicity: May damage the unborn child.

Developmental effects : No known significant effects or critical hazards.

Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|-----------------------|--|
| Dermal | 2173.1 mg/kg 1527.4 mg/kg 11.56 mg/l |
| initialation (vapors) | 11.30 mg/i |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-------------------------|--------------------------------------|--|----------|
| Amines | Acute EC50 8.42 mg/l Fresh water | Algae - Desmodesmus subspicatus | 72 hours |
| | Acute LC50 >100000 μg/l Marine water | Crustaceans - Crangon crangon - Adult | 48 hours |
| | Acute LC50 170 mg/l Fresh water | Fish - Carassius auratus | 96 hours |
| Proprietary Glycol | Acute LC50 1300000 µg/l Fresh water | Fish - Lepomis macrochirus | 96 hours |
| surfactant | Acute EC50 91 mg/l | Daphnia | 48 hours |
| | Acute LC50 36 mg/l | Fish | 96 hours |
| surfactant | Acute LC50 6900000 μg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 41000000 μg/l Fresh water | Daphnia - Daphnia magna - Neonate | 48 hours |
| | Acute LC50 8050000 μg/l Fresh water | Fish - Pimephales promelas | 96 hours |

Persistence and degradability

Not available.

Bioaccumulative potential

| Product/ingredient name | LogPow | BCF | Potential |
|-------------------------|--------|-----|-----------|
| Amines | -1.31 | - | low |
| Proprietary Glycol | 1 | - | low |
| Solvent. | -0.2 | - | low |
| surfactant | 2.8 | - | low |
| surfactant | -1.36 | - | low |

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

| | DOT Classification | TDG Classification | Mexico Classification | UN | IMDG | IATA |
|--|--|--|--|--|--|--|
| UN number | UN3267 | UN3267 | UN3267 | UN3267 | UN3267 | UN3267 |
| UN proper shipping name | Corrosive liquid, basic, organic, n.o.s. (Amines) | Corrosive liquid, basic, organic, n.o.s. (Amines) | Corrosive liquid, basic, organic, n.o.s. (Amines) | Corrosive liquid, basic, organic, n.o.s. (Amines) | Corrosive liquid, basic, organic, n.o.s. (Amines) | Corrosive liquid, basic, organic, n.o.s. (Amines) |
| Transport hazard class(es) | 8 | 8 | 8 | 8 | 8 | 8 |
| Packing group | III | III | III | III | III | III |
| Environmental hazards | No. | Yes. The environmentally hazardous substance mark is not required. | Yes. The environmentally hazardous substance mark is not required. | Yes. The environmentally hazardous substance mark is not required. | Yes. | Yes. The environmentally hazardous substance mark is not required. |
| Additional information - DOT Classification Additional information - IMDG Classification | ERG# 153 The marine pollutant mark is not required when transported in sizes of ≤5 L or ≤5 kg. | | | | | |
| Additional information - IATA Classification | The environmentally hazardous substance mark may appear if required by other transportation regulations. | | | | | |

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 14. Transport information

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rules: Solvent.

TSCA 5(a)2 final significant new use rule (SNUR): No products were found.

TSCA 12(b) one-time export: Solvent.

TSCA 12(b) annual export notification: No products were found.

United States inventory

(TSCA 8b)

: All components are listed or exempted.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : Immediate (acute) health hazard

Delayed (chronic) health hazard

SARA 313

| | Product name | CAS number | % |
|---------------------------------|-------------------------------|------------|----------------|
| Form R - Reporting requirements | Proprietary Glycol surfactant | - | 30-40 0.1-1 |
| Supplier notification | Proprietary Glycol surfactant | - | 30-40 0.1-1 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada

Canada inventory: Not determined.

International lists

National inventory

Australia : Not determined.

China : All components are listed or exempted.
Europe : All components are listed or exempted.
Japan : All components are listed or exempted.

Malaysia: Not determined.New Zealand: Not determined.Philippines: Not determined.

Republic of Korea : All components are listed or exempted.

Taiwan : All components are listed or exempted.


Thailand : Not determined.

Turkey : Not determined.

Viet Nam : Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Procedure used to derive the classification

| Classification | Justification | |
|-------------------------------|-----------------------|--|
| Acute Tox. 4, H312 | Calculation method | |
| Acute Tox. 4, H332 | Calculation method | |
| Skin Corr. 1, H314 | On basis of test data | |
| Eye Dam. 1, H318 | On basis of test data | |
| Skin Sens. 1, H317 | Calculation method | |
| Repr. 1B, H360 (Unborn child) | Calculation method | |
| STOT SE 3, H335 | Calculation method | |
| STOT RE 2, H373 (kidneys) | Calculation method | |
| Aquatic Acute 2, H401 | Calculation method | |
| Aquatic Chronic 2, H411 | Calculation method | |

History

Date of issue/Date of

revision

: January 20 2022.

Date of previous issue

: January 20 2022.

Version

2.05

Prepared by

: Regulatory Affairs Department

enthone.msds@macdermidenthone.com

Key to abbreviations

: ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

▼ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.9.04b4933