

SAFETY DATA SHEET

Revision Date 30-Jul-2021 Version 4

1. IDENTIFICATION

Product identifier

Product Name HIGH-TEMP RED RTV SILICONE GASKET POWERBEAD 7.25 OZ AE

Other means of identification

Product Code 85915

Recommended use of the chemical and restrictions on use

Recommended Use Sealant

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex 6875 Parkland Blvd. Solon, Ohio 44139 USA Telephone: 1-87-Permatex

(866) 732-9502

24-hour emergency phone number

Chem-Tel: 800-255-3924 International Emergency: 00+1+ 813-248-0585

Contract Number: MIS0003453

E-mail address: mail@permatex.com

May Also Be Distributed by:

ITW Permatex Canada 101-2360 Bristol Circle

Oakville, ON Canada L6H 6M5 Telephone: (800) 924-6994

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Gases under pressure	Compressed gas

Label elements

Emergency Overview

Signal word Warning

Causes skin irritation

Causes serious eye irritation

Contains gas under pressure; may explode if heated



Appearance Red Physical state Paste / Gel Liquid Odor Acetic acid

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

Specific treatment (see .? on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation occurs: Get medical advice/attention Take off contaminated clothing and wash before reuse

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Not applicable.

Unknown acute toxicity 8.5 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
AMORPHOUS SILICA	7631-86-9	7 - 13
ACETIC ACID	64-19-7	1 - 5

4. FIRST AID MEASURES

Description of first aid measures

General advice Call 911 or emergency medical service. Remove and isolate contaminated clothing and

shoes.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin contact In case of contact with liquefied gas, thaw frosted parts with lukewarm water.

Inhalation Move victim to fresh air. If breathing is irregular or stopped, administer artificial respiration.

Administer oxygen if breathing is difficult.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by mouth

to an unconscious person. Call a physician. Do NOT induce vomiting.

Self-protection of the first aider Ensure that medical personnel are aware of the material(s) involved and take precautions to

protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Keep victim warm and quiet.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Use extinguishing agent suitable for type of surrounding fire, Dry chemical or CO2, Water spray, fog or regular foam, Move containers from fire area if you can do it without risk, Damaged cylinders should be handled only by specialists

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Some may burn but none ignite readily. Ruptured cylinders may rocket.

Explosion data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Do not touch or walk through spilled material. Stop leak if you can do it without risk.

Other Information Ventilate the area.

Environmental precautions

Environmental precautionsUse water spray to reduce vapors or divert vapor cloud drift. Avoid allowing water runoff to

contact spilled material. Prevent entry into waterways, sewers, basements or confined

areas.

Methods and material for containment and cleaning up

Methods for containment If possible, turn leaking containers so that gas escapes rather than liquid. Allow substance

to evaporate.

Methods for cleaning upDo not direct water at spill or source of leak.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Contents under pressure. Do not puncture or incinerate cans. Avoid contact with skin and

eyes. Wash thoroughly after handling. Use with local exhaust ventilation. All equipment used when handling the product must be grounded. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use personal protective equipment as required. Do not breathe dust/fume/gas/mist/vapors/spray. Take necessary action to avoid static electricity

discharge (which might cause ignition of organic vapors).

Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Protect from sunlight. Store in a well-ventilated place. Keep

containers tightly closed in a cool, well-ventilated place. Keep away from heat. Keep in

properly labeled containers.

Incompatible materials Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
AMORPHOUS SILICA	-	TWA: 50 μg/m ³ excludes	IDLH: 3000 mg/m ³
7631-86-9		construction work, agricultural	TWA: 6 mg/m ³
		operations, and exposures that	_
		result from the processing of	
		sorptive clays	
		(vacated) TWA: 6 mg/m ³ <1%	
		Crystalline silica	
		TWA: 20 mppcf	
		: (80)/(% SiO2) mg/m ³ TWA	
ACETIC ACID	STEL: 15 ppm	TWA: 10 ppm	IDLH: 50 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m ³	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 25 mg/m³
		(vacated) TWA: 25 mg/m ³	STEL: 15 ppm
			STEL: 37 mg/m ³

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.

appropriate.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Polymerization

Polymerization

9.1. Information on basic physical and chemical properties

Physical state Paste / Gel Liquid

Appearance Red Odor Acetic acid

Odor threshold No information available

Property Values Remarks • Method

pH No information available
Melting point / freezing point
Boiling point / boiling range No information available
No information available

Flash point > 95 °C / > 203 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available

Vapor pressure <5 mm Hg Vapor density >1 Air = 1

Relative density 1.05

Water solubility Not applicable

Solubility(ies) No information available **Partition coefficient** No information available **Autoignition temperature** No information available No information available Hyphen No information available Kinematic viscosity Dynamic viscosity No information available **Explosive properties** No information available Oxidizing properties No information available

Other Information

Softening pointNo information availableMolecular weightNo information availableDensityNo information availableBulk densityNo information availableSADT (self-acceleratingNo information available

decomposition temperature)

10. STABILITY AND REACTIVITY

Reactivity

No information available

Chemical stability

Stable under normal conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides Nitrogen oxides (NOx) Acetic acid Oxides of sulfur Formaldehyde

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation May cause irritation of respiratory tract.

Eye contact Contact with eyes may cause irritation. May cause redness and tearing of the eyes.

Skin contact May cause skin irritation and/or dermatitis.

Ingestion Ingestion may cause irritation to mucous membranes.

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
AMORPHOUS SILICA = 7900 mg/kg (Rat)		> 5000 mg/kg (Rabbit)	> 2.2 mg/L (Rat)1 h
7631-86-9			
ACETIC ACID	= 3310 mg/kg (Rat)	= 1060 mg/kg (Rabbit)	= 11.4 mg/L (Rat) 4 h
64-19-7			

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available. Germ cell mutagenicityNo information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA	
AMORPHOUS SILICA	-	Group 3	-	-	
7631-86-9					

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans Not classifiable as a human carcinogen NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Target organ effects Eyes, Respiratory system, Skin, Teeth.

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (oral) 26925 mg/kg ATEmix (dermal) 15654 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

0 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical name	Partition coefficient
ACETIC ACID	-0.31
64-19-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number Not applicable

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste Status
ACETIC ACID	Toxic
64-19-7	Corrosive
	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID No 1950

Proper shipping name Aerosols, Limited Quantity (LQ)

Transport hazard class(es) 2.2 Emergency Response Guide 126

Number

<u>IATA</u>

UN number or ID number ID 8000

Proper shipping name Consumer commodity

Transport hazard class(es) 9 ERG Code 9L

IMDG

UN number or ID number 1950

Proper shipping name Aerosols, Limited Quantity (LQ)

Transport hazard class(es) 2.2 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies **DSL/NDSL** Complies **EINECS/ELINCS** Not determined **ENCS** Not determined **IECSC** Complies Complies **KECL** Complies **PICCS** Not determined AICS

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
ACETIC ACID	5000 lb	-	-	X
64-19-7				

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name Hazardous Substances RQs		CERCLA/SARA RQ	Reportable Quantity (RQ)	
	ACETIC ACID	5000 lb	-	RQ 5000 lb final RQ
	64-19-7			RQ 2270 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

The product contains are renorming respectation of chemicals	
Chemical name	California Proposition 65
AMORPHOUS SILICA	*Carcinogen
7631-86-9	

^{• *}The asterisked chemical(s) listed are not subject to Proposition 65 because they are not airborne in the finished product U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ACETIC ACID	X	X	X
64-19-7			

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

Non-controlled

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Health hazards 1 Flammability 1 Instability 0 -

HMIS Health hazards 1 Flammability 1 Physical hazards 0 Personal protection B

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

Revision Date

30-Jul-2021

Disclaimer

Illinois Tool Works Inc. believes the information contained in this data sheet is accurate as of the date compiled. However, Illinois Tool Works Inc. makes no warranty, express or implied, as to the accuracy, reliability or completeness of the information. User is responsible for evaluating whether such information or this product is fit for a particular purpose and suitable for a particular use or application. The information in this data sheet may not be valid if this product is used in combination with other products or in processes for which it was not designed. Illinois Tool Works Inc. disclaims any liability for consequential or incidental damages of any kind, including lost profits, arising from the sale or use of this product. Ensure you have the most current version of this data sheet by contacting us or reviewing our web site.

End of Safety Data Sheet