Safety Data Sheet



Revision Number: 006.0

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name:

Product type: Cyanoad Restriction of Use: None ide Company address: Henkel Electronic Materials LLC 14000 Jamboree Road Irvine, CA 92606

LOCTITE 4307 LIGHT CURING ADHESIVE known as 4307 Flashcure(R) Light Cure A Cyanoacrylate None identified rials LLC

Item number:37441Region:CanadaContact information:Telephone: +1 (888) 943-6535MEDICAL EMERGENCY Phone: Poison Control Center1-877-671-4608 (toll free) or 1-303-592-1711TRANSPORT EMERGENCY Phone: CHEMTREC1-800-424-9300 (toll free) or 1-703-527-3887Internet: www.henkel.com/electronics

487920

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW WARNING: BONDS SKIN IN SECONDS. COMBUSTIBLE LIQUID. CAUSES EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
FLAMMABLE LIQUID	4
EYE IRRITATION	2B
SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE	3

PICTOGRAM(S)	

Precautionary Statements

Prevention:	Keep away from heat, sparks, open flames, hot surfaces - no smoking. Avoid breathing vapors, mist, or spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves, eve protection, and face protection.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison control center or physician if you feel unwell. If eye irritation persists: Get medical attention. In case of fire: Use foam, dry chemical or carbon dioxide to extinguish.
Storage:	Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

IDH number: 487920

Product name: LOCTITE 4307 LIGHT CURING ADHESIVE known as 4307 Flashcure(R) Light Cure A

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Ethyl 2-cyanoacrylate	7085-85-0	60 - 100
Thickener	Proprietary	5 - 10

* Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES			
•	4. FIRST AID MEASURES		
Inhalation:	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.		
Skin contact:	Do not pull bonded skin apart. Soak in warm soapy water. Gently peel apart using a blunt instrument. If skin is burned due to the rapid generation of heat by a large drop, seek medical attention. If lips are bonded, apply warm water to the lips and encourage wetting and pressure from saliva in mouth. Peel or roll lips apart. Do not pull lips apart with direct opposing force.		
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. Get medical attention. If eyelids are bonded closed, release eyelashes with warm water by covering with a wet pad. Do not force eye open. Cyanoacrylate will bond to eye protein and will cause a lachrymatory effect which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical attention should be sought in case solid particles of polymerized cyanoacrylate trapped behind the eyelid caused abrasive damage.		
Ingestion:	Ensure breathing passages are not obstructed. The product will polymerize rapidly and bond to the mouth making it almost impossible to swallow. Saliva will separate any solidified product in several hours. Prevent the patient from swallowing any separated mass.		
Symptoms:	See Section 11.		
Notes to physician:	Surgery is not necessary to separate accidentally bonded tissues. Experience has shown that bonded tissues are best treated by passive, non-surgical first aid. If rapid curing has caused thermal burns they should be treated symptomatically after adhesive is removed.		
5.	FIRE FIGHTING MEASURES		
Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.		
Special firefighting procedures:	Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA).		
Unusual fire or explosion hazards:	None		
Hazardous combustion products:	Trace amounts of toxic and/or irritating fumes may be released and the use of		

6. ACCIDENTAL RELEASE MEASURES

breathing apparatus is recommended.

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:

Ventilate area. Do not allow product to enter sewer or waterways.

IDH number: 487920

Product name: LOCTITE 4307 LIGHT CURING ADHESIVE known as 4307 Flashcure(R) Light Cure A Page 2 of 6

Clean-up methods:

Do not use cloths for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste. Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.

7. HANDLING AND STORAGE

Handling:

Storage:

Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Avoid contact with fabric or paper goods. Contact with these materials may cause rapid polymerization which can generate smoke and strong irritating vapors, and cause thermal burns.

Keep in a cool, well ventilated area away from heat, sparks and open flame.

Keep container tightly closed until ready for use.

Shelf Life Statement: Not available.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Ethyl 2-cyanoacrylate	0.2 ppm TWA	None	None	None
Thickener	None	None	None	None
	•	•		

Engineering controls:	Use positive down-draft exhaust ventilation if general ventilation is insufficient to maintain vapor concentration below established exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.
Eye/face protection:	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists.
Skin protection:	Use nitrile gloves and aprons as necessary to prevent contact. Do not use PVC, nylon or cotton.

9. PHYSICAL AND CHEMICAL PROPERTIES

Liquid

Physical state:
Color:
Odor:
Odor threshold:
pH:
Vapor pressure:
Boiling point/range:
Melting point/ range:
Specific gravity:
Vapor density:
Flash point:
Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Evaporation rate:
Solubility in water:
Partition coefficient (n-octanol/water):
VOC content:
Viscosity:
Decomposition temperature:
Decomposition temperature.

Yellow green, to, Dark blue-green Irritating, Sharp Not available. Not applicable < 0.2 mm hg > 149 °C (> 300.2 °F) Not determined 1.0717 at 20 °F (-6.67 °C) 3 Approximately 80 - 93 °C (176°F - 199.4 °F) Tagliabue closed cup Not determined Not determined 485 °C (905°F) Not applicable Not available. Polymerises in presence of water. Not applicable < 2 %; < 20 g/l (California SCAQMD Method 316B) (Estimated) Not available. Not available.

IDH number: 487920

10. STABILITY AND REACTIVITY

Stability:	Stable under recommended storage conditions.	
Hazardous reactions:	Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.	
Hazardous decomposition products:	None	
Incompatible materials:	Water, amines, alkalis and alcohols.	
Reactivity:	Not available.	
Conditions to avoid:	Spontaneous polymerization.	
	11. TOXICOLOGICAL INFORMATION	

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	May cause respiratory tract irritation. Exposure to vapors above the established exposure limit results in respiratory irritation, which may lead to difficulty in breathing and tightness in the chest.
Skin contact:	May cause skin irritation. Bonds skin in seconds. Cyanoacrylates have been reported to cause allergic reaction but due to rapid polymerization at the skin surface, an allergic response is rare. Cyanoacrylates generate heat on solidification. In rare circumstances a large drop will burn the skin. Cured adhesive does not present a health hazard even if bonded to the skin.
Eye contact:	Irritating to eyes. Causes excessive tearing. Eyelids may bond.
Ingestion:	Not expected to be harmful by ingestion. Rapidly polymerizes (solidifies) and bonds in mouth. It is almost impossible to swallow.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Ethyl 2-cyanoacrylate	None	Irritant, Allergen, Respiratory
Thickener	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Ethyl 2-cyanoacrylate	No	No	No
Thickener	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information:

Not available.

Information provided is for unused product only. Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. 14. **TRANSPORT INFORMATION** The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration. Canada Transportation of Dangerous Goods - Ground Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None International Air Transportation (ICAO/IATA) Proper shipping name: Aviation regulated liquid, n.o.s. (Cyanoacrylate ester) Hazard class or division: 9 Identification number: UN 3334 Packing group: Ш

13. DISPOSAL CONSIDERATIONS

Primary packs containing less than 500ml are unregulated by this mode of transport and may be shipped unrestricted. Water Transportation (IMO/IMDG) Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None **15. REGULATORY INFORMATION**

shipped unrestricted.

Not more than 500 ml (each inner package) - Unrestricted, Primary packs containing less than 500ml are unregulated by this mode of transport and may be

Canada Regulatory Information

Exceptions:

Exceptions:

CEPA DSL/NDSL Status: Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Safety Data Sheet format.

Prepared by: Catherine Bimler, Regulatory Affairs Specialist

Issue date: 06/28/2016 **DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.