

TECHNICAL DATA

# Fluke BTL20ANG Intelligent Test Probe Set



## Key features

- Access to hard-to-reach battery terminals using long or short probe extensions with angled measurement tips
- Optimized handle and cable design so measurement probes won't get caught or tangled on battery terminals
- CAT II 1000V and CAT III 600V rated

## Product overview: Fluke BTL20ANG Intelligent Test Probe Set

Available with the BT520ANG and BT521ANG, or as a standalone accessory the BTL520ANG Intelligent Test Probe Set makes Fluke 500 Series Battery Analyzers the ideal test tools for maintaining, troubleshooting and performance testing individual storage batteries and battery banks used in critical battery back-up applications. With optimized tip angles and coil placement the BTL520ANG gives you the maneuverability you need to avoid obstacles and get into narrow cabinet spaces—all while offering the same CAT II 1000V and CAT III 600V you've come to expect from Fluke Battery Analyzers.

## Specifications: Fluke BTL20ANG Intelligent Test Probe Set

General Specifications	
BTL20ANG with long angled probe (overall length)	242.2 cm (95.38 in)
BTL20ANG with short angled probe (overall length)	216.8 cm (85.38 in)
Overall span (coil relaxed)	10.1 cm (4 in)
Overall maximum span (coil extended)	109.2 cm (43 in)



BTL20ANG probe tip angle	20 degrees from horizontal
--------------------------	----------------------------

## Ordering information



### **FLUKE-BTL20ANG**

Fluke BTL20ANG Intelligent Test Probe Set

---

Includes:

- BTL20ANG Intelligent Test Probe Set
-



**Fluke.** *Keeping your world up and running.®*

**Fluke Corporation**  
PO Box 9090, Everett, WA 98206 U.S.A.

**For more information call:**  
In the U.S.A. (800) 443-5853  
In Canada (800) 36-FLUKE  
From other countries +1 (425) 446-5500  
[www.fluke.com](http://www.fluke.com)

©2022 Fluke Corporation.  
Specifications subject to change without notice.  
11/2022

**Modification of this document is not permitted  
without written permission from Fluke Corporation.**