Safety Data Sheet



Revision Number: 005.0 Issue date: 09/01/2022

PRODUCT AND COMPANY IDENTIFICATION

IDH number: Product name: LOCTITE EA E-120HP known as DB

EPOXY ADH E-120HP 400 ML.

29355_209548 Product type/use: Adhesive Item number: Restriction of Use: None identified Region: United States

Company address: Henkel Corporation

One Henkel Way

Rocky Hill, Connecticut 06067

DANGER:

Contact information: Telephone: +1 (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center

702026

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

MAY CAUSE AN ALLERGIC SKIN REACTION.

HAZARD CLASS	HAZARD CATEGORY
SKIN CORROSION	1B
SERIOUS EYE DAMAGE	1
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: Avoid breathing vapors, mist, or spray. Wash affected area thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace. Wear protective

gloves, clothing, eye and face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off Response:

immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical attention. Wash

contaminated clothing before reuse.

Store locked up. Storage:

Dispose of contents and/or container according to Federal, State/Provincial and local Disposal:

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	68082-29-1	60 - 80
Amines, polyethylenepoly-, tetraethylenepentamine fraction	90640-66-7	10 - 30
3.6-diazaoctanethylenediamine	112-24-3	5 - 10

Product name: LOCTITE EA E-120HP known as DB EPOXY ADH E-120HP 400 ML. IDH number: 702026 Page 1 of 5

Amines, polyethylenepoly-, triethylenetetramine fraction	90640-67-8	1 - 5
3,6,9,12- tetraazatetradecamethylenediamine	4067-16-7	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. Get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove

contaminated clothing and footwear. Get medical attention. Wash clothing

before reuse. Thoroughly clean shoes before reuse.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get

immediate medical attention.

Ingestion: DO NOT induce vomiting unless directed to do so by medical personnel.

Rinse the mouth. Drink 1-2 glasses of water. Never give anything by mouth to

an unconscious person. Get immediate medical attention.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Dry chemical. Carbon dioxide. Alcohol foam.

Special firefighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as

turn-out gear.

Unusual fire or explosion hazards: Personnel in vicinity and downwind should be evacuated. Burning produces

obnoxious and toxic fumes. In case of fire, keep containers cool with water spray. Closed containers may rupture (due to build up of pressure) when

exposed to extreme heat.

Hazardous combustion products: Ammonia. Oxides of carbon. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:Do not allow product to enter sewer or waterways.

Clean-up methods: Ensure adequate ventilation. Wear appropriate personal protective equipment.

Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Scrape up spilled material and place in a closed

container for disposal.

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling. Use only with adequate ventilation. Keep

container closed.

Storage: For safe storage, store between 0 °C (32°F) and 32 °C (89.6 °F)

Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials. Keep away from heat, spark and flame. Protect from

direct sunlight. Avoid moisture.

IDH number: 702026 Product name: LOCTITE EA E-120HP known as DB EPOXY ADH E-120HP 400 ML.
Page 2 of 5

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	None	None	None
Amines, polyethylenepoly-, tetraethylenepentamine fraction	None	None	None	None
3,6-diazaoctanethylenediamine	None	None	1 ppm (6 mg/m3) TWA (SKIN)	None
Amines, polyethylenepoly-, triethylenetetramine fraction	None	None	None	None
3,6,9,12- tetraazatetradecamethylenediamine	None	None	None	None

Engineering controls: Use local ventilation if general ventilation is insufficient to maintain vapor

concentration below established exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection: Use chemical resistant, impermeable clothing including gloves and either an

apron or body suit to prevent skin contact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:LiquidColor:AmberOdor:SlightOdor threshold:Not available.pH:Not available.Vapor pressure:Not available.

Boiling point/range: > 93 °C (> 199.4 °F)1,013 hPa

Melting point/ range:Not available.Specific gravity:0.9 - 1.1Vapor density:Not available.

Flash point: > 93 °C (> 199.4 °F); Estimated

Flammable/Explosive limits - lower:
Flammable/Explosive limits - upper:
Autoignition temperature:
Flammability:
Flammability:
Evaporation rate:
Solubility in water:
Partially miscible
Partition coefficient (n-octanol/water):
Not available.
Not available.
Not available.

VOC content: < 1.0 %; < 10 g/l Estimated

Viscosity:Not available.Decomposition temperature:Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Ammonia. Oxides of carbon. Oxides of nitrogen.

Incompatible materials: Strong oxidizing agents. Acids.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials. Exposure to water vapour.

Exposure to sunlight.

IDH number: 702026 Product name: LOCTITE EA E-120HP known as DB EPOXY ADH E-120HP 400 ML.
Page 3 of 5

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Mists, vapors or liquid may cause severe irritation or burns. Skin contact: Causes skin burns. May cause allergic skin reaction.

Eye contact: Causes serious eye damage.

Ingestion: If ingested, severe burns of the mouth and throat may occur, as well as perforation of the

esophagus and the stomach.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	None	No Records	
Amines, polyethylenepoly-, tetraethylenepentamine fraction	None	No Data	
3,6-diazaoctanethylenediamine	None	Allergen, Corrosive, Developmental, Irritant, Mutagen	
Amines, polyethylenepoly-, triethylenetetramine fraction	None	No Data	
3,6,9,12- tetraazatetradecamethylenediamine	None	Irritant, Allergen	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
C18 Fatty acid dimer, tall oil fatty acid, triethylenetetramine polymer	No	No	No
Amines, polyethylenepoly-, tetraethylenepentamine fraction	No	No	No
3,6-diazaoctanethylenediamine	No	No	No
Amines, polyethylenepoly-, triethylenetetramine fraction	No	No	No
3,6,9,12- tetraazatetradecamethylenediamine	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Tetraethylene pentamine, Triethylenetetramine,

dimer fatty acid(C18)poly amido amine resin)

Hazard class or division: 8

Identification number: UN 2735
Packing group: III

International Air Transportation (ICAO/IATA)

Proper shipping name: Amines, liquid, corrosive, n.o.s. (Tetraethylene pentamine, Triethylenetetramine)

Hazard class or division:

Identification number: UN 2735
Packing group:

IDH number: 702026 Product name: LOCTITE EA E-120HP known as DB EPOXY ADH E-120HP 400 ML.

Page 4 of 5

Water Transportation (IMO/IMDG)

Proper shipping name: AMINES, LIQUID, CORROSIVE, N.O.S. (Tetraethylene pentamine, Triethylenetetramine, dimer fatty acid(C18)poly amido amine resin)

Hazard class or division: Identification number: UN 2735

Packing group: Ш

Marine pollutant: dimer fatty acid(C18)poly amido amine resin

REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

IDH number: 702026

CEPA DSL/NDSL Status: All components are listed on or are exempt from listing on the Canadian Domestic

Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,13,14,15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 09/01/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.