

**3M General Offices** 3M Center St. Paul, MN 55144-1000 1-800-364-3577 or (651) 737-6501 (24 hours)

## Safety Data Sheet

Purchase Order #: Customer Number: 163167 0016124695 2024-01-18 21:33:56.797

SDS Coordinator HISCO CONCORD PARK DR 6650 HOUSTON, TX 77040-4098 USA

Dear SDS Coordinator

Enclosed is the Safety Data Sheet (SDS)\* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at www.3m.com/MSDSSearch.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

# If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at emsdsadmin@mmm.com

\*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



### **Safety Data Sheet**

### Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group:	34-6375-9	Version Number:	3.01
Issue Date:	08/07/23	Supercedes Date:	07/21/21

### **SECTION 1: Identification**

**1.1. Product identifier** 3M<sup>TM</sup> Novec<sup>TM</sup> Flux Remover

r rouuct identification Number	Product	Identification	Numbers
--------------------------------	---------	----------------	---------

ID Number	UPC	ID Number	UPC
98-0212-4891-3	0 00 51138 99268 2	98-0212-4892-1	0 00 51138 99269 9

7010352611, 7100067836

### 1.2. Recommended use and restrictions on use

Recommended use Flux Remover Restrictions on use

For Industrial Use only. Not intended for consumer sale or use. Not intended for use as a medical device or drug.

1.3. Supplier's details MANUFACTURER: DIVISION: ADDRESS: Telephone:

3M Electronics Materials Solutions Division 3M Center, St. Paul, MN 55144-1000, USA 1-888-3M HELPS (1-888-364-3577)

**1.4. Emergency telephone number** 

1-800-364-3577 or (651) 737-6501 (24 hours)

### **SECTION 2: Hazard identification**

### 2.1. Hazard classification

Gas Under Pressure: Liquefied gas. Serious Eye Damage/Irritation: Category 2A. Specific Target Organ Toxicity (single exposure): Category 3.

**2.2. Label elements Signal word** Warning

Symbols

Gas cylinder | Exclamation mark |

Pictograms



Hazard Statements Contains gas under pressure; may explode if heated.

Causes serious eye irritation. May cause drowsiness or dizziness.

#### **Precautionary Statements**

#### **Prevention:**

Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wear eye/face protection. Wash thoroughly after handling.

### **Response:**

IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage:** 

Protect from sunlight. Store in a well-ventilated place. Store locked up.

#### **Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

#### **Supplemental Information:**

Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.

### **SECTION 3: Composition/information on ingredients**

Ingredient	C.A.S. No.	% by Wt
1,2-Trans-Dichloroethylene	156-60-5	55 - 70 Trade Secret *
Methyl nonafluoroisobutyl ether	163702-08-7	19.8 - 32.4
Methyl nonafluorobutyl ether	163702-07-6	3.6 - 16.2
Carbon Dioxide	124-38-9	1 - 5
Isopropanol	67-63-0	<= 3

\*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

#### Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

#### Skin Contact:

Wash with soap and water. If you feel unwell, get medical attention.

#### Eye Contact:

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

#### If Swallowed:

Rinse mouth. If you feel unwell, get medical attention.

#### 4.2. Most important symptoms and effects, both acute and delayed

Central nervous system depression (headache, dizziness, drowsiness, incoordination, nausea, slurred speech, giddiness, and unconsciousness).

#### 4.3. Indication of any immediate medical attention and special treatment required

Not applicable

### **SECTION 5: Fire-fighting measures**

### 5.1. Suitable extinguishing media

Use a fire fighting agent suitable for the surrounding fire.

### 5.2. Special hazards arising from the substance or mixture

Closed containers exposed to heat from fire may build pressure and explode.

### 5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

### **SECTION 6: Accidental release measures**

### 6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

If possible, seal leaking container. Place leaking containers in a well-ventilated area, preferably an operating exhaust hood, or if necessary outdoors on an impermeable surface until appropriate packaging for the leaking container or its contents is available. Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorized person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and SDS. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

### **SECTION 7: Handling and storage**

### 7.1. Precautions for safe handling

Do not breathe thermal decomposition products. Store work clothes separately from other clothing, food and tobacco products. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid contact with oxidizing agents (eg. chlorine, chromic acid etc.) No smoking: Smoking while using this product can result in contamination of the tobacco and/or smoke and lead to the formation of hazardous decomposition products.

### 7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store away from heat. Store away from strong bases. Store away from oxidizing agents.

### **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters

### **Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	<b>Additional Comments</b>
Carbon Dioxide	124-38-9	ACGIH	TWA:5000 ppm;STEL:30000	
			ppm	
Carbon Dioxide	124-38-9	OSHA	TWA:9000 mg/m3(5000 ppm)	
1,2-Trans-Dichloroethylene	156-60-5	ACGIH	TWA:200 ppm	
Methyl nonafluorobutyl ether	163702-07-	AIHA	TWA:750 ppm	
	6			
Methyl nonafluoroisobutyl ether	163702-08-	AIHA	TWA:750 ppm	
	7			
Isopropanol	67-63-0	ACGIH	TWA:200 ppm;STEL:400 ppm	A4: Not class. as human
				carcin
Isopropanol	67-63-0	OSHA	TWA:980 mg/m3(400 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

### 8.2.2. Personal protective equipment (PPE)

#### **Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended: Full Face Shield Indirect Vented Goggles

#### Skin/hand protection

No chemical protective gloves are required.

### **Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

Organic vapor respirators may have short service life.

For questions about suitability for a specific application, consult with your respirator manufacturer.

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid
Color	Colorless
Specific Physical Form:	Aerosol
Odor	Slight Odor
Odor threshold	No Data Available
рН	No Data Available
Melting point	Not Applicable
Boiling Point	42.5 °C
Flash Point	No flash point
Evaporation rate	No Data Available
Flammability (solid, gas)	Not Applicable
Flammable Limits(LEL)	5.9 % volume
Flammable Limits(UEL)	14.5 % volume
Vapor Pressure	310.7 mmHg
Vapor Density	2.3 [ <i>Ref Std</i> :AIR=1]
Density	1.3 g/ml
Specific Gravity	1.3 [ <i>Ref Std</i> :WATER=1]
Solubility In Water	28 ppm
Solubility- non-water	No Data Available
Partition coefficient: n-octanol/ water	No Data Available
Autoignition temperature	408 °C
Decomposition temperature	No Data Available
Viscosity	0.0004 Pa-s
Molecular weight	Not Applicable
Percent volatile	No Data Available

### **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

Heat

### **10.5. Incompatible materials**

Strong bases Strong oxidizing agents

### 10.6. Hazardous decomposition products

<u>Substance</u> Hydrogen Chloride Hydrogen Fluoride Perfluoroisobutylene (PFIB) <u>Condition</u> At Elevated Temperatures At Elevated Temperatures At Elevated Temperatures

If the product is exposed to extreme condition of heat from misuse or equipment failure, toxic decomposition products that include hydrogen fluoride and perfluoroisobutylene can occur.

### **SECTION 11: Toxicological information**

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

### Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May cause additional health effects (see below).

#### Skin Contact:

Contact with the skin during product use is not expected to result in significant irritation.

#### **Eye Contact:**

Severe Eye Irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

#### **Ingestion:**

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May cause additional health effects (see below).

#### **Additional Health Effects:**

#### Single exposure may cause target organ effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

#### **Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

### **Acute Toxicity**

Name	Route	Species	Value
Overall product	Inhalation- Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
1,2-Trans-Dichloroethylene	Dermal	Rabbit	LD50 > 5,000 mg/kg
1,2-Trans-Dichloroethylene	Inhalation- Vapor (4 hours)	Rat	LC50 95.6 mg/l
1,2-Trans-Dichloroethylene	Ingestion	Rat	LD50 7,902 mg/kg
Methyl nonafluoroisobutyl ether	Dermal		LD50 estimated to be $>$ 5,000 mg/kg
Methyl nonafluoroisobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Methyl nonafluoroisobutyl ether	Ingestion	Rat	LD50 > 5,000 mg/kg
Methyl nonafluorobutyl ether	Dermal		LD50 estimated to be $> 5,000 \text{ mg/kg}$
Methyl nonafluorobutyl ether	Inhalation- Vapor (4 hours)	Rat	LC50 > 1,000 mg/l
Methyl nonafluorobutyl ether	Ingestion	Rat	LD50 > 5,000 mg/kg
Carbon Dioxide	Inhalation- Gas (4 hours)	Rat	LC50 > 53,000 ppm
Isopropanol	Dermal	Rabbit	LD50 12,870 mg/kg
Isopropanol	Inhalation- Vapor (4 hours)	Rat	LC50 72.6 mg/l
Isopropanol	Ingestion	Rat	LD50 4,710 mg/kg

ATE = acute toxicity estimate

### Skin Corrosion/Irritation

Name	Species	Value
1,2-Trans-Dichloroethylene	Rabbit	Minimal irritation
Methyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Methyl nonafluorobutyl ether	Rabbit	No significant irritation
Isopropanol	Multiple	No significant irritation
	animal	
	species	

### Serious Eye Damage/Irritation

Name	Species	Value
1,2-Trans-Dichloroethylene	Rabbit	Moderate irritant
Methyl nonafluoroisobutyl ether	Rabbit	No significant irritation
Methyl nonafluorobutyl ether	Rabbit	No significant irritation
Isopropanol	Rabbit	Severe irritant

#### **Skin Sensitization**

Name	Species	Value
Methyl nonafluoroisobutyl ether	Guinea	Not classified
	pig	
Methyl nonafluorobutyl ether	Guinea	Not classified
	pig	
Isopropanol	Guinea	Not classified
	pig	

### **Respiratory Sensitization**

For the component/components, either no data are currently available or the data are not sufficient for classification.

### Germ Cell Mutagenicity

Name	Route	Value
1,2-Trans-Dichloroethylene	In Vitro	Not mutagenic
1,2-Trans-Dichloroethylene	In vivo	Not mutagenic
Methyl nonafluoroisobutyl ether	In Vitro	Not mutagenic
Methyl nonafluoroisobutyl ether	In vivo	Not mutagenic
Methyl nonafluorobutyl ether	In Vitro	Not mutagenic
Methyl nonafluorobutyl ether	In vivo	Not mutagenic
Isopropanol	In Vitro	Not mutagenic
Isopropanol	In vivo	Not mutagenic

### Carcinogenicity

Name	Route	Species	Value
Isopropanol	Inhalation	Rat	Some positive data exist, but the data are not
			sufficient for classification

### **Reproductive Toxicity**

### **Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test Result	Exposure Duration
1,2-Trans-Dichloroethylene	Inhalation	Not classified for development	Rat	NOAEL 24 mg/l	during organogenesi s
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluoroisobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Methyl nonafluorobutyl ether	Inhalation	Not classified for female reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluorobutyl ether	Inhalation	Not classified for male reproduction	Rat	NOAEL 129 mg/l	1 generation
Methyl nonafluorobutyl ether	Inhalation	Not classified for development	Rat	NOAEL 307 mg/l	during gestation
Carbon Dioxide	Inhalation	Not classified for male reproduction	Mouse	LOAEL 350,000 ppm	not available
Carbon Dioxide	Inhalation	Not classified for development	Rat	LOAEL 60,000 ppm	24 hours
Isopropanol	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	2 generation
Isopropanol	Ingestion	Not classified for male reproduction	Rat	NOAEL 500 mg/kg/day	2 generation
Isopropanol	Ingestion	Not classified for development	Rat	NOAEL 400 mg/kg/day	during organogenesi s
Isopropanol	Inhalation	Not classified for development	Rat	LOAEL 9 mg/l	during gestation

### Target Organ(s)

### Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1,2-Trans-Dichloroethylene	Inhalation	central nervous system depression	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
1,2-Trans-Dichloroethylene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
1,2-Trans-Dichloroethylene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	LOAEL 4,500 mg/kg	not applicable
Methyl nonafluoroisobutyl	Inhalation	nervous system	Not classified	Dog	LOAEL 913	10 minutes

ether					mg/l	
Methyl nonafluoroisobutyl	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913	10 minutes
ether					mg/l	
Methyl nonafluorobutyl	Inhalation	nervous system	Not classified	Dog	LOAEL 913	10 minutes
ether					mg/l	
Methyl nonafluorobutyl	Inhalation	cardiac sensitization	Not classified	Dog	NOAEL 913	10 minutes
ether					mg/l	
Isopropanol	Inhalation	central nervous	May cause drowsiness or	Human	NOAEL Not	
		system depression	dizziness		available	
Isopropanol	Inhalation	respiratory irritation	Some positive data exist, but the	Human	NOAEL Not	
			data are not sufficient for		available	
			classification			
Isopropanol	Inhalation	auditory system	Not classified	Guinea	NOAEL 13.4	24 hours
				pig	mg/l	
Isopropanol	Ingestion	central nervous	May cause drowsiness or	Human	NOAEL Not	poisoning
		system depression	dizziness		available	and/or abuse

### Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
1,2-Trans- Dichloroethylene	Inhalation	endocrine system   liver   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 16 mg/l	90 days
1,2-Trans- Dichloroethylene	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
1,2-Trans- Dichloroethylene	Ingestion	blood   liver	Not classified	Rat	NOAEL 125 mg/kg/day	14 weeks
1,2-Trans- Dichloroethylene	Ingestion	heart   immune system   respiratory system	Not classified	Rat	NOAEL 2,000 mg/kg/day	14 weeks
Methyl nonafluoroisobutyl ether	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluoroisobutyl ether	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Methyl nonafluoroisobutyl ether	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluoroisobutyl ether	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Methyl nonafluorobutyl ether	Inhalation	liver	Not classified	Rat	NOAEL 155 mg/l	13 weeks
Methyl nonafluorobutyl ether	Inhalation	bone, teeth, nails, and/or hair	Not classified	Rat	NOAEL 129 mg/l	11 weeks
Methyl nonafluorobutyl ether	Inhalation	heart   skin   endocrine system   gastrointestinal tract   hematopoietic system   immune system   muscles   nervous system   eyes   kidney and/or	Not classified	Rat	NOAEL 155 mg/l	13 weeks

		bladder   respiratory				
Methyl nonafluorobutyl ether	Ingestion	endocrine system   liver   heart   hematopoietic system   immune system   nervous system   eyes   kidney and/or bladder   respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Carbon Dioxide	Inhalation	heart   bone, teeth, nails, and/or hair   liver   nervous system   kidney and/or bladder   respiratory system	Not classified	Rat	LOAEL 60,000 ppm	166 days
Isopropanol	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 12.3 mg/l	24 months
Isopropanol	Inhalation	nervous system	Not classified	Rat	NOAEL 12 mg/l	13 weeks
Isopropanol	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 400 mg/kg/day	12 weeks

### **Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

### **SECTION 12: Ecological information**

#### **Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

### Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

### **SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Facility must be capable of handling aerosol cans. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

### EPA Hazardous Waste Number (RCRA): Not regulated

### **SECTION 14: Transport Information**

For Transport Information, please visit http://3M.com/Transportinfo or call 1-800-364-3577 or 651-737-6501.

### **SECTION 15: Regulatory information**

### **15.1. US Federal Regulations**

Contact 3M for more information.

### EPCRA 311/312 Hazard Classifications:

### Physical Hazards

Gas under pressure

### Health Hazards

Serious eye damage or eye irritation	
Specific target organ toxicity (single or repeated exposure)	

### This material contains a chemical which requires export notification under TSCA Section 12[b]:

Ingredient (Category if applicable)	<u>C.A.S. No</u>	Regulation	<u>Status</u>
1,2-Trans-Dichloroethylene	156-60-5	Toxic Substances Control Act (TSCA) 4	Applicable
		Test Rule Chemicals	

### **15.2. State Regulations**

Contact 3M for more information.

### **15.3.** Chemical Inventories

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

Contact 3M for more information.

### **15.4. International Regulations**

Contact 3M for more information.

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

### **SECTION 16: Other information**

### NFPA Hazard Classification

Health: 3 Flammability: 1 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

The NFPA Health code of 3 is due to emergency situations where the material may thermally decompose and release Hydrogen Fluoride and Perfluoroisobutylene (PFIB). During normal use conditions, please reference Section 2 and Section 11 of the SDS for additional health hazard information.

#### **HMIS Hazard Classification**

Health: 2 Flammability: 1 Physical Hazard: 0 Personal Protection: X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use

and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group:	34-6375-9	Version Number:	3.01
Issue Date:	08/07/23	Supercedes Date:	07/21/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

### 3M USA SDSs are available at www.3M.com