

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 1. IDENTIFICATION

Product name : EASYPOXY® K-45 Part A Resin

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone : INFOTRAC - 1-800-535-5053
number

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.
Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin irritation : Category 2

Eye irritation : Category 2A

Skin sensitisation : Category 1

Specific target organ toxicity : Category 3 (Respiratory system)
- single exposure

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
Storage:
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P405 Store locked up.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified epoxy resin

Hazardous components

| Component | CAS-No. | Concentration (%) |
|----------------------|-------------|-------------------|
| Epoxy Resin | 25068-38-6 | >= 80 - < 100 |
| Amorphous silica gel | 112945-52-5 | >= 1 - < 5 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

- If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Provide sufficient air exchange and/or exhaust in work rooms.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
The chemical reaction that cures mixed epoxy is exothermic (heat generating). If left to cure in a contained mass, such as in a mixing vessel, it can generate enough heat to melt plastic, burn skin or ignite surrounding combustible materials. The larger or thicker the epoxy mass, the more heat generated.
- Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------|-------------|----------------------------------|---|-----------|
| Amorphous silica gel | 112945-52-5 | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |
| Amorphous silica gel | | TWA (Dust) | 80 mg/m ³ / %SiO ₂ (Silica) | OSHA Z-3 |
| Amorphous silica gel | | TWA | 6 mg/m ³ (Silica) | NIOSH REL |

Hazardous components without workplace control parameters

- Engineering measures** : Use with adequate ventilation.
All application areas should be ventilated in accordance with applicable OSHA regulations. (e.g. 29 CFR 1910.94)

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.

Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.

Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.

Repeated inhalation of such dust may cause lung injury.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Vapour pressure : No data available

Flash point : > 201 °F (> 94 °C)
Method: No information available.
Information taken from reference works and the literature.

Upper explosion limit : No data available

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

| | |
|--|--|
| Lower explosion limit | : No data available |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Relative vapour density | : No data available |
| Relative Density/Specific Gravity | : No data available |
| Density | : 1.1599 g/cm ³ (77 °F (25 °C)) |
| Solubility(ies) | |
| Water solubility | : No data available |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature | : No data available |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : > 21 mm ² /s (104 °F (40 °C)) |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|--|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. |
| Conditions to avoid | : No data available |
| Hazardous decomposition products | : The by-products expected in incomplete pyrolysis or combustion of epoxy resins are mainly phenolics, CO and water. |

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : 2,617 mg/kg
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : 2,617 mg/kg
Method: Calculation method

Components:**25068-38-6 Epoxy Resin:**

Acute oral toxicity : LD50 (Rat): 11,400 mg/kg
LD50 (Rat, female): > 2,000 mg/kg
Method: OECD Test Guideline 420
GLP: yes

Acute inhalation toxicity : LC50 : Remarks: No data available

Acute dermal toxicity : LD50 (Rabbit): 23,400 mg/kg
LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
GLP: yes

112945-52-5 Amorphous silica gel:

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.1390 mg/l

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation and/or dermatitis.

Components:**25068-38-6 Epoxy Resin:**

Species: Rabbit
Result: Moderate skin irritation

Species: Rabbit
Exposure time: 4 h
Method: OECD Test Guideline 404
Result: Skin irritation

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

GLP: yes

112945-52-5 Amorphous silica gel:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: Causes serious eye irritation.

Components:**25068-38-6 Epoxy Resin:**

Species: Rabbit

Result: Eye irritation

112945-52-5 Amorphous silica gel:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

Components:**25068-38-6 Epoxy Resin:**

Test Type: Mouse Local Lymph Node assay (LLNA)

Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

GLP: yes

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

Aspiration toxicity**Components:****25068-38-6 Epoxy Resin:**

No aspiration toxicity classification

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological
information

: No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

: WC: SA

EPA Hazardous Waste
Code(s)

: none

Waste from residues

: Do not dispose of waste into sewer.

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Catalyzed resin can generate hazardous exothermic heat if allowed to polymerize in a mass. All soiled or waste materials must be water soaked, and kept in a closed bin until disposed of.
Dispose of the solid mass only if cure is complete and the mass has cooled. Follow federal, state or local disposal regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International Regulations****IATA-DGR**

UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**49 CFR**

UN/ID/NA number : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(Epoxy resin)
Class : 9

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

| | |
|------------------|---|
| Packing group | : III |
| Labels | : CLASS 9 |
| ERG Code | : 171 |
| Marine pollutant | : yes (Epoxy resin) |
| Remarks | : IMDG: Marine pollutants packaged in single or combination packagings containing a net quantity per single or inner packaging of 5 l or less for liquids or having a net mass per single or inner packaging of 5 kg or less for solids are not subject to any other provisions of this Code relevant to marine pollutants provided the packagings meet the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8. In the case of marine pollutants also meeting the criteria for inclusion in another hazard class all provisions of this Code relevant to any additional hazards continue to apply. |

SECTION 15. REGULATORY INFORMATION**EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards : Per the June 13, 2016 Federal Register notice, EPA harmonized the EPCRA 311/312 hazard categories with the 2012 OSHA hazard communication standard for classifying and labeling of chemicals (i.e. GHS). Please refer to Section 2 of the SDS to identify the appropriate hazard categories for reporting purposes.

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt) : Refer to the product technical data sheet for VOC information.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

New Jersey Trade Secret Registry Number for the product (NJ TSRN) : Not Applicable

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.


The components of this product are reported in the following inventories:

TSCA : All components of this product are listed active and/or are exempt

Section 4 / 12(b) : Not applicable

Section 5a : Not applicable

Section 6 : Not applicable

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

| | |
|------------------------|----------|
| HEALTH | 2 |
| FLAMMABILITY | 1 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 =Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

EASYPOXY® K-45 Part A Resin

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

Revision Date : 01/17/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 1. IDENTIFICATION

Product name : EASYPOXY® K-45 Part B Hardener

Manufacturer or supplier's details

Company : ELANTAS PDG, INC.
5200 North 2nd Street
St. Louis MO 63147

Telephone : (314) 621-5700

Visit our web site : www.elantas.com

E-mail address : Todd.Thomas@altana.com

Emergency telephone : INFOTRAC - 1-800-535-5053
number

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive

Restrictions on use : This product is for industrial use only. It is not intended for consumer use or retail sale.
Refer to Section 15 for any restrictions that may apply

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Skin corrosion : Category 1C

Serious eye damage : Category 1

Skin sensitisation : Category 1

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

Response:

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P363 Wash contaminated clothing before reuse.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Modified Mercaptan Polymer

Hazardous components

| Component | CAS-No. | Concentration (%) |
|-----------------------------------|-------------|-------------------|
| Mercaptan Terminated Curing Agent | 72244-98-5 | >= 80 - < 100 |
| Amorphous silica gel | 112945-52-5 | >= 5 - < 10 |
| Mannich base | 90-72-2 | >= 5 - < 10 |

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.

In case of skin contact : Immediate medical treatment is necessary as untreated

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

- wounds from corrosion of the skin heal slowly and with difficulty.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Small amounts splashed into eyes can cause irreversible tissue damage and blindness.
In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
Continue rinsing eyes during transport to hospital.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do NOT induce vomiting.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
To avoid spills during handling keep bottle on a metal tray.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Store under conditions specified on the product Technical Data Sheet to maintain product quality.
Keep container tightly closed in a dry and well-ventilated place.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Components with workplace control parameters**

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|----------------------|-------------|----------------------------------|---|-----------|
| Amorphous silica gel | 112945-52-5 | TWA (Dust) | 20 Million particles per cubic foot (Silica) | OSHA Z-3 |
| Amorphous silica gel | | TWA (Dust) | 80 mg/m ³ / %SiO ₂ (Silica) | OSHA Z-3 |
| Amorphous silica gel | | TWA | 6 mg/m ³ (Silica) | NIOSH REL |

Hazardous components without workplace control parameters

Engineering measures : Use with adequate ventilation.
All application areas should be ventilated in accordance with

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

applicable OSHA regulations. (e.g. 29 CFR 1910.94)
This product contains a particulate(s) that is considered hazardous per OSHA (29 CFR 1910.1200) and is listed in Section III as a precautionary warning.
Under normal conditions of use, this product as supplied does not pose a health risk from particulate matter.
Physical degradation of the cured product (i.e. sanding, abrading, etc.) may pose a dust hazard.
Repeated inhalation of such dust may cause lung injury.

Personal protective equipment

- Respiratory protection : Respiratory protection may be required if material is used in poorly ventilated areas or if material is sprayed or heated.
- Hand protection
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.
- Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Appearance : liquid
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Initial boiling point and boiling range : No data available
- Vapour pressure : No data available
- Flash point : > 201 °F (> 94 °C)
Method: No information available.
Information taken from reference works and the literature.

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

| | |
|--|--|
| Upper explosion limit | : No data available |
| Lower explosion limit | : No data available |
| Evaporation rate | : No data available |
| Flammability (solid, gas) | : No data available |
| Relative vapour density | : No data available |
| Relative Density/Specific Gravity | : No data available |
| Density | : 1.1899 g/cm ³ (77 °F (25 °C)) |
| Solubility(ies) | |
| Water solubility | : No data available |
| Solubility in other solvents | : No data available |
| Partition coefficient: n-octanol/water | : No data available |
| Ignition temperature | : No data available |
| Thermal decomposition | : No data available |
| Viscosity | |
| Viscosity, dynamic | : No data available |
| Viscosity, kinematic | : > 21 mm ² /s (104 °F (40 °C)) |

SECTION 10. STABILITY AND REACTIVITY

| | |
|------------------------------------|---|
| Reactivity | : No decomposition if stored and applied as directed. |
| Chemical stability | : No decomposition if stored and applied as directed. |
| Possibility of hazardous reactions | : No decomposition if stored and applied as directed. |
| Conditions to avoid | : No data available |
| Hazardous decomposition products | : Carbon monoxide in a fire. Nitrogen oxides in a fire. Ammonia |

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure****Acute toxicity****Product:**

Acute oral toxicity : Acute toxicity estimate : > 5,000 mg/kg
Method: Calculation method

Components:**112945-52-5 Amorphous silica gel:**

Acute oral toxicity : LD50 (Rat): > 10,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 0.1390 mg/l

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: Extremely corrosive and destructive to tissue.

Components:**112945-52-5 Amorphous silica gel:**

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

GLP: yes

Serious eye damage/eye irritation**Product:**

Remarks: May cause irreversible eye damage.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:**112945-52-5 Amorphous silica gel:**

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

GLP: yes

Respiratory or skin sensitisation**Product:**

Remarks: Causes sensitisation.

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

Carcinogenicity**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Further information**Product:**

Remarks: No data available

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: No data available

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

: WC: SD

EPA Hazardous Waste
Code(s)

: none

Waste from residues

: Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Send to a licensed waste management company.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.**SECTION 14. TRANSPORT INFORMATION****International Regulations****Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

National Regulations**SECTION 15. REGULATORY INFORMATION****EPCRA - Emergency Planning and Community Right-to-Know Act****US. EPA CERCLA Hazardous Substances (40 CFR 302)**

This material does not contain any components with a CERCLA RQ.

SARA 304 - Emergency Release Notification

This material does not contain any components with a section 304 EHS RQ.

**US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III
Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)**

This material does not contain any components with a SARA 302 RQ.

SARA 311/312 Hazards: Per the June 13, 2016 Federal Register notice, EPA
harmonized the EPCRA 311/312 hazard categories with the
2012 OSHA hazard communication standard for classifying
and labeling of chemicals (i.e. GHS). Please refer to Section 2
of the SDS to identify the appropriate hazard categories for
reporting purposes.

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SARA 302

: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

Non-volatile (Wt)

: Refer to the product technical data sheet for VOC information.

Massachusetts Right To Know

No components are subject to the Massachusetts Right to Know Act.

New Jersey Trade Secret Registry Number for the product (NJ TSRN)

: Not Applicable

California Prop. 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

The components of this product are reported in the following inventories:

TSCA

: All components of this product are listed active and/or are exempt

Section 4 / 12(b)

: Not applicable

Section 5a

: Not applicable

Section 6


: Not applicable

EASYPOXY® K-45 Part B Hardener

Version 1

Revision Date 01/17/2024

Print Date 01/17/2024

SECTION 16. OTHER INFORMATION**Further information****NFPA:****HMIS III:**

| | |
|------------------------|----------|
| HEALTH | 3 |
| FLAMMABILITY | 1 |
| PHYSICAL HAZARD | 0 |

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

Revision Date : 01/17/2024

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.