



3M General Offices
3M Center
St. Paul, MN 55144-1000
1-800-364-3577 or (651) 737-6501 (24 hours)

Safety Data Sheet

2024-05-02 21:45:22.97

Purchase Order #: 185854
Customer Number: 0016124695

SDS Coordinator
HISCO
CONCORD PARK DR 6650
HOUSTON, TX 77040-4098
USA

Dear SDS Coordinator

Enclosed is the Safety Data Sheet (SDS)* for the product that your company recently purchased from 3M.

Please forward the attached document(s) to the individual in your organization responsible for hazard communication.

If you are a distributor and resell this product, OSHA and EPA require that you transmit this SDS information to your customers at the time of first shipment or whenever you receive revised SDSs from 3M.

3M SDSs are available over the Internet at www.3m.com/MSDSSearch.

3M is committed to meeting our customer requirements. Please contact your 3M customer service or sales representative if you have any questions. If you do not know whom to contact, please call the 3M Product Information Center at 1-800-364-3577.

If you are not currently receiving 3M SDSs by e-mail and would like to do so, please contact our eSDS Administrator at emsdsadmin@mmm.com

*An Article Information Sheet (AIS) or Article Information Letter (AIL) may be enclosed in place of an SDS if the product is an article which does not require an SDS under the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.



Safety Data Sheet

Copyright, 2023, 3M Company.

All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document Group: 19-7627-3
Issue Date: 12/15/23

Version Number: 11.03
Supersedes Date: 06/11/21

SECTION 1: Identification

1.1. Product identifier

Sharpshooter™ Extra Strength No Rinse Mark Remover

Product Identification Numbers

ID Number	UPC	ID Number	UPC
LN-DCCX-224B-0		70-0712-8531-9	500-48011-16861-1
70-0712-8533-5	500-48011-19344-6		
7010384720, 7000029810			

1.2. Recommended use and restrictions on use

Recommended use

Light duty graffiti remover for washable hard surfaces, Hard Surface Cleaner

1.3. Supplier's details

MANUFACTURER: 3M
DIVISION: Commercial Solutions Division
ADDRESS: 3M Center, St. Paul, MN 55144-1000, USA
Telephone: 1-888-3M HELPS (1-888-364-3577)

1.4. Emergency telephone number

1-800-364-3577 or (651) 737-6501 (24 hours)

SECTION 2: Hazard identification

2.1. Hazard classification

Serious Eye Damage/Irritation: Category 1.

Skin Corrosion/Irritation: Category 1B.

2.2. Label elements

Signal word

Danger

Symbols

Corrosion |

Pictograms

**Hazard Statements**

Causes severe skin burns and eye damage.

Precautionary Statements**General:**

Keep out of reach of children.

Prevention:

Do not breathe dust/fume/gas/mist/vapors/spray.

Wear protective gloves, protective clothing, and eye/face protection.

Wash thoroughly after handling.

Response:

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER or doctor/physician.

Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Storage:

Keep cool.

Keep container tightly closed.

Store locked up in a well-ventilated place.

Disposal:

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

2.3. Hazards not otherwise classified

May cause chemical gastrointestinal burns.

1% of the mixture consists of ingredients of unknown acute inhalation toxicity.

SECTION 3: Composition/information on ingredients

Ingredient	C.A.S. No.	% by Wt
WATER	7732-18-5	80 - 95 Trade Secret *
2-BUTOXYETHANOL	111-76-2	3 - 6 Trade Secret *
ETHANOLAMINE	141-43-5	1 - 5 Trade Secret *
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	84133-50-6	0.5 - 1.5 Trade Secret *
ALCOHOLS, C6-12 ETHOXYLATED	68439-45-2	0.5 - 1.5 Trade Secret *
Potassium Hydroxide	1310-58-3	< 1 Trade Secret *
POLY(OXY-1,2-ETHANEDIYL), .ALPHA.-HYDRO-.OMEGA.-HYDROXY-,MONO-c10-14-ALKYL ETHERS, PHOSPHATES	68585-36-4	< 0.5 Trade Secret *
TETRASODIUM	64-02-8	< 0.5 Trade Secret *

ETHYLENEDIAMINETETRAACETATE

*The specific chemical identity and/or exact percentage (concentration) of this composition has been withheld as a trade secret.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Remove person to fresh air. If you feel unwell, get medical attention.

Skin Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye Contact:

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

If Swallowed:

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No critical symptoms or effects. See Section 11.1, information on toxicological effects.

4.3. Indication of any immediate medical attention and special treatment required

Not applicable.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Material will not burn. Use a fire fighting agent suitable for the surrounding fire.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

No special protective actions for fire-fighters are anticipated.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. For large spills, if necessary, get assistance from professional spill clean up team. For small spills, carefully neutralize spill by adding appropriate dilute acid such as vinegar. Work slowly to avoid boiling or spattering. Continue to add neutralizing agent until reaction stops. Let cool before collecting. Or use a commercially available caustic (alkaline or basic) spill clean-up kit. Follow kit directions exactly. Working from around the edges of the spill inward, cover with bentonite,

vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a metal container approved for use in transportation by appropriate authorities. The container must be lined with polyethylene plastic or contain a plastic drum liner made of polyethylene. Clean up residue with water. Cover, but do not seal for 48 hours. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Keep out of reach of children. Do not breathe dust/fume/gas/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Wash contaminated clothing before reuse. Keep away from reactive metals (eg. Aluminum, zinc etc.) to avoid the formation of hydrogen gas that could create an explosion hazard.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Protect from sunlight. Store away from acids. Store away from areas where product may come into contact with food or pharmaceuticals.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
2-BUTOXYETHANOL	111-76-2	ACGIH	TWA:20 ppm	A3: Confirmed animal carcin.
2-BUTOXYETHANOL	111-76-2	OSHA	TWA:240 mg/m3(50 ppm)	SKIN
Potassium Hydroxide	1310-58-3	ACGIH	CEIL:2 mg/m3	
ETHANOLAMINE	141-43-5	ACGIH	TWA:3 ppm;STEL:6 ppm	
ETHANOLAMINE	141-43-5	OSHA	TWA:6 mg/m3(3 ppm)	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

OSHA : United States Department of Labor - Occupational Safety and Health Administration

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapors/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors

For questions about suitability for a specific application, consult with your respirator manufacturer.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance****Physical state**

Liquid

Color

Colorless

Odor

Mild Solvent

Odor threshold*Not Applicable***pH**

12.5 - 13.5

Melting point*Not Applicable***Boiling Point**

> 212 °F

Flash Point

No flash point

Evaporation rate

Approximately 1 [Ref Std: WATER=1]

Flammability (solid, gas)

Not Applicable

Flammable Limits(LEL)*Not Applicable***Flammable Limits(UEL)***Not Applicable***Vapor Pressure**

< 27 psia [@ 131 °F]

Vapor Density*Not Applicable***Density**

Approximately 1.002 g/ml

Specific Gravity

Approximately 1.001 - 1.011 [Ref Std: WATER=1]

Solubility in Water

Complete

Solubility- non-water*Not Applicable***Partition coefficient: n-octanol/ water***Not Applicable***Autoignition temperature***Not Applicable***Decomposition temperature***Not Applicable***Viscosity**

< 100 centipoise

Volatile Organic Compounds

6 - 8 % weight [Test Method:calculated per CARB title 2]

Percent volatile

80 - 100 % weight

VOC Less H2O & Exempt Solvents

850 - 870 g/l [Test Method:calculated per CARB title 2]

SECTION 10: Stability and reactivity**10.1. Reactivity**

This material is considered to be non reactive under normal use conditions.

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

None known.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified
Oxides of Nitrogen	Not Specified

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1. Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Skin Contact:

Corrosive (Skin Burns): Signs/symptoms may include localized redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction.

Eye Contact:

Corrosive (Eye Burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion:

Gastrointestinal Corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain; nausea; vomiting; and diarrhea; blood in the feces and/or vomitus may also be seen.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
------	-------	---------	-------

Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Vapor(4 hr)		No data available; calculated ATE >50 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
2-BUTOXYETHANOL	Dermal	Guinea pig	LD50 > 2,000 mg/kg
2-BUTOXYETHANOL	Inhalation-Vapor (4 hours)	Guinea pig	LC50 > 2.6 mg/l
2-BUTOXYETHANOL	Ingestion	Guinea pig	LD50 1,200 mg/kg
ETHANOLAMINE	Inhalation-Vapor	official classification	LC50 estimated to be 10 - 20 mg/l
ETHANOLAMINE	Dermal	Rabbit	LD50 2,504 mg/kg
ETHANOLAMINE	Ingestion	Rat	LD50 1,089 mg/kg
ALCOHOLS, C6-12 ETHOXYLATED	Dermal	Rabbit	LD50 1,500 mg/kg
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Dermal	Rat	LD50 > 14,000 mg/kg
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Inhalation-Dust/Mist (4 hours)	Rat	LC50 1.1 mg/l
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Ingestion	Rat	LD50 > 412 mg/kg
ALCOHOLS, C6-12 ETHOXYLATED	Ingestion	Rat	LD50 5,100 mg/kg
Potassium Hydroxide	Dermal	Rabbit	LD50 > 1,260 mg/kg
Potassium Hydroxide	Ingestion	Rat	LD50 273 mg/kg
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.5 mg/l
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Ingestion	Rat	LD50 1,658 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	In vitro data	Corrosive
2-BUTOXYETHANOL	Rabbit	Irritant
ETHANOLAMINE	Rabbit	Corrosive
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Professional judgement	Irritant
Potassium Hydroxide	Rabbit	Corrosive
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
2-BUTOXYETHANOL	Rabbit	Severe irritant
ETHANOLAMINE	Rabbit	Corrosive
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Professional judgement	Corrosive
Potassium Hydroxide	Rabbit	Corrosive
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Rabbit	Corrosive

Skin Sensitization

Name	Species	Value
2-BUTOXYETHANOL	Guinea pig	Not classified
ETHANOLAMINE	Guinea pig	Not classified

ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Human	Not classified
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Human and animal	Not classified

Respiratory Sensitization

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
2-BUTOXYETHANOL	In Vitro	Some positive data exist, but the data are not sufficient for classification
ETHANOLAMINE	In Vitro	Not mutagenic
ETHANOLAMINE	In vivo	Not mutagenic
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	In Vitro	Some positive data exist, but the data are not sufficient for classification
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
2-BUTOXYETHANOL	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Ingestion	Multiple animal species	Not carcinogenic

Reproductive Toxicity

Reproductive and/or Developmental Effects

Name	Route	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHANOL	Dermal	Not classified for development	Rat	NOAEL 1,760 mg/kg/day	during gestation
2-BUTOXYETHANOL	Ingestion	Not classified for development	Rat	NOAEL 100 mg/kg/day	during organogenesis
2-BUTOXYETHANOL	Inhalation	Not classified for development	Multiple animal species	NOAEL 0.48 mg/l	during organogenesis
ETHANOLAMINE	Dermal	Not classified for development	Rat	NOAEL 225 mg/kg/day	during organogenesis
ETHANOLAMINE	Ingestion	Not classified for development	Rat	NOAEL 450 mg/kg/day	during organogenesis
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Ingestion	Not classified for female reproduction	Rat	NOAEL 250 mg/kg/day	4 generation
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Ingestion	Not classified for male reproduction	Rat	NOAEL 250 mg/kg/day	4 generation
TETRASODIUM ETHYLENEDIAMINETETRAACETATE	Ingestion	Not classified for development	Rat	LOAEL 1,000 mg/kg/day	during gestation

Target Organ(s)

Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHANOL	Dermal	endocrine system	Not classified	Rabbit	NOAEL 902 mg/kg	6 hours
2-BUTOXYETHANOL	Dermal	liver	Not classified	Rabbit	LOAEL 72	not available

					mg/kg	
2-BUTOXYETHANOL	Dermal	kidney and/or bladder	Not classified	Rabbit	LOAEL 451 mg/kg	6 hours
2-BUTOXYETHANOL	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	
2-BUTOXYETHANOL	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
2-BUTOXYETHANOL	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
2-BUTOXYETHANOL	Inhalation	blood	Not classified	Multiple animal species	NOAEL Not available	
2-BUTOXYETHANOL	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
2-BUTOXYETHANOL	Ingestion	blood	Not classified	Multiple animal species	NOAEL Not available	
2-BUTOXYETHANOL	Ingestion	kidney and/or bladder	Not classified	Human	NOAEL Not available	poisoning and/or abuse
ETHANOLAMINE	Inhalation	respiratory irritation	May cause respiratory irritation	Human and animal	NOAEL Not available	
ALCOHOLS, C12-14-SECONDARY, ETHOXYLATED	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Potassium Hydroxide	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL not available	
TETRASODIUM ETHYLENEDIAMINETE TRAACETATE	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test Result	Exposure Duration
2-BUTOXYETHANOL	Dermal	blood	Not classified	Multiple animal species	NOAEL Not available	not available
2-BUTOXYETHANOL	Dermal	endocrine system	Not classified	Rabbit	NOAEL 150 mg/kg/day	90 days
2-BUTOXYETHANOL	Inhalation	liver	Not classified	Rat	NOAEL 2.4 mg/l	14 weeks
2-BUTOXYETHANOL	Inhalation	kidney and/or bladder	Not classified	Rat	NOAEL 0.15 mg/l	14 weeks
2-BUTOXYETHANOL	Inhalation	blood	Not classified	Rat	LOAEL 0.15 mg/l	6 months
2-BUTOXYETHANOL	Inhalation	endocrine system	Not classified	Dog	LOAEL 1.9 mg/l	8 days
2-BUTOXYETHANOL	Ingestion	blood	Not classified	Rat	LOAEL 69 mg/kg/day	13 weeks
2-BUTOXYETHANOL	Ingestion	kidney and/or bladder	Not classified	Multiple animal species	NOAEL Not available	not available
ETHANOLAMINE	Inhalation	hematopoietic system liver	Not classified	Rat	NOAEL 0.1559 mg/l	28 days
ETHANOLAMINE	Inhalation	respiratory system	Not classified	Rat	LOAEL 0.0102 mg/l	28 days
ETHANOLAMINE	Inhalation	heart endocrine system immune system nervous system eyes kidney and/or bladder	Not classified	Rat	NOAEL 0.1559 mg/l	28 days

ETHANOLAMINE	Ingestion	hematopoietic system liver kidney and/or bladder respiratory system	Not classified	Rat	NOAEL Not available	
TETRASODIUM ETHYLENEDIAMINETE TRAACETATE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.003 mg/l	13 weeks
TETRASODIUM ETHYLENEDIAMINETE TRAACETATE	Inhalation	liver heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system immune system muscles nervous system eyes kidney and/or bladder vascular system	Not classified	Rat	NOAEL 0.015 mg/l	13 weeks
TETRASODIUM ETHYLENEDIAMINETE TRAACETATE	Ingestion	hematopoietic system liver	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
TETRASODIUM ETHYLENEDIAMINETE TRAACETATE	Ingestion	heart gastrointestinal tract muscles kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 5,000 mg/kg/day	13 weeks

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information**Ecotoxicological information**

Please contact the address or phone number listed on the first page of the SDS for additional ecotoxicological information on this material and/or its components.

Chemical fate information

Please contact the address or phone number listed on the first page of the SDS for additional chemical fate information on this material and/or its components.

SECTION 13: Disposal considerations**13.1. Disposal methods**

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

EPA Hazardous Waste Number (RCRA): D002 (Corrosive)

SECTION 14: Transport Information

For Transport Information, please visit <http://3M.com/Transportinfo> or call 1-800-364-3577 or 651-737-6501.

SECTION 15: Regulatory information

15.1. US Federal Regulations

EPCRA 311/312 Hazard Classifications:

Physical Hazards

Not applicable

Health Hazards

Hazard Not Otherwise Classified (HNOC)

Serious eye damage or eye irritation

Skin Corrosion or Irritation

Section 313 Toxic Chemicals subject to the reporting requirements of that section and 40 CFR part 372 (EPCRA):

<u>Ingredient</u>	<u>C.A.S. No</u>	<u>% by Wt</u>
2-BUTOXYETHANOL (GLYCOL ETHERS)	111-76-2	Trade Secret 3 - 6

15.2. State Regulations

15.3. Chemical Inventories

The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the new substance notification requirements of CEPA.

The components of this material are in compliance with the China "Measures on Environmental Management of New Chemical Substance". Certain restrictions may apply. Contact the selling division for additional information.

The components of this material are in compliance with the provisions of the Korean Toxic Chemical Control Law. Certain restrictions may apply. Contact the selling division for additional information.

The components of this product are in compliance with the chemical notification requirements of TSCA. All required components of this product are listed on the active portion of the TSCA Inventory.

15.4. International Regulations

This SDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: Other information

NFPA Hazard Classification

Health: 3 Flammability: 0 Instability: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

HMIS Hazard Classification**Health:** 3 **Flammability:** 0 **Physical Hazard:** 0 **Personal Protection:** X - See PPE section.

Hazardous Material Identification System (HMIS® IV) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS® IV ratings are to be used with a fully implemented HMIS® IV program. HMIS® is a registered mark of the American Coatings Association (ACA).

Document Group: 19-7627-3
Issue Date: 12/15/23**Version Number:** 11.03
Supersedes Date: 06/11/21

DISCLAIMER: The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M USA SDSs are available at www.3M.com