

## Specification Sheet

Part Number: 156-04053

Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.

Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Two-piece assembly allows the mount to slide along the strap ensuring proper orientation.



2-Piece Cable Tie with Edge Clip, 8.0"L, EC5B, 1 - 3 mm Panel, 50lb, PA66HIRHS/PA66HIRHSUV, OG/BK,500/pkg

|                |           |
|----------------|-----------|
| Article Number | 156-04053 |
|----------------|-----------|

|      |          |
|------|----------|
| Type | T50REC5B |
|------|----------|

|       |                                           |
|-------|-------------------------------------------|
| Color | Black (BK) Orange (OG), High Voltage (HV) |
|-------|-------------------------------------------|

|              |      |
|--------------|------|
| Quantity Per | pack |
|--------------|------|

|                     |                                                                                                                                                                                                                                                                                                                                            |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product Description | HellermannTyton's Two-Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place. |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                   |                                                                                                           |
|-------------------|-----------------------------------------------------------------------------------------------------------|
| Short Description | 2-Piece Cable Tie with Edge Clip, 8.0"L, EC5B, 1 - 3 mm Panel, 50lb, PA66HIRHS/PA66HIRHSUV, OG/BK,500/pkg |
|-------------------|-----------------------------------------------------------------------------------------------------------|

|                  |                                      |
|------------------|--------------------------------------|
| Global Part Name | T50REC5B-PA66HIRHS/PA66HIRHSUV-OG/BK |
|------------------|--------------------------------------|

|                                     |    |
|-------------------------------------|----|
| Minimum Tensile Strength (Imperial) | 50 |
|-------------------------------------|----|

|                                   |     |
|-----------------------------------|-----|
| Minimum Tensile Strength (Metric) | 225 |
|-----------------------------------|-----|

|                     |     |
|---------------------|-----|
| Length L (Imperial) | 8.0 |
|---------------------|-----|

|                   |       |
|-------------------|-------|
| Length L (Metric) | 203.2 |
|-------------------|-------|

|                 |           |
|-----------------|-----------|
| Fixation Method | Edge Clip |
|-----------------|-----------|

|                               |      |
|-------------------------------|------|
| Identification Plate Position | none |
|-------------------------------|------|

|                    |    |
|--------------------|----|
| Releasable Closure | No |
|--------------------|----|

|         |                 |
|---------|-----------------|
| Variant | Inside Serrated |
|---------|-----------------|

|                    |      |
|--------------------|------|
| Width W (Imperial) | 0.18 |
|--------------------|------|

|                  |     |
|------------------|-----|
| Width W (Metric) | 4.6 |
|------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Min (Imperial) | 0.16 |
|--------------------------------|------|

|                              |     |
|------------------------------|-----|
| Bundle Diameter Min (Metric) | 4.0 |
|------------------------------|-----|

|                                |      |
|--------------------------------|------|
| Bundle Diameter Max (Imperial) | 1.97 |
|--------------------------------|------|

|                              |      |
|------------------------------|------|
| Bundle Diameter Max (Metric) | 50.0 |
|------------------------------|------|

|                        |      |
|------------------------|------|
| Thickness T (Imperial) | 0.05 |
|------------------------|------|

|                                |                                                                                                                                              |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------|
| Thickness T (Metric)           | 1.2                                                                                                                                          |
| Height H (Imperial)            | 0.05                                                                                                                                         |
| Height H (Metric)              | 1.2                                                                                                                                          |
| Panel Thickness Min (Imperial) | 0.04                                                                                                                                         |
| Panel Thickness Max (Imperial) | 0.12                                                                                                                                         |
| Panel Thickness Min (Metric)   | 1.0                                                                                                                                          |
| Panel Thickness Max (Metric)   | 3.0                                                                                                                                          |
| Material                       | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)<br>Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV) |
| Foot Part Material             | PA66HIRHSUV                                                                                                                                  |
| Material Shortcut              | PA66HIRHSUV PA66HIRHS                                                                                                                        |
| Material Cable Tie             | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)                                                                             |
| Flammability                   | UL 94 HB                                                                                                                                     |
| UV Resistant (Yes/No)          | Yes                                                                                                                                          |
| Use Conditions                 | For Indoor and Outdoor Use                                                                                                                   |
| Operating Temperature          | -40°F to +221°F (-40°C to +105°C)                                                                                                            |

|                             |            |
|-----------------------------|------------|
| ROHS Compliant              | Yes        |
| Package Quantity (Imperial) | 500        |
| Package Quantity (Metric)   | 500        |
| Customs Number              | 3926909988 |

7930 N. Faulkner Road, Milwaukee, WI 53224  
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.  
[Contact Us](#)   [RoHS/WEEE Compliance](#)   [Disclaimer](#)   [Terms and Conditions](#)