Safety Data Sheet



Revision Number: 003.0 Issue date: 02/26/2020

1. PRODUCT AND COMPANY IDENTIFICATION

Product name: TECHNOMELT PA 7809FR IDH number: 420483
9FR PS 25LB PA

Product type/use:AdhesiveItem number:83676Restriction of Use:None identifiedRegion:United States

Company address:Contact information:Henkel CorporationTelephone: +1 (860) 571-5100

One Henkel Way MEDICAL EMERGENCY Phone: Poison Control Center Rocky Hill, Connecticut 06067 1-877-671-4608 (toll free) or 1-303-592-1711

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW
MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.

VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND

RESPIRATORY TRACT IRRITATION.

STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR FLAMMABLE VAPORS MAY CAUSE IGNITION.

HAZARD CLASS	HAZARD CATEGORY
None	None

PICTOGRAM(S)		
	None	

Precautionary Statements

Prevention: Not prescribed Response: Not prescribed Storage: Not prescribed Disposal: Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
None	None	None

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

Skin contact: Cool skin rapidly with cold water after contact with molten material. Cover

affected areas with clean sheeting or gauze and seek immediate medical

attention.

IDH number: 420483 Product name: TECHNOMELT PA 7809FR 9FR PS 25LB PA

Eye contact: If eye contact occurs with molten material immediately cool with water. Do not

remove adhesive. Seek medical attention.

Ingestion: Do not induce vomiting. Seek medical advice.

Symptoms: See Section 11.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear self-contained breathing apparatus.

Unusual fire or explosion hazards: None

Hazardous combustion products: Oxides of carbon, oxides of nitrogen, irritating organic vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Do not allow material to contaminate ground water system. Do not allow

material to contaminate ground water system.

Clean-up methods: Sweep up spilled material. Avoid creating dust. Keep in suitable and closed

containers for disposal. Sweep up spilled material. Avoid creating dust. Keep

in suitable and closed containers for disposal.

7. HANDLING AND STORAGE

Handling: Do not place wet or damp solid into melt tank. Follow suggested application

temperature. Always be careful around molten material. Avoid skin contact with molten resins. Do not wear contact lenses. Avoid dust formation.

Storage: Keep cool in accordance with information on label and in Technical Data

Sheets.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls: Use adequate ventilation to remove molten vapors or fumes.

Respiratory protection: Solid Resin: Dust safety masks are recommended when the potential for dust

inhalation exists. Molten Resin: No personal respiratory protective equipment normally required. Where the potential exists for exposure to decomposition products due to heating or elevated temperatures, wear NIOSH approved respiratory protection as appropriate. Observe OSHA regulations for respirator

use (29 CFR 1910.134).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists. Do not wear

contact lenses.

Skin protection: Insulated gloves and long sleeved clothing are strongly recommended when

working with molten adhesive.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Solid

Color: Colorless to light yellow

Odor: Odorless
Odor threshold: Not available.
pH: Not available.
Vapor pressure: Not determined

IDH number: 420483 Product name: TECHNOMELT PA 7809FR 9FR PS 25LB PA

Page 2 of 5

> 280.0 °C (> 536°F) Boiling point/range: Not available.

Melting point/ range: Specific gravity: 0.98

Vapor density: Not available.

> 280.00 °C (> 536°F); Estimated Flash point:

Flammable/Explosive limits - lower: Not available. Flammable/Explosive limits - upper: Not available. Autoignition temperature: Not available. Flammability: Not applicable **Evaporation rate:** Not available. Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available. 0.00 % **VOC** content:

Viscosity: Not available. **Decomposition temperature:** Not available.

STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: Will not occur. Will not occur.

Hazardous decomposition

products:

Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be

generated by thermal decomposition or combustion.

Incompatible materials: Acids. Bases. Oxidizing agents. Acids. Bases. Oxidizing agents.

Reactivity: Not available. Conditions to avoid: Excessive heat.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Molten adhesive., Skin, Eyes

Potential Health Effects/Symptoms

Inhalation: Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts

from solid adhesive may cause irritation.

Skin contact: Molten adhesive may cause severe burns. Solid adhesive has no hazards.

Eye contact: Molten adhesive in eyes will cause severe and permanant damage. Can cause mechanical

irritation if dusts are generated.

Not expected under normal conditions of use. May cause gastrointestinal tract irritation if Ingestion:

swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects	
None	None	None	

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
mazardous component(s)	WIF Carcinogen	IARC Carcinogen	(Specifically Regulated)
None	None	None	None

ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 420483 Product name: TECHNOMELT PA 7809FR 9FR PS 25LB PA

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal. Dispose

of according to Federal, State and local governmental regulations.

Hazardous waste number:Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated Hazard class or division: None Identification number: None Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health

CERCLA/SARA Section 313: None above reporting de minimis.

California Proposition 65: No California Proposition 65 listed chemicals are known to be present.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the

Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 15

Prepared by: Product Safety and Regulatory Affairs

Issue date: 02/26/2020

IDH number: 420483 Product name: TECHNOMELT PA 7809FR 9FR PS 25LB PA

Page 4 of 5

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 420483 Product name: TECHNOMELT PA 7809FR 9FR PS 25LB PA