



Revision Number: 002.0

Issue date: 05/02/2017

**1. PRODUCT AND COMPANY IDENTIFICATION**

<b>Product name:</b>	<b>TECHNOMELT PA 638 BK</b>	<b>IDH number:</b>	79123
<b>Product type:</b>	Hotmelt adhesive	<b>Item number:</b>	OM-638-I3
<b>Restriction of Use:</b>	None identified	<b>Region:</b>	United States
<b>Company address:</b>	<b>Contact information:</b>		
Henkel Corporation	Telephone: +1 (860) 571-5100		
One Henkel Way	MEDICAL EMERGENCY Phone: Poison Control Center		
Rocky Hill, Connecticut 06067	1-877-671-4608 (toll free) or 1-303-592-1711		
	TRANSPORT EMERGENCY Phone: CHEMTREC		
	1-800-424-9300 (toll free) or 1-703-527-3887		
	Internet: www.henkelna.com		

**2. HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW**

MOLTEN ADHESIVE MAY CAUSE SEVERE BURNS.  
VAPORS ABOVE MOLTEN ADHESIVE MAY CAUSE EYE, SKIN AND  
RESPIRATORY TRACT IRRITATION.  
STATIC CHARGES GENERATED BY EMPTYING PACKAGE IN OR NEAR  
FLAMMABLE VAPORS MAY CAUSE IGNITION.

HAZARD CLASS	HAZARD CATEGORY
None	None

**PICTOGRAM(S)**

None

**Precautionary Statements**

<b>Prevention:</b>	Not prescribed
<b>Response:</b>	Not prescribed
<b>Storage:</b>	Not prescribed
<b>Disposal:</b>	Not prescribed

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

Hazardous Component(s)	CAS Number	Percentage*
Carbon black	1333-86-4	0.1 - 1

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

### **Non hazardous components**

Polyamide Based Hotmelt Adhesive

## **4. FIRST AID MEASURES**

<b>Inhalation:</b>	Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. If symptoms develop and persist, get medical attention.
<b>Skin contact:</b>	Molten adhesive may cause severe burns. Cool skin rapidly with cold water after contact with molten material. Cover affected areas with clean sheeting or gauze and seek immediate medical attention. No attempt should be made to remove material from skin or to remove contaminated clothing as damaged skin can be easily torn.
<b>Eye contact:</b>	If eye contact occurs with molten material immediately cool with water. Do not remove adhesive. Seek medical attention.
<b>Ingestion:</b>	Ingestion of solid adhesive is not expected to be hazardous. If symptoms develop and persist, get medical attention.
<b>Symptoms:</b>	See Section 11.

## **5. FIRE FIGHTING MEASURES**

<b>Extinguishing media:</b>	Use extinguishing measures appropriate to local circumstances and the surrounding environment. Water spray (fog), foam, dry chemical or carbon dioxide.
<b>Special firefighting procedures:</b>	Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.
<b>Unusual fire or explosion hazards:</b>	In case of fire, keep containers cool with water spray.
<b>Hazardous combustion products:</b>	Oxides of carbon. Acrid smoke and fumes.

## **6. ACCIDENTAL RELEASE MEASURES**

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

<b>Environmental precautions:</b>	Do not allow material to contaminate ground water system. No special environmental precautions required.
<b>Clean-up methods:</b>	Sweep up spilled material. Avoid creating dust. Health injuries are not known or expected under normal use.

## **7. HANDLING AND STORAGE**

<b>Handling:</b>	Avoid skin contact with molten resins. Do not place wet or damp solid into melt tank. Follow suggested application temperature. Do not wear contact lenses. Avoid dust formation.
<b>Storage:</b>	Keep cool in accordance with information on label and in Technical Data Sheets.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Carbon black	3 mg/m3 TWA Inhalable fraction.	3.5 mg/m3 PEL	None	None

<b>Engineering controls:</b>	Use adequate ventilation to remove molten vapors or fumes. Ventilation hoods and fans required when working with organic solvents or in hot melt applications. Heat only in areas with appropriate exhaust ventilation.
<b>Respiratory protection:</b>	Solid Resin: Dust safety masks are recommended when the potential for dust inhalation exists. Molten Resin: Use a NIOSH approved air-purifying respirator with an organic vapor cartridge.
<b>Eye/face protection:</b>	Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Do not wear contact lenses.
<b>Skin protection:</b>	Insulated gloves and long sleeved clothing are strongly recommended when working with molten adhesive.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state:</b>	Solid, granulated
<b>Color:</b>	Black
<b>Odor:</b>	None
<b>Odor threshold:</b>	Not available.
<b>pH:</b>	Not available.
<b>Vapor pressure:</b>	Not applicable
<b>Boiling point/range:</b>	Not available.
<b>Melting point/ range:</b>	137.7 °C (279.9 °F)
<b>Specific gravity:</b>	0.99
<b>Specific gravity:</b>	0.98
<b>Vapor density:</b>	Not available.
<b>Flash point:</b>	No flash point up to 200 °C
<b>Flammable/Explosive limits - lower:</b>	Not applicable
<b>Flammable/Explosive limits - upper:</b>	Not applicable
<b>Autoignition temperature:</b>	Not applicable
<b>Flammability:</b>	Not applicable
<b>Evaporation rate:</b>	Not applicable
<b>Solubility in water:</b>	Insoluble
<b>Partition coefficient (n-octanol/water):</b>	Not available.
<b>VOC content:</b>	Essentially Zero
<b>Viscosity:</b>	4,000.00 - 6,000.00 cp
<b>Decomposition temperature:</b>	Not available.

## 10. STABILITY AND REACTIVITY

<b>Stability:</b>	Stable
<b>Hazardous reactions:</b>	Will not occur.
<b>Hazardous decomposition products:</b>	Carbon dioxide, carbon monoxide and irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.
<b>Incompatible materials:</b>	Acids. Bases. Oxidizing agents.
<b>Reactivity:</b>	Not available.
<b>Conditions to avoid:</b>	Prolonged heating at temperatures above 200 °C.

## 11. TOXICOLOGICAL INFORMATION

**Relevant routes of exposure:** Molten adhesive., Skin, Inhalation, Eyes, Solid adhesive has no hazards.

### Potential Health Effects/Symptoms

**Inhalation:** Continuous breathing of vapors above molten adhesive may irritate mucous membranes. Dusts from solid adhesive may cause irritation.  
**Skin contact:** Molten adhesive may cause severe burns. Solid adhesive has no hazards.  
**Eye contact:** Molten adhesive in eyes will cause severe and permanent damage. Can cause mechanical irritation if dusts are generated.  
**Ingestion:** Not expected to be harmful by ingestion.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Carbon black	Oral LD50 (Rat) = > 8,000 mg/kg	Respiratory, Some evidence of carcinogenicity

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Carbon black	No	Group 2B	No

## 12. ECOLOGICAL INFORMATION

**Ecological information:** Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

**Recommended method of disposal:** Follow all local, state, federal and provincial regulations for disposal.

**Hazardous waste number:** Not a RCRA hazardous waste.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### U.S. Department of Transportation Ground (49 CFR)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### International Air Transportation (ICAO/IATA)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

### Water Transportation (IMO/IMDG)

**Proper shipping name:** Not regulated  
**Hazard class or division:** None  
**Identification number:** None  
**Packing group:** None

## 15. REGULATORY INFORMATION

### United States Regulatory Information

<b>TSCA 8 (b) Inventory Status:</b>	All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
<b>TSCA 12 (b) Export Notification:</b>	None above reporting de minimis
<b>CERCLA/SARA Section 302 EHS:</b>	None above reporting de minimis.
<b>CERCLA/SARA Section 311/312:</b>	Immediate Health
<b>CERCLA/SARA Section 313:</b>	None above reporting de minimis.
<b>California Proposition 65:</b>	This product contains a chemical known in the State of California to cause cancer.

### Canada Regulatory Information

<b>CEPA DSL/NDSL Status:</b>	Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.
------------------------------	---

## 16. OTHER INFORMATION

**This safety data sheet contains changes from the previous version in sections:** New Safety Data Sheet format.

**Prepared by:** Alicia Griffin, Regulatory Affairs Specialist

**Issue date:** 05/02/2017

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.