Moisture Guard Rust Inhibitor

PERFORMANCE CHARACTERISTICS:

- · Seals against corrosion and prevents moisture without bleeding
- Won't leech into ejectors, cams or core pins to cause bleeding
- Exceptional water repelling qualities
- Increases short and long term protection
- Rapid flash time
- · Maximum efficiency, minimum labor
- · Reduces excess usage and waste
- Will NOT induce bleeding
- Contains no fillers, only pure active ingredients
- Easily removed by flushing

DESCRIPTION:

DAC-101 Moisture Guard is a distinctive formulation that was developed to maximize performance in short and long term moisture displacement and rust prevention situations. There is a high cost associated with rejected parts due to marking. This is typically caused by excess penetration of product into ejector pins, cams, and slides. DAC-101 Moisture Guard eliminates this problem entirely due its rapid flash time, preventing running or dripping and therefore will not induce any kind of contamination due to leeching or bleeding. A light coating of DAC-101 Moisture Guard is all that is needed. Once applied it will remain active for extended periods of time.

REMOVAL SPECIFICATIONS:

Due to Moisture Guard's unique formulation it can simply and easily be removed by flushing with DAC-103 Universal All Purpose Degreaser with no risk of contamination.

Moisture Guard displaces moisture and provides a coating of excellent film strength which protects molds from both short and long-term corrosion.



NPCA Hazardous Materials ID System

,	
Health	1
Flammability	4
Reactivity	0
Personal Protection	*

©2024 DAC Industries, Inc. All Rights Reserved

Call for Orders, Product Information and Technical Support:

1-800-830-3423



DAC Industries, Inc. 1636 Gervais Avenue Maplewood, MN 55109 USA tel: 1-651-748-1750 fax: 1-651-748-1748 info@dac-industries.com www.dac-industries.com