

8241

ISOPROPYL ALCOHOL 70/30 or 75/25

Safety Data Sheet

Section 1: Product and Company Identification

Product Identifier and Other Means of Identification

Product Identifier: 8241**Other Means of Identification:** Isopropyl Alcohol 70/30 or Isopropyl Alcohol 75/25 or Surface Cleaner for Electronics**Related Part #** 8241-475ML, 8241-475MLCA, 8241-945ML, 8241-945MLCA, 8241-945MLX6, 8241-945MLCAX6, 8241-1G, 8241A-1G, 8241-20L, 8241-205L

Recommended Use and Restriction on Use

Use: Multipurpose cleaner for electronic**Uses Advised Against:** Not for use on monitor screens or glass with anti-glare coatings.

Details of Manufacturer or Importer

ManufacturerMG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA+1-800-340-0772
+1-905-331-1396**E-mail**info@mgchemicals.com
support@mgchemicals.com**Web**www.mgchemicals.com**E-MAIL**(Competent Person): sds@mgchemicals.com**Distributor**Mouser Electronics
1000 North Main Street
Mansfield, TX 76063
United States

1-800-346-6873

Emergency Phone Number

For hazardous material incidents ONLY (leaks, spills, fires, exposures or accidents)
USA or CANADA—Call Verisk 3E at **+1-866-519-4752** or **+1-760-476-3962**
(Service access code: 335388)**For emergencies involving the transport of dangerous goods;** 24/7 service
CANADA—Call CANUTEC collect at **+1-613-996-6666** or ***666** on cellular phones

8241
ISOPROPYL ALCOHOL 70/30 or 75/25

Section 2: Hazards Identification



Classification of Hazardous Chemical

GHS Categories

Criteria	Category	Signal Word	Pictograms
Flammable Liquid	2	Danger	Flame
Eye irritation	2A	Warning	Exclamation
Specific Target Organ Toxicity Single Exposure	3	Warning	Exclamation

Note: The degree of severity is ranked within each hazard class from 1 (Highest Severity) to up to 5 (Lowest Severity). Severity categories do not allow comparisons between classes.

Label Elements

Signal Word	DANGER
Pictograms	Hazard Statements
	H225: Highly flammable liquid and vapor
	H319: Causes serious eye irritation H336: May cause drowsiness or dizziness
Prevention	Precautionary Statements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof equipment.
P243	Take action to prevent static discharges.
P261	Avoid breathing mist, vapors or spray.
P271	Use only outdoors or in a well-ventilated area.

Section continued on the next page

8241
ISOPROPYL ALCOHOL 70/30 or 75/25
Continued...

Prevention	Precautionary Statements
P264	Wash hands thoroughly after handling.
P280	Wear protective gloves and eye protection.
Response	Precautionary Statements
P370 + P378	In case of fire: Use dry chemical, carbon dioxide, chemical foam, or water spray to extinguish.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice or attention.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTRE or doctor if you feel unwell.
Storage	Precautionary Statements
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
Disposal	Precautionary Statements
P501	Dispose of contents in accordance to local, regional, national, and international regulations.

Other Hazards

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms
Defats skin	Repeated exposure may cause skin dryness or cracking.	None	None

Section 3: Hazardous Ingredients

CAS #	Chemical Name	% (weight)
67-63-0	propan-2-ol ^{a)}	65-75%
7732-18-5	water	25-35%

a) Commonly known as isopropyl alcohol (IPA)

8241

ISOPROPYL ALCOHOL 70/30 or 75/25

Section 4: First-Aid Measures

<i>Exposure Condition</i>	<i>GHS Code: Precautionary Statement</i>
IF ON SKIN (or hair)	P303 + P361 + P353
Immediate Symptoms	<i>Low toxicity: dry skin, redness</i>
Response	Take off immediately all contaminated clothing. Rinse skin with water or shower.
IF IN EYES	P305 + P351 + P338, P337 + P313
Immediate Symptoms	<i>irritation, tearing, redness, pain</i>
Response	Rinse cautiously with water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.
IF INHALED	P304 + P340 + P312
Immediate Symptoms	<i>cough, dizziness, drowsiness, headaches, weakness, unconsciousness</i>
Response	Remove person to fresh air and keep comfortable for breathing. If feeling unwell: Call a POISON CENTRE or doctor.
IF SWALLOWED	P301 + P330 + P331
Immediate Symptoms	<i>Low toxicity: nausea, headaches, dizziness, weakness, unconsciousness</i>
Response	Rinse mouth. Do NOT induce vomiting.

Section 5: Fire-Fighting Measures

Extinguishing Media	In case of fire: Use dry chemical, carbon dioxide, water fog, or chemical foam to extinguish. Use water spray to cool containers.
Specific Hazards	The vapors are heavier than air and may accumulate in low-lying areas. Vapors may travel long distances and ignite at an ignition source, which can cause a flashback or an explosion.
Combustion Products	Produces carbon oxides (CO, CO ₂)
Fire-Fighter	Wear self-contained breathing apparatus for fire fighting

8241

ISOPROPYL ALCOHOL 70/30 or 75/25

Section 6: Accidental Release Measures

Personal Protection	See personal protection recommendations in Section 8.
Precautions for Response	Remove or keep away all sources of ignition or extreme heat. Avoid breathing vapors.
Environmental Precautions	Prevent spill from entering drains and waterways.
Containment Methods	Contain with inert and non-flammable absorbent (such as soil, sand, vermiculite).
Cleaning Methods	Collect liquid in a sealable, solvent-resistant container. Wipe up further residue with paper towel and place dirty towels in container. Wash spill area with soap and water to remove the last traces of residue. RECOMMENDATION: Use a grounded stainless steel or carbon steel container or a solvent resistant plastic container.
Disposal Methods	Dispose of spill waste according to Section 13.

Section 7: Handling and Storage

Prevention	Keep out of reach of children. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take action to prevent static discharges. Use explosion-proof electrical, ventilating, and lighting equipment. Avoid breathing mist, vapors, or spray. Use only outdoors or in a well-ventilated area. Keep container tightly closed.
Handling	Wear protective gloves, protective clothing, and eye protection. Wash hands thoroughly after handling.
Storage	Store in a well-ventilated area. Keep cool. Store locked up.

8241

ISOPROPYL ALCOHOL 70/30 or 75/25

Section 8: Exposure Controls/Personal Protection**Substances with Occupational Exposure Limit Values**

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
propan-2-ol	ACGIH	200 ppm (TWA)	400 ppm
	U.S.A. OSHA PEL	400 ppm	Not established
	Canada AB	200 ppm	400 ppm
	Canada BC	200 ppm	400 ppm
	Canada ON	200 ppm	400 ppm
	Canada QC	400 ppm	500 ppm

Note: The ACGIH¹, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from suppliers' SDS were also consulted. Short term exposure limits (STEL) are usually for 15 min and long-term permissible exposure limits (PEL) for 8 h.

Engineering Controls**Ventilation**

Keep airborne concentrations below the occupational exposure limits (OEL).

Personal Protective Equipment**Eye protection**

Wear appropriate protective eyeglasses or chemical safety goggles.

RECOMMENDATION: Use safety glasses with lateral protection (side shields).

Skin Protection

For likely contacts, use of protective butyl rubber, nitrile, neoprene, polyethylene gloves or other chemically resistant gloves.

For incidental contacts, use disposable nitrile or neoprene gloves, or other chemically resistant gloves.

Do NOT use latex rubber, polyvinyl alcohol (PVA) or PVC gloves.

Section continued on the next page

8241
ISOPROPYL ALCOHOL 70/30 or 75/25
Respiratory Protection

For over-exposures up to 10 x OEL of mist, vapors, and spray, wear respirator such as a half-mask respirator with organic vapor cartridges.

Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

RECOMMENDATION: Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

General Hygiene Considerations

Wash hands thoroughly with water and soap after handling.

Section 9: Physical and Chemical Properties

Physical State	Liquid	Lower Flammability Limit	2%
Appearance	Colorless	Upper Flammability Limit	12%
Odor	Alcohol like	Vapor Pressure @20 °C	4.2 kPa [32 mmHg]
Odor Threshold	0.44 ppm	Vapor Density	2.1 (Air = 1)
pH	Not available	Relative Density @20 °C	0.86–0.87
Freezing/Melting Point	Not available	Solubility in Water	Fully miscible
Initial Boiling Point	≥80.6 °C [≥177 °F]	Partition Coefficient n-octanol/water	Not available
Flash Point ^{a)}	18 °C [64 °F]	Auto-ignition Temperature	≥425 °C [≥797 °F]
Evaporation Rate	1.5 (ButAc = 1)	Decomposition Temperature	Not available
Flammability	Highly Flammable	Viscosity @25 °C	≥2.4 mPa·s [≥3.1 mm ² /s]

a) Tag closed cup

8241**ISOPROPYL ALCOHOL 70/30 or 75/25****Section 10: Stability and Reactivity**

Reactivity	At elevated temperatures, may react with aluminum and generate hydrogen gas.
Chemical Stability	Chemically stable at normal temperatures and pressures
Conditions to Avoid	Avoid ignition sources, excessive heat, and incompatible substances. Vapors may form explosive mixture with air.
Incompatibilities	Strong oxidizing agents, strong acids, strong bases, halogenated compounds, aluminum at temperatures $\geq 49\text{ }^{\circ}\text{C}$ [$\geq 120\text{ }^{\circ}\text{F}$]
Polymerization	Will not occur
Decomposition	Will not decompose under normal conditions. For thermal decomposition, see combustion products in Section 5

Section 11: Toxicological Information**Summary of Effects and Symptoms by Routes of Exposure**

Eyes	Causes serious eye irritation, tearing, redness or pain.
Skin	Cause dry skin and redness.
Inhalation	May cause cough, drowsiness, or dizziness. Excessive exposure may cause narcotic effects, weakness, headaches, and unconsciousness.
Ingestion	See inhalation symptoms.
Chronic	Prolonged or repeated exposure may defat skin and cause skin dryness and cracking, and local redness and discomfort.

Acute Toxicity (Lethal Exposure Concentrations)

Chemical Name	LD50 oral	LD50 dermal	LC50 inhalation
propan-2-ol	5 840 mg/kg Rat	12 800 mg/kg Rabbit	16 000 ppm 8 h Rat

Note: Toxicity data from the ECHA database was consulted. The data from supplier SDSs were also consulted.

Section continued on the next page

8241**ISOPROPYL ALCOHOL 70/30 or 75/25****Other Toxicological Effects**

Skin corrosion/irritation	Based on available data, the classification criteria are not met. Propan-2-ol may provoke a light irritation of the skin according to Draize tests on rabbits.
Serious eye damage/irritation	Causes moderate to severe eye irritation based on Draize tests on rabbits
Sensitization (allergic reactions)	Based on available data, the classification criteria are not met.
Carcinogenicity (risk of cancer)	Not classified or listed as a carcinogen by IARC, ACGIH, CA Prop 65, or NTP.
Mutagenicity (risk of heritable genetic effects)	Based on available data, the classification criteria are not met.
Reproductive Toxicity (risk to sex functions)	Based on available data, the classification criteria are not met.
Teratogenicity (risk of fetus malformation)	Based on available data, the classification criteria are not met.
STOT-single exposure	Propan-2-ol can affect the central nervous system by inhalation causing drowsiness or dizziness.
STOT-repeated exposure	Based on available data, the classification criteria are not met.
Aspiration hazard	The liquid content does not meet the aspiration hazard criteria. The are no category 1 substances.

Section 12: Ecological Information

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<http://echa.europa.eu>), and other reliable sources.

Based on available data, propan-2-ol are not classifiable as toxic for the aquatic environment a minimal LC50 and EC50 >100 mg/L.

- Propan-2-ol is readily biodegradable and has a minimal LC50 96 h of 9 640 mg/L for Pimephales promelas (fathead minnow); an EC50 24 h of 5 102 mg/L Daphnia magna (water flea); and an EC50 72 h of >2 000 mg/L Desmodesmus subspicatus (green algae).

Section continued on the next page

8241**ISOPROPYL ALCOHOL 70/30 or 75/25****Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds

Chronic Ecotoxicity

Available toxicity data does not meet classification thresholds

Biodegradability

Not available

Other EffectsVolatile Organic Content (VOC) $\leq 70\%$ (603 g/L)**Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.

Section 14: Transport Information**Ground****Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations);
USA DOT 49 CFR (Parts 100 to 185) **Regulations.**Sizes 1 L and under
8241-475ML, 8241-475MLCA
Limited QuantitySizes greater than 1 L
8241-1G, 8241A-1G, 8241-20L
UN number: UN1219
Shipping Name: ISOPROPANOL
Class: 3
Packing Group: II
Marine Pollutant: No*Section continued on the next page*

8241
ISOPROPYL ALCOHOL 70/30 or 75/25
Air
Refer to ICAO-IATA Dangerous Goods Regulations.
Sizes 0.5 L and under

8241-475ML, 8241-475MLCA

Limited Quantity

Max Net Qty/Outer Pkg
= 1 L

**Sizes 0.5 L up to 5 L (passenger),
60 L (cargo)**

8241-1G, 8241A-1G, 8241-20L

UN number: UN1219

Shipping Name: ISOPROPANOL

Class: 3

Packing Group: II

Marine Pollutant: No

Sea
Refer to IMDG regulations.
Sizes 1 L and under

8241-475ML, 8241-475MLCA

Limited Quantity

Sizes greater than 1 L

8241-1G, 8241A-1G, 8241-20L

UN number: UN1219

Shipping Name: ISOPROPANOL

Class: 3

Packing Group: II

Marine Pollutant: No


Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

Section 15: Regulatory Information
Canada
Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2015.


Section continued on the next page

8241**ISOPROPYL ALCOHOL 70/30 or 75/25****USA****OSHA Hazard Communication Standard (29 CFR Part 1900)**

The safety data sheet and label comply with HCS 2024.

Other Classifications**HMIS[®] RATING**

HEALTH:	2
FLAMMABILITY:	3
PHYSICAL HAZARD:	0
PERSONAL PROTECTION:	

NFPA[®] 704 CODES

Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45)

This product contains propan-2-ol (CAS# 67-63-0) which is subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

TSCA (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

California Proposition 65 (Chemicals known to cause cancer or reproductive toxicity, USA)

This product does not contain any of the listed substances.

Europe**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

WEEE (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

8241**ISOPROPYL ALCOHOL 70/30 or 75/25****Section 16: Other Information****MSDS Prepared by** MG Chemical's Regulatory Department**Date of Revision** 05 February 2025**Supersedes** 15 April 2024**Reason for Changes:** Added company address.**References**

1) ACGIH 2024 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2024).

Abbreviations

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

8241**ISOPROPYL ALCOHOL 70/30 or 75/25**

Technical Queries Contact us regarding any questions, improvement suggestions, or problems with this product. Application notes, instructions, and FAQs are located at www.mgchemicals.com.

Email: support@mgchemicals.com

Mailing Addresses *Manufacturing & Support*
1210 Corporate Drive
Burlington, Ontario, Canada
L7L 5R6

Head Office
9347-193rd Street
Surrey, British Columbia, Canada
V4N 4E7

Phone: +1-905-331-1396

Disclaimer

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.