

# **Safety Data Sheet**

#### Section 1: Identification

#### **Product Identifier and Other Means of Identification**

Product Identifier: Carbon Conductive Grease

**Other Means of Identification: 846** 

Related Part # 846-80G, 846-1P, 846-1G, 846-3.78L, 846-18.9L

#### Recommended Use and Restriction on Use

**Use:** Electrically conductive lubricant for switches

Uses Advised Against: Avoid uses that result in aerosolizing

#### **Details of Manufacturer or Importer**

#### Manufacturer

MG Chemicals
1210 Corporate Drive
Burlington, Ontario L7L 5R6
CANADA

Mouser Electronics
1000 North Main Street
Mansfield, TX 76063
USA

**≅** +1-800-340-0772 **≅** +1-817-804-3800

+1-905-331-1396 **E-MAIL** support@mgchemicals.com **E-MAIL** info@mgchemicals.com

WEB www.mgchemicals.com

**E-MAIL** (Competent Person): <a href="mailto:sds@mgchemicals.com">sds@mgchemicals.com</a>

### **Emergency Phone Number**

**For hazardous material incidents ONLY** (leaks, spills, fires, exposures or accidents) USA or CANADA—Call Verisk 3E at +1-866-519-4752 or +1-760-476-3962 (Service access code: 335388)

**For emergencies involving the transport of dangerous goods**; 24/7 service CANADA—Call CANUTEC collect at **+1-613-996-6666** or **\*666** on cellular phones



### Section 2: Hazard(s) Identification

### **Classification of Hazardous Chemical**

### **GHS Categories**

Based on available data, this product does not meet the HCS 2024 or WHMIS 2023 classification criteria.

#### **Label Elements**

Signal Word	No signal word
Pictograms	Hazard Statements
None	None

### **Hazards Not Otherwise Classified**

Other Criteria	Hazard Statements/Precautionary Statement	Signal Word	Pictograms	
None	None	None	None	

### **Section 3: Composition/Information on Ingredients**

CAS #	Chemical Name	%(weight)
1333-86-4	carbon black	20%



### **Section 4: First-Aid Measures**

Exposure Condition	GHS Code/Symptoms/Precautionary Statements
IF ON SKIN	P302 + P352
Immediate Symptoms	low toxicity: no symptoms known or expected
Response	Wash with plenty of water.
IF INHALED	P304 + P340 (Not a likely route of exposure under normal use)
Immediate Symptoms	low toxicity: no symptoms known or expected
Response	Remove person to fresh air (out of the contaminated zone) and keep comfortable for breathing.
IF IN EYES	P305 + P351 + P338
Immediate Symptoms	low toxicity: redness, mild irritation
Response	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
IF SWALLOWED	P301 + P330 + P331, P314
Immediate Symptoms	low toxicity: no symptoms known or expected
Response	Rinse mouth. Do NOT induce vomiting.

## **Section 5: Fire-Fighting Measures**

Extinguishing Media	In case of fire: Use material suitable for surrounding material.
Specific Hazards	At temperatures of 150 °C [302 °F] and above, formaldehyde can be generated in the presence of oxygen. Formaldehyde is classified as a human carcinogen, skin sensitizer, respiratory sensitizer, and eye and throat irritant.
	Prevent fire-fighting wash from entering waterway or sewer system.
<b>Combustion Products</b>	Produces carbon oxides (CO, CO <sub>2</sub> ), SiO <sub>2</sub> and formaldehyde
Fire-Fighter	Wear self-contained breathing apparatus and full fire-fighting turn-out gear.



#### ISO 9001:2015 Quality Management System

SAI Global File #004008 Burlington, Ontario, Canada

846

### **Section 6: Accidental Release Measures**

**Personal Protection** See personal protection recommendations in Section 8.

Precautions for

Avoid breathing fumes or vapors. Remove or keep away all

Response

sources of extreme heat or open flames.

**Environmental Precautions** 

Avoid releasing to the environment.

**Containment** Contain the spill and cover drains.

**Cleaning** The material presents a slip hazard and must be cleaned

thoroughly. Collect grease in a sealable container. Scoop into the container. Wipe up further residue with paper towel and place dirty towels in container. Wash spill area with steam, solvents, or detergents to remove the last traces of residue.

**Disposal** Dispose of spill waste according to Section 13.

### Section 7: Handling and Storage

**Prevention** Keep out of reach of children.

**Handling** Wear protective gloves, protective clothing, and eye protection.

Wash hands thoroughly after handling.

**Storage RECOMMENDATION:** Keep in a dry and clean area, away from

incompatible substances.



### **Section 8: Exposure Controls/Personal Protection**

### **Substances with Occupational Exposure Limit Values**

Chemical Name	Country	Long Term Exposure Limits (PEL)	Short Term Exposure Limits (STEL)
carbon black <sup>a)</sup>	ACGIH U.S.A. OSHA PEL Canada AB Canada BC Canada ON Canada QC	3.5 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup> 3 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup> 3.5 mg/m <sup>3</sup>	Not established Not established Not established Not established Not established Not established

*Note:* The ACGIH<sup>1</sup>, OSHA (Table Z-1), and Canadian provinces exposure limits were consulted. Limits from the suppliers' SDS were also consulted. Short term exposure limits (STEL) are for 15 min and long-term permissible exposure limits (PEL) for 8 h.

a) Respirable airborne particles

#### **Engineering Controls**

Ventilation	Keep airborne concentrations below the occupational exposure
venthation	keep all bottle concentrations below the occupational exposure

limits (OEL).

Because the carbon black is bound to the liquid mixture, it does not present an airborne hazard under normal use. Ensure adequate ventilation if the product is mechanically misted or aerosolized.

#### **Personal Protective Equipment**

	1 4 /					<i>~</i> .
Eve protection	Wear an	aronriate	nrotective	eveniasses	or chemical sat	retv

goggles.

**RECOMMENDATION:** Use safety glasses with lateral protection

(side shields).

**Skin Protection** For likely contacts, use of protective butyl rubber, neoprene,

or other chemically resistant gloves.

For incidental contacts, use nitrile, polyvinyl alcohol (PVA) or

other chemically resistant gloves.

Section continued on the next page

Page **5** of **13** 



**Respiratory Protection** For over-exposures up to 10 x OEL of vapors, wear respirator such as a half-mask respirator with organic vapor cartridges.

> Above 10 x OEL, use a positive-pressure, air-supplied respirator or a self-contained breathing apparatus.

**RECOMMENDATION:** Consult your local safety supply store to ensure that your respirator has a NIOSH (U.S.) approved filter cartridges appropriate for the ingredients listed in Section 3. The respirator should be fitted to the employee by a professional. Ensure vapor cartridges are stored in sealed plastic bags when not being used.

### **General Hygiene Considerations**

Wash hands thoroughly with water and soap after handling.

### **Section 9: Physical and Chemical Properties**

Physical State	Liquid	Lower Flammability Limit	Not available
Appearance	Black grease	Upper Flammability Limit	Not available
Odor	Not	Vapor Pressure	0.13 kPa
	available	@25°C	[1 mmHg]
Odor Threshold	Not available	Vapor Density	>1 (Air =1)
pH	Not available	Relative Density @25°C	1.1
Freezing/Melting	Not	Solubility in	Insoluble
Point	available	Water	
Initial Boiling	>200 °C	Partition Coefficient n-octanol/water	Not
Point	[>392 °F]		available
Flash Point a)	>300 °C	Auto-ignition	Not
	[572 °F]	Temperature	available
Evaporation	<1	Decomposition	Not
Rate	(ButAc = 1)	Temperature	available
Flammability	Non Flammable	Viscosity @25 °C	570 000 cSt

a) Cleveland open cup

Burlington, Ontario, Canada



846

### **Section 10: Stability and Reactivity**

**Reactivity** Not available

**Chemical** Chemically stable at normal temperatures and pressures.

Stability

**Conditions to** Ignition sources, excessive heat, and incompatible substances.

Avoid

**Incompatibilities** Strong oxidizing agents, strong acids

**Polymerization** Will not occur

**Decomposition** Will not decompose under normal conditions. For thermal

decomposition, see combustion products in Section 5.

### Section 11: Toxicological Information

#### **Summary of Effects and Symptoms by Routes of Exposure**

**Eyes** Low toxicity: may cause mild eye irritation, redness.

SkinLow toxicity: no symptoms known or expectedInhalationLow toxicity: no symptoms known or expectedIngestionLow toxicity: no symptoms known or expectedChronicLow toxicity: no symptoms known or expected

### **Acute Toxicity (Lethal Exposure Concentrations)**

<b>Chemical Name</b>	LD50	LD50	LC50
	oral	dermal	inhalation
carbon black	>15 g/kg	>3 g/kg	Not
	Rat	Rabbit	available

*Note:* Toxicity data from the ECHA database were consulted. The data from supplier SDSs were also consulted.

Section continued on the next page



(risk of cancer)

#### ISO 9001:2015 Quality Management System

SAI Global File #004008 Burlington, Ontario, Canada

846

Skin corrosion/irritation Based on available data, the classification criteria are

not met.

Serious eye damage/irritation May cause mild eye irritation.

Based on available data, the classification criteria are Sensitization

(allergic reactions) not met.

Carcinogenicity The carbon black [1333-86-4] is possibly carcinogenic

by airborne routes of exposures under WHMIS.

Because the carbon black is bound in the liquid

mixture, it is not available as an airborne hazard (dust)

under normal use.

Carbon Black [1333-86-4]

IARC Group 2B: Possibly carcinogenic to humans

ACGIH A4: Not classified as a human carcinogen CA Prop 65: Listed as a carcinogen (airborne, as

unbound particles of respirable size)

NTP: Not listed

Mutagenicity

Based on available data, the classification criteria are (risk of heritable genetic effects)

not met.

**Reproductive Toxicity** 

(risk to sex functions)

Based on available data, the classification criteria are

not met.

**Teratogenicity** 

(risk of fetus malformation)

Based on available data, the classification criteria are

not met.

**STOT-single exposure** Based on available data, the classification criteria are

not met.

STOT-repeated exposure Based on available data, the classification criteria are

not met.

Aspiration hazard There are no category 1 components, and the kinematic

viscosity is >20.5 mm<sup>2</sup>/s at 40 °C.



### **Section 12: Ecological Information**

Ecological classifications are based on the IMDG/GHS criteria in conjunction with ecotoxicological data from our suppliers, the European Chemical Agency database (<a href="http://echa.europa.eu">http://echa.europa.eu</a>), and other reliable sources.

The polysiloxane fluid and carbon black are not classifiable as ecotoxic hazards under GHS criteria.

### **Acute Ecotoxicity**

Available toxicity data does not meet classification thresholds

### **Chronic Ecotoxicity**

Available toxicity data does not meet classification thresholds.

#### **Biodegradability**

Not readily biodegradable

#### Other Effects

Regulated VOC (Volatile Organic Compound) content = 0% [0 g/L] All components are VOC exempt in Canada and the USA.

#### **Section 13: Disposal Information**

Dispose of contents in accordance with all local, regional, national, and international regulations.



#### **Section 14: Transport Information**

#### **Ground**

**Refer to TDG regulations** (Canadian Transportation of Dangerous Goods regulations) and USA 49CFR Regulations (Parts 100 to 185).

Not Regulated

#### Air

Refer to ICAO-IATA Dangerous Goods Regulations.

Not Regulated

### Sea

Refer to IMDG regulations.

Not Regulated

Note: Shipper must be appropriately trained and certified before involvement with the transport of dangerous goods.

### **Section 15: Regulatory Information**

#### Canada

**Domestic Substance List (DSL) / Non-Domestic Substance Lists (NDSL)** 

All hazardous ingredients are listed on the DSL/NDSL.

Hazardous Products Act (R.S.C., 1985, c. H-3)

The safety data sheet and label comply with the Hazardous Product Act and WHMIS 2023.

Section continued on the next page



#### USA

### **OSHA Hazard Communication Standard (29 CFR Part 1900)**

The safety data sheet and label comply with HCS 2024.

#### Other Classifications

#### **HMIS® RATING**

HEALTH:	*	1
FLAMMABILITY:		1
PHYSICAL HAZARD:	(	0
PERSONAL PROTECTION:		

#### NFPA® 704 CODES



Approximate HMIS and NFPA Risk Ratings Legend:

0 (Low or none); 1 (Slight); 2 (Moderate); 3 (Serious); 4 (Severe)

CAA (Clean Air Act, USA)

This product does not contain any class 1 ozone depleting substances.

This product does not contain any class 2 ozone depleting substances.

This product does not contain substances that are listed as hazardous air pollutants.

EPCRA (Emergency Planning and Right to Know Act, USA, 40 CFR 372.45

This product does not contain ingredients that are subject to the reporting requirements of section 313 Title III of the SARA of 1986 and 40 CFR part 372.

**TSCA** (Toxic Substances Control Act of 1976, USA)

All substances are TSCA listed.

**California Proposition 65** (Chemicals known to cause cancer or reproductive toxicity, USA).

This product contains carbon black, but it is bound and exposures during normal conditions of uses are below the Safe Harbor Threshold.

Section continued on the next page





#### Europe

**RoHS** (Restriction of Hazardous Substances Directive)

This product does not contain any lead, cadmium, mercury, hexavalent chromium, PBB's, PBDE's, DEHP, BBP, DBP, or DIBP and complies with European RoHS regulations.

**WEEE** (Waste Electrical and Electronic Equipment Directive)

This product is not a piece of electrical or electronics equipment and is therefore not governed by this regulation.

### **Section 16: Other Information**

**SDS Prepared by** MG Chemicals' Regulatory Department

**Date of Revision** 15 November 2024 **Supersedes** 10 March 2023

**Reason for Changes:** Updated to WHMIS 2023 and HCS 2024 requirements.

#### References

1) ACGIH 2023 TLVs and BEIs: Based on the documentation of the threshold limit values for chemical substances and physical agents & biological exposure indices, American Conference of Governmental of Industrial Hygienist Cincinnati, OH (2023).

#### **Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists (USA)
EC50	Half maximal effective concentration
EL50	Half maximal effective loading
NOELR	No observable effect loading ratio
GHS	Globally Harmonized System of Classification of Labeling of Chemicals
LC50	Lethal Concentration 50%
LCLo	Lowest published lethal concentration
LD50	Lethal Dose 50%
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
TCLo	Lowest published toxic concentration
TWA	Time Weighted Average
VOC	Volatile Organic Content

Section continued on the next page

Page **12** of **13** 



#### ISO 9001:2015 Quality Management System

SAI Global File #004008 Burlington, Ontario, Canada

846

**Technical Queries** Contact us regarding any questions, improvement suggestions, or

problems with this product. Application notes, instructions, and FAQs

are located at www.mgchemicals.com.

Email: <a href="mailto:support@mgchemicals.com">support@mgchemicals.com</a>

Phone: +1-905-331-1396

**Mailing Addresses** *Manufacturing & Support* 

1210 Corporate Drive

Burlington, Ontario, Canada

L7L 5R6

**Disclaimer** 

This safety data sheet is provided as an information resource only. *M.G. Chemicals, Ltd.* believes the information contained herein is accurate and compiled from reliable sources. It is the responsibility of the user to query and verify any information seeming suspect where doubt on the validity may exist. The buyer assumes all responsibility of using and handling the product in accordance with local, regional, national, and international regulations.