

CESL8 32VDC PREMIUM BRUSHLESS, SHUT-OFF CLUTCH

The Delta Regis CESL8 Series Premium Brushless Screwdrivers provide the ultimate combination of ergonomics, precision, performance and environmental cleanliness to the installation of fasteners. The quiet, brushless DC motor does not create the carbon dust generated by the brushes in a conventional DC motor, and its low power consumption results in a tool that runs cooler, even under demanding applications.

The CESL8 Series 32VDC Brushless Screwdriver can be used with either the standard BECT620C/820(N) Hi/Lo Speed Controller or with our BECT832(N)-SSO-V4.0 FASTEN/COUNT/VERIFY Controller for applications requiring batch counting and input/output interface with external equipment.

- Precise torque control, low torque reaction
- Quiet, brushless DC motor means no carbon dust — 3 year motor warranty
- Compact body design results in exceptional maneuverability and operator comfort
- Less heat build-up and higher duty cycle capabilities than conventional brush motors
- Optional ESD-safe housing available
- CE/RoHS compliant

Tool Includes



6 PIN, 2m
TOOL CABLE



TORQUE LOCK SLEEVE



PH 1/4" HEX BITS



0.2–26.0 in-lbs (0.02–2.94 Nm)

Model Number		Start Type	Torque Range		Speed (rpm)	Driver Bit Type	Length mm / in	Diameter mm / in	Weight g / lbs	
Standard Housing	ESD Housing		in-lbs	Nm						
—	CESL810-ESD	Lever	0.2–3.1	0.02–0.35	1000 / 700	1/4" hex*	185 / 7.3	32 / 1.3	385 / 0.8	
—	CESL810S-ESD				500 / 350					
—	CESL811-ESD		0.4–6.2	0.05–0.69	1000 / 700					
—	CESL812-ESD				1000 / 700					
—	CESL812S-ESD		0.9–8.7	0.1–0.98	280					
—	CESL812P-ESD	Push	1.8-8.7	0.2-0.98	1000 / 700	1/4" hex	245 / 9.6	36 / 1.4	520 / 1.1	
CESL823	CESL823-ESD	Lever	1.3–10.5	0.15–1.18	1000 / 700					
CESL823P	CESL823P-ESD	Push			2000					
CESL823F	CESL823F-ESD	Lever								
CESL823PF	CESL823PF-ESD	Push								
CESL824	CESL824-ESD	Lever	2.6–16.5	0.29–1.86	1000 / 700					
	CESL824S-ESD				500					
CESL824P	CESL824P-ESD	Push			1000 / 700					
	CESL824PS-ESD				500					
CESL824F	CESL824F-ESD	Lever	2.6–14.7	0.29–1.67	2000					
CESL824PF	CESL824PF-ESD	Push								
—	CESL827B-ESD**	Lever	8.7–26.0	0.98–2.94	1200 / 900	1/4" hex	278 / 10.9	39.5 / 1.6	800 / 1.8	
—	CESL827BP-ESD**	Push								

*Drivers available with optional 4mm round (winged bit) bit holder — Add suffix '-4mm' to model number

**CESL827B(P)-ESD is for hard joint, non-prevailing torque applications below 20% duty cycle. Use 40V model CESL828 for more demanding requirements.



7370 Commercial Circle, Fort Pierce, FL 34951

☎ 772.465.4302

www.deltaregis.com

sales@deltaregis.com