

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

SDS No.: 213458

V004.0

Revision: 18.03.2025

printing date: 19.03.2025

Replaces version from: 22.10.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE ECCOBOND FP4531

LOCTITE ECCOBOND FP4531 UFI: SP8E-3XQD-020H-UTVA

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Encapsulant

1.3. Details of the supplier of the safety data sheet

Henkel Ireland

Operations and Research Limited Tallaght Business Park, Whitestown

24 Dublin

Ireland

Phone: +353 (0353) 1 404 6444

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

00353 14046280

National Poisons Information Centre: Members of Public: +353 (1) 809 2166. (8.00 a.m. to 10.00 p.m. 7 days a week) Healthcare Professionals: +353 (1) 809 2566 (24-hour service)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye damage Category 1

H318 Causes serious eye damage.

Respiratory sensitizer Category 1

 $H334 \quad May \ cause \ allergy \ or \ asthma \ symptoms \ or \ breathing \ difficulties \ if \ inhaled.$

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Germ cell mutagenicity Category 2

H341 Suspected of causing genetic defects.

Chronic hazards to the aquatic environment Category 3

H412 Harmful to aquatic life with long lasting effects.

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 2 of 16

V004.0

2.2. Label elements

Label elements (CLP):



Contains hexahydromethylphthalic anhydride

1,6-Naphthalenediol diglycidyl ether Bisphenol-F epichlorhydrin resin; MW<700

Signal word:	Danger
Hazard statement:	H315 Causes skin irritation.
	H317 May cause an allergic skin reaction.
	H318 Causes serious eye damage.
	H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
	H341 Suspected of causing genetic defects.
	H412 Harmful to aquatic life with long lasting effects.
Precautionary statement:	P261 Avoid breathing vapors.
Prevention	P273 Avoid release to the environment.
	P280 Wear protective gloves/protective clothing/eye protection/face protection.
	
Precautionary statement:	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
Response	P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
	P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

LOCTITE ECCOBOND FP4531 Page 3 of 16

V004.0

SDS No.: 213458

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
hexahydromethylphthalic anhydride 25550-51-0 247-094-1 01-2119845474-33	10- < 20 %	Eye Dam. 1, H318 Skin Sens. 1, H317 Resp. Sens. 1, H334		SVHC
1,6-Naphthalenediol diglycidyl ether 27610-48-6 429-960-2	5- < 10 %	Muta. 2, H341 Acute Tox. 4, Dermal, H312 Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Irrit. 2, H319 Aquatic Chronic 3, H412	oral:ATE = 2.500 mg/kg	
Bisphenol-F epichlorhydrin resin; MW<700 500-006-8 01-2119454392-40	5-< 10 %	Skin Irrit. 2, H315 Skin Sens. 1A, H317 Aquatic Chronic 2, H411		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

RESPIRATORY: Irritation, coughing, shortness of breath, chest tightness.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

SKIN: Redness, inflammation.

After eye contact: Corrosive, may cause permanent damage to eyes (impairment of vision).

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

V004.0

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Good industrial hygiene practices should be observed.

Do not eat, drink or smoke while working.

Wash hands before work breaks and after finishing work.

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container.

Protect against contamination.

Store in a cool, dry place.

Ensure that storage and workrooms are adequately ventilated.

Must be stored in a room with spill collection facilities.

Keep away from heat and direct sunlight.

Refer to Technical Data Sheet.

7.3. Specific end use(s)

Encapsulant

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 5 of 16

V004.0

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silica, vitreous 60676-86-0 [SILICA, FUSED]		0,08	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS]		6	Time Weighted Average (TWA):		IR_OEL
Silicon dioxide 7631-86-9 [SILICA, AMORPHOUS]		2,4	Time Weighted Average (TWA):		IR_OEL

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Silica, vitreous 60676-86-0 [SILICA, FUSED, RESPIRABLE DUST]		0,08	Time Weighted Average (TWA):		EH40 WEL
Si-oxide amorphous (fumed) 7631-86-9 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Si-oxide amorphous (fumed) 7631-86-9 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Si-oxide amorphous (fumed) 7631-86-9 [Silica, amorphous, inhalable dust]		6	Time Weighted Average (TWA):		EH40 WEL
Si-oxide amorphous (fumed) 7631-86-9 [Silica, amorphous, respirable dust]		2,4	Time Weighted Average (TWA):		EH40 WEL

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 6 of 16

V004.0

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
		F	mg/l	ppm	mg/kg	others	
Hexahydromethylphthalic anhydride 25550-51-0	aqua (freshwater)		0,1 mg/l				
Hexahydromethylphthalic anhydride 25550-51-0	aqua (marine water)		0,01 mg/l				
Hexahydromethylphthalic anhydride 25550-51-0	sewage treatment plant (STP)		2,19 mg/l				
Hexahydromethylphthalic anhydride 25550-51-0	sediment (freshwater)				2,69 mg/kg		
Hexahydromethylphthalic anhydride 25550-51-0	sediment (marine water)				0,269 mg/kg		
Hexahydromethylphthalic anhydride 25550-51-0	Air						no hazard identified
Hexahydromethylphthalic anhydride 25550-51-0	Soil				0,603 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin)	aqua (freshwater)		0,003 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin)	aqua (marine water)		0,0003 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin)	sewage treatment plant (STP)		10 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin)	sediment (freshwater)				0,294 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin)	sediment (marine water)				0,0294 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin)	Soil				0,237 mg/kg		
Reaction mass bisphenol-F-(epichlorhydrin)	aqua (intermittent releases)		0,0254 mg/l				
Reaction mass bisphenol-F-(epichlorhydrin)	Air						no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin)	Predator						no potential for bioaccumulation

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Reaction mass bisphenol-F-(epichlorhydrin)	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m3	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin)	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin)	Workers	dermal	Acute/short term exposure - local effects		0,0083 mg/cm2	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin)	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m3	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin)	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	no hazard identified
Reaction mass bisphenol-F-(epichlorhydrin)	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	no hazard identified

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 7 of 16

V004.0

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly

ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid Colour Black

Odor little intrinsic odour

Physical state liquid

Melting point Not applicable, Product is a liquid

Initial boiling point Not applicable, Polymerizes before boiling point is reached.

Flammability The product is not flammable.

Explosive limits Not available., The product is not flammable. Explosive limits Not applicable, The product is not flammable.

Flash point $> 121,00 \,^{\circ}\text{C} (> 249.8 \,^{\circ}\text{F})$

Auto-ignition temperature Not applicable, The product is not flammable.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

pH Not applicable, Product is non-soluble (in water).

Viscosity (kinematic) Currently under determination

Viscosity, dynamic 5.000 - 15.000 cp COI OLN 2B; Stress Rheology

(Cone and plate; Instrument: HBT; 25 °C (77 °F); speed of rotation: 10 min-1; Spindle No: 52)

Solubility (qualitative) Not miscible or difficult to mix

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 8 of 16

V004.0

(20 °C (68 °F); Solvent: Water)

Solubility (qualitative) Partially miscible

(20 °C (68 °F); Solvent: ketones)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure Not available.

Density 1,7 g/cm3 no method / method unknown $(20 ^{\circ}\text{C} (68 ^{\circ}\text{F}))$

Relative vapour density:

Particle characteristics

Not applicable
Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants. Reaction with strong acids.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
hexahydromethylphthalic	LD50	> 2.000 mg/kg	rat	EU Method B.1 tris (Acute Oral Toxicity)
anhydride				
25550-51-0				
1,6-Naphthalenediol	LD50	> 2.000 mg/kg	rat	EPA OTS 798.1175 (Acute Oral Toxicity)
diglycidyl ether				
27610-48-6				
1,6-Naphthalenediol	Acute	2.500 mg/kg		Expert judgement
diglycidyl ether	toxicity			
27610-48-6	estimate			
	(ATE)			
Bisphenol-F	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
epichlorhydrin resin;				Toxicity)
MW<700				

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 9 of 16

V004.0

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
hexahydromethylphthalic anhydride 25550-51-0	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
1,6-Naphthalenediol diglycidyl ether 27610-48-6	LD50	> 1.000 - < 2.000 mg/kg	rat	EPA OTS 798.1100 (Acute Dermal Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

No data available.

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
hexahydromethylphthalic anhydride 25550-51-0	moderately irritating	24 h	rabbit	other guideline:
1,6-Naphthalenediol diglycidyl ether 27610-48-6	irritating		rabbit	EPA OTS 798.4470 (Acute Dermal Irritation)
Bisphenol-F epichlorhydrin resin; MW<700	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
1,6-Naphthalenediol	irritating		rabbit	EPA OTS 798.4500 (Acute Eye Irritation)
diglycidyl ether				
27610-48-6				
Bisphenol-F	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye
epichlorhydrin resin;				Irritation / Corrosion)
MW<700				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Test type	Species	Method
CAS-No.				
1,6-Naphthalenediol	sensitising	Buehler test	guinea pig	EPA OTS 798.4100 (Skin Sensitisation)
diglycidyl ether				
27610-48-6				
Bisphenol-F	Sub-Category 1A	Mouse local lymphnode	mouse	OECD Guideline 429 (Skin Sensitisation:
epichlorhydrin resin;	(sensitising)	assay (LLNA)		Local Lymph Node Assay)
MW<700		-		• •

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 10 of 16

V004.0

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
hexahydromethylphthalic anhydride 25550-51-0	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
hexahydromethylphthalic anhydride 25550-51-0	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
hexahydromethylphthalic anhydride 25550-51-0	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
1,6-Naphthalenediol diglycidyl ether 27610-48-6	negative	in vitro mammalian chromosome aberration test	with		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
1,6-Naphthalenediol diglycidyl ether 27610-48-6	positive	in vitro mammalian chromosome aberration test	without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Bisphenol-F epichlorhydrin resin; MW<700	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
1,6-Naphthalenediol diglycidyl ether 27610-48-6	positive	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)

Carcinogenicity

No data available.

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
hexahydromethylphthalic anhydride 25550-51-0	NOAEL P 450 mg/kg	screening	oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Bisphenol-F epichlorhydrin resin; MW<700	NOAEL P > 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two- generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 11 of 16

V004.0

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of	Species	Method
			treatment		
hexahydromethylphthalic	NOAEL 450 mg/kg	oral: gavage	28 d	rat	OECD Guideline 407
anhydride			once a day, 7 days a		(Repeated Dose 28-Day
25550-51-0			week		Oral Toxicity in Rodents)
Bisphenol-F	NOAEL 250 mg/kg	oral: gavage	13 w	rat	OECD Guideline 408
epichlorhydrin resin;			daily		(Repeated Dose 90-Day
MW<700					Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 12 of 16

V004.0

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
hexahydromethylphthalic anhydride 25550-51-0	LC50	500 mg/l	48 h	1	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol-F epichlorhydrin resin; MW<700	LC50	5,7 mg/l	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
hexahydromethylphthalic	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202
anhydride					(Daphnia sp. Acute
25550-51-0					Immobilisation Test)
Bisphenol-F epichlorhydrin	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202
resin; MW<700					(Daphnia sp. Acute
					Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol-F epichlorhydrin resin; MW<700	NOEC	0,3 mg/l	21 d	1	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 13 of 16

V004.0

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
hexahydromethylphthalic anhydride 25550-51-0	EC50	135 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
hexahydromethylphthalic anhydride 25550-51-0	NOEC	32 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
hexahydromethylphthalic anhydride 25550-51-0	EC20	95,3 mg/l	3 h	ζ.,	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
hexahydromethylphthalic anhydride 25550-51-0	not readily biodegradable.	aerobic	2 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Bisphenol-F epichlorhydrin resin; MW<700	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Bioconcentratio	Exposure time	Temperature	Species	Method
CAS-No.	n factor (BCF)				
hexahydromethylphthalic	11,12			calculated	QSAR (Quantitative Structure
anhydride					Activity Relationship)
25550-51-0					

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 14 of 16

V004.0

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
hexahydromethylphthalic anhydride 25550-51-0	2,59	25 °C	QSAR (Quantitative Structure Activity Relationship)
Bisphenol-F epichlorhydrin resin; MW<700	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
hexahydromethylphthalic anhydride	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
25550-51-0	Bioaccumulative (vPvB) criteria.
Bisphenol-F epichlorhydrin resin; MW<700	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
	Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 15 of 16

V004.0

SECTION 14: Transport information

14.1. UN number or ID number

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590): Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable Not applicable Not applicable

VOC content (2010/75/EC)

< 3 %

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SDS No.: 213458 LOCTITE ECCOBOND FP4531 Page 16 of 16

V004.0

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H341 Suspected of causing genetic defects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

Substance with a Union workplace exposure limit

EU EXPLD 1:

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.