

Technical Data Sheet

ROHS WEEE REACH COMPLANT lead-free

GlobalTech® Ink & Screen Cleaner

Product Description

GlobalTech Ink & Screen Cleaner (IKS) features an innovative formulation to remove conductive, resistive, and dielectric thick film inks, as well as commercial inks used in the electronics and commercial printing industries. This powerful cleaner safely removes pastes, silicones and flux residues without damaging fragile emulsions. Ideal for use as a general degreaser.

Features

Completely water soluble High flash point
Dries to zero residue Low toxicity
Fast evaporator Non-corrosive

Applications

Batch ultrasonic cleaners Misprinted discs Screen/stencils cleaners Screens, stencils and squeegees Tools, machinery and benches

Method of Use

Brush, wipe, spray, dip or immerse. Ideal for batch ultrasonic cleaners and screen/stencil cleaning machines. Use at room temperature, do not elevate above the flash point. Drying can be enhanced with a IPA rinse followed by an air knife. Not for vapor condensation cleaning. Solvent and rinse water may be separated by elevating temperature to approximately 212°F / 100°C.

Ingredients

Aliphatic Glycol Ethers, Aliphatic Ether Alcohol

Physical & Chemical Properties

· ··yorom or orrormom · · op or moo	
Appearance	Clear Colorless Liquid
Boiling Point (@ 30 mm Hg)	302°F / 150°C
Evaporation Rate (BuAc=1)	0.22
Flash Point TCC	119°F / 48°C
Melting/Freezing Point	-94°F / -70°C
Odor	Mild
% Volatile (by weight)	100
Solubility In Water	Complete
Specific Gravity (water=1)	0.88
Vapor Density (air=1)	4
Vapor Pressure (20°C @ mm Hg)	1.7
Viscosity	NA
VOC (g/L)	880

Hazard Data

Hazard Ratings

NFPA Health Hazard: 1, Flammability: 2, Instability: 0, Special Hazards: ND HMIS Health Hazard: 1, Flammability: 2, Instability: 0, Personal Protection: B

Environmental

Clean Air Act (CAA)

Global Warming Potential (GWP)

Hazardous Air Pollutant (HAP)

Ozone Depletion Potential (ODP)

Significant New Alternatives Policy (SNAP)

Superfund Amendments and Reauthorization Act (SARA)

Toxic Substance Control Act (TSCA Inventory)

Not Regulated

No Regulated

No Reportable

All Ingredients Listed

Material Compatibility

Not recommended for use on PVC, vinyl, acrylics or ABS plastics or Styrenes. May affect some painted surfaces and thermoplastics. If substrate is unknown, test sample area before general use. Pump and valve seals should be made of EPDM, Teflon® or Kalrez®.

Waste Disposal

For disposal methods, consult a licensed waste management firm or the appropriate local, state and federal agencies in your area. Liquid solvent can be reclaimed by distillation using the proper equipment or continuous filtered automatic cleaning equipment with built-in carbon or micro filtration. Foil Refill Packs for our SuperSaturated SmartWipes® canisters help reduce environmental waste.

Storage & Shelf Life

IKS has a 12 month shelf life from date of shipment. Store at room temperature.

Ordering Information

Drums	DR55IKS
Weight	444 lbs
Dimensions	24" x 36"
Gallons (HDPE), 4/cs	GA4IKS
Weight	34 lbs
Dimensions	16" x 10" x 13"
Foil Refill Packs (ESD safe), 100 ct, 6" x 9", 12/cs	FR100lKS-12
Weight	17 lbs
Dimensions	17" x 13" x 9"
Spray Bottles, 1 pint (16oz), 6/cs	SB6IKS
Weight	7 lbs
Dimensions	10" x 7" x 10"
SuperSaturated SmartWipes, 100 ct, 6" x 9", 12/cs	SW100IKS
Weight	21 lbs
Dimensions	16" x 11" x 16"

Availability

Products are available through global sales and a nationwide network of distributors.

Environmental Policy

As a leading manufacturer and supplier of SMT production supplies; JNJ is committed to providing high quality products and services in a manner that does not impact upon, but enhances the environment.

