

# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

#### **SECTION 1. IDENTIFICATION**

Product name : ARATHANE® 5750 A

Manufacturer or supplier's details

Company name of supplier

: Huntsman Advanced Materials Americas LLC

Address

Telephone

P.O. Box 4980 The Woodlands,

TX 77387

United States of America (USA)
: Non-Emergency: (800) 257-5547

E-mail address of person

responsible for the SDS

: Global\_Product\_EHS\_AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Component of a Polyurethane System.

#### **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 3

Acute toxicity (Inhalation) : Category 4

Skin irritation : Category 2

Eye irritation : Category 2B

Respiratory sensitisation : Category 1

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity

- single exposure

: Category 3 (Respiratory system)

Specific target organ toxicity

- repeated exposure

: Category 2 (Liver, Lungs, Kidney)

Short-term (acute) aquatic

hazard

: Category 3

#### **GHS** label elements



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 400001009196 1.1 03/16/2020 Date of first issue: 06/23/2017

Print Date 08/13/2020

Hazard pictograms







Signal word : Danger

: H226 Flammable liquid and vapour. Hazard statements

> H315 + H320 Causes skin and eye irritation. H317 May cause an allergic skin reaction.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (Liver, Lungs, Kidney)

through prolonged or repeated exposure.

H402 Harmful to aquatic life.

#### Precautionary statements

#### : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/

face protection.

P285 In case of inadequate ventilation wear respiratory protection.

#### Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsina.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.

P337 + P313 If eye irritation persists: Get medical advice/ attention.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

P362 Take off contaminated clothing and wash before reuse. P370 + P378 In case of fire: Use dry sand, dry chemical or

alcohol-resistant foam to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international

regulations.

#### Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

Chemical nature : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
4,4'-methylenediphenyl diisocyanate	101-68-8	50 - 70
Benzene, 1,1'-methylenebis[isocyanato-, homopolymer	39310-05-9	20 - 30
toluene	108-88-3	5 - 10
2,4'-methylenediphenyl diisocyanate	5873-54-1	1 - 5
triethyl phosphate	78-40-0	1 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Do not leave the victim unattended.

Get medical attention immediately if symptoms occur. Show this safety data sheet to the doctor in attendance.

If inhaled : If breathed in, move person into fresh air.

Call a physician or poison control centre immediately.

Keep patient warm and at rest. Keep respiratory tract clear. If breathing is difficult, give oxygen.

If breathing is irregular or stopped, administer artificial

respiration.

If unconscious, place in recovery position and seek medical

advice.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Consult a physician immediately if symptoms such as

shortness of breath or asthma are observed.

A hyper-reactive response to even minimal concentrations of diisocyanates may develop in sensitised persons.

The exposed person may need to be kept under medical

surveillance for 48 hours.

LC50 (rat): ca. 490 mg/m³ (4 hours): using experimentally produced respirable aerosol having aerodynamic diameter <5microns.

Methods used to generate the exposure concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for acute inhalation toxicity.

----

In case of skin contact

In case of contact, immediately flush skin with soap and plenty

Take off contaminated clothing and shoes immediately.

Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse.

Call a physician if irritation develops or persists.

An MDI study has demonstrated that a polyglycol-based skin cleanser (such as D-Tam™, PEG-400) or corn oil may be

more effective than soap and water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Protect unharmed eye.

Keep eye wide open while rinsing.

Seek medical advice.

If swallowed : Gently wipe or rinse the inside of the mouth with water.

DO NOT induce vomiting unless directed to do so by a

physician or poison control center.

Keep respiratory tract clear.

Keep at rest.

If a person vomits when lying on his back, place him in the

recovery position.

Never give anything by mouth to an unconscious person.

Take victim immediately to hospital. If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed

Severe allergic skin reactions, bronchiospasm and

anaphylactic shock

This product is a respiratory irritant and potential respiratory sensitiser: repeated inhalation of vapour or aerosol at levels above the occupational exposure limit could cause respiratory sensitisation.

Symptoms may include irritation to the eyes, nose, throat and lungs, possibly combined with dryness of the throat, tightness



# **ARATHANE® 5750 A**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/23/2017

 1.1
 03/16/2020
 400001009196
 Date of first issue: 06/23/2017

Print Date 08/13/2020

of chest and difficulty in breathing.

The onset of the respiratory symptoms may be delayed for

several hours after exposure.

A hyper-reactive response to even minimal concentrations of

MDI may develop in sensitised persons.

Protection of first-aiders : No action shall be taken involving any personal risk or without

suitable training.

It may be dangerous to the person providing aid to give

mouth-to-mouth resuscitation.

If potential for exposure exists refer to Section 8 for specific

personal protective equipment.

First Aid responders should pay attention to self-protection

and use the recommended protective clothing

Notes to physician : Symptomatic and supportive therapy as needed. Following

severe exposure medical follow-up should be monitored for at

least 48 hours.

The first aid procedure should be established in consultation

with the doctor responsible for industrial medicine.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Foam

Carbon dioxide (CO2)

Dry powder

Unsuitable extinguishing

media

Water may be used if no other available and then in copious

quantities. Reaction between water and hot isocyanate may

be vigorous.

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

The pressure in sealed containers can increase under the

influence of heat.

Exposure to decomposition products may be a hazard to

health.

Hazardous combustion

products

Combustion products may include: carbon monoxide, carbon

dioxide, nitrogen oxides, hydrocarbons and HCN. In the event of extreme heat (>500 degrees C), aniline is suspected of

being formed.

onig romioai

No hazardous combustion products are known

Specific extinguishing

methods

: Cool containers/tanks with water spray.

Further information : Standard procedure for chemical fires.

Due to reaction with water producing CO2-gas, a hazardous build-up of pressure could result if contaminated containers



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

are re-sealed.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Prevent fire extinguishing water from contaminating surface

water or the ground water system.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

Wear an approved positive pressure self-contained breathing

apparatus in addition to standard fire fighting gear.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Immediately evacuate personnel to safe areas.

Use personal protective equipment.

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

Ensure adequate ventilation.

Keep people away from and upwind of spill/leak.

Only qualified personnel equipped with suitable protective

equipment may intervene.

For additional precautions and advice on safe handling, see

section 7.

Never return spills in original containers for re-use.

Make sure that there is a sufficient amount of neutralizing/

absorbent material near the storage area.

The danger areas must be delimited and identified using

relevant warning and safety signs.

Treat recovered material as described in the section "Disposal

considerations".

For disposal considerations see section 13.

**Environmental precautions** 

: Do not allow uncontrolled discharge of product into the

environment.

Do not allow material to contaminate ground water system.

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages

cannot be contained.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Clean-up methods - small spillage

Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local /

national regulations (see section 13). Clean contaminated surface thoroughly.

Sweep up or vacuum up spillage and collect in suitable

container for disposal.

Neutralize small spillages with decontaminant.

The compositions of liquid decontaminants are given in

Section 16.

Remove and dispose of residues.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Clean-up methods - large spillage If the product is in its solid form:

Spilled MDI flakes should be picked up carefully.

The area should be vacuum cleaned to remove remaining

dust particles completely.

If the product is in its liquid form:

Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust). Leave to react for at least 30 minutes.

Shovel into open-top drums for further decontamination.

Wash the spillage area with water. Test atmosphere for MDI vapour.

Keep in suitable, closed containers for disposal.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Local/Total ventilation : Use only with adequate ventilation.

Advice on protection against

fire and explosion

Normal measures for preventive fire protection.

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : For personal protection see section 8.

Avoid formation of aerosol.

Do not breathe vapours or spray mist.

Do not breathe vapours/dust.

Do not swallow.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Avoid exposure - obtain special instructions before use. Smoking, eating and drinking should be prohibited in the

application area.

Provide sufficient air exchange and/or exhaust in work rooms.

Keep container closed when not in use.

Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national

regulations.

Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being

used.

Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)

Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated

place.

Keep in properly labelled containers.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Observe label precautions. Protect from moisture.

Electrical installations / working materials must comply with the

technological safety standards.

Containers which are opened must be carefully resealed and kept

upright to prevent leakage.

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 36 - 104 °F / 2 - 40 °C

Further information on

storage stability

No decomposition if stored and applied as directed.

#### **SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

# Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
4,4'-methylenediphenyl diisocyanate	101-68-8	TWA	0.005 ppm	ACGIH
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	OSHA Z-1
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm ((10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
2,4'-methylenediphenyl diisocyanate	5873-54-1	С	0.02 ppm 0.2 mg/m3	OSHA Z-1
		TWA	0.005 ppm 0.05 mg/m3	NIOSH REL
		С	0.02 ppm 0.2 mg/m3	NIOSH REL

#### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
toluene	108-88-3	Toluene	In blood	Prior to last shift of workwee	0.02 mg/l	ACGIH BEI



# **ARATHANE® 5750 A**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/23/2017

 1.1
 03/16/2020
 400001009196
 Date of first issue: 06/23/2017

	_	_	Print Date 08/	/13/2020
		k		
Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

## Personal protective equipment

Respiratory protection : Use a properly fitted, air-purifying or air-fed respirator

complying with an approved standard if a risk assessment

indicates this is necessary.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe

working limits of the selected respirator.

In emergency, non-routine and unknown exposure situations, including confined space entries, a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA)or a full facepiece pressure demand supplied air respirator (SAR) with auxiliary self-contained air

supply, should be used.

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Solvent-resistant gloves (butyl-rubber)

Material : Nitrile rubber Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Protective gloves should be worn when handling freshly made polyurethane products to avoid contact with trace residual materials which may be hazardous in contact with

skin.

Use chemical resistant gloves classified under Standard

EN374: protective gloves against chemicals and

microorganisms. Examples of glove materials that might provide suitable protection include: Butyl rubber, Chlorinated polyethylene, Polyethylene, Ethyl vinyl alcohol copolymers

laminated ("EVAL"), Polychloroprene (Neoprene\*),



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 400001009196 1.1 03/16/2020 Date of first issue: 06/23/2017

Print Date 08/13/2020

Nitrile/butadiene rubber ("nitrile" or "NBR"), Polyvinyl chloride

("PVC" or "vinyl"), Fluoroelastomer (Viton\*).

When prolonged or frequently repeated contact may occur, a glove with protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN374) is recommended.

When only brief contact is expected, a glove with protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN374) is recommended.

Notice: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all requisite workplace factors such as, but not limited to: other chemicals that may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), as well as instructions/specifications provided by the glove supplier

By industrial use of aprotic polar solvents for cleaning: Butyl rubber (0.7mm), Nitrile rubber (0.4mm), Chloroprene (0.5mm)

Eye protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. Chemical splash goggles.

Always wear eye protection when the potential for inadvertent

eye contact with the product cannot be excluded.

Please follow all applicable local/national requirements when selecting protective measures for a specific workplace. Ensure that eyewash stations and safety showers are close

to the workstation location. Eye wash bottle with pure water Tightly fitting safety goggles

Skin and body protection

Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Recommended:

Overall (preferably heavy cotton) or Tyvek-Pro Tech 'C',

Tyvek Pro 'F' disposable coverall.

Impervious clothing

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Protective measures

Personal protective equipment comprising: suitable protective

gloves, safety goggles and protective clothing

The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Ensure that eye flushing systems and safety showers are

located close to the working place.

Hygiene measures

: Handle in accordance with good industrial hygiene and safety

practice.

Wash face, hands and any exposed skin thoroughly after

handling.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Remove contaminated clothing and protective equipment

before entering eating areas.

When using do not eat, drink or smoke.

Contaminated work clothing should not be allowed out of the

workplace.

Wash hands before breaks and immediately after handling

the product.

Wash hands before breaks and at the end of workday.

When using do not eat or drink. When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : yellow

Odour : aromatic

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : No data is available on the product itself.

Flash point : 88 °F / 31 °C

Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : No data is available on the product itself.

Relative vapour density : No data is available on the product itself.

Relative density : No data is available on the product itself.

Density : 1.2 g/cm3

Solubility(ies)

Water solubility : Water reactive (68 °F / 20 °C)



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

Auto-ignition temperature

: No data is available on the product itself.

: No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Self-Accelerating

decomposition temperature

(SADT)

No data is available on the product itself.

Viscosity

Viscosity, dynamic : 30 mPa.s

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

#### **SECTION 10. STABILITY AND REACTIVITY**

Reactivity

Chemical stability
Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

: Stable under normal conditions.

Reaction with water (moisture) produces CO2-gas.

Exothermic reaction with materials containing active hydrogen

groups.

The reaction becomes progressively more vigorous and can be violent at higher temperatures if the miscibility of the reaction partners is good or is supported by stirring or by the

presence of solvents.

MDI is insoluble with, and heavier than water and sinks to the

bottom but reacts slowly at the interface.

A solid water-insoluble layer of polyurea is formed at the

interface by liberating carbon dioxide gas.

Conditions to avoid : Extremes of temperature and direct sunlight.

Exposure to air or moisture over prolonged periods.

Incompatible materials : Acids

Amines Bases Metals water

Hazardous decomposition

products

Combustion products may include: carbon monoxide, carbon dioxide, nitrogen oxides, hydrocarbons and HCN. In the event

of extreme heat (>500 degrees C), aniline is suspected of

being formed.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 400001009196 1.1 03/16/2020 Date of first issue: 06/23/2017

Print Date 08/13/2020

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : No data is available on the product itself.

exposure

**Acute toxicity** 

Acute oral toxicity - Product : Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity -

Product

: Assessment: The substance/mixture is not toxic on inhalation

as defined by dangerous goods regulations.

Remarks: Methods used to generate the exposure

concentrations in the animal studies use extreme laboratory conditions and does not represent actual exposure conditions of the material in the workplace, storage, transportation or expected use on the market due to the very low vapor pressure. Therefore, these test results cannot be used to for hazard classification of the material. Rather, an acute toxicity estimate is calculated based on weight of evidence and expert judgement and is used to justify a modified classification for

acute inhalation toxicity.

Acute toxicity estimate: 1.66 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: Calculation method

#### **Components:**

4,4'-methylenediphenyl diisocyanate:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg

Method: OECD Test Guideline 402

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg

Method: OECD Test Guideline 402

toluene:

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

2,4'-methylenediphenyl diisocyanate:

Acute dermal toxicity : LD50 (Rabbit, male and female): > 9,400 mg/kg

Method: OECD Test Guideline 402

triethyl phosphate:

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Acute toxicity (other routes of : No data available



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

administration)

#### Skin corrosion/irritation

#### **Components:**

4,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Method: OECD Test Guideline 404

Result: Irritating to skin.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rabbit Result: Skin irritation

toluene:

Species: Rabbit

Method: Directive 67/548/EEC, Annex V, B.4.

Result: Skin irritation

2,4'-methylenediphenyl diisocyanate:

Species: Rabbit Assessment: Irritant

Method: OECD Test Guideline 404

Result: Irritating to skin.

triethyl phosphate: Species: Rabbit

Assessment: No skin irritation Method: OECD Test Guideline 404

Result: No skin irritation

#### Serious eye damage/eye irritation

#### Components:

4,4'-methylenediphenyl diisocyanate:

Species: Rabbit

Result: Mild eye irritation

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rabbit

Result: Mild eye irritation

Method: OECD Test Guideline 405

toluene:

Species: Rabbit Result: No eye irritation

Method: OECD Test Guideline 405

2,4'-methylenediphenyl diisocyanate:

Species: Humans

Result: Irritation to eyes, reversing within 7 days

Assessment: Mild eye irritant
Method: OECD Test Guideline 405

Remarks: Mild eye irritation

triethyl phosphate:



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Species: Rabbit Result: Eye irritation

Method: OECD Test Guideline 405

# Respiratory or skin sensitisation

#### **Components:**

4,4'-methylenediphenyl diisocyanate:

Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429

Result: May cause sensitisation by skin contact.

**Exposure routes: Respiratory Tract** 

Species: Guinea pig

Result: May cause sensitisation by inhalation.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406

Result: May cause sensitisation by skin contact.

**Exposure routes: Respiratory Tract** 

Species: Guinea pig

Result: May cause sensitisation by inhalation.

toluene:

Exposure routes: Skin Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6. Result: Does not cause skin sensitisation.

2,4'-methylenediphenyl diisocyanate:

Exposure routes: Skin Species: Mouse

Assessment: May cause sensitisation by skin contact.

Result: Causes sensitisation.

**Exposure routes: Respiratory Tract** 

Species: Guinea pig

Assessment: May cause sensitisation by inhalation.

Result: Causes sensitisation.

triethyl phosphate: Exposure routes: Skin Species: Mouse

Method: OECD Test Guideline 429 Result: Does not cause skin sensitisation.

## Components:

4,4'-methylenediphenyl diisocyanate:

Assessment: May cause sensitisation by inhalation and skin contact.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Assessment: May cause sensitisation by inhalation and skin contact.

2,4'-methylenediphenyl diisocyanate:

Assessment: Mild eye irritation

# Germ cell mutagenicity

# **Components:**

4,4'-methylenediphenyl diisocyanate:

Genotoxicity in vitro : Concentration: 200 ug/plate

Metabolic activation: with and without metabolic activation

Method: Directive 67/548/EEC, Annex, B.13/14

Result: negative

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Genotoxicity in vitro : Concentration: ca 50 ug/plate

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

toluene:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

2,4'-methylenediphenyl diisocyanate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

triethyl phosphate:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Method: OECD Test Guideline 482

Result: negative

#### **Components:**

4,4'-methylenediphenyl diisocyanate:

Genotoxicity in vivo : Application Route: Inhalation

Exposure time: 3 Weeks Dose: 118 mg/m3

Method: OECD Test Guideline 474

Result: negative

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Genotoxicity in vivo : Application Route: Inhalation

Exposure time: 3 Weeks

Dose: 118 mg/m3

Method: OECD Test Guideline 474

Result: negative

toluene:

Genotoxicity in vivo : Application Route: Intraperitoneal injection



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Method: OPPTS 870.5385

Result: negative

2,4'-methylenediphenyl diisocyanate:

Genotoxicity in vivo : Application Route: Inhalation

Exposure time: 3 w Dose: 118 mg/m3

Method: OECD Test Guideline 474

Result: negative

triethyl phosphate:

Genotoxicity in vivo : Application Route: Intraperitoneal injection

Method: OECD Test Guideline 478

Result: negative

#### **Components:**

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Germ cell mutagenicity- : Animal testing did not show any mutagenic effects.

Assessment

# Carcinogenicity

#### **Product:**

Remarks: Rats have been exposed for two years to a respirable aerosol of polymeric MDI which resulted in a chronic pulmonary irritation at high concentrations. Only at the top level (6 mg/m3), there was a significant incidence of a benign tumour of the lung (adenoma) and one malignant tumour (adenocarcinoma). There were no lung tumours at 1 mg/m3 and no effects at 0.2 mg/m3. Overall, the tumour incidence, both benign and malignant, and the number of animals with the tumours were not different from controls. The increased incidence of lung tumours is associated with prolonged respiratory irritation and the concurrent accumulation of yellow material in the lung, which occurred throughout the study. In the absence of prolonged exposure to high concentrations leading to chronic irritation and lung damage, it is highly unlikely that tumour formation will occur.

Remarks: Industrial use of aprotic polar solvents for cleaning can release hazardous primary aromatic amines (>0.1%)

Based on animal studies, primary aromatic amines are considered as potential carcinogen to humans. Some of those chemicals are proven carcinogens to humans

Provided the recommended personal protective equipment and hygiene measures are applied, no adverse effects to human health are to be expected

Carcinogenicity - : No data available

Assessment

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

#### Reproductive toxicity

## **Components:**

toluene:

Effects on fertility : Species: Rat, male and female

Application Route: Inhalation

General Toxicity - Parent: No observed adverse effect level:

1.875 mg/l

General Toxicity F1: No observed adverse effect level: 1.875

mq/l

Symptoms: Reduced foetal weight Method: OECD Test Guideline 416

#### 2,4'-methylenediphenyl diisocyanate:

Species: Rat, female Application Route: Inhalation Method: OECD Test Guideline 414

Result: Animal testing did not show any effects on fertility.

Species: Rat, male and female Application Route: Inhalation Method: OECD Test Guideline 414

Result: Animal testing did not show any effects on fertility.

## **Components:**

4,4'-methylenediphenyl diisocyanate:

Effects on foetal : Species: Rat, female

development Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level: 4

mg/m<sup>3</sup>

Method: OECD Test Guideline 414 Result: No teratogenic effects

#### Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level: 4

mg/m<sup>3</sup>

Method: OECD Test Guideline 414 Result: No teratogenic effects

toluene:

Species: Rat, female

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

2,812 mg/m<sup>3</sup>

Method: Other guidelines Result: No teratogenic effects

#### 2,4'-methylenediphenyl diisocyanate:

Species: Rat, male and female



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level: 4

mg/m<sup>3</sup>

Method: OECD Test Guideline 414 Result: No teratogenic effects

triethyl phosphate:

Species: Rat

Application Route: Oral

General Toxicity Maternal: No observed adverse effect level:

125 mg/kg body weight

Method: OECD Test Guideline 414 Result: No teratogenic effects

# **Components:**

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Reproductive toxicity - : No evidence of adverse effects on sexual function and fertility,

Assessment or on development, based on animal experiments.

toluene:

Reproductive toxicity - : Some evidence of adverse effects on development, based on

Assessment animal experiments.

## STOT - single exposure

#### Components:

4,4'-methylenediphenyl diisocyanate:

Exposure routes: Inhalation
Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Exposure routes: inhalation (dust/mist/fume)

Target Organs: Respiratory Tract

Assessment: May cause respiratory irritation.

toluene:

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

2,4'-methylenediphenyl diisocyanate:

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single

exposure, category 3 with respiratory tract irritation.

#### STOT - repeated exposure

## **Components:**

toluene:

Target Organs: Liver, Lungs, Kidney



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Assessment: May cause damage to organs through prolonged or repeated exposure.

#### Repeated dose toxicity

#### **Components:**

4,4'-methylenediphenyl diisocyanate: Species: Rat, male and female

NOEC: 0.2 mg/m3 Exposure time: 2 yr Number of exposures: 5 d

Method: OECD Test Guideline 453

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Species: Rat, male and female

NOEC: 0.2 mg/m3

Test atmosphere: dust/mist

Exposure time: 2 yr Number of exposures: 5 d

Method: OECD Test Guideline 453

toluene:

Species: Rat, male and female LOEC: 625 mg/kg, 600 ppm Application Route: Ingestion Test atmosphere: vapour Exposure time: 13 Weeks Number of exposures: 6 d

Method: OECD Test Guideline 453

2,4'-methylenediphenyl diisocyanate:

Species: Rat, male and female

NOEC: 0.2 mg/m3 Exposure time: 2 yr Number of exposures: 5 d

Method: OECD Test Guideline 453

triethyl phosphate:

Species: Rat, male and female

NOAEL: 1000 mg/kg Application Route: Ingestion

Exposure time: 4 Weeks Number of exposures: 7 d Method: Subacute toxicity

#### Components:

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Repeated dose toxicity - : No adverse effect has been observed in chronic toxicity

Assessment test

2,4'-methylenediphenyl diisocyanate:



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Repeated dose toxicity -

Assessment

: Mild eye irritation

#### **Aspiration toxicity**

#### **Components:**

toluene:

May be fatal if swallowed and enters airways.

#### **Experience with human exposure**

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

# Toxicology, Metabolism, Distribution

No data available

#### **Neurological effects**

No data available

#### **Further information**

Ingestion: No data available

#### **SECTION 12. ECOLOGICAL INFORMATION**

# **Ecotoxicity**

#### Components:

4,4'-methylenediphenyl diisocyanate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 203

toluene:



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Toxicity to fish : LC50: 5.5 mg/l

Exposure time: 96 h

Test Type: flow-through test Test substance: Fresh water

2,4'-methylenediphenyl diisocyanate:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 1,000 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

triethyl phosphate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water

Components:

4,4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

aquatic invertebrates Exposure time: 24 h
Test Type: static test

Test substance: Fresh water

Method: OECD Test Guideline 202

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

aquatic invertebrates Exposure time: 24 h

Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

toluene:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Ceriodaphnia dubia (Water flea)): 3.78 mg/l

Exposure time: 48 h

Test Type: Other guidelines Test substance: Fresh water

Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater

**Daphnids** 

2,4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

aquatic invertebrates Exposure time: 24 h

Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 202

triethyl phosphate:

Toxicity to daphnia and other : LC50: > 100 mg/l

aquatic invertebrates Exposure time: 96 h
Test Type: static test

Test Type: static test
Test substance: Fresh water

Components:



# **ARATHANE® 5750 A**

Version Revision Date: Date of last issue: 06/23/2017 SDS Number: 400001009196 1.1 03/16/2020 Date of first issue: 06/23/2017

Print Date 08/13/2020

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to algae/aquatic

: EC50 (Desmodesmus subspicatus (green algae)): > 1,640 ma/l

plants

Exposure time: 72 h

Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

triethyl phosphate:

Toxicity to algae/aquatic

: EC50 (Desmodesmus subspicatus (green algae)): 901 mg/l

plants

Exposure time: 72 h Test Type: static test

Test substance: Fresh water

M-Factor (Acute aquatic

toxicity)

: No data available

#### Components:

toluene:

Toxicity to fish (Chronic : NOEC: 1.39 mg/l Exposure time: 40 d

toxicity)

Test Type: flow-through test Test substance: Fresh water

#### Components:

4,4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 10 mg/l

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d Test Type: semi-static test Test substance: Fresh water Method: OECD Test Guideline 211

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

: NOEC (Daphnia magna (Water flea)): >= 10 mg/l Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d Test Type: semi-static test

Test substance: Fresh water Method: OECD Test Guideline 211

toluene:

Toxicity to daphnia and other

: NOEC (Ceriodaphnia dubia (Water flea)): 0.74 mg/l Exposure time: 7 d

aquatic invertebrates

Test Type: Other guidelines

(Chronic toxicity) Test substance: Fresh water

Method: Daphnid Chronic Toxicity Test

2.4'-methylenediphenyl diisocyanate:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): >= 10 mg/l

aquatic invertebrates (Chronic toxicity)

Exposure time: 21 d Test Type: semi-static test

Test substance: Fresh water Method: OECD Test Guideline 211

triethyl phosphate:

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 31.6 mg/l



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

aquatic invertebrates Exposure time: 21 d

(Chronic toxicity) Test substance: Fresh water

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

: No data available

**Components:** 

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

2,4'-methylenediphenyl diisocyanate:

Toxicity to microorganisms : EC50 (activated sludge): > 100 mg/l

Exposure time: 3 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 209

triethyl phosphate:

Toxicity to microorganisms : (Pseudomonas putida): 2,985 mg/l

Exposure time: 0.5 h
Test Type: static test
Test substance: Fresh water

**Components:** 

4,4'-methylenediphenyl diisocyanate:

Toxicity to soil dwelling : NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg

organisms Exposure time: 336 h

Method: OECD Test Guideline 207

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Toxicity to soil dwelling : EC50 (Eisenia fetida (earthworms)): > 1,000 mg/kg

organisms Exposure time: 336 h

Method: OECD Test Guideline 207

2,4'-methylenediphenyl diisocyanate:

Toxicity to soil dwelling : NOEC (Eisenia fetida (earthworms)): >= 1,000 mg/kg

organisms Exposure time: 336 h

Method: OECD Test Guideline 207

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial : No data available

organisms

**Ecotoxicology Assessment** 

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

#### Persistence and degradability

#### Components:

4,4'-methylenediphenyl diisocyanate:

Biodegradability : Inoculum: Domestic sewage

Concentration: 30 mg/l Result: Not biodegradable Biodegradation: 0 % Exposure time: 28 d

Method: Inherent Biodegradability: Modified MITI Test (II)

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Biodegradability : Inoculum: Domestic sewage

Concentration: 30 mg/l Result: Not biodegradable Biodegradation: 0 % Exposure time: 28 d

Method: Inherent Biodegradability: Modified MITI Test (II)

toluene:

Biodegradability : Inoculum: Sewage (STP effluent)

Concentration: 10 mg/l Result: Readily biodegradable.

Biodegradation: 81 % Exposure time: 5 d

2,4'-methylenediphenyl diisocyanate:

Biodegradability : Inoculum: Domestic sewage

Concentration: 30 mg/l Result: Not biodegradable Biodegradation: 0 % Exposure time: 28 d

Method: Inherent Biodegradability: Modified MITI Test (II)

triethyl phosphate:

Biodegradability : Inoculum: activated sludge

Result: Not readily biodegradable.

Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Inoculum: activated sludge Result: Inherently biodegradable.

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 302B



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Biochemical Oxygen

Demand (BOD)

: No data available

Chemical Oxygen Demand

(COD)

: No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon

(DOC)

: No data available

Physico-chemical

removability

: No data available

#### Components:

4,4'-methylenediphenyl diisocyanate:

Stability in water : Degradation half life(DT50): 20 hrs (77 °F / 25 °C)

Remarks: Fresh water

triethyl phosphate:

Stability in water : Degradation half life(DT50): 5.5 yr (77 °F / 25 °C) pH: 7

Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage

**Treatment** 

: No data available

#### Bioaccumulative potential

#### Components:

4,4'-methylenediphenyl diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200 Remarks: Bioaccumulation is unlikely.

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200 Remarks: Bioaccumulation is unlikely.

2,4'-methylenediphenyl diisocyanate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 200 Remarks: Bioaccumulation is unlikely.

triethyl phosphate:

Bioaccumulation : Species: Cyprinus carpio (Carp)

Bioconcentration factor (BCF): 0.5 - 0.8

Exposure time: 42 d



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Test substance: Fresh water Method: semi-static test

**Components:** 

4,4'-methylenediphenyl diisocyanate:

Partition coefficient: n- : log Pow: 4.51 (68 °F / 20 °C)

octanol/water pH: 7

Method: OECD Test Guideline 117

Benzene, 1,1'-methylenebis[isocyanato-, homopolymer:

Partition coefficient: n- : log Pow: 8.56 (68 °F / 20 °C)

octanol/water

toluene:

Partition coefficient: n- : log Pow: 2.73 (68 °F / 20 °C)

octanol/water pH: 7

2,4'-methylenediphenyl diisocyanate:

Partition coefficient: n- : log Pow: 4.51 (68 °F / 20 °C)

octanol/water pH: 7

Method: OECD Test Guideline 117

triethyl phosphate:

Partition coefficient: n- : log Pow: 1.11

octanol/water Method: Partition coefficient

Mobility in soil

Mobility : No data available

**Components:** 

toluene:

Distribution among : Koc: 34 - 120

environmental compartments Method: OECD Test Guideline 312

Stability in soil : No data available

Other adverse effects

Environmental fate and

pathways

: No data available

Results of PBT and vPvB

assessment

: No data available

Endocrine disrupting

potential

: No data available

Adsorbed organic bound

halogens (AOX)

: No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I



**ARATHANE® 5750 A** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological

information

: No data available

Global warming potential

(GWP)

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods** 

Waste from residues : Do not dispose of waste into sewer.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

# **SECTION 14. TRANSPORT INFORMATION**

# International Regulations

**IATA** 

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : III

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

: 366

Packing instruction : 355

(passenger aircraft)

**IMDG** 

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

 Class
 : 3

 Packing group
 : III

 Labels
 : 3

 EmS Code
 : F-E, S-E

 Marine pollutant
 : no



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

# **National Regulations**

**DOT Classification** 

UN/ID/NA number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3 Packing group : III

Labels : FLAMMABLE LIQUID

ERG Code : 127 Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

# EPCRA - Emergency Planning and Community Right-to-Know Act CERCLA Reportable Quantity

Components	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
4,4'-methylenediphenyl	101-68-8	5000	8234
diisocyanate			
toluene	108-88-3	1000	12500
benzene	71-43-2	10	*
acetone	67-64-1	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Acute toxicity (any route of exposure) Respiratory or skin sensitisation

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

4,4'-methylenediphenyl 101-68-8  $\Rightarrow$  50 - < 70 %

diisocyanate

toluene 108-88-3 >= 5 - < 10 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

101-68-8

Print Date 08/13/2020

4,4'-methylenediphenyl

diisocyanate

toluene 108-88-3

## California Prop. 65

WARNING: This product can expose you to chemicals including benzene, naphthalene, ethylbenzene, cumene, which is/are known to the State of California to cause cancer, and toluene, benzene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

# The components of this product are reported in the following inventories:

CH INV : The formulation contains substances listed on the Swiss

Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

# US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.



# **ARATHANE® 5750 A**


Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Liquid decontaminants (percentages by weight or volume):

Decontaminant 1 : \*- sodium carbonate : 5 - 10 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 2 : \*- concentrated ammonia solution : 3 - 8 % \*- liquid detergent : 0.2 - 2 % \*- water : to make up to 100 %

Decontaminant 1 reacts slower with diisocyanates but is more environmentally friendly than decontaminant 2.

Decontaminant 2 contains ammonia. Ammonia presents health hazards. (See supplier safety information.)

Revision Date : 03/16/2020

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

NIOSH REL / C : Ceiling value not be exceeded at any time.

OSHA Z-1 / C : Ceiling

OSHA Z-2 / TWA : 8-hour time weighted average OSHA Z-2 / CEIL : Acceptable ceiling concentration

OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling

concentration for an 8-hr shift

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.



# **ARATHANE® 5750 A**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009196 Date of first issue: 06/23/2017

Print Date 08/13/2020

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

#### **SECTION 1. IDENTIFICATION**

Product name : ARATHANE® 5750 B(LV)

Manufacturer or supplier's details

Company name of supplier

: Huntsman Advanced Materials Americas LLC

Address

P.O. Box 4980 The Woodlands, TX 77387

United States of America (USA)

Telephone : Non-Emergency: (800) 257-5547

E-mail address of person responsible for the SDS

: Global Product EHS AdMat@huntsman.com

Emergency telephone number : Chemtrec: (800) 424-9300 or (703) 527-3887

Recommended use of the chemical and restrictions on use

Recommended use : Component used for the manufacture of electrical insulation

parts

# **SECTION 2. HAZARDS IDENTIFICATION**

GHS classification in accordance with 29 CFR 1910.1200

Flammable liquids : Category 2

Serious eye damage : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity

- repeated exposure

: Category 2 (Liver, Lungs, Kidney)

Short-term (acute) aquatic

hazard

: Category 3

**GHS** label elements

Hazard pictograms







Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H318 Causes serious eye damage.

H361d Suspected of damaging the unborn child.

H373 May cause damage to organs (Liver, Lungs, Kidney)

through prolonged or repeated exposure.



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

H402 Harmful to aquatic life.

Precautionary statements

#### : Prevention:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read

and understood.

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

# Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor.

P308 + P313 IF exposed or concerned: Get medical advice/ attention.

P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

#### Storage:

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

# Other hazards

None known.

#### **SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS**

Substance / Mixture : Mixture

#### **Hazardous components**

Chemical name	CAS-No.	Concentration (% w/w)
toluene	108-88-3	5 - 10
butanone	78-93-3	5 - 10
1,1'-phenyliminodipropan-2-ol	3077-13-2	3 - 5

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.



**ARATHANE® 5750 B(LV)** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

#### **SECTION 4. FIRST AID MEASURES**

General advice : Move out of dangerous area.

Consult a physician.

Show this safety data sheet to the doctor in attendance.

Treat symptomatically.

Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.

If on skin, rinse well with water. If on clothes, remove clothes.

In case of eye contact : Small amounts splashed into eyes can cause irreversible

tissue damage and blindness.

In the case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

Continue rinsing eyes during transport to hospital.

Remove contact lenses.

Keep eye wide open while rinsing.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician. Take victim immediately to hospital.

Most important symptoms and effects, both acute and

delayed

None known.

Notes to physician : Treat symptomatically.

#### **SECTION 5. FIREFIGHTING MEASURES**

Suitable extinguishing media : Alcohol-resistant foam

Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: No hazardous combustion products are known



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Specific extinguishing

methods

: No data is available on the product itself.

Further information : Collect contaminated fire extinguishing water separately. This

must not be discharged into drains.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored

separately in closed containments.

Use a water spray to cool fully closed containers.

Special protective equipment

for firefighters

: Wear self-contained breathing apparatus for firefighting if

necessary.

#### **SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas.

Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

**Environmental precautions** 

Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

#### **SECTION 7. HANDLING AND STORAGE**

Advice on protection against : fire and explosion

Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge

(which might cause ignition of organic vapours).

Use only explosion-proof equipment.

Keep away from open flames, hot surfaces and sources of

ignition.

Advice on safe handling : Do not breathe vapours/dust.

Avoid exposure - obtain special instructions before use.

Avoid contact with skin and eyes. For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Container may be opened only under exhaust ventilation

hood.

Open drum carefully as content may be under pressure. To avoid spills during handling keep bottle on a metal tray.



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Dispose of rinse water in accordance with local and national

regulations.

Conditions for safe storage : No smoking.

Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept

upright to prevent leakage. Observe label precautions.

Keep in properly labelled containers.

Materials to avoid : For incompatible materials please refer to Section 10 of this

SDS.

Recommended storage

temperature

: 64 - 104 °F / 18 - 40 °C

Further information on

storage stability

Stable under normal conditions.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible	Basis
			concentration	
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	200 ppm	OSHA Z-2
		CEIL	300 ppm	OSHA Z-2
		Peak	500 ppm ((10 minutes)	OSHA Z-2
		TWA	100 ppm 375 mg/m3	NIOSH REL
		ST	150 ppm 560 mg/m3	NIOSH REL
butanone	78-93-3	TWA	200 ppm	ACGIH
		STEL	300 ppm	ACGIH
		TWA	200 ppm 590 mg/m3	OSHA Z-1
		TWA	200 ppm 590 mg/m3	NIOSH REL
		ST	300 ppm 885 mg/m3	NIOSH REL

#### **Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Samplin g time	Permissible concentratio n	Basis
toluene	108-88-3	Toluene	In blood	Prior to last shift of workwee k	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As	0.03 mg/l	ACGIH BEI



**ARATHANE® 5750 B(LV)** 

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/23/2017

 1.1
 03/16/2020
 400001009911
 Date of first issue: 06/23/2017

					Print Date 08	/12/2020
				soon as possible after exposure ceases)		
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI
butanone	78-93-3	methyl ethyl ketone	Urine	End of shift (As soon as possible after exposure ceases)	2 mg/l	ACGIH BEI

#### Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines

Recommended Filter type:

Combined particulates and organic vapour type

Filter type : Filter type A-P

Respiratory protection : In the case of vapour formation use a respirator with an

approved filter.

Hand protection

Material : butyl-rubber

Break through time : > 8 h

Material : Nitrile rubber Break through time : 10 - 480 min

Material : Ethyl Vinyl Alcohol Laminate (EVAL)

Break through time : > 8 h

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough.

Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of

contact).

The suitability for a specific workplace should be discussed

with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Tightly fitting safety goggles

Wear face-shield and protective suit for abnormal processing

problems.

Skin and body protection : Impervious clothing

Choose body protection according to the amount and

concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.

When using do not smoke.

Wash hands before breaks and at the end of workday.

#### **SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : liquid

Colour : amber

Odour : aromatic

Odour Threshold : No data is available on the product itself.

pH : No data is available on the product itself.

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

Boiling point : 174 °F / 79 °C

Flash point : 63 °F / 17 °C

Method: Tag closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper

flammability limit

: No data is available on the product itself.

Lower explosion limit / Lower

flammability limit

: No data is available on the product itself.

Vapour pressure : ca. 152 hPa

Relative vapour density : No data is available on the product itself.

Relative density : 0.92

Density : 0.92 g/cm3 (68 °F / 20 °C)

Solubility(ies)



# **ARATHANE® 5750 B(LV)**

Version Revision Date: Date of last issue: 06/23/2017 SDS Number: 400001009911 1.1 03/16/2020 Date of first issue: 06/23/2017

Print Date 08/12/2020

Water solubility : partly soluble (68 °F / 20 °C)

Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-

octanol/water

: No data is available on the product itself.

Auto-ignition temperature : No data is available on the product itself.

Thermal decomposition : No data is available on the product itself.

Self-Accelerating

decomposition temperature

(SADT)

No data is available on the product itself.

Viscosity

Viscosity, dynamic : ca. 1.000 mPa.s

Explosive properties No data is available on the product itself.

Oxidizing properties No data is available on the product itself.

Particle size No data is available on the product itself.

#### **SECTION 10. STABILITY AND REACTIVITY**

No dangerous reaction known under conditions of normal use. Reactivity

Stable under normal conditions. Chemical stability

Possibility of hazardous

reactions

: Vapours may form explosive mixture with air.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials Strong acids and strong bases

Strong oxidizing agents

Hazardous decomposition

products

Nitrogen oxides (NOx)

Carbon oxides

Burning produces noxious and toxic fumes.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

Information on likely routes of : No data is available on the product itself.

Acute toxicity

exposure

Acute oral toxicity - Product

: Acute toxicity estimate : > 5,000 mg/kg

Method: Calculation method

#### **Components:**



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 400001009911 1.1 03/16/2020 Date of first issue: 06/23/2017

Print Date 08/12/2020

toluene:

: LC50 (Rat, male and female): 28.1 mg/l Acute inhalation toxicity

Exposure time: 4 h

Test atmosphere: vapour

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

butanone:

Acute inhalation toxicity : LC50 (Rat): 34.5 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

**Components:** 

toluene:

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

butanone:

Acute dermal toxicity : LD50 (Rabbit, male): > 10 ml/kg

1,1'-phenyliminodipropan-2-ol:

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Acute toxicity (other routes of : No data available

administration)

Skin corrosion/irritation

Components:

toluene:

Species: Rabbit

Method: Directive 67/548/EEC, Annex V, B.4.

Result: Skin irritation

butanone: Species: Rabbit

Result: Mild skin irritation

1,1'-phenyliminodipropan-2-ol: Result: Mild skin irritation

Serious eye damage/eye irritation

**Components:** 

toluene:

Species: Rabbit



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Result: No eye irritation

Method: OECD Test Guideline 405

butanone: Species: Rabbit

Result: Irritating to eyes. Assessment: Irritant

Species: Rabbit Result: slight irritation

Assessment: Mild eye irritant Method: OECD Test Guideline 405

1,1'-phenyliminodipropan-2-ol:

Result: Risk of serious damage to eyes.

### Respiratory or skin sensitisation

### **Components:**

toluene:

Exposure routes: Skin Species: Guinea pig

Method: Directive 67/548/EEC, Annex V, B.6. Result: Does not cause skin sensitisation.

butanone:

Exposure routes: Skin Species: Guinea pig

Method: OECD Test Guideline 406 Result: Does not cause skin sensitisation.

Assessment: No data available

#### Germ cell mutagenicity

### Components:

toluene:

Genotoxicity in vitro : Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

#### Components:

toluene:

Genotoxicity in vivo : Application Route: Intraperitoneal injection

Method: OPPTS 870.5385

Result: negative

Germ cell mutagenicity-

Assessment

: No data available

### Carcinogenicity

### Components:

toluene:

Species: Rat, male and female



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Application Route: Inhalation Exposure time: 103 weeks

Dose: 4522 mg/m<sup>3</sup>

Frequency of Treatment: 6.5 hour Method: OECD Test Guideline 453

Result: negative

Target Organs: Respiratory Tract, Kidney

Carcinogenicity -

Assessment

: No data available

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or

equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

# Reproductive toxicity

#### **Components:**

toluene:

Effects on fertility : Species: Rat, male and female

Application Route: Inhalation

General Toxicity - Parent: No observed adverse effect level:

1.875 mg/l

General Toxicity F1: No observed adverse effect level: 1.875

mg/l

Symptoms: Reduced foetal weight Method: OECD Test Guideline 416

butanone:

Species: Rat, male and female

Application Route: Oral

Method: OECD Test Guideline 416

Result: No effects on fertility and early embryonic

development were detected.

**Components:** 

toluene:

Effects on foetal : Species: Rat, female

development Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

2,812 mg/m<sup>3</sup>

Method: Other guidelines Result: No teratogenic effects



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

butanone:

Species: Rat

Application Route: Inhalation

General Toxicity Maternal: No observed adverse effect level:

1,002 ppm

Method: OECD Test Guideline 414

Result: Teratogenic effects

**Components:** 

toluene:

Reproductive toxicity -

Assessment

: Some evidence of adverse effects on development, based on

animal experiments.

STOT - single exposure

**Components:** 

toluene:

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

butanone:

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

**Components:** 

toluene:

Target Organs: Liver, Lungs, Kidney

Assessment: May cause damage to organs through prolonged or repeated exposure.

Repeated dose toxicity

**Components:** 

toluene:

Species: Rat, male and female LOEC: 625 mg/kg, 600 ppm Application Route: Ingestion Test atmosphere: vapour Exposure time: 13 Weeks Number of exposures: 6 d

Method: OECD Test Guideline 453

butanone:

Species: Rat, male and female

NOEC: 5041 ppm

Test atmosphere: vapour Exposure time: 2,160 h Number of exposures: 5 d

Method: OECD Test Guideline 413



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Repeated dose toxicity -

Assessment

: No data available

### **Aspiration toxicity**

### **Components:**

toluene:

May be fatal if swallowed and enters airways.

#### **Experience with human exposure**

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

### Toxicology, Metabolism, Distribution

No data available

#### **Neurological effects**

No data available

#### **Further information**

**Product:** 

Remarks: Solvents may degrease the skin.

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

# Components:

toluene:

Toxicity to fish : LC50: 5.5 mg/l

Exposure time: 96 h

Test Type: flow-through test Test substance: Fresh water

butanone:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2,993 mg/l

Exposure time: 96 h
Test Type: static test
Test substance: Fresh water



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Method: OECD Test Guideline 203

**Components:** 

toluene:

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Ceriodaphnia dubia (Water flea)): 3.78 mg/l

Exposure time: 48 h

Test Type: Other guidelines Test substance: Fresh water

Method: Aquatic Invertebrate Acute Toxicity Test, Freshwater

**Daphnids** 

butanone:

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 308 mg/l

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 202

**Components:** 

butanone:

Toxicity to algae/aquatic

plants

: EgC50 (Selenastrum capricornutum (green algae)): 1,888

mg/i

Exposure time: 48 h Test Type: static test

Test substance: Fresh water Method: OECD Test Guideline 201

M-Factor (Acute aquatic

toxicity)

: No data available

**Components:** 

toluene:

Toxicity to fish (Chronic

toxicity)

: NOEC: 1.39 mg/l Exposure time: 40 d

> Test Type: flow-through test Test substance: Fresh water

Components:

toluene:

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Ceriodaphnia dubia (Water flea)): 0.74 mg/l

Exposure time: 7 d

Test Type: Other guidelines Test substance: Fresh water

Method: Daphnid Chronic Toxicity Test

M-Factor (Chronic aquatic

toxicity)

: No data available

Toxicity to microorganisms : No data available

Toxicity to soil dwelling

organisms

: No data available



# **ARATHANE® 5750 B(LV)**

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 06/23/2017

 1.1
 03/16/2020
 400001009911
 Date of first issue: 06/23/2017

Print Date 08/12/2020

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial

organisms

: No data available

Ecotoxicology Assessment

Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

Other organisms relevant to

the environment

: No data available

### Persistence and degradability

#### Components:

toluene:

Biodegradability : Inoculum: Sewage (STP effluent)

Concentration: 10 mg/l

Result: Readily biodegradable.

Biodegradation: 81 % Exposure time: 5 d

butanone:

Biodegradability : Inoculum: activated sludge

Concentration: 2 mg/l

Result: Readily biodegradable.

Biodegradation: 98 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Biochemical Oxygen

Demand (BOD)

: No data available

Chemical Oxygen Demand

(COD)

: No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon

(DOC)

: No data available

Physico-chemical

removability

: No data available

Stability in water : No data available



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Photodegradation : No data available

Impact on Sewage

Treatment

: No data available

Bioaccumulative potential

**Components:** 

butanone:

Bioaccumulation : Bioconcentration factor (BCF): 1

**Components:** 

toluene:

Partition coefficient: n- : log Pow: 2.73 (68 °F / 20 °C)

octanol/water pH: 7

butanone:

Partition coefficient: n- : log Pow: 0.3 (104 °F / 40 °C)

octanol/water pH: 7

Method: OECD Test Guideline 117

Mobility in soil

Mobility : No data available

**Components:** 

toluene:

Distribution among : Koc: 34 - 120

environmental compartments Method: OECD Test Guideline 312

butanone:

Distribution among : Koc: 29 - 34

environmental compartments

Stability in soil : No data available

Other adverse effects

Environmental fate and

pathways

: No data available

Results of PBT and vPvB

assessment

: No data available

**Endocrine disrupting** 

potential

: No data available

Adsorbed organic bound

halogens (AOX)

: No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was



**ARATHANE® 5750 B(LV)** 

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological information - Product

: An environmental hazard cannot be excluded in the event of

unprofessional handling or disposal.

Harmful to aquatic life.

Global warming potential

(GWP)

: No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

### **Disposal methods**

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not contaminate ponds, waterways or ditches with

chemical or used container.

Send to a licensed waste management company.

Dispose of as hazardous waste in compliance with local and

national regulations.

Dispose of contents/ container to an approved waste disposal

plant.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product. Do not re-use empty containers.

Do not burn, or use a cutting torch on, the empty drum.

#### **SECTION 14. TRANSPORT INFORMATION**

### International Regulations

IATA

UN/ID No. : UN 1866
Proper shipping name : Resin solution

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

\_\_\_

Packing instruction

(passenger aircraft)

: 353

364

**IMDG** 

UN number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3 Packing group : II



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Labels : 3 EmS Code : F-E, <u>S-E</u> Marine pollutant : no

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **National Regulations**

### **DOT Classification**

UN/ID/NA number : UN 1866

Proper shipping name : RESIN SOLUTION

Class : 3 Packing group : II

Labels : FLAMMABLE LIQUID

ERG Code : 127 Marine pollutant : no

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### **SECTION 15. REGULATORY INFORMATION**

# EPCRA - Emergency Planning and Community Right-to-Know Act

### **CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	11481
xylenes	1330-20-7	100	*
butanone	78-93-3	5000	*
benzene	71-43-2	10	*
buta-1,3-diene	106-99-0	10	*
acetone	67-64-1	5000	*
methanol	67-56-1	5000	*

<sup>\*:</sup> Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)

Reproductive toxicity

Specific target organ toxicity (single or repeated exposure)

Serious eye damage or eye irritation

SARA 313 : The following components are subject to reporting levels

established by SARA Title III, Section 313:

toluene 108-88-3 >= 5 - < 10 %

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

toluene 108-88-3



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

#### California Prop. 65

WARNING: This product can expose you to chemicals including 4-vinylcyclohexene, benzene, buta-1,3-diene, which is/are known to the State of California to cause cancer, and toluene, 4-vinylcyclohexene, benzene, buta-1,3-diene, methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

### The components of this product are reported in the following inventories:

CH INV : The formulation contains substances listed on the Swiss

Inventory

DSL : All components of this product are on the Canadian DSL

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : On the inventory, or in compliance with the inventory

TCSI : On the inventory, or in compliance with the inventory

TSCA : On the inventory, or in compliance with the inventory

#### **Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

#### TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.

# US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.



# **ARATHANE® 5750 B(LV)**


Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard

Revision Date : 03/16/2020

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

OSHA Z-2 : USA. Occupational Exposure Limits (OSHA) - Table Z-2

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday 8-hour time weighted average

OSHA Z-1 / TWA : 8-hour time weighted average OSHA Z-2 / TWA : 8-hour time weighted average OSHA Z-2 / CEIL : Acceptable ceiling concentration

OSHA Z-2 / Peak : Acceptable maximum peak above the acceptable ceiling

concentration for an 8-hr shift

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.



# **ARATHANE® 5750 B(LV)**

Version Revision Date: SDS Number: Date of last issue: 06/23/2017 1.1 03/16/2020 400001009911 Date of first issue: 06/23/2017

Print Date 08/12/2020

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.