Safety Data Sheet



Revision Number: 009.2 Issue date: 06/03/2025

1. IDENTIFICATION

IDH number:

Product name: LOCTITE SI 5040 RTV SILICONE

POTTING COMPOUND known as LOCTITE® 5040™ POTTING COMPOUND/ COMPUESTO PARA

ENCAPSULAR

Product type/ Silicone sealant

Recommended use:

Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Item number: 40404

Region: United States

Contact information:

Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center

735868

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

MEDICAL EMERGENCY Phone: Poison Control Center

1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

	OVERVIEW	

WARNING: H317 - MAY CAUSE AN ALLERGIC SKIN REACTION.

H319 - CAUSES SERIOUS EYE IRRITATION.

HAZARD CLASS	HAZARD CATEGORY
EYE IRRITATION	2A
SKIN SENSITIZATION	1

PICTOGRAM(S)



Precautionary Statements

Prevention: P261 - Avoid breathing mist/vapours.

P264 - Wash affected area thoroughly after handling.

P272 - Contaminated work clothing should not be allowed out of the workplace.

P280 - Wear protective gloves, eye protection, and face protection.

Response: P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P333+P313 - If skin irritation or rash occurs: Get medical attention. P337+P313 - If eye irritation persists: Get medical attention.

P362+P364 - Take off contaminated clothing and wash it before reuse.

Storage: Not prescribed

Disposal: P501 - Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Other hazards Not available.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Weight %*
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	68909-20-6	10 - 30
Trimethoxy(methyl)silane	1185-55-3	5 - 10
Methanol	67-56-1	0.1 - 1

^{*} Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

First Aid Measures by likely routes of exposure

Inhalation: Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give

artificial respiration. If symptoms develop and persist, get medical attention.

Skin contact: Wipe off paste with paper towel or cloth. Wash with soap and water. If skin

irritation persists, call a physician.

Eye contact: Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes.

Ingestion: Do not induce vomiting. Get medical attention.

Most important symptoms and effects (acute

and delayed):

IDH number: 735868

The most important known symptoms and effects, both acute and delayed, are

described in Section 11: Toxicological Information.

Indication of any immediate medical attention /

special treatment needed:

Not available.

5. FIRE FIGHTING MEASURES

Extinguishing media: Foam, dry chemical or carbon dioxide. Do not use high volume water jet.

Improper extinguishing agents: Not available.

Special firefighting procedures: Prevent inhalation of fumes and gases. Wear self-contained breathing

apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: In case of fire, keep containers cool with water spray.

Hazardous combustion products: Oxides of carbon. Oxides of silicon. Formaldehyde. Irritating vapors.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:Do not allow material to contaminate ground water system.

Clean-up methods: Maintain good ventilation for large spills. Scrape up as much material as

possible. Place scrap material in a well ventilated area and allow to cure to

ubber

Product name: LOCTITE SI 5040 RTV SILICONE POTTING COMPOUND known as LOCTITE® 5040™ POTTING COMPOUND/ COMPUESTO PARA ENCAPSULAR

7. HANDLING AND STORAGE

Handling: Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist.

Wash thoroughly after handling.

Storage: For safe storage, store between 8.0 °C (46.4 °F) and 28.0 °C (82.4 °F)

Store in a dry area below 90° F.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
None	None	None	None	None

Engineering controls: Provide adequate local exhaust ventilation to maintain worker exposure below

exposure limits.

Respiratory protection: Use NIOSH approved respirator if there is potential to exceed exposure

limit(s).

Eye/face protection: Safety goggles or safety glasses with side shields. Full face protection should

be used if the potential for splashing or spraying of product exists.

Skin protection:Use impermeable gloves and protective clothing as necessary to prevent skin

ontact.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Viscous, Translucent

Color:Off whiteOdor:no valuationOdor threshold:Not available.

pH: Not applicable, Product is non-soluble (in water).

Vapor pressure: < 10 mm hg (21.1 °C (70°F)) < 10 mm hg (20 °C (68°F))

Boiling point/range:

Not applicable, Not determined

Melting point/ range:

Not applicable, Product is a liquid

Density/Relative density:1.1 at 20 °C (68°F)Relative vapor density:20 °C Heavier than air

Flash point: > 93.3 °C (> 199.94 °F) Tagliabue closed cup

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not applicable

Flammability: The product is not flammable.

Evaporation rate: Not available.

Solubility: Polymerises in presence of water. Water Not applicable

Partition coefficient n-octanol/water Not available.

(logarithmic value):

IDH number: 735868

VOC content: 0.38 %

Dynamic viscosity: Not available.

Kinematic viscosity: > 20.5 mm2/s

Particle characteristics: Not applicable, Product is a liquid

Decomposition temperature: Not available.

10. STABILITY AND REACTIVITY

Stability: Stable under normal conditions of storage and use.

Hazardous reactions: None under normal processing.

Hazardous decomposition

products:

Oxides of carbon. Oxides of silicon. Irritating vapors. Formaldehyde. Contact with water

liberates methanol.

Incompatible materials: Acids. Bases. Oxidizing agents. Heat, sunlight, or UV light. Water. Alkaline earth metals.

Reactivity: Not available.

Conditions to avoid: Product is sensitive to light and moisture.

11. TOXICOLOGICAL INFORMATION

Likely routes of exposure: Skin, Inhalation, Eyes, Ingestion

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors from uncured sealant may cause respiratory tract irritation. Overexposure

to methanol formed during cure may cause drowsiness, nausea, and vomiting. When heated to

temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible

limit.

Skin contact: May cause allergic skin reaction. May cause skin irritation.

Eye contact: Causes serious eye irritation.

Ingestion: Not expected under normal conditions of use. May cause gastrointestinal tract irritation if

swallowed.

Hazardous Component(s)	LD50s and LC50s	
Silanamine, 1,1,1-trimethyl-N-(trimethylsilyl)-, hydrolysis products with silica	None	
Trimethoxy(methyl)silane	Inhalation LC50 (Rat, 4 h) = > 26000 ppm	
Methanol	Oral LD50 (Rat) = 5,628 mg/kg Oral LD50 (Mouse) = 7,300 mg/kg Oral LD50 (Rabbit) = 14.4 g/kg Dermal LD50 (Rabbit) = 15,800 mg/kg	

Hazardous Component(s)	Immediate Health Effects	Delayed Health Effects	Chronic Health Effects
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica			
Trimethoxy(methyl)silane	Irritant	Allergen	
Methanol	Irritant		Eyes Metabolic Nervous System

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Silanamine, 1,1,1-trimethyl-N- (trimethylsilyl)-, hydrolysis products with silica	No	No	No
Trimethoxy(methyl)silane	No	No	No
Methanol	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

IDH number: 735868

Product name: LOCTITE SI 5040 RTV SILICONE POTTING COMPOUND known as LOCTITE® 5040™ POTTING COMPOUND/ COMPUESTO PARA ENCAPSULAR

Page 4 of 6

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any packaging.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

International Air Transportation (ICAO/IATA)

Proper shipping name:Not regulatedHazard class or division:NoneIdentification number:NonePacking group:None

Water Transportation (IMO/IMDG)

Proper shipping name:
Hazard class or division:
Identification number:
Packing group:

None

None

None

None

None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status:

All components are listed as active or are exempt from listing on the Toxic Substances

Control Act (TSCA) inventory.

None above reporting de minimis

TSCA 12 (b) Export Notification:
CERCLA/SARA Section 302 EHS:

None above reporting de minimis.

CERCLA/SARA Section 311/312:

Please refer to the GHS classification in Section 2

CERCLA/SARA Section 313:

None above reporting de minimis.

California Proposition 65:

This product contains a chemical known to the State of California to cause birth defects or

other reproductive harm.

Canada Regulatory Information

IDH number: 735868

CEPA DSL/NDSL Status:

Contains one or more components listed on the Non-Domestic Substances List. All other components are listed on or are exempt from listing on the Domestic Substances List. Components listed on the NDSL must be tracked by all Canadian Importers of Record as required by Environment Canada. They may be imported into Canada in limited quantities. Please contact Regulatory Affairs for additional details.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 9

Prepared by: Product Safety and Regulatory Affairs

Issue date: 06/03/2025

Product name: LOCTITE SI 5040 RTV SILICONE POTTING COMPOUND known as LOCTITE® 5040™ POTTING COMPOUND/ COMPUESTO PARA ENCAPSULAR

Page 5 of 6

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.

IDH number: 735868