

Specification Sheet

Part Number: 151-00378



Clips can be connected to each other to create a chain of cable harnesses.

Secures firmly to surfaces to eliminate moisture and corrosion.

Quick and easy installation ideal for the production environment.

Automatic Harness Clip, Connectable, 1.1" Bundle Max, PA66HIRHS, Black, 500/pkg

Article Number	151-00378
----------------	-----------

Type	IAHC3AH
------	---------

Color	Black (BK)
-------	------------

Quantity Per	pack
--------------	------

Product Description	Automatic Harness Clips offer a simple and secure method of attaching cables to panels and other surfaces. When the cable is pushed inside, it automatically activates the locking features which causes it to close. These are also connectable which allows for multiple cables to be positioned next to each other. These come in various sizes to fit different bundle diameters.
---------------------	---

Short Description	Automatic Harness Clip, Connectable, 1.1" Bundle Max, PA66HIRHS, Black, 500/pkg
-------------------	---

Global Part Name	IAHC3AH-PA66HIRHS-BK
------------------	----------------------

Length L (Imperial)	1.6
---------------------	-----

Length L (Metric)	40.0
-------------------	------

Fixation Method	Fir Tree
-----------------	----------

Width W (Imperial)	0.4
--------------------	-----

Width W (Metric)	13.5
------------------	------

Bundle Diameter Min (Imperial)	0.75
--------------------------------	------

Bundle Diameter Min (Metric)	19.0
------------------------------	------

Bundle Diameter Max (Imperial)	1.1
--------------------------------	-----

Bundle Diameter Max (Metric)	28.0
------------------------------	------

Height H (Imperial)	2.5
---------------------	-----

Height H (Metric)	64.5
-------------------	------

Panel Thickness Min (Imperial)	0.03
--------------------------------	------

Panel Thickness Max (Imperial)	0.11
--------------------------------	------

Panel Thickness Min (Metric)	0.5
------------------------------	-----

Panel Thickness Max (Metric)	2.7
------------------------------	-----

Mounting Hole Diameter D (Imperial)	0.24 - 0.26 "
Mounting Hole Diameter D (Metric)	6.2 - 6.7 mm
Mounting Hole Diameter D Min (Imperial)	0.24
Mounting Hole Diameter D Max (Imperial)	0.26
Mounting Hole Diameter D Max (Metric)	6.7
Disc Diameter (Metric)	24.0
Disc Diameter (Imperial)	0.94
Material	Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL 94 HB
UV Resistant (Yes/No)	No
Use Conditions	For Indoor and Outdoor Use
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes

Package Quantity (Imperial)	500
Package Quantity (Metric)	500
Customs Number	3926909988

7930 N. Faulkner Road, Milwaukee, WI 53224
Phone: (800) 537-1512 | Email: corp@htamericas.com

© 2025 HellermannTyton. All Rights Reserved.
[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)