

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

1/03/2025

### 1. Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product Identity**

SAF-T-EZE NICKEL PREMIUM ANTI-SEIZE

**Alternate Names**

Part Numbers: 80612, 80622, 80627, 80637, 80653, 80657, 80660, 80665, 80678, 80689, 80699  
Product Type: Lubricating Grease

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Intended use**

See Technical Data Sheet.

**Application Method**

See Technical Data Sheet.

#### 1.3. Details of the supplier of the safety data sheet

**Company Name**

SAF-T-LOK International Corporation  
300 EISENHOWER LANE NORTH  
LOMBARD, IL 60148

**Emergency**

**CHEMTREC (USA)**

(800) 424-9300

**24 hour Emergency Telephone No.**

(703) 527-3887

**Customer Service: SAF-T-LOK International Corporation**

(630) 495-2001

### 2. Hazard identification of the product

#### 2.1. Classification of the substance or mixture

Skin Sensitization

Category 1

May cause an allergic skin reaction

Carcinogenicity

Category 2

Suspected of causing cancer

Specific Target Organ Toxicity  
(repeated exposure)

Category 1

Causes damage to organs (lung, respiratory system)  
through prolonged or repeated exposure

#### 2.2. Label elements

Using the Toxicity Data listed in section 11 and 12 the product is labeled as follows.



**Warning**

H313 May be harmful in contact with skin.

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### [Prevention]:

P273 Avoid release to the environment  
Obtain special instructions before use  
Do not breathe dust/fume/gas/mist/vapor/spray  
Wear protective gloves

### [Response]:

P390 Collect spillage  
Allergic skin reaction  
Suspected of causing cancer  
Causes damage to organs (lung, respiratory system) through prolonged or repeated exposure  
P312 Call a POISON CENTER or doctor / physician if you feel unwell.

### [Storage]:

No GHS storage statements

### [Disposal]:

No GHS disposal statements

## 3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Petroleum distillates, hydrotreated heavy naphthenic CAS Number: 0064742-52-5	50-70	Acute Tox. 4; H312	[1]
Graphite CAS Number: 0007782-42-5	8-30		[1]
Nickel CAS Number: 007440-02-0	8-30	Skin sensitization, 1; H317 Carcinogenicity, 2; H351	[1][2]
Aluminum CAS Number: 007429-90-5	1-10		[1][2]

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

\*The full texts of the phrases are shown in Section 16.

## 4. First aid measures

### 4.1. Description of first aid measures

#### General

In all cases of doubt, or when symptoms persist, seek medical attention.  
Never give anything by mouth to an unconscious person.

#### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.

#### Eyes

Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

**Skin** Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.

**Ingestion** If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

**Overview**

**Skin Contact:** Usually no effect, however, as with any chemical, prolonged, excessive, or repeated exposure may cause mild to moderate skin irritation, exhibited by redness, drying and cracking of unprotected skin.

**Eye Contact:** May irritate with slight pain and redness.

**Respiratory/ Inhalation:** Usually none, however, as with any chemical product, some irritation may occur.

**Ingestion:** Rinse mouth thoroughly if ingested. Do not induce vomiting. Amounts transferred to mouth by fingers, etc, during normal operation should not cause injury. Get medical attention if any discomfort continues.

Medical conditions generally aggravated by exposure: None known, however any chemical product may enhance allergies already present in certain individuals.

This product does not require exceptional labeling due to the evaluation procedure of the "General Classification guideline for preparations of the EU". See section 2 for further details.

**Skin** May be harmful in contact with skin. (Not adopted by US OSHA)

## 5. Fire-fighting measures

### 5.1. Extinguishing media

Recommended extinguishing media; alcohol resistant foam, CO<sub>2</sub>, powder, water spray.  
Do not use; water jet.

### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition: Oxides of carbon and sulfur

### 5.3. Advice for fire-fighters

Air mask and procedures for fighting chemical fires. Do not inhale gases.  
Treat as an oil fire. Use a full-faced self-contained breathing apparatus along with full protective gear. Keep nearby containers and equipment cool with a water stream.

**ERG Guide No.** ----

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### 6. Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

#### 6.2. Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

#### 6.3. Methods and material for containment and cleaning up

Prevent material from entering floor drains, sewers, or any bodies of water.

Scoop up into waste container or soak up with absorbent material. Store in a closed container until disposal.

### 7. Handling and storage

#### 7.1. Precautions for safe handling

See section 2 for further details. - [Prevention]:

#### 7.2. Conditions for safe storage, including any incompatibilities

No special precautions necessary if used properly. Avoid breathing vapors. Wash hands thoroughly at mealtime and end of shift.

Isolated storage facility/ warehouse not required. Store in a cool, dry location (60-90°F) in a well-ventilated area in original container. Keep container tightly closed when not in use.

Incompatible materials: Strong Oxidizing Agents, Strong Acids and Alkalis.

See section 2 for further details. - [Storage]:

#### 7.3. Specific end use(s)

None

### 8. Exposure controls and personal protection

#### 8.1. Control parameters

##### Exposure

CAS No.	Ingredient	Source	Value
0007782-42-5	Graphite	OSHA	TWA: 15 mg/m <sup>3</sup> TWA: 15 mppcf
		ACGIH	TWA: 2 mg/m <sup>3</sup>
		NIOSH	TWA: 2.5 mg/m <sup>3</sup> (resp)
		Supplier	No Established Limit
0007440-02-0	Nickel	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

0064742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0007429-90-5	Aluminum	OSHA	TWA: 15 mg/m <sup>3</sup> (Total) TWA 5 mg/m <sup>3</sup> (resp)
		ACGIH	TWA: 1.0 mg/m <sup>3</sup> revised 2008
		NIOSH	TWA 10 mg/m <sup>3</sup> (Total) TWA 5 mg/m <sup>3</sup> (resp)
		Supplier	No Established Limit

Contains mineral oil. The exposure limits for oil mist are 5 mg/m<sup>3</sup> OSHA PEL and 10 mg/m<sup>3</sup> ACGIH.

### Carcinogen Data

CAS No.	Ingredient	Source	Value
0007429-90-5	Aluminum	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007440-02-01	Nickel	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0007782-42-5	Graphite	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0064742-52-5	Petroleum distillates, hydrotreated heavy naphthenic	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;

## 8.2. Exposure controls

### Respiratory

No respiratory protection required, but normal good ventilation is recommended. Forced ventilation may be required if concentrations exceed normal use exposure.

### Eyes

Not required if application method is proper. Avoid contact with eyes.

### Skin

Wear overalls to keep skin contact to a minimum. Use impermeable gloves (neoprene, butyl rubber, natural rubber), as necessary to avoid skin contact, as well as proper clothing or plastic apron. Wash hands before eating, drinking, or using restroom.

### Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

### Other Work Practices

Eye wash stations should be located within 100 feet or 10 second walk of the work area. Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. - [Prevention]:

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### 9. Physical and chemical properties

Appearance	Silver Grey Paste
Odor	Mild/Inoffensive
Odor threshold	Not Measured
pH	Not determined
Melting point / freezing point	Not determined
Initial boiling point and boiling range	600 F (316 C)
Flash Point	350 F (C.O.C.)
Evaporation rate (Ether = 1)	Not determined
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	<b>Lower Explosive Limit:</b> N/A <b>Upper Explosive Limit:</b> N/A
Vapor pressure (Pa)	<0.1 @ 70 F (mm Hg.)
Vapor Density	N/D
Specific Gravity	1.28
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not Measured
Decomposition temperature	Not Measured
Viscosity (cSt)	Not Measured
VOC %	<0.1% (Organic solvents)%(cut)
% Solid	35-50

#### 9.2. Other information

DMSO extract by IP346: Less than 3.0 wt % (mineral oil component only)

### 10. Stability and reactivity

#### 10.1. Reactivity

Hazardous Polymerization will not occur.

#### 10.2. Chemical stability

Stable under normal circumstances.

#### 10.3. Possibility of hazardous reactions

No data available.

#### 10.4. Conditions to avoid

Incompatible with strong oxidizing agents

#### 10.5. Incompatible materials

Strong Oxidizing Agents, Strong Acids and Alkalis.

#### 10.6. Hazardous decomposition products

Oxides of carbon and sulfur

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### 11. Toxicological information

#### Acute toxicity

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LD50, mg/L/4hr	Inhalation Dust/Mist LD50, mg/L/4hr	Inhalation Gas LD50, ppm
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Rat - Category: 5	2,000.00, Rabbit - Category: 4	No data available	No data available	No data available
Graphite-(0007782-42-5)	No data available	No data available	No data available	No data available	No data available
Nickel- (0007440-02-0)	>9000 mg/kg (Rat)	No data available	No data available	No data available	No data available
Aluminum- (0007429-90-5)	No data available	No data available	No data available	No data available	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	5	May be harmful in contact with skin. (Not adopted by US OSHA)
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	---	Not Applicable
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Suspected by inhalation
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

### 12. Ecological information

#### 12.1. Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Petroleum distillates, hydrotreated heavy naphthenic - (64742-52-5)	5,000.00, Oncorhynchus mykiss	1,000.00, Daphnia magna	1,000.00 (96 hr), Scenedesmus subspicatus
Graphite – (0007782-42-5)	Not Available	Not Available	Not Available
Nickel - (0007440-02-0)	1.3 mg/L LC50 Cyprinus carpio 96h semi-static 10.4 mg/L LC50 Cyprinus carpio 96h static 1000 mg/L LC50 Brachydanio rerio 96h	1 mg/L Daphnia magna 48h Static 100 mg/L EC50 Daphnia magna 48h	0.18 mg/L EC50 Pseudokirchnerilla subcapitata 72h 0.174 – 0.311 mg/L EC50 Pseudokirchnerilla subcapitata 96h static
Aluminum - (0007429-90-5)	Not Available	Not Available	Not Available

### 12.2. Persistence and degradability

There is no data available on the preparation itself.

### 12.3. Bioaccumulative potential

Not Measured

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

### 12.6. Other adverse effects

No data available.

## 13. Disposal considerations

### 13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

## 14. Transport information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	Not Applicable	Not Regulated	Not Regulated
14.2. UN proper shipping name	Not Regulated	Environmentally hazardous substance, liquid, N.O.S	
14.3. Transport hazard class(es)	DOT Hazard Class: Not Applicable DOT Label: ---	IMDG: 9 Sub Class: Not Applicable	Air Class: Not Applicable
14.4. Packing group	Not Applicable	Not Applicable	Not Applicable



# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### 14.5. Environmental hazards

IMDG Not Applicable

### 14.6. Special precautions for user

No further information

## 15. Regulatory information

**Regulatory Overview** The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.

**Toxic Substance Control Act (TSCA)** All components of this material are either listed as "active" or exempt from listing on the TSCA Inventory.

**WHMIS Classification** Skin Irritation, Suspected of Carcinogenicity

**US EPA Tier II Hazards**

**Fire:** No  
**Sudden Release of Pressure:** No  
**Reactive:** No  
**Immediate (Acute):** Yes  
**Delayed (Chronic):** No

**EPCRA 311/312 Chemicals and RQs:**  
(No Product Ingredients Listed)

**EPCRA 302 Extremely Hazardous:**  
(No Product Ingredients Listed)

**EPCRA 313 Toxic Chemicals:**  
(No Product Ingredients Listed)

**Proposition 65 - Carcinogens (>0.0%):**  
Nickel

**Proposition 65 - Developmental Toxins (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Female Repro Toxins (>0.0%):**  
(No Product Ingredients Listed)

**Proposition 65 - Male Repro Toxins (>0.0%):**  
(No Product Ingredients Listed)

**N.J. RTK Substances (>1%):**  
Aluminum  
Nickel  
Graphite

**Penn RTK Substances (>1%):**  
Aluminum  
Nickel  
Graphite

**Proposition 65 Label Warning):**



WARNING: This product can expose you to chemicals including [Nickel], which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# Safety Data Sheet

## NICKEL PREMIUM ANTI-SEIZE



SDS Revision Date:

01/03/2025

### 16. Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects, which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H312 Harmful in contact with skin.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

The information on this safety data sheet represents our current data and best opinion as to the proper use in handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet, or which involves using the product in combination with any other product or any other process is the responsibility of the user. SAF-T-LOK International Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of SAF-T-LOK International Corporation products.

End of Document