

Safety Data Sheet

Section 1. Identification

Product name : TSF-6522 Tacky Soldering Flux

Product code 4030004 **Product type** : Solid. : May 2 2025.

Date of issue/Date of

revision

Manufacturer - Supplier	Telephone no.:	Emergency phone:
Alpha Assembly Solutions Inc. Global Headquarters 140 Centennial Avenue Piscataway, NJ 08854	Toll Free: (800) 367-5460 Main Phone: (908) 791-3000	DOMESTIC NORTH AMERICA 202-464-2554
ALPHA METALS MEXICO SA DE CV Ave Nafta 800, Parque Industrial STIVA Apodaca NL 66600 Mexico	Tel: +52 81 1156-6602	Tel: 01 800 022 1400 Tel: +52 55 5559-1588
Alpha Assembly Solutions Brasil Soldas Ltda Rio Jaguarão, 1540 - Vila Buriti Manaus Amazonas 69072-055 Brasil	Tel: 55 92 3614-7400	Tel: 55 92 3614-7423

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : ACUTE TOXICITY (inhalation) - Category 4 SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 **CARCINOGENICITY - Category 2**

AQUATIC HAZARD (ACUTE) - Category 3 AQUATIC HAZARD (LONG-TERM) - Category 3

GHS label elements

Hazard pictograms







Signal word : Danger

Hazard statements : May cause an allergic skin reaction.

Causes serious eye damage.

Harmful if inhaled.

Suspected of causing cancer.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves, protective clothing and eye or face protection. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Avoid breathing dust.

Section 2. Hazards identification

Response

: IF exposed or concerned: Get medical advice or attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell. Wash contaminated clothing before reuse. IF ON SKIN: Wash with plenty of water. If skin irritation or rash occurs: Get medical advice or attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor.

Page: 2/13

May 2 2025.

Storage

: Store locked up.

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

: None known.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	%	CAS number
Proprietary Rosin/Resin	10-20	-
Glycol	1-10	-
surfactant	1-10	-
Thixotrope	1-10	-
Amide.	1-10	-
Aliphatic amide	1-10	-
Amine	0.1-1.0	-

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Check for and remove any contact lenses. Immediately flush eyes with running water for at least 30 minutes, keeping eyelids open. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 15 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Section 4. First aid measures

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Page: 3/13 May 2 2025.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Harmful if inhaled.

Skin contact: May cause an allergic skin reaction.

Ingestion: No known significant effects or critical hazards.

Over-exposure signs/symptoms

Eye contact: Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case

: In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments

: No specific treatment.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training. If it is suspected that mists are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: None known.

Specific hazards arising from the chemical

: This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Page: 4/13 May 2 2025.

Section 5. Fire-fighting measures

Hazardous thermal decomposition products

: Decomposition products may include the following materials: carbon dioxide carbon monoxide nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Small spill

: Move containers from spill area. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Large spill

: Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not ingest. Avoid release to the environment. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Section 7. Handling and storage

including any incompatibilities

Conditions for safe storage, : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Page: 5/13

May 2 2025.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

6lycol

Thixotrope

Aliphatic amide

Amine

OARS WEEL (United States, 4/2022).

TWA: 10 mg/m³ 8 hours.

ACGIH TLV (United States, 6/2007). TWA: 3 mg/m3 Form: Respirable TWA: 10 mg/m3 Form: Total OSHA PEL (United States, 6/2007).

TWA: 5 mg/m³ Form: Respirable TWA: 10 mg/m³ Form: Total

OARS WEEL (United States, 4/2022). Absorbed through skin.

TWA: 15 ppm 8 hours. STEL: 120 mg/m³ 15 minutes. STEL: 30 ppm 15 minutes. TWA: 60 mg/m³ 8 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 3 ppm 8 hours. TWA: 15 mg/m³ 8 hours.

TWA: 15 mg/m³ 8 hours. Form: All forms TWA: 3 ppm 8 hours. Form: All forms NIOSH REL (United States, 10/2020).

TWA: 3 ppm 10 hours. TWA: 15 mg/m³ 10 hours.

NIOSH REL (United States, 6/2001). TWA: 15 mg/m³ 10 hours. Form: All forms TWA: 3 ppm 10 hours. Form: All forms

ACGIH TLV (United States, 7/2023). Absorbed through skin. TWA: 1 mg/m³ 8 hours. Form: Inhalable fraction and vapor ACGIH TLV (United States, 2/2003). Absorbed through skin.

Notes: 1994-1995 Adoption

TWA: 2 mg/m3 8 hours. Form: All forms TWA: 0.46 ppm 8 hours. Form: All forms

Appropriate engineering controls

: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties and safety characteristics

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Appearance

Physical state : Solid. [Paste.]

Color Yellow. Odor : Mild.

: Not available. **Odor threshold** pН : Not available. **Melting point/freezing point** : Not available. **Boiling point, initial boiling** : 254.6°C (490.3°F)

point, and boiling range

Flash point : Closed cup: >93°C (>199.4°F)

Evaporation rate : Not available. **Flammability** : Not available. Lower and upper explosion : Not applicable.

limit/flammability limit

: 0.0013 kPa (0.00975078 mm Hg) Vapor pressure

Relative vapor density : Not applicable. **Relative density** : Not available. Solubility : Not available.

Miscible with water Yes. VOC : 523.5 g/l

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not applicable. : Not available. **Decomposition temperature**

Continued on next page

Page: 6/13 May 2 2025.

Section 9. Physical and chemical properties and safety characteristics

Viscosity : Not applicable. Flow time (ISO 2431) : Not available.

Particle characteristics

: Not available. Median particle size

Section 10. Stability and reactivity

Reactivity No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous : Under normal conditions of storage and use, hazardous reactions will not occur. reactions

Incompatibility with various : Reactive or incompatible with the following materials: oxidizing materials, reducing materials, acids, alkalis and moisture. substances

: Under normal conditions of storage and use, hazardous decomposition products should **Hazardous decomposition** products

not be produced.

: Under normal conditions of storage and use, hazardous polymerization will not occur. **Hazardous polymerization**

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Proprietary Rosin/Resin	LD50 Dermal	Rabbit	>2.5 g/kg	-
. ,	LD50 Oral	Mouse	>3 g/kg	-
	LD50 Oral	Rat	>4 g/kg	-
Glycol	LD50 Oral	Rat	2150 mg/kg	-
-	LD50 Oral	Rat	2410 mg/kg	-
	LD50 Oral	Rat	3750 mg/kg	-
surfactant	LC50 Inhalation Vapor	Rat	>20 mg/l	1 hours
	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	4600 mg/kg	-
Thixotrope	LD50 Oral	Rat	>5 g/kg	-
Amide.	LD50 Oral	Rat	710 mg/kg	-
Aliphatic amide	LD50 Dermal	Rabbit	8 g/kg	-
•	LD50 Dermal	Rat	8000 mg/kg	-
	LD50 Oral	Rat	3914 mg/kg	-
Amine	LD50 Dermal	Rabbit	8180 mg/kg	-
	LD50 Oral	Mouse	3300 mg/kg	-
	LD50 Oral	Rabbit	2200 mg/kg	-
	LD50 Oral	Rat	680 mg/kg	-

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
⊠ lycol	Eyes - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
	Eyes - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	500 mg	-
	Skin - Mild irritant	Rabbit	-	24 hours 500	-
				mg	
surfactant	Eyes - Severe irritant	Rabbit	-	0.1 MI	-
	Skin - Mild irritant	Rabbit	-	0.5 gm	-
Aliphatic amide	Eyes - Moderate irritant	Rabbit	-	100 mg	-
Amine	Eyes - Severe irritant	Rabbit	-	24 hours 750	-
				ug	

Page: 8/13 May 2 2025.

Section 11. Toxicological information

Eyes - Severe irritant	Rabbit	-	5500 mg	-
Skin - Mild irritant	Rabbit	-	24 hours 500	-
			mg	
Skin - Mild irritant	Rabbit	-	50 mg	-

Sensitization

Not available.

Mutagenicity

Not available.

Carcinogenicity

Not available.

Classification

Product/ingredient name	OSHA	IARC	NTP
Amine	-	2B	-

Reproductive toxicity

Product/ingredient name	Maternal toxicity	Fertility	Development toxin	Species	Dose	Exposure
⊠ iphatic amide	-	-	Equivocal	Rat	Oral: 9700 mg/ kg	-
Amine	Positive	-	Positive	Rat - Female	Subcutaneous: 1500 mg/ kg	9 days During Pregnancy; 6 hours per day
	-	Positive	-	Rat - Male	Oral: 2500 ppm	13 weeks; 7 days per week

Teratogenicity

Not available.

Specific target organ toxicity (single exposure)

Product/ingredient name		Route of exposure	Target organs
Aliphatic amide	Category 3		Respiratory tract irritation

Specific target organ toxicity (repeated exposure)

Product/ingredient name		Route of exposure	Target organs
Amine	Category 2		blood system, kidneys, liver

Aspiration hazard

Not available.

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Harmful if inhaled.

Skin contact: May cause an allergic skin reaction.

Ingestion : No known significant effects or critical hazards.

Page: 9/13 May 2 2025.

Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain watering redness

Inhalation : No specific data.

: Adverse symptoms may include the following: Skin contact

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate

: Not available.

effects

: Not available. Potential delayed effects

Long term exposure

Potential immediate

: Not available.

effects

: Not available. Potential delayed effects

Potential chronic health effects

Product/ingredient name	Result	Species	Dose	Exposure
Amine			1000 mg/kg	-
	Chronic TD50 Oral	Rat	25 mg/kg	-

General : Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

Carcinogenicity : Suspected of causing cancer. Risk of cancer depends on duration and level of

exposure.

: No known significant effects or critical hazards. Mutagenicity **Reproductive toxicity** : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	2894.52 mg/kg
	2665.12 mg/kg
Inhalation (vapors)	16.87 mg/l

Section 12. Ecological information

Toxicity

Section 12. Ecological information

Product/ingredient name	Result	Species	Exposure
Proprietary Rosin/Resin	LC50 60.3 mg/l	Fish	96 hours
Glycol	Acute LC50 650 ppm Marine water	Fish - Menidia beryllina	96 hours
surfactant	Acute EC50 91 mg/l	Daphnia	48 hours
	Acute LC50 36 mg/l	Fish	96 hours
Aliphatic amide	Acute LC50 1.23 ppm Fresh water	Daphnia - Daphnia magna	48 hours
	Acute LC50 832 ppm Fresh water	Fish - Lepomis macrochirus	96 hours
Amine	Acute EC50 103000 µg/l Marine water	Algae - Skeletonema costatum	96 hours
	Acute LC50 28800 µg/l Fresh water	Crustaceans - Ceriodaphnia	48 hours
		dubia - Neonate	
	Acute LC50 100 mg/l	Daphnia	96 hours
	Acute LC50 >100 mg/l	Daphnia	96 hours
	Acute LC50 2150 μg/l Fresh water	Daphnia - Daphnia pulex	48 hours
	Acute LC50 100 mg/l	Fish	96 hours
	Acute LC50 >100 mg/l	Fish	96 hours
	Acute LC50 1370 mg/l	Fish	96 hours
	Acute LC50 1480 mg/l	Fish	96 hours

Persistence and degradability

Not available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Proprietary Rosin/Resin	3.42	-	low
Glycol	-0.68 to 0.01	-	low
surfactant	2.8	-	low
Aliphatic amide	-0.46	-	low
Amine	-1.43	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	TDG Classification	Mexico Classification	UN	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-	-
Packing group	-	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.	No.

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 5(a)2 proposed significant new use rules: Aliphatic amide TSCA 5(a)2 final significant new use rules: bis(2-butoxyethyl) ether TSCA 12(b) one-time export: bis(2-butoxyethyl) ether; Aliphatic amide TSCA 12(b) annual export notification: No products were found.

United States inventory (TSCA 8b)

: All components are listed or exempted.

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 311/312

Classification : ACUTE TOXICITY (inhalation) - Category 4

> SERIOUS EYE DAMAGE - Category 1 SKIN SENSITIZATION - Category 1 CARCINOGENICITY - Category 2

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	lighter but oxyethyl) ether Aliphatic amide	112-73-2	20-30 1-10
Supplier notification	bis(2-butoxyethyl) ether Aliphatic amide	112-73-2 -	20-30 1-10

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

California Prop. 65

▲ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

 TSF-6522 Tacky Soldering Flux
 Page: 12/13

 4030004
 May 2 2025.

Section 15. Regulatory information

Canada

Canada inventory : At least one component is not listed in DSL but all such components are listed in NDSL.

International regulations

Inventory list

Australia : Not determined.

China : All components are listed or exempted.

Japan : Not determined.

New Zealand : Not determined.

Philippines : Not determined.

Republic of Korea : Not determined.

Taiwan : All components are listed or exempted.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Procedure used to derive the classification

Classification	Justification
ACUTE TOXICITY (inhalation) - Category 4	Calculation method
SERIOUS EYE DAMAGE - Category 1	Calculation method
SKIN SENSITIZATION - Category 1	Calculation method
CARCINOGENICITY - Category 2	Calculation method
AQUATIC HAZARD (ACUTE) - Category 3	Calculation method
AQUATIC HAZARD (LONG-TERM) - Category 3	Calculation method

History

Date of issue/Date of : 5/2/2025

revision

Date of previous issue : 2/23/2025 Version : 1.01

Regulatory Affairs Department

enthone.msds@macdermidenthone.com

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available SGG = Segregation Group UN = United Nations

References : Not available.

Indicates information that has changed from previously issued version.

Notice to reader

Page: 13/13 May 2 2025.

Section 16. Other information

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4.12.3.4 b7396 MAES SDS GHS Americas